

CSC112 Lab1: Printing Vowels and Consonants

You are given a C program “pthread vows cons.c” that creates two threads (`vow` and `cons`) that print words starting with vowels and consonants, respectively, while maintaining the original order of input words. It uses the syscall `sched_yield()` to allow threads to take turns.

Compile the program using command line (or VS Studio Code IDE):

```
gcc -pthread -o threadtest threadtest.c
```

Run the program by supplying a list of words as arguments, for example:

```
./threadtest apple banana orange grape kiwi umbrella
```

The output looks like this:

```
Vowel: apple
Consonant: banana
Vowel: orange
Consonant: grape
Consonant: kiwi
Vowel: umbrella
```

The program works as follows:

1. Input Handling: The program takes command-line arguments as input. Each argument is treated as a word.
2. Thread Creation: The `vow` thread prints words starting with vowels. The `cons` thread prints words starting with consonants.
3. Turn-Based Synchronization:
 - A shared variable `turn` determines which thread should process the current word:
 - `turn == 0`: Vowel thread's turn.
 - `turn == 1`: Consonant thread's turn.
 - Each thread checks whether it's its turn and processes the word accordingly. If it's not its turn, it calls `sched_yield()` to yield control to the other thread.
4. Word Processing:
 - Each thread checks whether the current word starts with a vowel or consonant and prints it accordingly.
 - The `current_index` ensures that both threads process words in sequence.

The system call `sched_yield()` lets the calling thread voluntarily give up control to the OS scheduler, in order to give other active threads a chance to run. The two threads use `sched_yield()` to take turns in printing out the vows and cons. The program preserves the original word sequence in the argument list because both threads operate on a shared index `current_index` and take turns based on the `turn` variable. No mutexes or explicit locking mechanisms are used.

Note: Since Windows has limited support for the POSIX API, esp. not the process `fork()` call, please work on a Linux machine, or install the Windows Subsystem for Linux (WSL): <https://learn.microsoft.com/en-us/windows/wsl/install>. If you use VS Code, then please install VS Code WSL extension <https://code.visualstudio.com/docs/remote/wsl>.

Task 1: Use pthreads and the mutex API to print words in original order

Your first task is to modify the program to use the mutex API instead of `sched_yield()` while keeping the same program behavior (of printing words starting with vowels and consonants, respectively while maintaining the original order of input words), i.e.,

```
pthread_mutex_t lock;  
pthread_mutex_lock(&lock);  
pthread_mutex_unlock(&lock);
```

Hints:

1. You still need the shared variable `'current_index'`, but not the shared variable `'turn'`.
2. You need to call `pthread_mutex_lock(&lock)` and `pthread_mutex_unlock(&lock)` within functions `print_vowels()` and `print_consonants()` to ensure mutual exclusion between them, since they are not yielding to each other voluntarily.

Task 2: Use pthreads to print all vowels before all consonants

Your second task is to modify the program to use pthreads to achieve the program behavior of printing out all vowels before all consonants. First, you need to modify the functions `print_vowels()` and `print_consonants()` to each iterate through all the input arguments and print out all vowels and consonants, respectively. Second, you need to make sure that the thread that runs `print_vowels()` runs and finishes before the thread that runs `print_consonants()`. This can be done by calling `pthread_create()` to create the first thread that runs `print_vowels()`, and `pthread_join()` to wait for it to finish, before calling `pthread_create()` to create the second thread that runs `print_consonants()`, and `pthread_join()` to wait for it to finish. (You do not need mutex protection for each function, since the two threads run sequentially, not concurrently.) Please refer to the following code snippet:

```
#include <pthread.h>  
...  
pthread_create(&vow_thread, NULL, print_vowels, NULL);  
pthread_join(vow_thread, NULL);  
pthread_create(&cons_thread, NULL, print_consonants, NULL);  
pthread_join(cons_thread, NULL);
```

Try the following, does it work?

```
pthread_create(&vow_thread, NULL, print_vowels, NULL);  
pthread_create(&cons_thread, NULL, print_consonants, NULL);  
pthread_join(vow_thread, NULL);  
pthread_join(cons_thread, NULL);
```

References:

Thread functions in C/C++

<https://www.geeksforgeeks.org/thread-functions-in-c-c/>

How to create and join threads in C (pthreads).

<https://www.youtube.com/watch?v=uA8X5zNOGw8>

Task 3: Use child processes to print all vowels before all consonants (only works on Linux)

Your third task is to modify the program to use process `fork()` and `join()` to achieve the program behavior of printing out all vowels before all consonants. This can be done by calling `fork()` to create the first child process that runs `print_vowels()`, and `waitpid()` to wait for it to finish, before calling `fork()` to create the second child process that runs `print_consonants()`, and `waitpid()` to wait for it to finish. (You do not need mutex protection for each function, since the two processes do not share memory, and they run sequentially.) Please refer to the following code snippet:

```
#include <sys/wait.h> //This does not work on Windows
...
pid_t vowel_pid = fork();
waitpid(vowel_pid, NULL, 0);
pid_t cons_pid = fork();
waitpid(cons_pid, NULL, 0);
```

Try the following, does it work?

```
pid_t vowel_pid = fork();
pid_t cons_pid = fork();
waitpid(vowel_pid, NULL, 0);
waitpid(cons_pid, NULL, 0);
```

References:

Slide 13 “wait()” in “Lecture 2 Processes and Threads”

`fork()` in C

<https://www.geeksforgeeks.org/fork-system-call/>

What to submit

Please submit the following on Canvas:

1. Task 1: A C program named `Task1.c` that uses the mutex API, and prints words starting with vowels and consonants, respectively while maintaining the original order of input words, and screenshots for running it against some inputs.
2. Task 2: A C program named `Task2.c` that uses pthreads to print all vowels before all consonants.
3. Task 3: A C program named `Task3.c` that uses child processes to print all vowels before all consonants.
4. A short PDF report explaining the code you have written and the execution results.