

# Package ‘polypharmacy’

September 25, 2020

**Type** Package

**Version** 0.1.0.9000

**Title** Calculate indicators of polypharmacy

**Description** Analyse prescription drugs deliveries to calculate several indicators of polypharmacy corresponding to the various definitions found in the literature.

**Maintainer** Guillaume Boucher <guiboucher8@gmail.com>

**BugReports** <https://github.com/guiboucher/polypharmacy/issues>

**License** GPL-3 + file LICENSE

**Imports** data.table (>= 1.13.0),  
lubridate (>= 1.7.9)

**Roxygen** list(markdown = TRUE)

**RoxygenNote** 7.1.1

**Encoding** UTF-8

**LazyData** true

**Suggests** knitr,  
rmarkdown

**VignetteBuilder** knitr

## R topics documented:

polypharmacy-package . . . . .	2
cst_tx_duration . . . . .	2
data_process . . . . .	3
drug_bkdn . . . . .	6
<b>Index</b>	<b>7</b>

---

polypharmacy-package    *Calculate indicators of polypharmacy*

---

## Description

This package analyse prescription drugs deliveries to calculate several indicators of polypharmacy corresponding to the various definitions found in the literature.

## Details

It is essential to know the concepts used to calculate the various polypharmacy indicators to adequately use this package.

The core of the package is the `data_process()` function that creates the `data.table` of pharmacists drug deliveries by restructuring the drug delivery records (usually extracted from a pharmacy or a health insurance information system) into continuous periods of drug availability, applying user-defined arguments such as the grace periods between renewals or the longest treatment duration that an individual may accumulate through the successive renewals.

Then, each polypharmacy indicator can be computed using the corresponding function (`ind_simult()`, `ind_stdcumul()`, `ind_wcumul()`, `ind_stdcontinuous()`, `ind_ucontinuous()`) or using the overall function `indicators()` and select all the desired indicator(s) to be calculated at once.

Prior to running `data_process()` the user may need to pre-process the table of original drug delivery records to break down combination drug into their individual components (`drugs_bkdn()`) and/or to overwrite the treatment duration of specified drugs with constant time periods (`cst_trt_dur()`).

## Author(s)

**Maintainer:** Guillaume Boucher <guiboucher8@gmail.com>

Authors:

- Bernard Candas <bernard.candas.1@gmail.com>
- Houssein Missaoui <missaoui\_houssein@hotmail.fr>

## See Also

Useful links:

- Report bugs at <https://github.com/guiboucher/polypharmacy/issues>

---

cst\_tx\_duration    *Constant treatment duration drugs*

---

## Description

Overwrites the treatment duration with constant durations for each drug code included in a user-provided table.

**Usage**

```
cst_tx_duration(
  Rx_deliv,
  Rx_drug_code,
  Rx_duration,
  cst_tx_dur,
  cst_drug_code,
  cst_duration
)
```

**Arguments**

<code>Rx_deliv</code>	Name of the table listing all prescription drugs delivered.
<code>Rx_drug_code</code>	Column name of <code>Rx_deliv</code> that contains the drug unique identifier.
<code>Rx_duration</code>	Column name of the constant treatment duration in the <code>Rx_deliv</code> table.
<code>cst_tx_dur</code>	Name of the table that contains the constant treatment durations that will overwrite that in the <code>Rx_deliv</code> table for the specified drug codes.
<code>cst_drug_code</code>	Column name of <code>cst_tx_dur</code> that contains the drug unique identifier (same format as <code>Rx_drug_code</code> ).
<code>cst_duration</code>	Column name of the constant treatment duration in the <code>cst_tx_dur</code> table (same format as <code>Rx_duration</code> ).

**Value**

`data.table` of the same structure than `Rx_deliv`, sorted by `Rx_drug_code`, listing all drugs in which a constant treatment duration replaces the original treatment duration.

**Examples**

```
Rx_dt <- data.frame(id = c(rep(1, 3), rep(2, 2)),
  code = c("A", "B", "C", "B", "D"),
  duration = c(rep(15, 3), 15, 90))
cst_dt <- data.frame(codes = c("A", "C", "D"),
  dur = c(50, 100, 45))
Rx_cst <- cst_tx_duration(Rx_deliv = Rx_dt,
  Rx_drug_code = "code", Rx_duration = "duration",
  cst_tx_dur = cst_dt,
  cst_drug_code = "codes", cst_duration = "dur")
```

---

data\_process

---

*Table required for the calculation of polypharmacy indicators*


---

**Description**

Reads a table of successive drug delivery records (usually extracted from a pharmacy or a health insurance information system) and creates the data required for the calculation of the polypharmacy indicators by applying various user-defined arguments, incorporating hospital stays into the treatment periods and reconstruct continuous treatment periods by merging quasi continuous and/or overlapping drugs deliveries.

**Usage**

```
data_process(
  Rx_deliv,
  Rx_id,
  Rx_drug_code,
  Rx_drug_deliv,
  Rx_duration,
  Cohort = NULL,
  Cohort_id = NULL,
  Hosp_stays = NULL,
  Hosp_id = NULL,
  Hosp_admis = NULL,
  Hosp_discharge = NULL,
  study_start = NULL,
  study_end = NULL,
  grace_fctr = 0.5,
  grace_cst = 0,
  max_reserve = NULL,
  final_date_names = c("tx_start", "tx_end"),
  final_as_date = TRUE
)
```

**Arguments**

Rx_deliv	Name of the table listing all prescription drugs delivered including a run-in period of 7 months prior to study_start. See <i>Details</i> .
Rx_id	Column name of Rx_deliv containing individuals' unique identifiers (any format).
Rx_drug_code	Column name of Rx_deliv that contains the drugs' unique identifiers (any format).
Rx_drug_deliv	Column name of Rx_deliv that contains the dates of the drug deliveries (Date format, see <i>Details</i> ).
Rx_duration	Column name of Rx_deliv that contains the delivered treatment duration (integer number).
Cohort	Name of the table providing the unique identifiers of the study cohort. Only the ids listed in both the Cohort and the Rx_deliv tables will be returned. if Cohort = NULL, all ids of the Rx_deliv table will be returned.
Cohort_id	Column name of Cohort containing individuals' unique identifiers (same format as Rx_id).
Hosp_stays	Name of the table listing all hospital stays. See <i>Details</i> . (see <i>Details</i> for possible format)
Hosp_id	Column name of Hosp_stays containing individuals' unique identifiers (same format as Rx_id).
Hosp_admis	Column name of Hosp_stays that contains the date of admission in hospital (Date format, see <i>Details</i> ).
Hosp_discharge	Column name of Hosp_stays that contains the date of discharge from hospital (Date format, see <i>Details</i> ).
study_start, study_end	Defines the first and last day of the study period for which the polypharmacy indicator(s) need to be calculated. All treatment periods prior to study_start

	and past study_end are not transcribed into the result table (date format, see <i>Details</i> ).
grace_fctr, grace_cst	Number $\geq 0$ . Two types of grace periods can be applied. One is proportional to the treatment duration of the previous delivery (grace_fctr) and the other is a constant number of days (grace_cst).
max_reserve	An integer number $\geq 0$ or NULL. Longest treatment duration, in days, that can be stored from successive overlapping deliveries. When max_reserve = NULL no limit is applied. When max_reserve = 0 no accumulation of extra treatment duration is accounted for.
final_date_names	Vector of two (2) values indicating the name of the first and last date of continued drug use. See <i>Value</i> .
final_as_date	Return final_date_names columns in date format (TRUE). Else, columns are returned as integer (FALSE, memory efficient). TRUE by default.

## Details

### Variables:

- Rx\_id, Cohort\_id and Hosp\_id columns must be of the same class (integer, numeric, character, ...).
- Rx\_drug\_deliv, Hosp\_admis and Hosp\_discharge can be 1) as.Date('yyyy-mm-dd'), 2) as.character('yyyy-mm-dd') or 3) as.integer() where 0 is January 1<sup>st</sup>, 1970.

### Arguments:

- study\_start and study\_end can be 1) as.Date("yyyy-mm-dd"), 2) as.character("yyyy-mm-dd") or 3) as.integer() where 0 is January 1<sup>st</sup>, 1970.

### Hospital stays:

Drug availability is considered to continue during the hospital stay as it is on the day prior admission. The patient is assumed to resume the consumption of the drugs delivered by community pharmacists (as recorded in Rx\_deliv) prior admission the day after hosp\_discharge.

### Run-in period:

A run-in period is necessary to account for the medications that are available to the individuals on the day of study\_start.

### Grace period:

The grace period is used to determine if two successive deliveries can be considered as a continuous treatment even if there is a gap of a few days for which no treatment is apparently available. Two successive deliveries of an identical drug are considered part of a single continuous treatment if the next delivery doesn't occur more than  $\text{grace\_cst} + (\text{grace\_fctr} \times \text{Rx\_duration})$  days after the end of the previous treatment duration. The availability of extra drugs accumulated over the successive deliveries is accounted for prior to evaluating the duration of the gap between deliveries.

### Performance

For better performance, date columns are converted to integer numbers.

## Value

data.table with four (4) variables:

- The individual unique identifier which name is defined by Rx\_id.

- The drug unique identifier which name is defined by Rx\_drug\_code.
- The date of initiation of the reconstructed continued treatment. The name of the variable is defined by final\_date\_names[1] (default: 'tx\_start').
- The date of the last day of the reconstructed continued treatment. The name of the variable is defined by final\_date\_names[2] (default: 'tx\_end').

---

drug\_bkdn

---

*Translate combination drug deliveries into single active ingredients*


---

## Description

Replaces each combination drug into several deliveries of elementary active ingredients according to a user-provided correspondence table.

## Usage

```
drug_bkdn(Rx_deliv, Rx_drug_code, Combn_drugs, Combn_drug_code, Combn_act_code)
```

## Arguments

Rx_deliv	Name of the table listing all prescription drugs delivered.
Rx_drug_code	Column name of Rx_deliv that contains the combination drugs' unique identifiers (any format).
Combn_drugs	Name of the correspondence table listing all elementary active ingredients that make up each combination drug.
Combn_drug_code	Column name of Combn_drugs that contains the combination drugs' unique identifiers (same format as Rx_drug_code).
Combn_act_code	Column name of elementary active ingredients that is present in Combn_drugs (same format as Rx_drug_code).

## Value

data.table of the same structure than Rx\_deliv sorted by Rx\_drug\_code.

## Examples

```
Rx_dt <- data.frame(
  id = c(1, 1, 2, 2, 2),
  codeDrug = c(159, 753, 123, 456, 789)
)
SplitCode <- data.frame(
  code = c(159, 159, 456, 456, 456),
  split_code = c(1591, 1592, 4567, 4568, 4569)
)
Rx_split <- drug_bkdn(Rx_deliv = Rx_dt, Rx_drug_code = "codeDrug",
  Combn_drugs = SplitCode, Combn_drug_code = "code",
  Combn_act_code = "split_code")
```

# Index

cst\_tx\_duration, [2](#)

data\_process, [3](#)

drug\_bkdn, [6](#)

polypharmacy (polypharmacy-package), [2](#)

polypharmacy-package, [2](#)