KUBECON NA 2026 · KUBEVELA

KubeVela MCP

Let your AI agent read the cluster, plan the change, and apply it only when you allow it.

vela mcp · stdio only · no port opened · nothing deployed in the cluster

ADD IT TO CLAUDE CODE

```
eval "claude mcp add --scope user kubevela \
   -- $(vela mcp config --format command)"
```

Also Cursor, Codex, Gemini CLI and Claude Desktop. `vela mcp config` prints the entry for each.

15 TOOLS · THREE CLASSES

Read

12 tools, always on

`explain_application`
`get_application`
`get_workflow`
`get_logs`
`describe_definition`
`get_platform_info`

and six more

Plan

2 tools

`dryrun_application`
`diff_application`

Render and compare without saving. The diff rates risk LOW, MEDIUM or HIGH.

Write

1 tool

`apply_application`

Needs `--allow-write`

Ask it

"Why is the checkout application in team-a not healthy?"

"Add a Redis cache to my app and show me what would change before anything is applied."

"Can this cluster create a DynamoDB table, and with which provisioner?"

Read-only by default

Runs with your kubeconfig and RBAC. `--namespace` limits what it can read.

Secrets and ConfigMaps return key names only. Secret-like values are redacted.

Apply needs a one-use diff token, valid for 15 minutes. HIGH risk changes are never applied directly.

Read the docs

`kubevela.io/docs/next/tutorials/vela-mcp`

Documented for the KubeVela Next version. Use a vela CLI with the same minor version as vela-core.