

Outline

- 1 How to Deal with \mathcal{NP} Problems
- 2 Approximation Algorithms
- 3 Heuristic Algorithms
- 4 Approximation Algorithms: Minimum Vertex Cover (MVC)
- 5 Traveling Salesman Problem (TSP)
- 6 TSP: Approximation Algorithm
- 7 TSP: Christofides Algorithm
- 8 Polynomial Time Approximation Scheme

Approximation Algorithms

- We have a \mathcal{NPC} problem Q .

Approximation Algorithms

- We have a \mathcal{NPC} problem Q .
- Then it is **extremely unlikely** Q can be solved in polynomial time.
- What to do? Just give up?

Approximation Algorithms

- We have a \mathcal{NP} problem Q .
- Then it is **extremely unlikely** Q can be solved in polynomial time.
- What to do? Just give up?
- Many \mathcal{NP} problems are natural problems with important applications. We cannot afford to just give up!

Approximation Algorithms

- We have a \mathcal{NP} problem Q .
- Then it is **extremely unlikely** Q can be solved in polynomial time.
- What to do? Just give up?
- Many \mathcal{NP} problems are natural problems with important applications. We cannot afford to just give up!
- Many \mathcal{NP} problems are hard to solve if we **insist on absolute optimal solution**.

Approximation Algorithms

- We have a \mathcal{NP} problem Q .
- Then it is **extremely unlikely** Q can be solved in polynomial time.
- What to do? Just give up?
- Many \mathcal{NP} problems are natural problems with important applications. We cannot afford to just give up!
- Many \mathcal{NP} problems are hard to solve if we **insist on absolute optimal solution**.
- But if we settle for **nearly optimal solutions** (for example, within 50% of optimal), it might be possible to solve Q .

Approximation Algorithms

- We have a $\mathcal{N}\mathcal{P}\mathcal{C}$ problem Q .
- Then it is **extremely unlikely** Q can be solved in polynomial time.
- What to do? Just give up?
- Many $\mathcal{N}\mathcal{P}\mathcal{C}$ problems are natural problems with important applications. We cannot afford to just give up!
- Many $\mathcal{N}\mathcal{P}\mathcal{C}$ problems are hard to solve if we **insist on absolute optimal solution**.
- But if we settle for **nearly optimal solutions** (for example, within 50% of optimal), it might be possible to solve Q .
- In many applications, a **nearly optimal solution** might be good enough.

Approximation Algorithms

- We have a \mathcal{NPC} problem Q .
- Then it is **extremely unlikely** Q can be solved in polynomial time.
- What to do? Just give up?
- Many \mathcal{NPC} problems are natural problems with important applications. We cannot afford to just give up!
- Many \mathcal{NPC} problems are hard to solve if we **insist on absolute optimal solution**.
- But if we settle for **nearly optimal solutions** (for example, within 50% of optimal), it might be possible to solve Q .
- In many applications, a **nearly optimal solution** might be good enough.
- This is the subject of **Approximation Algorithms**: **Try to find solutions not too far from optimal**.

Outline

- 1 How to Deal with \mathcal{NP} Problems
- 2 Approximation Algorithms**
- 3 Heuristic Algorithms
- 4 Approximation Algorithms: Minimum Vertex Cover (MVC)
- 5 Traveling Salesman Problem (TSP)
- 6 TSP: Approximation Algorithm
- 7 TSP: Christofides Algorithm
- 8 Polynomial Time Approximation Scheme

Approximation Algorithms

- First we have to define what we mean by “nearly optimal”.

Approximation Algorithms

- First we have to define what we mean by “nearly optimal”.
- If Q is a decision problem, the term **approximation** makes no sense: The answer is either **yes** or **no**. Nothing to be approximated.

Approximation Algorithms

- First we have to define what we mean by “nearly optimal”.
- If Q is a decision problem, the term **approximation** makes no sense: The answer is either **yes** or **no**. Nothing to be approximated.
- So we now switch back to **optimization problems**.

Approximation Algorithms for Minimization Problems

Approximation Algorithm

- Q : a minimization problem.
- A : an algorithm for solving Q .
- I : an instance of Q .
- $Opt(I)$: the optimal solution of I .
- $|Opt(I)|$: the value of $Opt(I)$.
- $A(I)$: the solution found by A on input I .
- $|A(I)|$: the value of $A(I)$.
- If $\frac{|A(I)|}{|Opt(I)|} \leq r$ for some constant r and for ALL input instances I , then we say “ A is an approximation algorithm for Q with performance ratio r .”

Example: TSP

Example: Q is TSP

- I : an instance of TSP: Given a complete graph $G = (V, E)$ and weight function $w(*)$, find a HC C of G with **minimum** total length $w(C)$.

Example: TSP

Example: Q is TSP

- I : an instance of TSP: Given a complete graph $G = (V, E)$ and weight function $w(*)$, find a HC C of G with **minimum** total length $w(C)$.
- A : an algorithm for solving TSP. It finds a HC in G , not necessarily with minimum length.

Example: TSP

Example: Q is TSP

- I : an instance of TSP: Given a complete graph $G = (V, E)$ and weight function $w(*)$, find a HC C of G with **minimum** total length $w(C)$.
- A : an algorithm for solving TSP. It finds a HC in G , not necessarily with minimum length.
- $Opt(G, w)$: the optimal solution. Namely an HC of G with minimum length. (Caution: since TSP is \mathcal{NP} C, **$Opt(G, w)$ is unknown!**.)

Example: TSP

Example: Q is TSP

- I : an instance of TSP: Given a complete graph $G = (V, E)$ and weight function $w(*)$, find a HC C of G with **minimum** total length $w(C)$.
- A : an algorithm for solving TSP. It finds a HC in G , not necessarily with minimum length.
- $Opt(G, w)$: the optimal solution. Namely an HC of G with minimum length. (Caution: since TSP is \mathcal{NP} C, **$Opt(G, w)$ is unknown!**.)
- $|Opt(G, w)|$: the length of $Opt(G, w)$.

Example: TSP

Example: Q is TSP

- I : an instance of TSP: Given a complete graph $G = (V, E)$ and weight function $w(*)$, find a HC C of G with **minimum** total length $w(C)$.
- A : an algorithm for solving TSP. It finds a HC in G , not necessarily with minimum length.
- $Opt(G, w)$: the optimal solution. Namely an HC of G with minimum length. (Caution: since TSP is \mathcal{NP} C, **$Opt(G, w)$ is unknown!**.)
- $|Opt(G, w)|$: the length of $Opt(G, w)$.
- $A(G, w)$: the solution found by A . Namely, a HC of G found by A .

Example: TSP

Example: Q is TSP

- I : an instance of TSP: Given a complete graph $G = (V, E)$ and weight function $w(*)$, find a HC C of G with **minimum** total length $w(C)$.
- A : an algorithm for solving TSP. It finds a HC in G , not necessarily with minimum length.
- $Opt(G, w)$: the optimal solution. Namely an HC of G with minimum length. (Caution: since TSP is $\mathcal{NP}\mathcal{C}$, **$Opt(G, w)$ is unknown!**)
- $|Opt(G, w)|$: the length of $Opt(G, w)$.
- $A(G, w)$: the solution found by A . Namely, a HC of G found by A .
- $|A(G, w)|$: the length of the HC of G found by A .

Example: TSP

Example: Q is TSP

- I : an instance of TSP: Given a complete graph $G = (V, E)$ and weight function $w(*)$, find a HC C of G with **minimum** total length $w(C)$.
- A : an algorithm for solving TSP. It finds a HC in G , not necessarily with minimum length.
- $Opt(G, w)$: the optimal solution. Namely an HC of G with minimum length. (Caution: since TSP is \mathcal{NPC} , **$Opt(G, w)$ is unknown!**)
- $|Opt(G, w)|$: the length of $Opt(G, w)$.
- $A(G, w)$: the solution found by A . Namely, a HC of G found by A .
- $|A(G, w)|$: the length of the HC of G found by A .
- If $\frac{|A(I)|}{|Opt(I)|} \leq 1.5$ for **ALL** input instances I , then we say **" A is an approximation algorithm for TSP with performance ratio 1.5."**

Example: TSP

Example: Q is TSP

- I : an instance of TSP: Given a complete graph $G = (V, E)$ and weight function $w(*)$, find a HC C of G with **minimum** total length $w(C)$.
- A : an algorithm for solving TSP. It finds a HC in G , not necessarily with minimum length.
- $Opt(G, w)$: the optimal solution. Namely an HC of G with minimum length. (Caution: since TSP is $\mathcal{NP}\mathcal{C}$, **$Opt(G, w)$ is unknown!**)
- $|Opt(G, w)|$: the length of $Opt(G, w)$.
- $A(G, w)$: the solution found by A . Namely, a HC of G found by A .
- $|A(G, w)|$: the length of the HC of G found by A .
- If $\frac{|A(I)|}{|Opt(I)|} \leq 1.5$ for **ALL** input instances I , then we say **"A is an approximation algorithm for TSP with performance ratio 1.5."**
- So, for any input G, w , A will always find a HC of G within 50% of the optimal length.

Approximation Algorithms

- Since we are dealing with **minimization** problem, the value of $A(I)$ is always \geq the value of $Opt(I)$.

Approximation Algorithms

- Since we are dealing with **minimization** problem, the value of $A(I)$ is always \geq the value of $Opt(I)$.
- So we always have $\frac{|A(I)|}{|Opt(I)|} \geq 1$.

Approximation Algorithms

- Since we are dealing with **minimization** problem, the value of $A(I)$ is always \geq the value of $Opt(I)$.
- So we always have $\frac{|A(I)|}{|Opt(I)|} \geq 1$.
- Hence **the performance ratio r is always ≥ 1** . (If the ratio $r = 1$, then $A(I)$ is an optimal solution!).

Approximation Algorithms

- Since we are dealing with **minimization** problem, the value of $A(I)$ is always \geq the value of $Opt(I)$.
- So we always have $\frac{|A(I)|}{|Opt(I)|} \geq 1$.
- Hence **the performance ratio r is always ≥ 1** . (If the ratio $r = 1$, then $A(I)$ is an optimal solution!).
- If r is closer to 1, then the solution found by A is closer to the optimal solution. (if $r = 1.01$, then A always finds a solution within 1% of optimal.)

Approximation Algorithms

- Since we are dealing with **minimization** problem, the value of $A(I)$ is always \geq the value of $Opt(I)$.
- So we always have $\frac{|A(I)|}{|Opt(I)|} \geq 1$.
- Hence **the performance ratio r is always ≥ 1** . (If the ratio $r = 1$, then $A(I)$ is an optimal solution!).
- If r is closer to 1, then the solution found by A is closer to the optimal solution. (if $r = 1.01$, then A always finds a solution within 1% of optimal.)
- The goals of approximation algorithm design:
 - Reduce the performance ratio r .
 - Reduce the run time.

Approximation Algorithms

- The two goals often conflict:
 - If we allow $\Theta(n^2)$ time, we might find an algorithm with performance ratio $r = 1.5$.

Approximation Algorithms

- The two goals often conflict:
 - If we allow $\Theta(n^2)$ time, we might find an algorithm with performance ratio $r = 1.5$.
 - If we allow $\Theta(n^3)$ time, we might be able to find an algorithm with performance ratio $r = 1.2$.

Approximation Algorithms

- The two goals often conflict:
 - If we allow $\Theta(n^2)$ time, we might find an algorithm with performance ratio $r = 1.5$.
 - If we allow $\Theta(n^3)$ time, we might be able to find an algorithm with performance ratio $r = 1.2$.
 - If we allow $\Theta(2^n)$ time, we may find an algorithm with performance ratio $r = 1$, namely the algorithm always find an optimal solution.

Approximation Algorithms

- The two goals often conflict:
 - If we allow $\Theta(n^2)$ time, we might find an algorithm with performance ratio $r = 1.5$.
 - If we allow $\Theta(n^3)$ time, we might be able to find an algorithm with performance ratio $r = 1.2$.
 - If we allow $\Theta(2^n)$ time, we may find an algorithm with performance ratio $r = 1$, namely the algorithm always find an optimal solution.
- Depending on applications, one goal might be more important than the other goal.

Approximation Algorithms

- The two goals often conflict:
 - If we allow $\Theta(n^2)$ time, we might find an algorithm with performance ratio $r = 1.5$.
 - If we allow $\Theta(n^3)$ time, we might be able to find an algorithm with performance ratio $r = 1.2$.
 - If we allow $\Theta(2^n)$ time, we may find an algorithm with performance ratio $r = 1$, namely the algorithm always find an optimal solution.
- Depending on applications, one goal might be more important than the other goal.
- For most approximation algorithm research, the primary goal is to reduce the performance ratio as long as we stay within polynomial time.

Approximation Algorithm For Maximization Problems

Maximization Problem

- Let Q be a maximization problem (such as Maximum Independent Set problem.)

Approximation Algorithm For Maximization Problems

Maximization Problem

- Let Q be a maximization problem (such as Maximum Independent Set problem.)
- The definitions of I , $A(I)$, $Opt(I)$ etc are exactly the same as before, except:

Approximation Algorithm For Maximization Problems

Maximization Problem

- Let Q be a maximization problem (such as Maximum Independent Set problem.)
- The definitions of I , $A(I)$, $Opt(I)$ etc are exactly the same as before, except:
- If $\frac{|Opt(I)|}{|A(I)|} \leq r$ for some constant r and for ALL input instances I , then we say “ A is an approximation algorithm for Q with performance ratio r .”

Approximation Algorithm For Maximization Problems

Maximization Problem

- Let Q be a maximization problem (such as Maximum Independent Set problem.)
- The definitions of I , $A(I)$, $Opt(I)$ etc are exactly the same as before, except:
- If $\frac{|Opt(I)|}{|A(I)|} \leq r$ for some constant r and for ALL input instances I , then we say “ A is an approximation algorithm for Q with performance ratio r .”
- Since we are dealing with maximization problems, the value of $A(I)$ is always \leq the value of $Opt(I)$.

Approximation Algorithm For Maximization Problems

Maximization Problem

- Let Q be a **maximization problem** (such as **Maximum Independent Set** problem.)
- The definitions of I , $A(I)$, $Opt(I)$ etc are exactly the same as before, except:
- If $\frac{|Opt(I)|}{|A(I)|} \leq r$ for some **constant r** and for **ALL** input instances I , then we say “ **A is an approximation algorithm for Q with performance ratio r .**”
- Since we are dealing with **maximization problems**, the value of $A(I)$ is **always \leq the value of $Opt(I)$.**
- By our definition, the performance ratio r is always ≥ 1 .

Approximation Algorithm For Maximization Problems

Maximization Problem

- Let Q be a **maximization problem** (such as **Maximum Independent Set** problem.)
- The definitions of I , $A(I)$, $Opt(I)$ etc are exactly the same as before, except:
- If $\frac{|Opt(I)|}{|A(I)|} \leq r$ for some **constant r** and for **ALL** input instances I , then we say “ **A is an approximation algorithm for Q with performance ratio r .**”
- Since we are dealing with **maximization problems**, the value of $A(I)$ is **always \leq the value of $Opt(I)$.**
- By our definition, the performance ratio r is always ≥ 1 .
- **Our goal is still to reduce r .**

Outline

- 1 How to Deal with \mathcal{NP} Problems
- 2 Approximation Algorithms
- 3 Heuristic Algorithms**
- 4 Approximation Algorithms: Minimum Vertex Cover (MVC)
- 5 Traveling Salesman Problem (TSP)
- 6 TSP: Approximation Algorithm
- 7 TSP: Christofides Algorithm
- 8 Polynomial Time Approximation Scheme

Heuristic Algorithms

Heuristic Algorithm is another approach for solving hard optimization problems:

Heuristic Algorithms

Heuristic Algorithm is another approach for solving hard optimization problems:

- Using intuition, try to achieve the optimization goal.

Heuristic Algorithms

Heuristic Algorithm is another approach for solving hard optimization problems:

- Using intuition, try to achieve the optimization goal.
- Easy to design and understand.

Heuristic Algorithms

Heuristic Algorithm is another approach for solving hard optimization problems:

- Using intuition, try to achieve the optimization goal.
- Easy to design and understand.
- No need to prove the **performance ratio**.

Heuristic Algorithms

Heuristic Algorithm is another approach for solving hard optimization problems:

- Using intuition, try to achieve the optimization goal.
- Easy to design and understand.
- No need to prove the **performance ratio**.
- **The worst drawback: You never know how far is your solution from the optimal.**

Heuristic Algorithms

Heuristic Algorithm is another approach for solving hard optimization problems:

- Using intuition, try to achieve the optimization goal.
- Easy to design and understand.
- No need to prove the **performance ratio**.
- **The worst drawback: You never know how far is your solution from the optimal.**
- In some cases, the solutions produced by heuristic algorithms can be very bad. **And you don't know it!**

Approximation Algorithms vs Heuristic Algorithms

In contrast, the approximation algorithm:

- Must prove the performance ratio.

Approximation Algorithms vs Heuristic Algorithms

In contrast, the **approximation algorithm**:

- Must prove the **performance ratio**.
- Harder to design. (How do you compare the solution constructed by the algorithm with **the optimal solution which is UNKNOWN?**)

Approximation Algorithms vs Heuristic Algorithms

In contrast, the **approximation algorithm**:

- Must prove the **performance ratio**.
- Harder to design. (How do you compare the solution constructed by the algorithm with **the optimal solution which is UNKNOWN?**)
- Sometimes, they are counter-intuitive. (**They must consider the worst cases.**)

Approximation Algorithms vs Heuristic Algorithms

In contrast, the **approximation algorithm**:

- Must prove the **performance ratio**.
- Harder to design. (How do you compare the solution constructed by the algorithm with **the optimal solution which is UNKNOWN?**)
- Sometimes, they are counter-intuitive. (**They must consider the worst cases.**)
- However, **because of the existence of the performance ratio**, we know how the solution constructed by the algorithm compares with the optimal solution. (**If $r = 1.5$, our solution is at most within 50% of optimal.**)

Outline

- 1 How to Deal with \mathcal{NP} Problems
- 2 Approximation Algorithms
- 3 Heuristic Algorithms
- 4 Approximation Algorithms: Minimum Vertex Cover (MVC)**
- 5 Traveling Salesman Problem (TSP)
- 6 TSP: Approximation Algorithm
- 7 TSP: Christofides Algorithm
- 8 Polynomial Time Approximation Scheme

Approximation Algorithms: Minimum Vertex Cover (MVC)

Minimum Vertex Cover (MVC)

Input: An undirected graph $G = (V, E)$.

Find: A **vertex cover** $C \subseteq V$ of G such that the size $|C|$ is minimum.

Approximation Algorithms: Minimum Vertex Cover (MVC)

Minimum Vertex Cover (MVC)

Input: An undirected graph $G = (V, E)$.

Find: A **vertex cover** $C \subseteq V$ of G such that the size $|C|$ is minimum.

- The goal of the problem is: **cover all edges of G by using as few vertices as possible.**

Approximation Algorithms: Minimum Vertex Cover (MVC)

Minimum Vertex Cover (MVC)

Input: An undirected graph $G = (V, E)$.

Find: A **vertex cover** $C \subseteq V$ of G such that the size $|C|$ is minimum.

- The goal of the problem is: **cover all edges of G by using as few vertices as possible.**
- So the intuition is: Include in C the vertices that **cover many edges.**

Approximation Algorithms: Minimum Vertex Cover (MVC)

Minimum Vertex Cover (MVC)

Input: An undirected graph $G = (V, E)$.

Find: A **vertex cover** $C \subseteq V$ of G such that the size $|C|$ is minimum.

- The goal of the problem is: **cover all edges of G by using as few vertices as possible.**
- So the intuition is: Include in C the vertices that **cover many edges.**
- If $\deg(v) = k$, then the vertex v will **cover k edges.**

Approximation Algorithms: Minimum Vertex Cover (MVC)

Minimum Vertex Cover (MVC)

Input: An undirected graph $G = (V, E)$.

Find: A **vertex cover** $C \subseteq V$ of G such that the size $|C|$ is minimum.

- The goal of the problem is: **cover all edges of G by using as few vertices as possible.**
- So the intuition is: Include in C the vertices that **cover many edges.**
- If $\deg(v) = k$, then the vertex v will **cover k edges.**
- Thus, the heuristic algorithm should include in C the vertices with high degrees.

MVC: Heuristic Algorithm

Heuristic-MVC(G)

- 1 $C \leftarrow \emptyset$
- 2 **while** $E \neq \emptyset$ **do**
- 3 pick a vertex v with the highest $\deg(v)$ (break ties arbitrarily)
- 4 $C \leftarrow C \cup \{v\}$
- 5 delete all edges incident to v from E
- 6 **output** C

MVC: Heuristic Algorithm

Heuristic-MVC(G)

- 1 $C \leftarrow \emptyset$
 - 2 **while** $E \neq \emptyset$ **do**
 - 3 pick a vertex v with the highest $\deg(v)$ (break ties arbitrarily)
 - 4 $C \leftarrow C \cup \{v\}$
 - 5 delete all edges incident to v from E
 - 6 **output** C
- The algorithm is very simple

MVC: Heuristic Algorithm

Heuristic-MVC(G)

- 1 $C \leftarrow \emptyset$
 - 2 **while** $E \neq \emptyset$ **do**
 - 3 pick a vertex v with the highest $\deg(v)$ (break ties arbitrarily)
 - 4 $C \leftarrow C \cup \{v\}$
 - 5 delete all edges incident to v from E
 - 6 **output** C
- The algorithm is very simple
 - It's also very intuitive: Since the goal is to cover all edges using as few vertices as possible, we should include the vertex that covers most edges first. What else can you do?

MVC: Heuristic Algorithm

Heuristic-MVC(G)

- 1 $C \leftarrow \emptyset$
 - 2 **while** $E \neq \emptyset$ **do**
 - 3 pick a vertex v with the highest $\deg(v)$ (break ties arbitrarily)
 - 4 $C \leftarrow C \cup \{v\}$
 - 5 delete all edges incident to v from E
 - 6 **output** C
- The algorithm is very simple
 - It's also very intuitive: Since the goal is to cover all edges using as few vertices as possible, we should include the vertex that covers most edges first. What else can you do?
 - How well it performs?

MVC: Heuristic Algorithm

Heuristic-MVC(G)

- 1 $C \leftarrow \emptyset$
 - 2 **while** $E \neq \emptyset$ **do**
 - 3 pick a vertex v with the highest $\deg(v)$ (break ties arbitrarily)
 - 4 $C \leftarrow C \cup \{v\}$
 - 5 delete all edges incident to v from E
 - 6 **output** C
- The algorithm is very simple
 - It's also very intuitive: Since the goal is to cover all edges using as few vertices as possible, we should include the vertex that covers most edges first. What else can you do?
 - How well it performs?
 - It can be infinitely bad!

Heuristic Algorithm: Minimum Vertex Cover (MVC)

Fact

For any $r > 0$, there exists graphs G so that $\frac{|\text{Heuristic-MVC}(G)|}{|\text{Opt}(G)|} \geq r$.

Heuristic Algorithm: Minimum Vertex Cover (MVC)

Fact

For any $r > 0$, there exists graphs G so that $\frac{|\text{Heuristic-MVC}(G)|}{|\text{Opt}(G)|} \geq r$.

- Fix an integer k , (we will set the value of k later).

Heuristic Algorithm: Minimum Vertex Cover (MVC)

Fact

For any $r > 0$, there exists graphs G so that $\frac{|\text{Heuristic-MVC}(G)|}{|\text{Opt}(G)|} \geq r$.

- Fix an integer k , (we will set the value of k later).
- Pick an integer n so that each of $2, 3, \dots, k$ divides n . ($n = k!$ would do. But actual n could be much smaller than $k!$.)

Heuristic Algorithm: Minimum Vertex Cover (MVC)

Fact

For any $r > 0$, there exists graphs G so that $\frac{|\text{Heuristic-MVC}(G)|}{|\text{Opt}(G)|} \geq r$.

- Fix an integer k , (we will set the value of k later).
- Pick an integer n so that each of $2, 3, \dots, k$ divides n . ($n = k!$ would do. But actual n could be much smaller than $k!$.)
- We will construct a bipartite graph $G = (X, Y, E)$.

Heuristic Algorithm: Minimum Vertex Cover (MVC)

Fact

For any $r > 0$, there exists graphs G so that $\frac{|\text{Heuristic-MVC}(G)|}{|\text{Opt}(G)|} \geq r$.

- Fix an integer k , (we will set the value of k later).
- Pick an integer n so that each of $2, 3, \dots, k$ divides n . ($n = k!$ would do. But actual n could be much smaller than $k!$.)
- We will construct a bipartite graph $G = (X, Y, E)$.
- $|Y| = n$.

Heuristic Algorithm: Minimum Vertex Cover (MVC)

Fact

For any $r > 0$, there exists graphs G so that $\frac{|\text{Heuristic-MVC}(G)|}{|\text{Opt}(G)|} \geq r$.

- Fix an integer k , (we will set the value of k later).
- Pick an integer n so that each of $2, 3, \dots, k$ divides n . ($n = k!$ would do. But actual n could be much smaller than $k!$.)
- We will construct a bipartite graph $G = (X, Y, E)$.
- $|Y| = n$.
- $X = X_1 \cup X_2 \cup \dots \cup X_k$.

Heuristic Algorithm: Minimum Vertex Cover (MVC)

Fact

For any $r > 0$, there exists graphs G so that $\frac{|\text{Heuristic-MVC}(G)|}{|\text{Opt}(G)|} \geq r$.

- Fix an integer k , (we will set the value of k later).
- Pick an integer n so that each of $2, 3, \dots, k$ divides n . ($n = k!$ would do. But actual n could be much smaller than $k!$.)
- We will construct a bipartite graph $G = (X, Y, E)$.
- $|Y| = n$.
- $X = X_1 \cup X_2 \cup \dots \cup X_k$.
- $|X_1| = n$. Each vertex in X_1 is adjacent to 1 vertex in Y .

Heuristic Algorithm: Minimum Vertex Cover (MVC)

Fact

For any $r > 0$, there exists graphs G so that $\frac{|\text{Heuristic-MVC}(G)|}{|\text{Opt}(G)|} \geq r$.

- Fix an integer k , (we will set the value of k later).
- Pick an integer n so that each of $2, 3, \dots, k$ divides n . ($n = k!$ would do. But actual n could be much smaller than $k!$.)
- We will construct a bipartite graph $G = (X, Y, E)$.
- $|Y| = n$.
- $X = X_1 \cup X_2 \cup \dots \cup X_k$.
- $|X_1| = n$. Each vertex in X_1 is adjacent to 1 vertex in Y .
- $|X_2| = n/2$. Each vertex in X_2 is adjacent to 2 vertices in Y .

Heuristic Algorithm: Minimum Vertex Cover (MVC)

Fact

For any $r > 0$, there exists graphs G so that $\frac{|\text{Heuristic-MVC}(G)|}{|\text{Opt}(G)|} \geq r$.


- Fix an integer k , (we will set the value of k later).
- Pick an integer n so that each of $2, 3, \dots, k$ divides n . ($n = k!$ would do. But actual n could be much smaller than $k!$.)
- We will construct a bipartite graph $G = (X, Y, E)$.
- $|Y| = n$.
- $X = X_1 \cup X_2 \cup \dots \cup X_k$.
- $|X_1| = n$. Each vertex in X_1 is adjacent to 1 vertex in Y .
- $|X_2| = n/2$. Each vertex in X_2 is adjacent to 2 vertices in Y .
- $|X_3| = n/3$. Each vertex in X_3 is adjacent to 3 vertices in Y .

Heuristic Algorithm: Minimum Vertex Cover (MVC)

- ...
- $|X_k| = n/k$. Each vertex in X_k is adjacent to k vertices in Y .

Heuristic Algorithm: Minimum Vertex Cover (MVC)


- ...
- $|X_k| = n/k$. Each vertex in X_k is adjacent to k vertices in Y .



- The above graph is an example with $k = 3$ and $n = 6$.

Heuristic Algorithm: Minimum Vertex Cover (MVC)

- ...
- $|X_k| = n/k$. Each vertex in X_k is adjacent to k vertices in Y .



- The above graph is an example with $k = 3$ and $n = 6$.
- Every vertex in X_1 has degree 1.
- Every vertex in X_2 has degree 2.
- ...
- Every vertex in X_k has degree k .
- Every vertex in Y has degree k

Heuristic Algorithm: Minimum Vertex Cover (MVC)

- The Heuristic-MVC algorithm include all vertices in X_k into C .

Heuristic Algorithm: Minimum Vertex Cover (MVC)

- The Heuristic-MVC algorithm include all vertices in X_k into C .
- Then all vertices in X_{k-1} into C .

Heuristic Algorithm: Minimum Vertex Cover (MVC)

- The Heuristic-MVC algorithm include all vertices in X_k into C .
- Then all vertices in X_{k-1} into C .
- ...
- Then all vertices in X_1 into C .

Heuristic Algorithm: Minimum Vertex Cover (MVC)

- The Heuristic-MVC algorithm include all vertices in X_k into C .
- Then all vertices in X_{k-1} into C .
- ...
- Then all vertices in X_1 into C .
- So $\text{Heuristic-MVC}(G) = X_1 \cup \dots \cup X_k = X$.

Heuristic Algorithm: Minimum Vertex Cover (MVC)

- The Heuristic-MVC algorithm include all vertices in X_k into C .
- Then all vertices in X_{k-1} into C .
- ...
- Then all vertices in X_1 into C .
- So $\text{Heuristic-MVC}(G) = X_1 \cup \dots \cup X_k = X$.
- However, $\text{Opt}(G) = Y$.

$$\begin{aligned}\frac{|\text{Heuristic-MVC}(G)|}{|\text{Opt}(G)|} &= \frac{n + n/2 + n/3 + \dots + n/k}{n} \\ &= 1 + \frac{1}{2} + \frac{1}{3} + \dots + \frac{1}{k} \sim \ln k\end{aligned}$$

Heuristic Algorithm: Minimum Vertex Cover (MVC)

- The Heuristic-MVC algorithm include all vertices in X_k into C .
- Then all vertices in X_{k-1} into C .
- ...
- Then all vertices in X_1 into C .
- So $\text{Heuristic-MVC}(G) = X_1 \cup \dots \cup X_k = X$.
- However, $\text{Opt}(G) = Y$.

$$\begin{aligned}\frac{|\text{Heuristic-MVC}(G)|}{|\text{Opt}(G)|} &= \frac{n + n/2 + n/3 + \dots + n/k}{n} \\ &= 1 + \frac{1}{2} + \frac{1}{3} + \dots + \frac{1}{k} \sim \ln k\end{aligned}$$

- The last sum is the **Harmonic series (remember?)**, and it approaches to $\ln k$.

Heuristic Algorithm: Minimum Vertex Cover (MVC)

- The Heuristic-MVC algorithm include all vertices in X_k into C .
- Then all vertices in X_{k-1} into C .
- ...
- Then all vertices in X_1 into C .
- So $\text{Heuristic-MVC}(G) = X_1 \cup \dots \cup X_k = X$.
- However, $\text{Opt}(G) = Y$.

$$\begin{aligned}\frac{|\text{Heuristic-MVC}(G)|}{|\text{Opt}(G)|} &= \frac{n + n/2 + n/3 + \dots + n/k}{n} \\ &= 1 + \frac{1}{2} + \frac{1}{3} + \dots + \frac{1}{k} \sim \ln k\end{aligned}$$

- The last sum is the **Harmonic series (remember?)**, and it approaches to $\ln k$.
- Since $\ln k \rightarrow \infty$ when $k \rightarrow \infty$, we can chose k so that $\ln k > r$ for any r .

Approximation Algorithm: MVC

Appr-MVC($G = (V, E)$)

- 1 $C \leftarrow \emptyset$ (C will be a VC of G)
- 2 $M \leftarrow \emptyset$ (M will be a matching of G . It is not really needed by the algorithm. However, it will help to prove the performance ratio.)

Approximation Algorithm: MVC

Appr-MVC($G = (V, E)$)

- 1 $C \leftarrow \emptyset$ (C will be a VC of G)
- 2 $M \leftarrow \emptyset$ (M will be a matching of G . It is not really needed by the algorithm. However, it will help to prove the performance ratio.)
- 3 **while** $E \neq \emptyset$ **do**:
 - 4 pick **any** edge $e = (u, v)$ in G
 - 5 $C \leftarrow C \cup \{u, v\}$
 - 6 $M \leftarrow M \cup \{e\}$
 - 7 delete all edges that are incident to u or v from E
- 8 **output** C

Approximation Algorithms: MVC

- The algorithm clearly takes polynomial time.

Approximation Algorithms: MVC

- The algorithm clearly takes polynomial time.
- C is a VC of G : Any edge e deleted from E at line 7, has at least one end vertex is included in C .

Approximation Algorithms: MVC

- The algorithm clearly takes polynomial time.
- C is a VC of G : Any edge e deleted from E at line 7, has at least one end vertex is included in C .
- We will show the performance ratio is $r \leq 2$.

Approximation Algorithms: MVC

- The algorithm clearly takes polynomial time.
- C is a VC of G : Any edge e deleted from E at line 7, has at least one end vertex is included in C .
- We will show the performance ratio is $r \leq 2$.
- M is a matching of G : When we add an edge e into M at line 6, all edges that share a common end vertex with e are deleted from E at line 7.

Approximation Algorithms: MVC

- The algorithm clearly takes polynomial time.
- C is a VC of G : Any edge e deleted from E at line 7, has at least one end vertex is included in C .
- We will show the performance ratio is $r \leq 2$.
- M is a matching of G : When we add an edge e into M at line 6, all edges that share a common end vertex with e are deleted from E at line 7.
- Clearly, $|C| = 2 \cdot |M|$ (whenever we include 1 edge into M , we include 2 vertices into C).

Approximation Algorithms: MVC

- The algorithm clearly takes polynomial time.
- C is a VC of G : Any edge e deleted from E at line 7, has at least one end vertex is included in C .
- We will show the performance ratio is $r \leq 2$.
- M is a matching of G : When we add an edge e into M at line 6, all edges that share a common end vertex with e are deleted from E at line 7.
- Clearly, $|C| = 2 \cdot |M|$ (whenever we include 1 edge into M , we include 2 vertices into C).
- Let $\text{Opt}(G)$ be an optimal VC of G (which is unknown).

Approximation Algorithms: MVC

Lemma

Let $G = (V, E)$ be a graph. Let C be **any** vertex cover of G . Let M be **any** matching of G . Then $|C| \geq |M|$.

Approximation Algorithms: MVC

Lemma

Let $G = (V, E)$ be a graph. Let C be **any** vertex cover of G . Let M be **any** matching of G . Then $|C| \geq |M|$.

Proof.

- Any edge $e \in M$ must be covered by a vertex in C .
- No two edges $e_1, e_2 \in M$ can be covered by the same vertex in C , because e_1 and e_2 have no common end vertex.
- Therefore $|C| \geq |M|$.



Approximation Algorithms: MVC

- So $|\text{Opt}(G)| \geq |M|$.

Approximation Algorithms: MVC

- So $|\text{Opt}(G)| \geq |M|$.
- Hence: $\frac{|\text{Appr-MVC}(G)|}{|\text{Opt}(G)|} = \frac{|C|}{|\text{Opt}(G)|} \leq \frac{2 \cdot |M|}{|M|} = 2$, as to be shown.

Approximation Algorithms: MVC

- So $|\text{Opt}(G)| \geq |M|$.
- Hence: $\frac{|\text{Appr-MVC}(G)|}{|\text{Opt}(G)|} = \frac{|C|}{|\text{Opt}(G)|} \leq \frac{2 \cdot |M|}{|M|} = 2$, as to be shown.
- This algorithm is **counter-intuitive**: In order to cover the edge $e = (u, v)$ picked at line 4, **we only need to include one end vertex (u or v) into C . But we included both of them into C at line 5.**

Approximation Algorithms: MVC

- So $|\text{Opt}(G)| \geq |M|$.
- Hence: $\frac{|\text{Appr-MVC}(G)|}{|\text{Opt}(G)|} = \frac{|C|}{|\text{Opt}(G)|} \leq \frac{2 \cdot |M|}{|M|} = 2$, as to be shown.
- This algorithm is **counter-intuitive**: In order to cover the edge $e = (u, v)$ picked at line 4, **we only need to include one end vertex (u or v) into C . But we included both of them into C at line 5.**
- Nevertheless, it works well.

Approximation Algorithms: MVC

- So $|\text{Opt}(G)| \geq |M|$.
- Hence: $\frac{|\text{Appr-MVC}(G)|}{|\text{Opt}(G)|} = \frac{|C|}{|\text{Opt}(G)|} \leq \frac{2 \cdot |M|}{|M|} = 2$, as to be shown.
- This algorithm is **counter-intuitive**: In order to cover the edge $e = (u, v)$ picked at line 4, **we only need to include one end vertex (u or v) into C . But we included both of them into C at line 5.**
- Nevertheless, it works well.
- This simple algorithm is the best approximation algorithm for MVC for general graphs.

Outline

- 1 How to Deal with \mathcal{NP} Problems
- 2 Approximation Algorithms
- 3 Heuristic Algorithms
- 4 Approximation Algorithms: Minimum Vertex Cover (MVC)
- 5 Traveling Salesman Problem (TSP)**
- 6 TSP: Approximation Algorithm
- 7 TSP: Christofides Algorithm
- 8 Polynomial Time Approximation Scheme

Traveling Salesman Problem (TSP)

TSP

Input: A complete graph $G = (V, E)$ with edge weight function $w(*) \geq 0$.

Find: A HC C of G so that the total weight $w(C)$ is minimum.

Traveling Salesman Problem (TSP)

TSP

Input: A complete graph $G = (V, E)$ with edge weight function $w(*) \geq 0$.

Find: A HC C of G so that the total weight $w(C)$ is minimum.

We consider a special case:

Traveling Salesman Problem (TSP)

TSP

Input: A complete graph $G = (V, E)$ with edge weight function $w(*) \geq 0$.

Find: A HC C of G so that the total weight $w(C)$ is minimum.

We consider a special case:

Δ -TSP

It is the same as the general TSP problem, except that the weight function $w(*)$ must satisfy the **triangle inequality**: For any three vertices $x, y, z \in V$ we have:

$$w(x, y) + w(y, z) \geq w(x, z)$$

Traveling Salesman Problem (TSP)

TSP

Input: A complete graph $G = (V, E)$ with edge weight function $w(*) \geq 0$.

Find: A HC C of G so that the total weight $w(C)$ is minimum.

We consider a special case:

Δ -TSP

It is the same as the general TSP problem, except that the weight function $w(*)$ must satisfy the **triangle inequality**: For any three vertices $x, y, z \in V$ we have:

$$w(x, y) + w(y, z) \geq w(x, z)$$

- For most applications, we have the Δ -TSP. (Flying directly from city x to z is cheaper than flying from x to y , then from y to z .)

Traveling Salesman Problem (TSP)

TSP

Input: A complete graph $G = (V, E)$ with edge weight function $w(*) \geq 0$.

Find: A HC C of G so that the total weight $w(C)$ is minimum.

We consider a special case:

Δ -TSP

It is the same as the general TSP problem, except that the weight function $w(*)$ must satisfy the **triangle inequality**: For any three vertices $x, y, z \in V$ we have:

$$w(x, y) + w(y, z) \geq w(x, z)$$

- For most applications, we have the Δ -TSP. (Flying directly from city x to z is cheaper than flying from x to y , then from y to z .)
- Δ -TSP is still \mathcal{NP} .

TSP: Heuristic Algorithm

Heuristic-TSP(G)

- 1 start at the beginning vertex v_1
- 2 **for** $k = 2$ **to** n **do**:
- 3 goto the next vertex $v_k =$ the un-visited vertex that is **closest** to the current vertex v_{k-1}
- 4 go back from v_n to v_1

TSP: Heuristic Algorithm

Heuristic-TSP(G)

- 1 start at the beginning vertex v_1
- 2 **for** $k = 2$ **to** n **do**:
- 3 goto the next vertex $v_k =$ the un-visited vertex that is **closest** to the current vertex v_{k-1}
- 4 go back from v_n to v_1

Fact

For any $r > 0$, there exists instance $I = \langle G, w(*) \rangle$ of Δ -TSP so that

$$\frac{|\text{Heuristic-TSP}(I)|}{|\text{Opt}(I)|} \geq r.$$

TSP: Heuristic Algorithm

Heuristic-TSP(G)

- 1 start at the beginning vertex v_1
- 2 **for** $k = 2$ **to** n **do**:
- 3 goto the next vertex $v_k =$ the un-visited vertex that is **closest** to the current vertex v_{k-1}
- 4 go back from v_n to v_1

Fact

For any $r > 0$, there exists instance $I = \langle G, w(*) \rangle$ of Δ -TSP so that

$$\frac{|\text{Heuristic-TSP}(I)|}{|\text{Opt}(I)|} \geq r.$$

This heuristic algorithm can perform very badly, and you would not know it!

Outline

- 1 How to Deal with \mathcal{NP} Problems
- 2 Approximation Algorithms
- 3 Heuristic Algorithms
- 4 Approximation Algorithms: Minimum Vertex Cover (MVC)
- 5 Traveling Salesman Problem (TSP)
- 6 TSP: Approximation Algorithm**
- 7 TSP: Christofides Algorithm
- 8 Polynomial Time Approximation Scheme

TSP: Approximation Algorithm


Appr-TSP(G)

- 1 construct a minimum spanning tree T of G .
- 2 let L be the list of the vertices in the **preorder** of T .
- 3 return L

TSP: Approximation Algorithm

Appr-TSP(G)

- 1 construct a minimum spanning tree T of G .
- 2 let L be the list of the vertices in the **preorder** of T .
- 3 return L



In the above example, the HC returned by the algorithm is: *abefgdca*.

TSP: Approximation Algorithm

Theorem

The performance ratio of **Appr-TSP** is $r = 2$.

TSP: Approximation Algorithm

Theorem

The performance ratio of **Appr-TSP** is $r = 2$.

- The output L can be viewed as constructed as follows:

TSP: Approximation Algorithm

Theorem

The performance ratio of **Appr-TSP** is $r = 2$.


- The output L can be viewed as constructed as follows:
- Start with the MST T .

TSP: Approximation Algorithm

Theorem

The performance ratio of **Appr-TSP** is $r = 2$.

- The output L can be viewed as constructed as follows:
- Start with the MST T .
- Travel **around** T , using each edge of T exactly twice. This is a tour H of G . (It is not a HC of G , since some vertices are traveled more than once).
- So $w(H) = 2 \cdot w(T)$.



TSP: Approximation Algorithm

Short-Cut Operation

Suppose that a vertex v is visited by H more than once. Let $u \rightarrow v \rightarrow w$ be a section of H containing v . A **short-cut at v** is the operation that replaces $u \rightarrow v \rightarrow w$ by $u \rightarrow w$.

Note: A short-cut operation **cannot increase the length of the tour** because of the **triangle inequality**.

TSP: Approximation Algorithm

Short-Cut Operation

Suppose that a vertex v is visited by H more than once. Let $u \rightarrow v \rightarrow w$ be a section of H containing v . A **short-cut at v** is the operation that replaces $u \rightarrow v \rightarrow w$ by $u \rightarrow w$.

Note: A short-cut operation **cannot increase the length of the tour** because of the **triangle inequality**.

- L is obtained from H by a sequence of short-cut operations.

TSP: Approximation Algorithm

Short-Cut Operation

Suppose that a vertex v is visited by H more than once. Let $u \rightarrow v \rightarrow w$ be a section of H containing v . A **short-cut at v** is the operation that replaces $u \rightarrow v \rightarrow w$ by $u \rightarrow w$.

Note: A short-cut operation **cannot increase the length of the tour** because of the **triangle inequality**.

- L is obtained from H by a sequence of short-cut operations.
- So $w(L) \leq w(H) = 2 \cdot w(T)$.

TSP: Approximation Algorithm

Short-Cut Operation

Suppose that a vertex v is visited by H more than once. Let $u \rightarrow v \rightarrow w$ be a section of H containing v . A **short-cut at v** is the operation that replaces $u \rightarrow v \rightarrow w$ by $u \rightarrow w$.

Note: A short-cut operation **cannot increase the length of the tour** because of the **triangle inequality**.

- L is obtained from H by a sequence of short-cut operations.
- So $w(L) \leq w(H) = 2 \cdot w(T)$.
- Let O be an optimal HC of G . Namely $w(O)$ is the minimum among all HCs of G . O is not known. Since TSP is \mathcal{NP} , we cannot find O in polynomial time.

TSP: Approximation Algorithm

Short-Cut Operation

Suppose that a vertex v is visited by H more than once. Let $u \rightarrow v \rightarrow w$ be a section of H containing v . A **short-cut at v** is the operation that replaces $u \rightarrow v \rightarrow w$ by $u \rightarrow w$.

Note: A short-cut operation **cannot increase the length of the tour** because of the **triangle inequality**.

- L is obtained from H by a sequence of short-cut operations.
- So $w(L) \leq w(H) = 2 \cdot w(T)$.
- Let O be an optimal HC of G . Namely $w(O)$ is the minimum among all HCs of G . O is not known. Since TSP is \mathcal{NP} , we cannot find O in polynomial time.
- However, in order to prove the performance ratio, we must find a **lower bound** for $w(O)$.

TSP: Approximation Algorithm

- Let e be any edge on O .

TSP: Approximation Algorithm

- Let e be any edge on O .
- Consider $P = O - \{e\}$. P is a path and passing through all vertices of G .
So P is a spanning tree of G .

TSP: Approximation Algorithm

- Let e be any edge on O .
- Consider $P = O - \{e\}$. P is a path and passing through all vertices of G .
So P is a spanning tree of G .
- However, since T is a MST, we have $w(T) \leq w(P)$.

TSP: Approximation Algorithm

- Let e be any edge on O .
- Consider $P = O - \{e\}$. P is a path and passing through all vertices of G .
So P is a spanning tree of G .
- However, since T is a MST, we have $w(T) \leq w(P)$.
- Hence: $w(O) = w(P) + w(e) \geq w(P) \geq w(T)$.

TSP: Approximation Algorithm

- Let e be any edge on O .
- Consider $P = O - \{e\}$. P is a path and passing through all vertices of G .
So P is a spanning tree of G .
- However, since T is a MST, we have $w(T) \leq w(P)$.
- Hence: $w(O) = w(P) + w(e) \geq w(P) \geq w(T)$.
- Therefore:

$$\frac{w(L)}{w(O)} \leq \frac{2 \cdot w(T)}{w(T)} = 2$$

TSP: Approximation Algorithm

- Let e be any edge on O .
- Consider $P = O - \{e\}$. P is a path and passing through all vertices of G .
So P is a spanning tree of G .
- However, since T is a MST, we have $w(T) \leq w(P)$.
- Hence: $w(O) = w(P) + w(e) \geq w(P) \geq w(T)$.
- Therefore:

$$\frac{w(O)}{w(T)} \leq \frac{2 \cdot w(T)}{w(T)} = 2$$

- So the performance ratio of **Appr-TSP** is $r = 2$.

TSP: Approximation Algorithm

- Let e be any edge on O .
- Consider $P = O - \{e\}$. P is a path and passing through all vertices of G .
So P is a spanning tree of G .
- However, since T is a MST, we have $w(T) \leq w(P)$.
- Hence: $w(O) = w(P) + w(e) \geq w(P) \geq w(T)$.
- Therefore:

$$\frac{w(O)}{w(T)} \leq \frac{2 \cdot w(T)}{w(T)} = 2$$

- So the performance ratio of **Appr-TSP** is $r = 2$.

We can do better.

Outline





- 1 How to Deal with \mathcal{NP} Problems
- 2 Approximation Algorithms
- 3 Heuristic Algorithms
- 4 Approximation Algorithms: Minimum Vertex Cover (MVC)
- 5 Traveling Salesman Problem (TSP)
- 6 TSP: Approximation Algorithm
- 7 TSP: Christofides Algorithm**
- 8 Polynomial Time Approximation Scheme

TSP: Christofides Algorithm

Christofides($G = (V, E)$)

- 1 construct a minimum spanning tree T of G .
- 2 let $V_1 \subseteq V$ be the set of vertices that have **odd degrees** in T .
- 3 let $G_1 = (V_1, E_1)$ be the subgraph of G consisting of all vertices in V_1 and all edges connecting them.
- 4 find **a minimum weight perfect matching** M in G_1 . (Namely, M is a perfect matching of G_1 so that $w(M)$ is the minimum among all perfect matchings of G_1 .)
- 5 consider the graph consisting of the edges $T \cup M$. Every vertex has **even degree** in this graph.
- 6 find an Euler tour H in $T \cup M$. (H visits each vertex of G at least once.)
- 7 take short-cuts on H , until it becomes a HC L of G .
- 8 return L

TSP: Christofides Algorithm



TSP: Christofides Algorithm

Theorem

The performance ratio of Christofides algorithm is $r = 1.5$.

TSP: Christofides Algorithm

Theorem

The performance ratio of **Christofides algorithm** is $r = 1.5$.

- Let O be an optimal HC of G (which is unknown.)

TSP: Christofides Algorithm

Theorem

The performance ratio of **Christofides algorithm** is $r = 1.5$.

- Let O be an optimal HC of G (which is unknown.)
- Same as before, we have $w(O) \geq w(T)$.

TSP: Christofides Algorithm

Theorem

The performance ratio of **Christofides algorithm** is $r = 1.5$.

- Let O be an optimal HC of G (which is unknown.)
- Same as before, we have $w(O) \geq w(T)$.
- **Suppose we can show $w(M) \leq \frac{w(O)}{2}$ then:**

$$\begin{aligned} w(L) &\leq w(H) && (L \text{ is obtained from } H \text{ by short-cuts.}) \\ &= w(T) + w(M) && (\text{because } H = T \cup M) \\ &\leq w(O) + w(O)/2 \\ &= 1.5w(O) \end{aligned}$$

Then we will have $\frac{w(L)}{w(O)} \leq 1.5$ (this is all we want to show.)

TSP: Christofides Algorithm

The only thing remains to be shown: $w(M) \leq w(O)/2$

TSP: Christofides Algorithm

The only thing remains to be shown: $w(M) \leq w(O)/2$

- Suppose $V_1 = \{i_1, i_2, \dots, i_k\}$. (Note: k must be even. Why?)
- Suppose that the vertices in V_1 appear in O in this order. (If not, we can just rename them. So we can do this without loss of generality.)

TSP: Christofides Algorithm


The only thing remains to be shown: $w(M) \leq w(O)/2$

- Suppose $V_1 = \{i_1, i_2, \dots, i_k\}$. (Note: k must be even. Why?)
- Suppose that the vertices in V_1 appear in O in this order. (If not, we can just rename them. So we can do this without loss of generality.)
- Let $O' = \langle i_1 \rightarrow i_2 \rightarrow \dots \rightarrow i_k \rightarrow i_1 \rangle$. (O' is a sub-cycle obtained from O by taking short-cuts.)

TSP: Christofides Algorithm

The only thing remains to be shown: $w(M) \leq w(O)/2$

- Suppose $V_1 = \{i_1, i_2, \dots, i_k\}$. (Note: k must be even. Why?)
- Suppose that the vertices in V_1 appear in O in this order. (If not, we can just rename them. So we can do this without loss of generality.)
- Let $O' = \langle i_1 \rightarrow i_2 \rightarrow \dots \rightarrow i_k \rightarrow i_1 \rangle$. (O' is a sub-cycle obtained from O by taking short-cuts.)
- Let $M_1 = \{(i_1, i_2), (i_3, i_4), \dots, (i_{k-1}, i_k)\}$ and $M_2 = \{(i_2, i_3), (i_4, i_5) \dots (i_k, i_1)\}$



TSP: Christofides Algorithm

- Both M_1 and M_2 are perfect matchings of G_1 .

TSP: Christofides Algorithm

- Both M_1 and M_2 are perfect matchings of G_1 .
- However, M is a minimum weight perfect matching of G_1 .

TSP: Christofides Algorithm

- Both M_1 and M_2 are **perfect matchings** of G_1 .
- However, M is a **minimum weight perfect matching** of G_1 .
- So we have: $w(M) \leq w(M_1)$ and $w(M) \leq w(M_2)$.

TSP: Christofides Algorithm

- Both M_1 and M_2 are **perfect matchings** of G_1 .
- However, M is a **minimum weight perfect matching** of G_1 .
- So we have: $w(M) \leq w(M_1)$ and $w(M) \leq w(M_2)$.
- Hence:

$$\begin{aligned}w(O) &\geq w(O') && \text{(because } O' \text{ is obtained from } O \text{ by short-cuts)} \\&= w(M_1) + w(M_2) && \text{(because } O' = M_1 \cup M_2\text{.)} \\&\geq w(M) + w(M) \\&= 2 \cdot w(M)\end{aligned}$$





- This implies $w(M) \leq w(O)/2$, as to be shown.

TSP: Christofides Algorithm

- Christofides Algorithm was discovered in 1976. It remains the best algorithm for solving the Δ TSP problem (with the best performance ratio).

TSP: Christofides Algorithm

- Christofides Algorithm was discovered in 1976. It remains the best algorithm for solving the Δ TSP problem (with the best performance ratio).
- The following is an example that shows the ratio is actually 1.5.



TSP: Christofides Algorithm

- Fig (1) is a graph:
 - It has $k + 1$ vertices on the lower line and $k + 2$ vertices on the upper line.
 - Each edge shown has length 1, except the long arc has length $k + 1$.
 - The length of all un-shown edges $e = (x, y)$ is the length of the shortest path between x and y .
 - It is easy to check the length function $w(*)$ defined this way satisfies the triangle inequality.

TSP: Christofides Algorithm

- Fig (1) is a graph:
 - It has $k + 1$ vertices on the lower line and $k + 2$ vertices on the upper line.
 - Each edge shown has length 1, except the long arc has length $k + 1$.
 - The length of all un-shown edges $e = (x, y)$ is the length of the shortest path between x and y .
 - It is easy to check the length function $w(*)$ defined this way satisfies the triangle inequality.
- Figure (2) shows a MST T of G (in red color). a and b are the only vertices in T with odd degree.

TSP: Christofides Algorithm

- Fig (1) is a graph:
 - It has $k + 1$ vertices on the lower line and $k + 2$ vertices on the upper line.
 - Each edge shown has length 1, except the long arc has length $k + 1$.
 - The length of all un-shown edges $e = (x, y)$ is the length of the shortest path between x and y .
 - It is easy to check the length function $w(*)$ defined this way satisfies the triangle inequality.
- Figure (2) shows a MST T of G (in red color). a and b are the only vertices in T with odd degree.
- Figure (3) shows the HC L constructed by Christofides algorithm. Note that $w(L) = 2(k + 1) + (k + 1) = 3k + 3$.

TSP: Christofides Algorithm

- Fig (1) is a graph:
 - It has $k + 1$ vertices on the lower line and $k + 2$ vertices on the upper line.
 - Each edge shown has length 1, except the long arc has length $k + 1$.
 - The length of all un-shown edges $e = (x, y)$ is the length of the shortest path between x and y .
 - It is easy to check the length function $w(*)$ defined this way satisfies the triangle inequality.
- Figure (2) shows a MST T of G (in red color). a and b are the only vertices in T with odd degree.
- Figure (3) shows the HC L constructed by Christofides algorithm. Note that $w(L) = 2(k + 1) + (k + 1) = 3k + 3$.
- Fig (4) shows the optimal HC O . Note that $w(O) = 2k + 3$.

TSP: Christofides Algorithm

- Fig (1) is a graph:
 - It has $k + 1$ vertices on the lower line and $k + 2$ vertices on the upper line.
 - Each edge shown has length 1, except the long arc has length $k + 1$.
 - The length of all un-shown edges $e = (x, y)$ is the length of the shortest path between x and y .
 - It is easy to check the length function $w(*)$ defined this way satisfies the triangle inequality.
- Figure (2) shows a MST T of G (in red color). a and b are the only vertices in T with odd degree.
- Figure (3) shows the HC L constructed by Christofides algorithm. Note that $w(L) = 2(k + 1) + (k + 1) = 3k + 3$.
- Fig (4) shows the optimal HC O . Note that $w(O) = 2k + 3$.
- So the ratio on this graph is $\frac{3k+3}{2k+3} \rightarrow 1.5$ when $k \rightarrow \infty$.

Outline

- 1 How to Deal with \mathcal{NP} Problems
- 2 Approximation Algorithms
- 3 Heuristic Algorithms
- 4 Approximation Algorithms: Minimum Vertex Cover (MVC)
- 5 Traveling Salesman Problem (TSP)
- 6 TSP: Approximation Algorithm
- 7 TSP: Christofides Algorithm
- 8 Polynomial Time Approximation Scheme**

Polynomial Time Approximation Scheme

Polynomial Time Approximation Scheme (PTAS)

Let Q be a given optimization problem. A **PTAS** for Q is a class of algorithms so that, for any $\epsilon > 0$, we have an algorithm A_ϵ in this class with following properties:

- The runtime of A_ϵ is polynomial in n (it may depend on ϵ in any way).
- The **performance ratio** of A_ϵ is at most $1 + \epsilon$.

Polynomial Time Approximation Scheme

Polynomial Time Approximation Scheme (PTAS)

Let Q be a given optimization problem. A **PTAS** for Q is a class of algorithms so that, for any $\epsilon > 0$, we have an algorithm A_ϵ in this class with following properties:

- The runtime of A_ϵ is polynomial in n (it may depend on ϵ in any way).
- The performance ratio of A_ϵ is at most $1 + \epsilon$.
- Example: The runtime of A_ϵ is $O(n^{\frac{1}{\epsilon}})$.

Polynomial Time Approximation Scheme

Polynomial Time Approximation Scheme (PTAS)

Let Q be a given optimization problem. A **PTAS** for Q is a class of algorithms so that, for any $\epsilon > 0$, we have an algorithm A_ϵ in this class with following properties:

- The runtime of A_ϵ is polynomial in n (it may depend on ϵ in any way).
 - The performance ratio of A_ϵ is at most $1 + \epsilon$.
-
- Example: The runtime of A_ϵ is $O(n^{\frac{1}{\epsilon}})$.
 - Let $\epsilon = 0.1$. Then we have an algorithm $A_{0.1}$ with performance ratio 1.1 (namely within 10% of optimal), with runtime $O(n^{10})$.

Polynomial Time Approximation Scheme

Polynomial Time Approximation Scheme (PTAS)

Let Q be a given optimization problem. A **PTAS** for Q is a class of algorithms so that, for any $\epsilon > 0$, we have an algorithm A_ϵ in this class with following properties:

- The runtime of A_ϵ is polynomial in n (it may depend on ϵ in any way).
 - The **performance ratio of A_ϵ is at most $1 + \epsilon$** .
-
- Example: The runtime of A_ϵ is $O(n^{\frac{1}{\epsilon}})$.
 - Let $\epsilon = 0.1$. Then we have an algorithm $A_{0.1}$ with performance ratio 1.1 (namely within 10% of optimal), with runtime $O(n^{10})$.
 - Let $\epsilon = 0.01$. Then we have an algorithm $A_{0.01}$ with performance ratio 1.01 (namely within 1% of optimal), with runtime $O(n^{100})$.

Polynomial Time Approximation Scheme

Polynomial Time Approximation Scheme (PTAS)

Let Q be a given optimization problem. A **PTAS** for Q is a class of algorithms so that, for any $\epsilon > 0$, we have an algorithm A_ϵ in this class with following properties:

- The runtime of A_ϵ is polynomial in n (it may depend on ϵ in any way).
 - The **performance ratio of A_ϵ is at most $1 + \epsilon$** .
-
- Example: The runtime of A_ϵ is $O(n^{\frac{1}{\epsilon}})$.
 - Let $\epsilon = 0.1$. Then we have an algorithm $A_{0.1}$ with performance ratio 1.1 (namely within 10% of optimal), with runtime $O(n^{10})$.
 - Let $\epsilon = 0.01$. Then we have an algorithm $A_{0.01}$ with performance ratio 1.01 (namely within 1% of optimal), with runtime $O(n^{100})$.
 - Letting ϵ smaller and smaller, we can approximate the optimal solution with arbitrarily small error. But we pay a heavy price on run time.

Polynomial Time Approximation Scheme

Fully Polynomial Time Approximation Scheme (FPTAS)

Let Q be a given optimization problem. A **FPTAS** for Q is a class of algorithms so that, for any $\epsilon > 0$, we have an algorithm A_ϵ in this class with following properties:

- The runtime of A_ϵ is polynomial in both n and $1/\epsilon$.
- The performance ratio of A_ϵ is at most $1 + \epsilon$.

Polynomial Time Approximation Scheme

Fully Polynomial Time Approximation Scheme (FPTAS)

Let Q be a given optimization problem. A **FPTAS** for Q is a class of algorithms so that, for any $\epsilon > 0$, we have an algorithm A_ϵ in this class with following properties:

- The runtime of A_ϵ is polynomial in both n and $1/\epsilon$.
- The performance ratio of A_ϵ is at most $1 + \epsilon$.
- Example: The runtime of A_ϵ is $O(n^{\frac{1}{\epsilon}})$. It is not a FPTAS: The runtime is polynomial in n , but exp in $1/\epsilon$.
- Example: The runtime of A_ϵ is $O(n^3 \cdot (\frac{1}{\epsilon})^4)$. The runtime is polynomial in both n and $1/\epsilon$. This is a FPTAS.

Polynomial Time Approximation Scheme

- Barring the extremely unlikely event that $\mathcal{NP} = \mathcal{P}$, a FPTAS is **the best we can hope for solving an \mathcal{NPC} problem**:
 - We can approximate the optimal solution within arbitrarily small error.
 - The runtime is polynomial
 - The runtime is polynomial in error rate $1/\epsilon$.

Euclidean TSP

This is a special case of the Δ TSP:

- The vertices are the points on the 2D plane (or high dimension space.)
- The weight function is $w(u, v)$ = the Euclidean distance between the point u and the point v .

Polynomial Time Approximation Scheme

Euclidean TSP

This is a special case of the Δ TSP:

- The vertices are the points on the 2D plane (or high dimension space.)
 - The weight function is $w(u, v)$ = the Euclidean distance between the point u and the point v .
-
- Euclidean TSP is still \mathcal{NP} C.
 - Aurora showed (1992): There is a FPTAS for solving Euclidean TSP.
 - In contrast, Christofides algorithm is the best known algorithm for solving the Δ TSP.

Polynomial Time Approximation Scheme

- Can we find approximation algorithm for **all \mathcal{NP} problems?**
- Some are easier than others.
- Some are **almost impossible**.

Polynomial Time Approximation Scheme

- Can we find approximation algorithm for **all \mathcal{NP} problems?**
- Some are easier than others.
- Some are **almost impossible**.

Theorem

If there exists a polynomial time approximation algorithm for solving the Maximum Clique problem (or the Maximum Independent Set problem) **for any constant performance ratio r** , then $\mathcal{NP} = \mathcal{P}$.

- So unless $\mathcal{NP} = \mathcal{P}$, we **cannot** have an approximation algorithm for MC with performance ratio $r = 100$, $r = 10000$, **any r !**