LEIC - Organização de Computadores (2026/2027)

Laboratory Assignment 1: System Profiling and Modeling

Section 2: Exploring Cache Behaviour Through Timing

Question a) Experimental Environment

- **Processor model:** Intel® Xeon® CPU E5-2650 0 @ 2.00GHz
- **Operating system:** NixOS 25.05 (Warbler)
- **Compiler version:** GCC 14.2.1
- **Compilation options:** `-O2 -std=gnu11 -Wall -Wextra`

Question b) 16 KiB Array Access Pattern

Stride (bytes)	First four byte offsets accessed	Number of elements updated per pass
1	0, 1, 2, 3	16,384
32	0, 32, 64, 96	512
64	0, 64, 128, 192	256

Explanation: The calculations above are based on an array size of 16,384 bytes (16 KiB). The first four byte offsets follow the sequence 0, s, $2s$, and $3s$, where s is the access stride. The total number of elements updated per pass is determined by dividing the total array size by the stride (N/s), demonstrating that as the stride increases, fewer memory locations are accessed within a single pass across the working set.

Question c) L1 Data-Cache Capacity Estimate



Figure 1: Median time per update (ns) vs. stride (bytes) across working set sizes up to 1.00 MiB.

- **Estimate:** 32 KiB
- **Justification:** By analyzing the plot and the summary table, arrays up to 32 KiB maintain a consistently low execution time (e.g., 1.09 ns/update at a 64-byte stride). When the working set increases to 64 KiB, there is a distinct, sustained upward shift in the execution time (jumping to 3.40 ns/update at the same 64-byte stride). This sharp increase indicates that the 64 KiB array no longer fits entirely within the L1 data cache, resulting in capacity misses and forcing the CPU to retrieve data from the slower L2 cache.

Question d) L2 Data-Cache Capacity Sweep

- **Minimum array size used:** 64 KiB
- **Maximum array size used:** 64 MiB




Figure 2: Stride sweep by working-set size for L2 investigation (64 KiB to 64 MiB).

- **Estimated L2 Capacity:** 256 KiB (or interval [256 KiB, 512 KiB])

Justification:
Comparing the timing curves across working set sizes at identical strides reveals that working sets of 64 KiB, 128 KiB, and 256 KiB exhibit almost identical, low execution times (e.g., ~3.43 ns to 3.71 ns at a 64 B stride). When the array size increases from 256 KiB to 512 KiB, a clear, sustained jump in execution time occurs across all measured strides (e.g., increasing from 3.71 ns to 4.76 ns at 64 B stride, and from 12.30 ns to 14.06 ns at 4 KiB stride). This sustained rise indicates that array sizes exceeding 256 KiB can no longer fit within the L2 data cache and must be retrieved from the slower L3 cache or main memory. This 256 KiB estimate aligns with the per-core L2 cache hardware specification of the Intel Xeon E5-2650 processor.

Question e) L1 Data-Cache Line Size Estimate

- **Selected Array Size:** 128 KiB (Larger than the 32 KiB L1 capacity, smaller than the 256 KiB L2 capacity).
- **Estimated L1 Cache Line Size:** 64 bytes.

Justification:
As the stride increases, spatial reuse within a fetched cache line decreases, causing the time per update to rise. In an idealised repeated-access model, once the stride is equal to or greater than the line size, consecutive updates access distinct lines, so increasing stride no longer reduces within-line spatial reuse. A timing plateau can support a line-size estimate, although it is not a direct measurement of individual miss latency.

Looking at the 128 KiB working set, the median time per update rises from 1.17 ns at a 16 B stride, to 1.82 ns at a 32 B stride, and reaches 3.53 ns at a 64 B stride. For strides of 128 B, 256 B, and 512 B, the time plateaus at approximately 3.50 ns. This identical plateau pattern at 64 B is also visible on the 64 KiB and 256 KiB working sets. Because the time per update stops rising at a stride of 64 bytes, it indicates that spatial reuse has been fully exhausted, supporting an estimated cache line size of 64 bytes.

Section 3: Exploring Cache Behaviour Through Hardware Counters

Question a) Experimental Environment & Event Details

- **Processor model:** Intel® Xeon® CPU E5-2650 0 @ 2.00GHz
- **Operating system:** NixOS 25.05 (Warbler) / Linux 6.12.40
- **Compiler version:** GCC 14.2.1
- **Compilation options:** `-O2 -std=c11 -Wall -Wextra`

L1 Event Used: `PAPI_L1_DCM`

- **Short Description:** L1D cache misses
- **Native Event Description:** Number of cache lines brought into the L1D cache (L1D:REPLACEMENT)

L2 Event Used: `PAPI_L2_DCM`

- **Short Description:** L2D cache misses
- **Native Event Description:** Core-originated cacheable demand requests to L3 (LAST_LEVEL_CACHE_REFERENCES)

Counter interpretation: Results below are reported as events per update, following the benchmark's denominator and the recorded native-event descriptions. These hardware-counter measurements are distinct from the idealised per-access hit and miss counters in Ripes.

Question b) L1 Data-Cache Capacity Estimate



- **Estimated L1 Capacity: 32 KiB**
- **Array-size range used:** 4 KiB to 1 MiB

Explanation: The measurements support an L1 data-cache capacity of approximately **32 KiB**. Arrays up to 32 KiB have a low event count per update (for example, approximately 0.002 at a 64-byte stride). At 64 KiB, the count rises to approximately 1.0 event per update at the same stride. This sustained change is consistent with the accessed line footprint exceeding L1 capacity and supports the timing estimate in Section 2.

The plotted quantity is **counted events per array update**, rather than automatically a cache-miss probability. Each update reads and writes a byte, and the selected native event and other accesses in the measured region determine the count. The transition supports a capacity estimate; it does not prove that every individual update generates exactly one architectural cache miss.

Question c) L2 Data-Cache Capacity Estimate



- **Estimated L2 Capacity: 256 KiB** (interval [256 KiB, 512 KiB])
- **Array-size range used:** 64 KiB to 64 MiB

Explanation: The L2-event measurements support an estimated capacity of **256 KiB**, with the interval **[256 KiB, 512 KiB]** expressing the tested transition. At a 64-byte stride, the count is approximately 0.18 events per update for the 256 KiB array and rises to approximately 0.97 for the 512 KiB array. Comparing several array sizes at the same stride makes this a stronger observation than a single isolated measurement.

Interpretation follows the recorded native event: here, PAPI_L2_DCM maps to LAST_LEVEL_CACHE_REFERENCES, described above as core-originated cacheable demand requests to L3. Its precise scope must be respected rather than assuming it measures every L2 data-cache miss directly. Prefetching, request types, and overlap can affect the observations. These results support the proposed L2 transition and agree with the timing experiment, but the event count alone does not establish an exact cache boundary.

The lecture's **local L2 miss rate** uses accesses reaching L2 as its denominator. The benchmark instead divides by array updates, so these events-per-update values must not be substituted directly for the local L2 miss-rate term in a multilevel AMAT formula.

Question d) L1 Data-Cache Line Size Estimate

- **Selected Array Size: 128 KiB** *(Chosen because it is strictly larger than the 32 KiB L1 capacity, but smaller than the 256 KiB L2 capacity).*
- **Estimated L1 Cache Line Size: 64 bytes**

Explanation: For the selected 128 KiB array, the L1-event count per update is approximately 0.25 at a 16-byte stride, 0.50 at a 32-byte stride, and 1.0 at a 64-byte stride. It remains near 1.0 at the representative 128-byte and 256-byte strides. The repeatable rise followed by a plateau supports an estimated **64-byte L1 line size**.

This interpretation follows spatial locality: when the stride is smaller than a line, several updates can use bytes from the same fetched line; at strides equal to or larger than a line, consecutive updates no longer share that line. The numerical pattern is consistent with the simplified stride-to-line-size model, but hardware prefetching and the native event definition prevent interpreting it as exact per-access probabilities. In particular, the change around 64 bytes is more informative than decreases at very large strides, where few locations are revisited repeatedly.

Question e) Justification & Comparison

Capacity and line-size evidence:

- **L1 capacity:** the count at a 64-byte stride rises from approximately 0.002 events per update for a 32 KiB array to approximately 1.0 for a 64 KiB array, supporting an L1 estimate near 32 KiB.
- **L2 capacity:** at the same 64-byte stride, the count rises from approximately 0.18 events per update for a 256 KiB array to approximately 0.97 for a 512 KiB array, supporting the proposed [256 KiB, 512 KiB] transition.
- **L1 line size:** for the 128 KiB array, the increase from approximately 0.25 to 0.50 to 1.0 events per update as stride increases from 16 to 32 to 64 bytes, followed by a plateau at representative larger strides, supports a line size near 64 bytes.

Comparison with Section 2: Both experiments ran on the same Intel Xeon E5-2650 machine accessed remotely. They support compatible estimates: approximately 32 KiB for L1, approximately 256 KiB for L2 (with the tested transition interval noted above), and approximately 64 bytes per line.

The counter plots make the transitions clearer in these results, because event counts can expose cache activity even when access latencies overlap with other work. Timing per update also includes loop execution and the effects of pipelining, out-of-order execution, and measurement variability. Nevertheless, counters remain processor-specific measurements affected by native-event definitions, prefetching, and other accesses; they provide supporting evidence rather than mathematical certainty. No substantive disagreement is apparent between the two sets of estimates, within their experimental resolution.

Section 4: Exploring Cache Design with Ripes

4.1 Workload and Memory-Access Pattern

The supplied `workload.asm` was used without changing its instructions or memory layout. The assembly reserves a 2048-byte buffer and places the four arrays at fixed offsets from its beginning. Each integer is a four-byte word.

Array	Starting byte offset from `buffer`	Elements accessed	Successive access distance	Operations in loop 1	Operations in loop 2
`a`	0	`a[0]` to `a[63]`	4 bytes	Write 123	Write `b[i] + 567`
`b`	256	`b[0]` to `b[63]`	4 bytes	Write 234	Read
`c`	512	`c[0]` to `c[63]`	4 bytes	Write 345	Write `d[3*i] + 678`
`d`	768	`d[0], d[3], ..., d[189]`	12 bytes	Write 456	Read

The first loop performs four stores per iteration for 64 iterations, giving 256 data-cache accesses. The second loop performs two loads and two stores per iteration for another 256 accesses. A complete execution therefore contains **512 data accesses: 128 reads and 384 writes**. These are the data accesses being compared; instruction fetches belong to the separate instruction cache.

The workload exhibits both spatial and temporal locality. Consecutive elements of `a`, `b`, and `c` can reuse a fetched cache line. The stride of three integers in `d` skips two words between accesses, reducing this opportunity. The second loop revisits the data written by the first, providing potential temporal reuse if the required lines have survived in the cache.

4.2 Experimental Setup and Interpretation of Parameters

- **Simulator:** Ripes, browser version at https://ripes.dk/.
- **Exact Ripes version/build: v2.2.6-106-g5b8a616**
- **Processor:** 32-bit RISC-V single-cycle processor.
- **Cache under investigation:** L1 data cache; instruction-cache settings were left unchanged.
- **Program:** the supplied `workload.asm`, unchanged.
- **Measurement procedure:** configure the data cache, reset execution and cache contents/statistics, and execute the complete program once. Both loops are included, with no warm-up run. The totals below are consistent with one complete execution: hits plus misses equals 512 in every case.

A cache has S sets, A ways (cache lines per set), and W four-byte words per line. Its number of lines is SA, its line size is $4W$ bytes, and its data capacity is:

$$ C = S \times A \times W \times 4 \quad \text{bytes}. $$

The fields labelled 2^n in the supplied screenshots are **Sets** and **Words per Line**. Their displayed values must be converted from exponents: 5 sets means $2^5=32$ sets, 4 means 16 sets, 0 means one set, and 2 words per line means four words. In these screenshots, **Ways is displayed as an ordinary count**, without the 2^n label. Therefore a displayed Ways value of 5 means **five ways**, and a value of 1 means **one way**.

Address fields and terminology. A block (or cache line) is the transfer unit; a word is one four-byte item inside it. Following OC5, slides 12 and 30-32, a 32-bit byte address is divided into tag, set index, and block offset. For the selected B9 configuration, the fields are:

Address field in B9	Bits	Purpose
Tag	24	Distinguishes memory blocks that share a set
Set index	2	Selects one of four sets
Block offset	6	Selects a byte within a 64-byte line

The six offset bits comprise four word-offset bits and two byte-offset bits. The four ways are alternative placements **within the indexed set**; there are no separate way-index bits in the address. A hit requires a matching tag in a valid way. Resetting the cache invalidates its lines, ensuring a cold start.

The simulator's **Size (bits)** includes metadata in addition to data storage. It must not be substituted for C. Hit rate is calculated from the final access counters:

$$ \text{Hit rate} = \frac{\text{hits}}{\text{hits}+\text{misses}} \times 100%. $$

A hit means the accessed block was present; a miss means it was absent. With write-allocate, a store miss brings the corresponding line into the cache. With write-back, writes mark cached lines dirty; replacing a dirty line generates a writeback. Dirty lines still present at program termination are not automatically counted as additional writebacks in the reported statistics.

4.3(a) Comparing Three Selected Presets

Preset selection and interface limitation. The three built-in data-cache presets available in the browser version were selected and measured. Their original settings and results are retained below. However, the Ways values populated by the presets labelled two-way and fully associative did not match the geometries implied by their names: the fields showed one way and five ways, respectively. A supplementary run corrected the two-way configuration to **two ways**, preserving its 16 sets and four words per line. The resulting custom preset is labelled **Corrected 2-way** in the new screenshot.

The corresponding correction to 32 ways for the fully associative preset could not be applied because the browser's Ways field rejected values above 10. Its original measured configuration is therefore reported transparently as one set with five ways, rather than represented as a 32-line cache. The report distinguishes the three original preset measurements from the additional corrected two-way measurement.

Identification of the runs

Run	Preset or configuration	Source of results
P1	32-entry 4-word direct-mapped	`image(6).png`
P2	32-entry 4-word fully associative, as automatically instantiated	`image(7).png`
P3-original	32-entry 4-word 2-way set associative, as automatically instantiated	`image(8).png`
P3-corrected	Corrected 2-way; manual adjustment of Ways from 1 to 2	`Captura de ecrã 2026-10-16 004431.png`

Geometry and data capacity

Only Sets and Words per Line are displayed as powers of two in these screenshots. Ways is a direct count. The table reports actual counts, rather than the exponents entered in the interface.

Run	Sets S	Ways A	Words/line W	Total lines SA	Line size	Data capacity
P1	32	1	4	32	16 B	512 B
P2	1	5	4	5	16 B	80 B
P3-original	16	1	4	16	16 B	256 B
P3-corrected	16	**2**	4	**32**	16 B	**512 B**

The data capacity is $C=SAW\times4$ bytes:

$$ C_{\mathrm{P1}}=32\times1\times4\times4=512\text{ B}, $$

$$ C_{\mathrm{P2}}=1\times5\times4\times4=80\text{ B}, $$

$$ C_{\mathrm{P3-original}}=16\times1\times4\times4=256\text{ B}, $$

$$ C_{\mathrm{P3-corrected}}=16\times2\times4\times4=512\text{ B}. $$

P1 is direct-mapped. P2 is fully associative in the sense that it has one set and any fetched line can occupy any of its five ways; its capacity is nevertheless only five lines. P3-original is effectively direct-mapped despite its preset label. P3-corrected is genuinely two-way set-associative and has the advertised 32 total lines. P1 and P3-corrected consequently have equal data capacity and line size.

Policies

Run	Write-hit policy	Write-miss policy	Replacement policy
P1	Write-back	Write-allocate	LRU; victim is forced with one way
P2	Write-back	Write-allocate	LRU
P3-original	Write-back	Write-allocate	LRU; victim is forced with one way
P3-corrected	Write-back	Write-allocate	LRU

Final statistics

Each measurement includes both loops from an empty cache, without a warm-up. All four runs contain 512 accesses, matching the supplied assembly.

Run	Hits	Misses	Writebacks	Total accesses	Hit rate	Miss rate	Ripes size including metadata
P1	120	392	315	512	23.4375%	76.5625%	4928 bits
P2	320	192	126	512	62.5000%	37.5000%	805 bits
P3-original	28	484	369	512	5.46875%	94.53125%	2480 bits
P3-corrected	**28**	**484**	**360**	**512**	**5.46875%**	**94.53125%**	**4960 bits**

For example, $120/(120+392)\times100=23.4375%$ for P1. P2 gives $320/512\times100=62.5%$, while both P3 runs give $28/512\times100=5.46875%$. Ripes displays rounded fractional hit rates, including approximately 0.05469 for the corrected run.

The data portions of the four configurations occupy 4096, 640, 2048, and 4096 bits respectively. Subtracting these from Ripes's total sizes gives metadata overheads of 832, 165, 432, and 864 bits. Thus the corrected two-way run's 4960-bit total is consistent with 512 bytes of data plus metadata; it does not mean a 620-byte data cache.

Effect of correcting the two-way preset

Changing P3 from one way to two ways doubles its data capacity from 256 B to 512 B and produces a genuine two-way design. The measured improvement is a reduction in writebacks:

$$ 369-360=9 \quad \text{fewer writebacks}, $$

$$ \frac{9}{369}\times100%\approx2.44%. $$

There is **no improvement in hits or misses**: both runs have 28 hits and 484 misses. The correction should therefore be described as a reduction in dirty-line writebacks, not as an increase in hit rate or a measured execution-time improvement. Moreover, this before/after comparison changes both associativity and capacity, so the nine fewer writebacks cannot be attributed to associativity alone.

Writebacks depend on which evicted lines are dirty. Increasing the available ways can change the retained and evicted lines even when the total miss count stays the same. Also, dirty lines still resident at program termination do not contribute an additional final flush to these recorded counts. This explains why equal miss counts do not require equal writeback counts.

Why two ways do not improve the hit rate here

The workload interleaves accesses to three sequential arrays, `a`, `b`, and `c`, whose starts are 256 bytes apart. With 16-byte lines and 16 sets, the spacing corresponds to 16 memory blocks, so their corresponding lines map to the same set:

$$ \text{set index}= \left\lfloor\frac{\text{address}}{16}\right\rfloor\bmod16. $$

For example, the first lines of `a`, `b`, and `c` all map to set 0. During the first four iterations, the program repeatedly needs those three distinct lines. A two-way set has room for only two, so the access sequence can keep evicting a line before it is reused. The interleaved `d` accesses can add further competition when they map to the same set. Having more total bytes therefore does not guarantee fewer misses if the data is concentrated into too few slots in particular sets.

As a consistency check, an independent LRU trace calculation for P3-original and P3-corrected reproduces 14 hits and 242 misses in each loop. In both cases, all `a`, `b`, and `c` accesses miss; the 14 hits per loop come from `d`. This calculation explains the measurements; it is not an additional Ripes run. It shows that the remaining conflicts are sufficient to prevent a hit-rate improvement after the two-way correction.

Comparison at equal data capacity

P1 and P3-corrected both store 32 lines of 16 bytes, or 512 B. Nevertheless, P1 has **392 misses**, compared with **484** for P3-corrected: the corrected two-way design has 92 more misses, an increase of approximately **23.47%** relative to P1. Its hit rate is lower by **17.96875 percentage points**, and its writeback count is 360 rather than 315.

The reason is that keeping capacity fixed while moving from one way to two ways reduces the set count from 32 to 16. In P1, corresponding `a` and `c` lines conflict, but the corresponding `b` line maps to a different set. In P3-corrected, all three compete within the same two-way set. Consequently, increasing associativity at fixed capacity is not guaranteed to improve this workload: the changed set mapping also matters.

Comparison with the available fully associative configuration

P2 has the fewest measured misses, 192, even though its data capacity is only 80 B. Its single set lets any fetched block occupy any of its five slots, avoiding fixed-set placement conflicts. Five slots can retain the current blocks of the four array streams long enough to exploit nearby accesses.

With four words per line, each sequential array touches 16 distinct lines and the strided `d` accesses touch 48. The workload therefore touches 96 distinct data lines. An independent LRU trace calculation for P2 gives 96 misses in each loop, matching the measured total of 192: the first loop begins cold, and the small cache cannot retain the complete footprint for the second pass.

Relative to P1, P2 has 200 fewer misses, a reduction of approximately 51.02%, and a hit rate higher by 39.0625 percentage points. This is a comparison of the measured configurations, not a claim about a 32-line fully associative cache, which could not be configured in this browser interface.

Scope of the conclusions

The measured ranking by misses is P2, P1, then P3-original and P3-corrected tied. The corrected two-way run demonstrates an actual architectural correction and a modest writeback reduction, while also illustrating that greater capacity and associativity need not reduce misses for an unfavourable mapping.

The original three preset results are included to document what the available browser presets produced, and the corrected two-way run is explicitly identified as an additional manual adjustment. The fully associative limitation is retained as a short reproducibility note rather than hidden by relabelling measurements. These runs do not determine the winner for question (b), which requires a separate comparison using its storage budget and power-of-two parameters.

4.3(b) Selecting a Configuration Within the 1 KiB Data Budget

Experimental design. Nine distinct data-cache configurations were tested using the unchanged workload and the 32-bit single-cycle processor. The experiment crosses three associativities (one, two, and four ways) with three line sizes (16, 32, and 64 bytes). All configurations use **write-back**, **write-allocate**, and **LRU**, and each uses the full 1024-byte data-storage budget. Instruction-cache settings remain unchanged.

For each configuration, execution and cache contents/statistics were reset before one complete run of both loops. Ripes's fast execution control (F8) was used to run without updating the interface at every instruction. The comparison uses final cache counters, not simulation speed, processor cycles, or the plotted moving average.

The constraint is:

$$ SAW\times32\leq8192\text{ bits}, $$

equivalently $SAW\times4\leq1024$ bytes. Every tested configuration satisfies equality. For example, B9 has:

$$ C_{\mathrm{B9}}=4\times4\times16\times4 =1024\text{ bytes}=8192\text{ data bits}. $$

This budget excludes tags, valid/dirty bits, and replacement metadata. A total Size (bits) above 8192 in the screenshots therefore does not violate the data budget.

Measured results. S, A, and W below are actual counts. A one-way cache is direct-mapped; the two-way and four-way configurations are set-associative. Hit rates are calculated from the exact counters and rounded to four decimal places.

Test	Sets S	Ways A	Words/line W	Line size B	Data capacity B	Hits	Misses	Writebacks	Hit rate
B1	64	1	4	16	1024	346	166	76	67.5781%
B2	32	2	4	16	1024	311	201	111	60.7422%
B3	16	4	4	16	1024	322	190	95	62.8906%
B4	32	1	8	32	1024	414	98	48	80.8594%
B5	16	2	8	32	1024	395	117	69	77.1484%
B6	8	4	8	32	1024	418	94	47	81.6406%
B7	16	1	16	64	1024	418	94	54	81.6406%
B8	8	2	16	64	1024	407	105	73	79.4922%
B9	4	4	16	64	1024	466	46	23	91.0156%

Every row satisfies **hits + misses = 512**, matching the 128 loads and 384 stores in the supplied program. The rounded hit rates shown in Ripes agree with these calculations.

Selection. B9 is the unique configuration with the fewest misses among the nine tested:

- **Geometry:** four sets, four ways, sixteen four-byte words per line.
- **Total lines:** $4\times4=16$.
- **Line size:** $16\times4=64$ bytes.
- **Data capacity:** 1024 bytes.
- **Policies:** write-back, write-allocate, LRU.
- **Final counters:** 466 hits, **46 misses**, and 23 writebacks.
- **Hit rate:** $466/512\times100=91.015625%$.
- **Miss rate:** $46/512\times100=8.984375%$.

There is **no tie for the minimum**. B6 and B7 tie with each other at 94 misses, but both have more than twice B9's miss count. B9 also has the fewest writebacks, although writebacks were not the selection criterion. The conclusion is limited to the tested configurations and this workload; the experiment does not establish a global optimum over every permitted cache geometry.

Selected configuration and final-statistics screenshot


 Figure 5: B9 configuration and final cache statistics.

Figure 5. Supplied final-run screenshot for B9, showing Sets exponent 2 (four sets), Ways 4, Words per Line exponent 4 (sixteen words), LRU/write-back/write-allocate, and final counters of 466 hits, 46 misses, and 23 writebacks. The displayed total size is 8640 bits: 8192 data bits plus 448 metadata bits.

Open the original B9 screenshot.

4.3© Justification and Applicability to Other Programs

Why B9 performs better than tested alternatives

B9 combines a large enough line to exploit nearby accesses with sufficient placement flexibility to retain the four active array-stream lines. Neither a larger line nor a higher associativity alone guarantees this result, because keeping capacity fixed also changes the number of sets and resident lines.

The workload performs sequential four-byte accesses in a, b, and c, while d is accessed every twelve bytes. The first loop writes all four streams; the second loop reads b and d and writes a and c. Reuse can occur both within each pass and between passes, but only when the relevant line survives intervening accesses.

Connection to the lecture model. OC6, slide 5, distinguishes the three sources of cache misses:

Miss type	Meaning in this experiment
Compulsory (cold-start)	The first access to a memory block after the empty-cache reset
Capacity	A previously accessed block cannot be retained even in a fully associative reference cache of the same data capacity and line size
Conflict (collision)	Placement restrictions evict a block that the fully associative reference would retain

These categories apply to **blocks**, not individual words or array elements. Thus fetching one 64-byte block can eliminate later misses to several nearby words, illustrating spatial locality. Revisiting the same block in the second loop illustrates potential temporal locality. OC5, slide 33, also stresses the trade-off: larger blocks mean fewer resident blocks at fixed capacity and may fetch unused data.

The lectures distinguish miss rate from overall speed. In OC6, slide 14:

$$ \mathrm{AMAT}=t_{\mathrm{hit}}+p_{\mathrm{miss}},t_{\mathrm{penalty}}. $$

B9 minimises the **measured miss rate among the tested configurations**, as the assignment requires. It does not establish minimum AMAT or CPU time: the experiment supplies no hit-time or miss-penalty measurements, and associativity and line size can affect both (OC6, slide 31). The policies follow OC6, slides 8-9: write-allocate fetches a line on a store miss, and write-back marks modified lines dirty until replacement.

1. Spatial locality: comparison with B6

B6 and B9 are both four-way caches with 1024 bytes of data. B6 uses eight sets and 32-byte lines; B9 uses four sets and 64-byte lines. B9 records **46 misses rather than 94**, a reduction of:

$$ \frac{94-46}{94}\times100%=51.0638%. $$

Its hit rate is higher by $91.015625-81.640625=9.375$ percentage points. Writebacks fall from 47 to 23. These are improvements in the reported counters; Ripes does not model cache-access latency, so they are not a measured execution-time speedup.

A 64-byte line contains sixteen consecutive integers. Once fetched, it can serve the subsequent accesses to neighbouring elements of a, b, or c. With the fixed array layout, the number of distinct lines touched by one pass is:

Line size	Lines in a	Lines in b	Lines in c	Lines touched in d	Total distinct lines
16 B	16	16	16	48	96
32 B	8	8	8	24	48
64 B	4	4	4	12	24

The array starts are aligned to these line sizes, so no line is shared between different arrays. Although only every third integer of d is used, its 12-byte stride still visits every line in its accessed span at all three

tested line sizes. Larger lines therefore reduce the number of first-time line fetches; some fetched words in d remain unused.

An independent LRU trace calculation reproduces the measured totals for all nine configurations. For B6 and B9, it gives the following explanatory breakdown:

Configuration	Loop 1 misses	Loop 2 misses	Total misses	Loop 1 writebacks	Loop 2 writebacks
B6: 32-byte lines, four ways	48	46	94	16	31
B9: 64-byte lines, four ways	24	22	46	8	15

These per-loop values are derived from the supplied assembly and cache model, not read as separate measurements from the screenshots. Both configurations have only first-time line misses in loop 1, so the larger lines are being reused successfully within that pass. In loop 2, previously accessed data has largely been evicted, although a small amount survives. The 48-miss difference between B6 and B9 is therefore consistent with improved spatial reuse across the complete two-loop workload. This comparison changes line size, set count, and line count together, as required to hold data capacity and associativity constant.

2. Placement conflicts: comparison with B7

B7 and B9 both have 64-byte lines and 1024 bytes of data. B7 is direct-mapped with 16 sets; B9 has four sets and four ways. B9 again reduces misses from **94 to 46**, or **51.0638%**, while writebacks decrease from 54 to 23.

For a 64-byte line, the set index is:

$$ \text{set index}= \left\lfloor\frac{\text{address}}{64}\right\rfloor\bmod S. $$

Relative to the aligned buffer base, the first lines of a, b, c, and d have block numbers 0, 4, 8, and 12.

In B7, these initially occupy distinct sets. However, the d stream advances across twelve blocks, with relative block numbers 12 through 23. Blocks 16 through 19 wrap onto sets 0 through 3, competing with a; blocks 20 through 23 map onto sets 4 through 7, competing with b. When the interleaved loop returns to an a or b line, a d access may already have displaced it. Initial separation therefore does not prevent later conflicts.

In B9, the initial four stream blocks all map to the same set, because 0, 4, 8, and 12 are all zero modulo four. Nevertheless, **four ways allow all four to coexist**. Thus mapping several active lines to the same set is not itself harmful when enough ways exist. The trace check gives 24 misses in B9's first loop, exactly the number of distinct blocks touched; B7 incurs 51 first-loop misses despite touching the same 24 blocks. B7 therefore reloads blocks within that first pass, while B9 avoids such reloads.

B8 provides another comparison at the same line size and capacity: its two-way/eight-set design has 105 misses and 73 writebacks, compared with B9's 46 and 23. The winner is determined by the interaction of the access sequence, set mapping, and available ways, rather than the associativity label alone.

3. Capacity limits and remaining misses

B9 stores sixteen 64-byte lines, whereas the full workload touches twenty-four distinct lines. The fetched line footprint is therefore $24\times64=1536$ bytes, exceeding the 1024-byte data capacity.

The program directly accesses only 256 words, or 1024 distinct bytes, across the four streams. That does not mean all required data fits: cache storage is allocated to entire lines, including the skipped words in d. The d stream accesses 256 bytes of useful words spread over twelve 64-byte lines, occupying 768 bytes of fetched line storage.

For B9, each set encounters one line from each of a, b, and c plus three different d lines over the full pass: six distinct blocks compete for four slots. Four ways are sufficient for the active streams during the first pass, but cannot retain all six blocks of each set until the second loop.

This explains why the second loop is not all hits. B9's 46 misses comprise 24 compulsory misses and 22 later misses to previously accessed blocks. To classify the latter using the lecture's three categories, the same access trace was also analysed with a fully associative LRU reference cache containing sixteen 64-byte lines, with the same write-allocate policy and empty initial state. At each actual miss, the reference contains or lacks the requested block. This derived classification gives **24 compulsory, 22 capacity, and 0 conflict misses** for B9. It reproduces the measured total of 46; it is an explanatory reference-model calculation, not three separately measured Ripes counters. In contrast, the within-pass reloads in B7 illustrate the effect of restricted placement.

The final 23 writebacks count dirty-line evictions during execution. They are not the number of stores: multiple stores may modify one resident line before it is written back, and dirty lines still cached at termination are not included as an additional final flush.

4. Why more associativity is not always better

At 16-byte lines, the direct-mapped B1 has 166 misses, fewer than B2's 201 and B3's 190. At 32-byte lines, B4 has 98 misses, B5 has 117, and B6 has 94. At 64-byte lines, B7 has 94, B8 has 105, and B9 has 46.

Therefore the measured results do not support a monotonic rule that increasing ways always reduces misses. At fixed data capacity and line size, increasing ways reduces the number of sets, changing which blocks compete. LRU operates separately inside each set, and the changed grouping can help or hurt this access sequence. The lecture's usual benefit of associativity is the removal of collisions, illustrated by the ping-pong example in OC6, slides 22-23. These measurements do not invalidate that mechanism: a particular trace can still favour a different grouping and replacement history, so the average trend shown in class is not a guarantee for every workload. B9 is the best tested combination, not evidence that every four-way cache is superior to every direct-mapped cache.

Would the same configuration be best for every program with the same total array size?

No. Total array size alone does not specify the order or frequency of memory accesses. A different program could change:

- **Stride and spatial reuse:** sparse accesses may fetch many unused words with 64-byte lines, whereas consecutive accesses can reuse those words.
- **Access order and set pressure:** processing arrays one at a time instead of interleaving them changes which lines must coexist.
- **Temporal reuse:** repeatedly revisiting a small subset of lines can favour a different allocation of line size, sets, and ways.
- **Memory layout:** changing array addresses or padding can change set-index collisions even if total allocated array storage remains the same.
- **Read/write behaviour:** writes, dirty-line lifetimes, and replacement order affect writebacks even when hit rates are similar.

This dependence on layout and order is also the motivation for the software techniques in OC7, slides 14-15 and 26-32: padding can reduce set collisions, loop fusion can reuse values earlier, and blocking can keep a reusable subset resident. These are explanations of how another program could behave differently; the supplied assembly and array layout were not changed in any reported experiment.

For example, increasing d's stride to one word per 64-byte block would eliminate its current within-line reuse, while processing a full array before moving to the next would alter simultaneous set conflicts. Neither program is represented by the present measurements. The defensible conclusion is that **B9 gives the fewest misses among these nine designs for this exact assembly, memory layout, reset procedure, and policy combination**.