Embedded System
&
Embedded Linux
Development
Part 6

Index of today's topic

- Use libraries in development
- Use libjpeg to display/save jpeg image
- Use camera on FL6410
- Exercise

What is library?

- a collection of resources used to develop software
- contain code and data that provide services to independent programs
- Code reuse

Application/Library/API



C Library

- Standard Library
  - Philosophies between C & Python
- GNU C Library (glibc)
- Math Library (libm)

C standard library

- <assert.h>
- <ctype.h>
- <errno.h>
- <float.h>
- <limits.h>
- <locale.h>
- <math.h>
- <setjmp.h>
- <signal.h>
- <stdarg.h>
- <stddef.h>
- <stdio.h>
- <stdlib.h>
- <string.h>
- <time.h>

C POSIX library header files

- <cpio.h> Magic numbers for the cpio archive format.
- <dirent.h> Allows the opening and listing of directories.
- <fcntl.h> File opening, locking and other operations.
- <grp.h> User group information and control.
- <pthread.h> Defines an API for creating and manipulating POSIX threads.
- <pwd.h> passwd (user information) access and control.
- <sys/ipc.h> Inter-process communication (IPC).
- <sys/msg.h> POSIX message queues.
- <sys/sem.h> POSIX semaphores.
- <sys/stat.h> File information (stat et al.).
- <sys/time.h> Time and date functions and structures.
- <sys/types.h> Various data types used elsewhere.
- <sys/utsname.h> uname and related structures.
- <sys/wait.h> Status of terminated child processes (see wait)
- <tar.h> Magic numbers for the tar archive format.
- <termios.h> Allows terminal I/O interfaces.
- <unistd.h> Various essential POSIX functions and constants.
- <utime.h> inode access and modification times.

Library

- Static Libraries
  - *.a
- Shared Libraries
  - *.so
- Dynamic Linking
  - Dll/so (Shared Object)

Link Library in Linux

- Include the header files in .c
  - **#include <library_file_header.h>**
- Compile
  - **gcc -c <object file> <source file> -I<library_header_path>**
- Link Shared Library
  - **gcc -o <output> <object files> -l<library_name> -L<library_file_path>**
- Link Static Library
  - **gcc -o <output> <object files> <library_file_name.a>**

Index of today's topic

- Use libraries in development
- Use libjpeg to display/save jpeg image
- Use camera on FL6410
- Exercise

libjpeg

- a library to decode & encode the jpeg file
- installed in most of the Linux distribution
- Official website:
  - http://sourceforge.net/projects/libjpeg/

Use libjpeg in your code

- include the jpeglib.h
  - **#include <jpeglib.h>**
- add **-ljpeg** to the linking options
  - **gcc -o test.o -c test.c**
  - **gcc -o test.out test.o -ljpeg**

Example:

- http://www.cim.mcgill.ca/~junaed/libjpeg.php

Key point in writing a JPEG file

- Convert RGB565 buffer to RGB888 buffer
- Write the jpeg file line by line

```
while (cinfo.next_scanline <
  cinfo.image_height) {
   row_pointer[0] =
     &image_buffer[cinfo.next_scanline *
     image_width * 3];
      (void) jpeg_write_scanlines(&cinfo,
  row_pointer, 1);
   }
```

Key point in displaying a JPEG file

- Read the jpeg file line by line
- Convert RGB888 pixel to RGB565 pixel
- Draw pixel by pixel

```
y = 0;
while (cinfo.output_scanline < cinfo.output_height)
{
      jpeg_read_scanlines(&cinfo, buffer, 1);
      for(x=0; x<cinfo.output_width||
           x<SCREEN_WIDTH; x++)
      {
            draw_pixel(x, y, COLOR(buffer[0][x*3],
                  buffer[0][x*3+1], buffer[0][x*3+2]));
      }
      y++;
}
```

Index of today's topic

- Use libraries in development
- Use libjpeg to display/save jpeg image
- Use camera on FL6410
- Exercise

Camera on FL6410



The use of the camera: camera outward, frame angle alignment, then energized.

Shut down power before plug/unplug camera!

Camera driver in Linux

- device name **/dev/video0**
- read() on this device will get the screen pixels with resolution=320*240 in RGB565 format

read(camerafd, cambuf, VIDEO_WIDTH * VIDEO_HEIGHT * VIDEO_DEPTH / 8)

- you need a buffer with size=320*240*2

Index of today's topic

- Use libraries in development
- Use libjpeg to display/save jpeg image
- Use camera on FL6410
- Exercise

Exercise tips

Read JPEG

Decompression procedure

1 allocates space for the object and
   initialize JPEG
2 Specify the decompressed data source
3 Getting file information
4 To decompress setting parameters,
    including image size, color space
5 Start decompression
6 Remove the data
7 decompression is completed
8 release resources

Write JPEG

Compression procedure

1 allocates space for the object and initialize JPEG
2 Specify the image output target
3 the compression set parameters,
   including the image size, color space
4 compression begins
5 write data
6 compression is completed
7 release resources

```
/* LCD pixel : 480x272 */
/* Camera    : 320x240 */
#define VIDEO_WIDTH 320
#define VIDEO_HEIGHT240
#define VIDEO_DEPTH 16
```

```
JSAMPROW row_pointer[1];
/* libjpeg data structure
for storing one row, that
is, scanline of an image
*/
```

Exercise 1

- Display a JPEG image file in the LCD screen



Exercise 2

- display camera video in the screen
  - open Framebuffer device
  - get screen size, do mmap
  - open camera device
  - while(1)
    - read camera data to buffer
    - copy data to framebuffer
  - you can see what you get in LCD

Tips

- `struct v4l2_format fmt;//Frame format, such as width, height`
- `int type = V4L2_BUF_TYPE_VIDEO_CAPTURE;`

- `fmt.type = V4L2_BUF_TYPE_VIDEO_CAPTURE;`
- `fmt.fmt.pix.width = VIDEO_WIDTH;`
- `fmt.fmt.pix.height = VIDEO_HEIGHT;`
- `fmt.fmt.pix.depth = VIDEO_DEPTH;`
- `fmt.fmt.pix.pixelformat= V4L2_PIX_FMT_RGB565;`

Tips

```
/*open camera */
camerafd = open("/dev/video0",
  O_RDWR);
/*Set video capture formats*/
ioctl(camerafd, VIDIOC_S_FMT, &fmt)
/*Start a video display functions*/
ioctl(camerafd, VIDIOC_STREAMON,
  &type)
```

Exercise 3

- Display Video on Screen
- When user press a button, save current picture to a JPEG file