



FAM Administration Guide

4 June 2026

Contents

Configuring AWS S3 to work with File Activity Monitoring 3

Configuring AWS S3 to work with File Activity Monitoring

In order for you to be able to onboard AWS S3 bucket data sources, you must first verify that certain prerequisites are met, before you perform the procedure outlined in the [Onboarding a new data source - Cloud - Amazon Web Services S3](#) topic in the **FAM User Guide**.

Further, if you intend you perform audits on your AWS S3 data sources, you need to configure one S3 bucket to act as a log destination. In AWS, to designate an S3 bucket as a log destination, you configure it as the storage location of a CloudTrail trail and you configure the CloudTrail events for the other S3 buckets.

Note that an S3 bucket configured as a CloudTrail storage location can receive and store logs from itself and thus also act as an AWS S3 bucket data source, as well as from other AWS S3 bucket data sources, if you so desire.

FAM cannot pull logs from an AWS S3 bucket data source unless that S3 bucket's logs are stored to a log destination.

Prerequisites

Onboarding a data source requires preparation, such as gathering permissions and collecting relevant information for your deployment. Assistance may be necessary from a cloud administrator, network administrator, and an IT administrator to successfully begin monitoring your data source.

Verify that the following items are properly configured or available for use. The information and permissions gathered in this step are required for the remaining onboarding steps.

- An account in AWS
- An S3 bucket in AWS
- Access key for the **key** authentication mechanism. For more information, see [Manage access keys for IAM users](#).

In addition, for audit, you must configure one S3 bucket as the log destination, by configuring it as the storage location of a CloudTrail trail and configuring the CloudTrail events for the other S3 buckets. See the procedure below.

AWS Resource Permissions

For auditing only, grant the AWS principal the following permissions:

- The access key that is configured for the AWS cloud account needs the following permissions
 - s3:ListBucket,
 - s3:GetObject,
 - s3:ListAllMyBuckets
- **AWSCloudTrail_FullAccess policy** - for creating and managing the CloudTrail trail. For more information, see [Prepare for creating a trail for your organization and AWSCloudTrail_FullAccess Reference Guide](#).

Enabling Audit on AWS S3

To configure AWS S3 buckets so that their logs can be pulled by FAM, configure one bucket as the log destination (by configuring it as a CloudTrail storage location).

To enable audit via the AWS Console:

1. In your AWS Console, navigate to **CloudTrail**. The **CloudTrail > Dashboard** window opens.
2. Click the **Create trail** button. The **Create trail** window opens.
3. Under the **General details** section, enter a **Trail name**.
4. Under the **General details** section, select an S3 bucket as a storage location for the CloudTrail logs (either an existing or a new one).

Note that this S3 bucket is used as a log destination from where FAM pulls audit logs.

Note further that if you define a Prefix here, you must provide it when onboarding the log destination in the FAM onboarding procedure.

5. Click **Next**.
6. On the **Choose log events** page, check the **Management events** (optional) and **Data events** (mandatory) checkboxes.
7. (Optional) Under the **Management events** section, select the **Read** and **Write** API events.

It is recommended that, under **Management events**, you check the following:

- **Exclude AWS KMS events**
- **Exclude Amazon RDS Data API events**

8. Under the **Data events** section, configure the below options using basic event selectors:
 - Select S3 from the **Data event source** drop down list.
 - You can select **All current and future S3 buckets**, **Read** and/or **Write**, or **Individual Bucket Selection**, where you select the buckets whose logs are stored by this CloudTrail trail.
 - Add additional filters as required. Adding a filter reduces the volume of events that are caught and logged.
9. Click **Next**.
10. Review your choices and click **Create Trail**.
11. Verify that the trail was successfully created and is actively collecting logs, as follows:
 - a. Generate traffic on the S3 bucket whose data events were selected (e.g. by uploading a file to the bucket).
 - b. Navigate to your S3 log destination and see that log files are being generated.



Note: Logs on S3 do not expire or get deleted. Consider purging these files as they mature or become irrelevant.