



Onboarding Databases to DSF Hub Reference Guide

3 June 2026

Contents

AWS Log Group Asset Specifications 3

AWS Log Group Asset Specifications

Overview

This page provides general guidelines for configuring this asset, including the following:

- The expected parameter fields in this asset's document
- Information about connecting to this asset (expected fields in the "connection" document)
- Information about Sensitive Data Management (SDM) connections (if supported)
- Auto-discovery action for this asset (if supported)

For detailed instructions about onboarding this database type to DSF Hub for Auditing, reporting, compliance and security purposes, see [Onboarding Databases to DSF Hub - Overview](#).

For general information about configuring assets and connections, see [Using Assets in DSF Hub](#).

Permissions

Permissions are required to use this asset with specific DSF Hub features, as described in the table below.

DSF Hub feature	Minimum permissions required
Audit Management	N/A
Data Privacy	N/A
Discovery	This source can be discovered by running Enable Audit / Connect Gateway against a relevant data source asset. Please check the AWS Asset Spec Page for permissions
SonarGateway	Please check the AWS Asset Spec Page for permissions

Asset Parameters

field Name	type	mandatory / optional	value / <description>
asset_id	string	Mandatory	<AWS ARN>
asset_display_name	string	mandatory	<Group name>
Server Type	string	mandatory	AWS LOG GROUP
timestamp	ISODate	Auto-generated	<Timestamp of the asset document version creation>
Server IP	string	mandatory	<AWS ARN>
Server Host Name	string	mandatory	<Endpoint URL, e.g. <<domain>>.amazon.com>
Service Name	string	mandatory	<empty string>
asset_source	string	mandatory	AWS
admin_email	string	mandatory	<The email address to notify about this asset>
jsonar_uid	string	Auto-generated	<Unique identifier (UID) attached to the jSonar machine controlling the asset>
jsonar_uid_display_name	string	Auto-generated	<Human-friendly ID attached to the jSonar machine controlling the

			asset>
Server Port	integer	mandatory	<Port used by the source server>
version	integer	optional	<Denotes the major version of the asset, e.g. postgres 9 vs. postgres 10>
location	string	optional	Region <Gateway requires this now as a workaround for 'region' field not being inserted into asset document>
used_for	string	optional	<Designates how this asset is used / the environment that the asset is supporting. Allowed values: Production Test Development Demonstration QA Staging Training Disaster Recovery>
owned_by	string	optional	<Email of Owner / person responsible for the asset; can be different from the person in the managed_by field. Defaults to admin_email.>
managed_by	string	optional	<Email of Person who

			maintains the asset; can be different from the owner specified in the owned_by field. Defaults to admin_email.>
criticality	integer	optional	<The asset's importance to the business. These values are measured on a scale from "Most critical" (1) to "Least critical" (4). Allowed values: 1, 2, 3, 4>
asset_model	string	optional	<You can dynamically group actual discovered or imported assets into logical, operational, and financial models / domain via this parameter. Examples: CRM application, HR data.>
urm_enabled	boolean	optional	<User rights management is enabled if this parameter is set to "True".>
database_name	string	optional	<Specifies the name of the database you are connected to (or default DB).>
db_engine	string	optional	<Specifies the version of the engine being used by the database (e.g. oracle-ee, oracle-se, oracle-se1, oracle-se2)>
application	string	optional	<The Asset ID of the application asset that "owns" the asset.>
service_endpoint_maxretries	integer	Optional	Maximum number of retry attempts. Default: 10

service_endpoint_scalefactor	integer	Optional	Length of time between retry attempts (in minutes). Default value: 25
enable_audit_management	boolean	optional	<If true, jSonar is responsible for setting and updating the policies. Default: false>
enable_audit_monitoring	boolean	optional	<If true, jSonar sends emails/alerts when the audit policies change. Default: false>
region	string	optional	Default: us-east-1
parent_asset_id	string	mandatory	<The asset_id of the asset this log group is linked to, such as the database that sends audit data to the log group. This is usually the database that sends audit events to the log group. That database must have an AWS account as its parent. In some cases, the parent can be the AWS account directly.>
entitlement_enabled	boolean	Optional	If true, Entitlement Management system is enabled. Default: False
SonarGateway Asset Parameters:			
gateway_service	string	Required for SonarGateway	gateway-aws@<DB type>.service
audit_pull_enabled	boolean	Required for SonarGateway	<"true" or "false" Must be set to "true" to

			enable auditing for SonarGateway>
arn	string	Required for SonarGateway	<AWS ARN>
audit_type	string	optional	When combined with "content_type" field, it accepts all the "audit_type" fields allowed by the <'parent' asset "Server Type">
content_type	string	optional	Content type should be set to the desired <'parent' asset "Server Type">, which is the one that uses this asset as a destination for logs. <i>NOTE: The content_type field will take precedence on the lookup for parent_asset_id field when checking which server is sending logs to this asset.</i>
service_endpoint	string	optional	<URL for service endpoint>
credentials_endpoint	string	optional	<URL for credentials endpoint>
proxy	string	optional	<Proxy to connect>

SonarGateway Parameters

SonarGateway requires additional parameters for this asset type; required and optional parameters for SonarGateway are located at the bottom of the Asset Parameters table (shown above).

Audit Information (audit_info) Sub-document

This asset type does not support Audit Information.

Connection

Authentication Mechanisms

- **default:** Uses the parent's authentication mechanism.
- **parent_resource:** Uses the parent's connection client. Should not be used unless explicitly told to by Imperva.

Connection Parameters

connection type	field	mandatory / optional	value / <description>
default	Server Type	mandatory	AWS LOG GROUP
default	auth_mechanism	mandatory	default
default	Service Name	mandatory	<empty string>
default	asset_id	mandatory	<string>
default	Server Host Name	mandatory	<string>
default	parent_asset_id	mandatory	<string>
default	region	mandatory	<string>
default	reason	optional	<string: Used to differentiate connections that belong to the same asset. Expected value: ▪ sonargateway Defaults to None>
parent_resource	Server Type	mandatory	AWS LOG GROUP

parent_resource	auth_mechanism	mandatory	parent_resource
parent_resource	Service Name	mandatory	<empty string>
parent_resource	asset_id	mandatory	<string>
parent_resource	Server Host Name	mandatory	<string>
parent_resource	parent_asset_id	mandatory	<string>
parent_resource	region	mandatory	<string>
parent_resource	reason	optional	<string: Used to differentiate connections that belong to the same asset. Expected value: sonargateway Defaults to None>

SDM Connections

This asset type does not currently support SDM connections.

Test Connection

This asset type supports the Test Connection action.

Auto-Discovery

This asset type does not currently support auto-discovery.

Document generated by Confluence on May 29, 2026 02:42

Atlassian