

FUNDAÇÃO GETÚLIO VARGAS

MODELAGEM MATEMÁTICA

A Simplified version of Bitcoin, implemented in Agda

Student:

Guilherme Horta Alvares da
Silva

Professor:

Flávio Codeço Coelho



Abstract

A cryptocurrency is a digital currency that works in a decentralized way, without a central authority and its states are maintained through distributed consensus. It has an important role in society because it is money that is ruled only by algorithms and it avoids big central power, like banks and government.

Agda is a functional programming language with dependent types. It is also a proof assistant based on the preposition-as-types paradigm, like Coq. This language is useful to prove properties about the code.

We present in this work an explanation about what is cryptocurrencies and their principal characteristics, a brief explanation about Lambda Calculus, dependents types and Agda, and we present a cryptocurrency model made in this language. Most of all parts of Bitcoin are coded and typed in this model. Since transactions, transactions tree, ledger, block, and blockchain. Cryptographic functions are all postulated like hash functions, transformation functions of a private key into a public key and addresses. Besides, in this work, there is code that transforms and validates transactions from plain text into our model.

Keywords: verification; formal methods; Agda; smart contract; Blockchain; cryptocurrency; Bitcoin

Resumo

Uma criptomoeda é uma moeda digital que funciona de maneira descentralizada, sem uma autoridade central e seus estados são mantidos por meio de consenso distribuído. Ela tem um papel importante na sociedade, porque é um dinheiro que é governado apenas por algoritmos e evita grande centralização de poder, como a de bancos e a do governo.

Agda é uma linguagem de programação funcional com tipos dependentes. É também um assistente de prova baseado no paradigma de preposição como tipos, assim como Coq. Essa linguagem é útil para provar propriedades sobre o código.

Apresentamos nesse trabalho uma explicação sobre o que são criptomoedas e suas principais características, uma breve explicação sobre o Lambda Calculus, tipos de dependentes e Agda, e apresentamos um modelo de criptomoeda feito nessa linguagem. A maioria das partes do Bitcoin é codificada e programada nesse modelo. Desde transações, árvore de transações, *Ledger*, bloco e cadeia de blocos. As funções criptográficas, como funções hash, funções de transformação de uma chave privada em uma chave pública e seus endereços, são postuladas. Além disso, neste trabalho, há código que transforma e valida transações de um texto sem formatação para o nosso modelo.

List of Figures

1	Transaction	18
2	Bitcoin account	19
3	Verification and signature of transactions	20
4	Blockchain	20
5	Wallet	22
6	Record account	25
7	UTXO transactions	26

Contents

1	Introduction	5
1.1	Context	5
2	Objectives	7
2.1	History	7
2.2	Proposes	7
3	Relevant Background	8
3.1	Literature Review	8
3.2	Agda Introduction	9
3.2.1	Syntax	9
3.2.2	Lambda Calculus	11
3.2.3	Martin-Löf type theory	15
3.2.4	Types Constructors	16
3.3	Bitcoin	18
3.4	Ethereum	21
4	Development	24
4.1	Bitcoin UTXO	25
4.2	Crypto Functions	28
4.3	Transactions	29
4.3.1	Definitions	29
4.3.2	Raw Transaction	30
4.4	Transaction Tree	39
4.4.1	Definition	39
4.4.2	Raw Transaction Tree	43
4.4.3	Proofs	44
4.5	Ledger	49
4.6	Blockchain	50
4.6.1	Definition	50
4.6.2	Creation	52
5	Conclusion	58
5.1	Future work	58
	References	59

1 Introduction

1.1 Context

In 1983, David Chaum created ecash (Panurach, 1996) an anonymous cryptographic electronic money. This cryptocurrency use RSA blind signatures (Chaum, 1983) to spend transactions. Later, in 1989, David Chaum found an electronic money corporation called DigiCash Inc. It was declared bankruptcy in 1998.

Adam Back developed a proof-of-work (PoW) scheme for spam control, Hashcash (Back et al., 2002). To send an email, the hash of the content of this email plus a nonce has to have a numerical value smaller than a defined target. So, to create a valid email, the sender (miner) has to spend a considerable CPU resource on it. Because hash functions produce practically random values, so the miner has to guess a lot of nonce values before finding some nonce that makes the hash of the email less than the target value. This idea is used in Bitcoin proof of work because each block has a nonce guessed by the miner and the hash of the block has to be less than the target value.

Wei Dai propose b-money (Dai, 1998) for the first proposal for distributed digital scarcity. And Hal Finney created Bit Gold (Wallace, 2011), a reusable proof of work for hash cash for its algorithm of proof of work.

On 31 October 2008, Satoshi Nakamoto registered the website “bitcoin.org” and put a link for his paper (Nakamoto et al., 2008) in a cryptography mailing list. In January 2009, Nakamoto released the Bitcoin software as an open-source code. The identity of Satoshi Nakamoto is still unknown. Since that time, the total market of Bitcoin came to 330 billion dollars in 17 of December of 2018 when its value reached a historic peak of 20 thousand dollars.

Other cryptocurrencies like Ethereum (Wood et al., 2014), Monero (Noether, 2015) and ZCash (Hopwood, Bowie, Hornby, & Wilcox, 2016) were created after Bitcoin, but Bitcoin is still the cryptocurrency with the biggest market value.

Ethereum is a cryptocurrency that uses an account model instead of UTXO used in Bitcoin for its transaction data structure. It uses Solidity as its programming language for smart contracts which resembles Javascript, so it is easier to program in it than in the stack machine programming language of Bitcoin. Ethereum is now transitioning from proof of work (used in Bitcoin) to proof of stake which will be the default proof mechanism of Ethereum 2.0 and will be released in 3 of January of 2020.

Monero and ZCash are both cryptocurrencies that focus on fungibility, privacy and

decentralization. Monero uses an obfuscated public ledger, so anyone can send transactions, but nobody can tell the source, amount or destination. Zcash uses the concept of zero-knowledge proof called zk-SNARKs, which guarantee privacy for its users.

2 Objectives

2.1 History

Cryptocurrencies are used as money and used in smart contracts in a decentralized way. Because of that, it is not possible to revert a transaction or undo the creation of the smart contract. There is no legal framework or agent to solve a problem in case of the existence of a bug. Because of that, the formal proofs are necessary in the cryptocurrency protocol. So it can avoid big financial loss.

In the case of Bitcoin, if there is some problem in the source code, it is possible to fix it using soft or hard forks. In soft fork, there is an upgrade in the software that is compatible with the old software. So it is possible the existence of old and new nodes in the same Bitcoin network. In hard forks, all the nodes should be upgraded at the same time. Because the newer version is not compatible with the older one. So it is very dangerous to do this kind of fork. Therefore in Bitcoin, this kind of fork never happened.

For example, in Bitcoin, the uniqueness of transaction IDs were not guaranteed. To fix this problem, it should put the block number in the coinbase transaction. This kind of change was solved in a soft fork named SegWit.

In Ethereum, there was a bug in DAO smart contract. Because of that, malicious users exploited a vulnerability in it. The total loss of this exploit was 150 million dollars on this day. There was a hard fork to undo most of the transactions that exploited this contract. This kind of hard fork violates the principle that smart contracts should be ruled just by algorithms without any human intervention. Because of that, the Ethereum blockchain that has not done the fork becomes the Ethereum classic. It is the version of Ethereum that has never done a hard fork before.

2.2 Proposes

The objective of this work is to give a formal definition of what a cryptocurrency should be. There are some different definitions of a cryptocurrency in this work, but there are some formal proofs that they are the same.

In this work, it is possible to generate proofs transactions from transactions without proofs. This means that a user can send a simple transaction without he worried to have to prove that the transaction is right to put in the blockchain. In Bitcoin, it happened in the same way. Because the node has to verify the transactions.

3 Relevant Background

3.1 Literature Review

Beukema (Beukema, 2014) was one of the first to try to define a formal specification of Bitcoin. In this work, functions interfaces of Bitcoin and what they should do were defined. Most of these functions define how the Bitcoin Network protocol should be. In this work, he does not utilize any programming language with dependent types like Agda or CoQ. mCRL2, a specification programming language, was used.

Chaudhary and his team (Chaudhary, Fehnker, Van De Pol, & Stoelinga, 2015) have created a model of Bitcoin blockchain in the model checker UPPAAL. In his work, they calculate the probability of a malicious attack to succeed in doing a double spend. For a small number of blocks, it is easier to do this attack. Because of that, it is usually recommended that the user wait for more blocks confirmations after a big transaction.

Bastiaan (Bastiaan, 2015) showed a stochastic model of Bitcoin using continuous Markov chains. In his work, he proposes a way of avoiding a 51% attack in the network, using two-phase proof of work.

Orestis Melkonian (Melkonian, 2019) in his masters have done the formal specification of BitML (smart contract language) in Agda. This language can be compiled to Script, the smart contract language of Bitcoin.

Kosba (Kosba, Miller, Shi, Wen, & Papamanthou, 2016) in his work made a programming language called Hawk for smart contracts. This language uses formal methods to verify privacy using zero-knowledge proofs. Using this language, the programmer does not have to worry about implementing the cryptography, because the compiler generates automatically an efficient one.

Bhargavan (Bhargavan et al., 2016) translated Solidity and Ethereum bytecode into F*. He verified that the Ethereum DAO bug was caught in its translation. Nowadays, they have an implementation of Ethereum Virtual Machine (EVM) and Solidity in OCaml, but they want to have a full implementation of EVM in F* too.

Luu (Luu, Chu, Olickel, Saxena, & Hobor, 2016) built a symbolic execution tool named OYENTE to look for potential bugs. In his work, he found a lot of contracts with real bugs. One of these bugs was TheDAO bug, that caused a loss of 60 million dollars. He used Z3 to find a potentially dangerous path of code.

Anton Setzer (Setzer, 2018) also contributed to modeling Bitcoin. He coded in Agda the definitions of transactions and transactions tree of Bitcoin. Orestis Melkonian

starts to formalize Bitcoin Script.

My work tries to extend Anton Setzer model and makes it possible to use the Bitcoin protocol from inputs and outputs from plain text. For example, the user sends a transaction in plain text to the software and it validates if it is correct. To use the Anton Setzer model, the user has to send the data and the proof that are both valid.

3.2 Agda Introduction

Agda is a dependently typed functional language developed by Norell at Chalmers University of Technology as his Ph.D. Thesis. The current version of Agda is Agda 2.

3.2.1 Syntax

In Agda, *Set* is equal to type. In languages with dependent types, it is possible to create a function that returns a type.

```
bool→Set : (b : Bool) → Set
bool→Set b = if b then ℕ else Bool
```

After the function name, it is two colon (`:`) and the arguments of the function. It is closed by *(name_of_argument : type_of_argument)*. After all, there is one arrow and the type of the result of the function. This “if, then, else” is not a function built-in in Agda. It is a function defined this way *if_then_else_*.

So it is possible to use this function in the default way.

```
bool→Set-und : Bool → Set
bool→Set-und b = if_then_else_ b ℕ Bool
```

Or use the arguments inside the underscore.

```
bool→Set' : Bool → Set
bool→Set' b = if b then ℕ else Bool
```

The same notation can be done using just arrows without naming the arguments.

Because of dependent types, it is possible to have a type that depends on the input.

It is possible in Agda to do pattern match. So it breaks the input in cases.

```

boolean→Set : (b : Boolean) → Set
boolean→Set true = ℕ
boolean→Set false = Bool

```

To create a new type with a different pattern match, it is used the data constructor.

```

data Boolean : Set where
  true : Boolean
  false : Boolean

```

This is another example of *Data Set*, but it depends on the argument.

```

data Vec : ℕ → Set where
  [] : Vec zero
  _::_ : {size : ℕ} → ℕ → Vec size → Vec (suc size)

nil : Vec zero
nil = []

vec-one : Vec (suc zero)
vec-one = zero :: nil

```

Vector zero is a type of a vector of size zero, so the only option to construct it is the empty vector. It is constructed from the first constructor. Other types of vectors like *Vector 1* (vector of size one), *Vector 2*, ... can only be constructed by the second constructor. It takes as argument a natural number and a vector and returns a vector with the size of the last vector plus one.

Records are data types with just one case of pattern match.

```

record Person : Set where
  constructor person
  field
    name : String
    age : ℕ

agePerson : (person : Person) → ℕ
agePerson (person name age) = age

```

The constructor is the name of the data constructor.

Implicits terms are elements that the compiler is smart enough to deduce it. So it is not necessary to put it as an argument of the function.

```
id : {A : Set} (x : A) → A
id x = x
```

Implicits arguments are inside $\{\}$. In this example, the name of the Set (A) can not be omitted (like the second function version of boolean to set), because it is used to say that x is of type A .

In the case of the function *id*, the type of input can be deduced by the compiler. For example, the only type that *zero* can be is Natural.

```
zeroN : ℕ
zeroN = id zero
```

Functions in Agda can be defined in two ways

```
id-nat : ℕ → ℕ
id-nat x = x

id-nat' : ℕ → ℕ
id-nat' = λ x → x
```

In the first case, the arguments are before equal sign ($=$). In the second case, it is used the lambda abstraction that means the same thing.

3.2.2 Lambda Calculus

Lambda Calculus is a minimalist Turing complete programming language with the concept of abstraction, application using binding and substitution. For example, x is a variable, $(\lambda x.M)$ is an Abstraction and $(M N)$ is an Application.

In Lambda Calculus, there are two types of conversions α -conversion and β -reduction. In α -conversion, $(\lambda x.M[x]) \rightarrow (\lambda y.M[y])$. So in every free variable in M will be renamed from x to y . For $M[x] = x$, an α -conversion is $(\lambda x.x) \rightarrow (\lambda y.y)$

A free variable is every variable that is not bound outside. For example, $((\lambda x.\text{blue } x)\text{red } x)$. The **blue** x is binded for the **green** x , but the **red** x is not binded for any function. So the **red** x is a free variable.

In β -reduction, it replaces the all free for the expression in the application. The β -reduction of this expression $((\lambda x.M)N) \rightarrow (M[x := N])$. So if $M = x$, the

β -reduction will be $((\lambda x.x)N) \rightarrow N$. If $M = (\lambda x.x)x$, the β -reduction will be $(\lambda x.((\lambda x.x)x))N \rightarrow (\lambda x.x)N$.

Agda uses typed lambda calculus. So in an application $(M N)$, M has to be of type $A \Rightarrow B$ and N has to be of type A . $(\lambda(x : A).x)$ is of type $A \Rightarrow A$, because x is of type A .

```
id : {A : Set} → A → A
id = λ x → x
```

The simplest function is the identity function made in Agda.

```
id' : {A : Set} → A → A
id' x = x
```

This is another way of writing the same function.

```
true : {A : Set} → A → A → A
true x y = x
```

```
false : {A : Set} → A → A → A
false x y = y
```

This is how true and false are encoded in lambda calculus.

```
zero : {A : Set} → (A → A) → A → A
zero suc z = z
```

```
one : {A : Set} → (A → A) → A → A
one suc z = suc z
```

```
two : {A : Set} → (A → A) → A → A
two suc z = suc (suc z)
```

This is how naturals numbers are defined in lambda calculus. Look that the definition of zero looks like the definition of false.

```
isZero : {A : Set} → ((A → A) → A → A) → (A → A → A)
isZero n true false = n (λ _ → false) true
```

```
isZero-zero : {A : Set} → Result (isZero {A} zero)
isZero-zero = res (λ true false → true)
```

```
isZero-two : {A : Set} → Result (isZero {A} two)
isZero-two = res (λ true false → false)
```

Defining natural numbers in this way, it is possible to say if a natural number is zero or not.

```
plus : {A : Set} → ((A → A) → A → A)
      → ((A → A) → A → A)
      → ((A → A) → A → A)
plus n m = λ suc z → n suc (m suc z)
```

```
_+_ : {A : Set} → ((A → A) → A → A)
      → ((A → A) → A → A)
      → ((A → A) → A → A)
_+_ n m suc z = n suc (m suc z)
```

Plus is defined this way using lambda calculus.

```
one+one : {A : Set} → Result (_+_ {A} one one)
one+one = res (λ suc z → suc (suc z))
```

This is one example of the calculation of one plus one in Lambda Calculus.

```
emptyList : {A List : Set} → (A → List → List) → List → List
emptyList _ :: _ nil = nil
```

```
natList : {A List : Set} → (((A → A) → A → A) → List → List) → List → List
natList _ :: _ nil = one :: (two :: nil)
```

This is how lists are defined in Lambda Calculus.

```
sumList : {A List : Set} → Result (natList {A} {(A → A) → A → A} _+_ zero)
sumList = res (λ suc z → suc (suc (suc z)))
```

Substituting the cons operation of list per plus and nil list to zero, it is possible to calculate the sum of the list.

```
left : {A B C : Set} → A → (A → C) → (B → C) → C
left x f g = f x
```

```
right : {A B C : Set} → B → (A → C) → (B → C) → C
right x f g = g x
```

In this way, it is possible to define *Either*. It is one way to create a type that can be a Natural or a Boolean.

```
zero-left : {A B C : Set} → (((A → A) → A → A) → C) → (B → C) → C
zero-left = left zero
```

```
one-left : {A B C : Set} → (((A → A) → A → A) → C) → (B → C) → C
one-left = left one
```

```
false-right : {A B C : Set} → (A → C) → ((B → B → B) → C) → C
false-right = right false
```

```
true-right : {A B C : Set} → (A → C) → ((B → B → B) → C) → C
true-right = right true
```

In these examples, it is defined zero, one in left and false, true in right.

```
zero-isZero : {A : Set} → Result (zero-left {A} isZero id)
zero-isZero = res (λ true false → true)
```

```
one-isZero : {A : Set} → Result (one-left {A} isZero id)
one-isZero = res (λ true false → false)
```

```
false-id : {A : Set} → Result (false-right {(A → A) → A → A} isZero id)
false-id = res (λ true false → false)
```

```
true-id : {A : Set} → Result (true-right {(A → A) → A → A} isZero id)
true-id = res (λ true false → false)
```

Either is useful when defining one function that works for left and another that works for the right. If the natural number is zero, the function chosen is the left and if it is an identity, the function chosen is the right.

```
tuple : {A B C : Set} → A → B → (A → B → C) → C
tuple x y f = f x y
```

This way is how tuple is defined in Lambda Calculus.

```
zero-false : {A B C : Set} → (((A → A) → A → A) → (B → B → B) → C) → C
zero-false = tuple zero false
```

```
one-true : {A B C : Set} → (((A → A) → A → A) → (B → B → B) → C) → C
one-true = tuple one true
```

This is how is defined the tuple zero false and the tuple one true.

```
add-true : {A : Set} → ((A → A) → A → A) → (A → A → A) → ((A → A) → A → A)
add-true n b suc z = b (suc (n suc z)) (n suc z)
```

```
add-zero-false : {A : Set} → Result (zero-false {(A → A) → A → A} add-true)
add-zero-false = res (λ suc z → z)
```

```
add-one-true : {A : Set} → Result (one-true {(A → A) → A → A} add-true)
add-one-true = res (λ suc z → suc (suc z))
```

This is one way of defining a function that adds one to the argument if the first element of the tuple is true.

3.2.3 Martin-Löf type theory

Agda also provides proof assistants based on the intentional Martin-Löf type theory.

In Martin-Löf type theory, there are three finite types and five constructors types. The zero type contain zero terms. It is called empty type and it is written bot.

```
data ⊥ : Set where

⊥-elim : {A : Set} (bot : ⊥) → A
⊥-elim ()
```

The first type is the type with just one canonical term and it represents existence. It is called unit type and it is written top.

```
data ⊤ : Set where
  tt : ⊤
```

The second type contains two canonical terms. It represents a choice between two values.

```
data Either {l : Level} (A : Set l) (B : Set l) : Set l where
  left : (l : A) → Either A B
  right : (r : B) → Either A B

Either-elim : {l l2 : Level} {A B : Set l} {motive : (eab : Either A B) → Set l2}
  (target : Either A B)
```



```

  (on-left : (l : A) → (motive (left l)))
  (on-right : (r : B) → (motive (right r)))
  -----
  → motive target
  Either-elim (left l) onleft onright = onleft l
  Either-elim (right r) onleft onright = onright r

```

The Boolean type is defined using the Trivial type and the Either type.

```

Bool : Set
Bool = Either ⊤ ⊤

```

If statement is defined using booleans.

```

if _ then _ else _ : {l : Level} {A : Set} l (b : Bool) (tRes fRes : A) → A
if b then tRes else fRes = Either-elim b (λ _ → tRes) λ _ → fRes

```

3.2.4 Types Constructors

The sum-types contain an ordered pair. The second type can depend on the first type. It has the same meaning to exist.

```

data ∑ (A : Set) (B : A → Set) : Set where
  ⟨_,_⟩ : (x : A) → B x → ∑ A B

∑-elim : ∀ {A : Set} {B : A → Set} {C : Set}
  → (∀ x → B x → C)
  → ∑ A B
  -----
  → C
∑-elim f ⟨ x , y ⟩ = f x y

```

The π -types contain functions. So given an input type, it will return an output type. It has the same meaning as a function:

```

∀-elim : ∀ {A : Set} {B : A → Set}
  (L : ∀ (x : A) → B x)
  (M : A)
  -----

```

$$\rightarrow B M$$

$$\forall\text{-elim } L M = L M$$

In Inductive types, it is a self-referential type. Naturals numbers are examples of that:

```
data ℕ : Set where
  zero : ℕ
  suc : ℕ → ℕ
```

Other data structs like a linked list of natural numbers, trees, graphs are inductive types too.

Proofs in inductive types are made by induction.

```
ℕ-elim : (target : ℕ) (motive : (ℕ → Set)) (base : motive zero)
  (step : (n : ℕ) → motive n → motive (suc n) ) → motive target
ℕ-elim zero motive base step = base
ℕ-elim (suc target) motive base step = step target (ℕ-elim target motive base step)
```

Universe types are created to allow proofs written in all types. For example, the type of *Nat* is *U0*.

It looks like CoQ, but does not have tactics. Agda is a total language, so it is guaranteed that the code always terminal and coverage all inputs. Agda needs it to be a consistent language.

Agda has inductive data types that are similar to algebraic data types in non-dependently typed programming language. The definition of Peano numbers in Agda is:

```
data ℕ : Set where
  zero : ℕ
  suc : ℕ → ℕ
```

Definitions in Agda are done using induction. For example, the sum of two numbers in Agda:

```
_+_ : ℕ → ℕ → ℕ
zero +_ m = m
suc n +_ m = suc (n + m)
```

In Agda, because of dependent types, it is possible to make some restrictions in types that are not possible in other languages. For example, get the first element of




Figure 1: Transaction

a vector. For it, it is necessary to specify in the type that the vector should have a size greater or equal then that one.

$$\begin{aligned} \text{head} &: \{A : \text{Set}\} \{n : \mathbb{N}\} (\text{vec} : \text{Vector } A \ (\text{suc } n)) \rightarrow A \\ \text{head} &(x :: \text{vec}) = x \end{aligned}$$

Another good example is that in the sum of two matrices, they should have the same dimensions.

$$\begin{aligned} _ + _ &: \{m \ n : \mathbb{N}\} (P \ Q : \text{Matrix } \mathbb{N} \ m \ n) \rightarrow \text{Matrix } \mathbb{N} \ m \ n \\ _ + _ &= _ \\ (vx :: P) + (vy :: Q) &= (vx + vy) :: (P + Q) \end{aligned}$$

3.3 Bitcoin

The Bitcoin was made to be a peer to peer electronic cash. It was made in one way that users can save and verify transactions without the need of a trusted party. Because of that no authority or government can block the Bitcoin.

Transactions in Bitcoins (like in Figure 1) are an array of input of previous transactions and an array of outputs. Each input and output is an address, each address is made from a public key that is made from a private key.




Figure 2: Bitcoin account

A private key is a big number. It is so big that it is almost impossible to generate two identical private keys.

The public key is generated from the private key (like in Figure 2 where account number is $f(p)$), but a private key can not be generated from a public key.

The mining transaction does require an input. For each input of the transaction, it is necessary a signature signed with a private key (like in Figure 2 where signature is $f(p, t)$) to prove the ownership of the Bitcoins. With the message and the signature, it is possible to know that the owner of the private key that generates the public key signed this message.

With the signature and the public key, it is not possible to know the private key. In Figure 2, the checker is a $f(t, s, a)$. So because of that, the owner of the private key can sign several messages without anyone knows his private key.

Transactions (shown in Figure 3) are grouped in a block (shown in Figure 4). Each block contains in its header the timestamp of its creation, the hash of the block, the previous hash and a nonce. A nonce is an arbitrary value that the miner has to choose to make the hash of the block respect some specific characteristics.

Each block has a size limit of 1 MB. Because of that, Bitcoin forms a blockchain (a chain of blocks). Each block should be created at an average of 10 minutes. This time was chosen because 10 minutes is enough to propagate the block throughout the world. To make the blockchain tamper-proof, there is a concept called proof of




Figure 3: Verification and signature of transactions




Figure 4: Blockchain

work in Bitcoin. So the miner has chosen a random value as nonce that makes the hash of the block less than a certain value. This value is chosen in a way that each block should be generated on 10 minutes on average. If the value is too low, miners will take more time to find a nonce that makes the hash block less than it. If it is too high, it will be easier to find a nonce and they will find it faster.

When two blocks are mined in nearly the same time, there are two valid blockchains. It is because the last block in both blockchains is valid but different. Because of this problem, in the Bitcoin protocol, the largest chain is always the right chain. While two valid chains have the same size, it is not possible to know which chain is the right. This situation is called fork and when it happens, it is necessary to wait to see in which chain the new block will be.

In Bitcoin, there is a possibility of a 51% attack. It happens when some miner, with more power than all network, mine secretly the blocks. So if the main network has 50 blocks, the miner could produce hidden blocks from 46 to 55 and he would have 10 hidden blocks from the network. When he shows their hidden blocks, his chain becomes the valid chain, because it is bigger. So all transactions from the previous blockchain from 46 to 50 blocks become invalid. Because of that, when someone makes a big transaction in the blockchain, it is a good idea to wait more time. So it is becoming harder and harder to make a 51% with more time. Bitcoin has the highest market value nowadays, so attacking the Bitcoin network is very expensive. Nowadays, this kind of attack is more common in new altcoins.

Wallet (shown in Figure 5) is software that tracks all transactions that the users received and sent. It also makes new transactions from previously received transactions.

3.4 Ethereum

Ethereum differs from Bitcoin in having an Ethereum Virtual Machine (EVM) to run script code. EVM is a stack machine and Turing complete while Bitcoin Script is not (it is impossible to do loops and recursion in Bitcoin).

Transactions in Bitcoin are all stored in the blockchain. In Ethereum, just the hash of it is stored in it. So it is saved in the off-chain database. Because of that, it is possible to save more information in Ethereum Blockchain.

In Bitcoin, the creator of the contract to pay the amount proportional to its size. In Ethereum, it is different, there is a concept of gas. Each smart contract in Ethereum is made by a series of instructions. Each instruction consumes different computational effort. Because of that, in Ethereum, there is a concept of gas, that




Figure 5: Wallet

measure how much computational effort each instruction needs. So in each smart contract, it is well known how much computational effort will be necessary to run it and it is measured in gas. Because computational effort is a scarce resource, to execute the smart contract, it is necessary to pay an amount in Ether for each gas to the miner run it. Smart contracts that pay more ether per gas run first because the miner will want to have the best profit and they will pick them. If the amount of ether per gas paid is not high enough, the contract will not be executed, because some other contracts pay more that will be executed instead of this one.

Because Ethereum has its EVM with more instructions than Bitcoin and it is Turing Complete, it is considered less secure. Ethereum has its high-level programming language called Solidity that looks like Javascript.

4 Development

Figure 6: Record account

4.1 Bitcoin UTXO


The UTXO model used in Bitcoin and the account model used in Ethereum are the two most used kinds of data structures to model accounts records and savings states.

In the account model, it is saved the address and the balance of each address (like in Figure 6). For example, the data structure will look like this $[(0xabc01, 1.01), (0xabc02, 2.02)]$. So the address $0xabc01$ has 1.01a of balance and the address $0xabc02$ has 2.02 of balance. In this way, it is possible to easily know how much balance each address has, but it is not possible to know how they got in this state.

In the UTXO model (shown in Figure 7), each transaction is saved in the transaction tree. Every transaction is composed of multiples inputs and multiples outputs. But all inputs have to never been spent before.

Because of that, in the UTXO model, it is easy to make a new transaction from the previous one, but it is harder to know how much each one has. The wallet that calculate how much balance each address has.

In the account model, there could be one kind of vulnerability that is less probable



Triple-Entry Bookkeeping (Transaction-To-Transaction Payments) As Used By Bitcoin

Figure 7: UTXO transactions

to happen in UTXO model. Because there is an undesirable intermediary state that there is some address without balance while another has not already received his money.

For example:

bobBalance -= 1

Intermediary State

aliceBalance += 1

In the account model, it is straight forward to know how much balance each address has. In the UTXO model, this calculation is made off-chain. It can be a good thing, because each user has more privacy.

4.2 Crypto Functions

The first thing that we define is the crypto functions that will be needed to make the cryptocurrency. Messages can be defined in multiple ways, one array of bytes, one string or a natural number. Messages in this context means some data.

The private key is a number, a secret that someone has. In Bitcoin, the private key is a 256-bit number. A private key is used to signed messages.

The public key is generated from a private key. But getting the private key from a public key is impossible. To verify who signed a message with a private key, he has to show the public key.

Hash is an injection function (the probability of collision is very low). The function is used from a big domain to a small domain. For example, a hash of big file (some GBs) is an integer of just some bytes. It is very useful to prove for example that 2 files are equal. If the hash of two files are equal, so the files are equal. It is used in torrents clients, so it is safe to download a program to untrusted peers, just have to verify if the hash of the file is equal to the hash of the file wanted.

These functions can be defined, but it is not the purpose of this theses. So they will be just postulates.

```

postulate _priv≡pub_ : PrivateKey → PublicKey → Set
postulate publicKey2Address : PublicKey → Address
postulate Signed : Msg → PublicKey → Signature → Set
postulate Signed? : (msg : Msg) (pk : PublicKey) (sig : Signature)
    → Dec $ Signed msg pk sig
postulate hashMsg : Msg → Hashed
postulate hash-inj : ∀ m n → hashMsg m ≡ hashMsg n → m ≡ n

record SignedWithSigPbk (msg : Msg)(address : Address) : Set where
  field
    publicKey : PublicKey
    pbkCorrect : publicKey2Address publicKey ≡ address
    signature : Signature
    signed : Signed msg publicKey signature

```

4.3 Transactions

4.3.1 Definitions

In Bitcoin, there are some transactions. In each transaction, there are multiple inputs and outputs. Each input is named `TXFieldWithId`. The input of one transaction is the output of another transaction. Firsts outputs are generated from coinbase transaction (there is just one of this transaction at each block). Coinbase transactions are the miner reward.

```
data VectorOutput : (time : Time) (size : Nat) (amount : Amount) → Set where
  el : ∀ {time : Time}
    (tx : TXFieldWithId)
    (sameId : TXFieldWithId.time tx ≡ time)
    (elStart : TXFieldWithId.position tx ≡ zero)
    → VectorOutput time 1 (TXFieldWithId.amount tx)

cons : ∀ {time : Time} {size : Nat} {amount : Amount}
  (listOutput : VectorOutput time size amount)
  (tx : TXFieldWithId)
  (sameId : TXFieldWithId.time tx ≡ time)
  (elStart : TXFieldWithId.position tx ≡ size)
  → VectorOutput time (suc size) (amount + TXFieldWithId.amount tx)
```

Vector output is the vector of outputs transactions. It is a non-empty vector. In its representation, it is possible to know in what time it was created (time is the position of they in all transactions), what is his size (quantity of outputs fields) and the total amount spent in this transaction,

`elStart` is proof that the position of `TXFieldWithId` is the last one. It is used after to specify which input is in the transaction.

```
record TXSigned
  {time    : Time}
  {outSize : Nat}
  {outAmount : Amount}
  (inputs  : List TXFieldWithId)
  (outputs : VectorOutput time outSize outAmount) : Set where
  constructor txsig
  field
    nonEmpty : NonNil inputs
```

```

signed : All
  (λ input →
    SignedWithSigPbk (txEls→MsgVecOut input outputs)
      (TXFieldWithId.address input))
    inputs
in≥out : txFieldList→TotalAmount inputs ≥ outAmount

```

A signed transaction is composed of a non-empty list of inputs and outputs. For each input, there is a signature that confirms that he accepted every output in the list of outputs. And in the transaction, there is proof that the total amount of money in all inputs are bigger than the total amount of outputs. The remainder will be used by the miner.

4.3.2 Raw Transaction

Raw transactions are transactions without any explicit dependent type. Here the definition of *raw signed transaction*:

```

record RawTXSigned : Set where
  field
    inputs  : List TXFieldWithId
    outputs : List TXFieldWithId
    txSig   : TXSignedRawOutput inputs outputs

```

Raw signed transactions is a record with *inputs*, *outputs* and the signature of *inputs* and *outputs*.

The definition of *Raw Input*:

```

record RawInput : Set where
  field
    time      : Time
    position  : Nat
    amount    : Amount
    msg       : Msg
    signature  : Signature
    publicKey : PublicKey

```

In each input, it is necessary to know the time, the position of it in the transaction, the amount spent, its message, the signature, and its public key. The signature is

the signature of the message. And the message is usually related to the amount spent in each output.

The definition of *raw transaction*:

```
record RawTransaction : Set where
  field
    inputs  : List RawInput
    outputs : List TXField
```

It is all inputs and all outputs.

The definition of *Raw TX*:

```
data RawTX : Set where
  coinbase : (tx : RawTXCoinbase) → RawTX
  normalTX : (tx : RawTransaction) → RawTX
```

The definition of *raw transaction coinbase*:

```
record RawTXCoinbase : Set where
  field
    outputs : List TXFieldWithId
```

The definition of *raw Vector Output*:

```
record RawVecOutput (outputs : List TXFieldWithId) : Set where
  field
    time      : Time
    outSize   : Nat
    amount    : Amount
    vecOut    : VectorOutput time outSize amount
    proof     : VectorOutput → List vecOut ≡ outputs
```

It has the time, its size, the total amount, the *vector output* and proof that this vector is the same as the list of outputs of this type.

The definition of the record that every input transaction is signed in a given time:

```
record TXSigAll (time : Time) (allInputs : List TXFieldWithId) : Set where
  field
    outSize : Nat
```



```

sub      : SubList allInputs
amount  : Amount
outputs : VectorOutput time outSize amount
signed  : TXSigned (sub→list sub) outputs

```

It has the size of vector output, the sublist of all inputs, the total amount, the *vector output* and a proof that all sublist of inputs are signed.

To get the proof that the transaction is signed from the raw transaction:

```

rawTXSigned→TXSigAll : (time : Time) (allInputs : List TXFieldWithId)
  (rawTXSigned : RawTXSigned) → Maybe $ TXSigAll time allInputs
rawTXSigned→TXSigAll time allInputs
  record { outputs = outputs ; txSig = txSig }
  with listTXField→VecOut outputs
... | nothing = nothing
... | just record { outSize = outSize ; vecOut = vecOut ;
  proof = proofVecOut } with list→subProof allInputs (txSigInput txSig)
...   | nothing = nothing
...   | just record { sub = sub ; proof = proofSub }
      with vecOutTime vecOut == time
...     | no _ = nothing
...     | yes refl = just $ record
  { outSize = outSize ; sub = sub ; outputs = vecOut ; signed = txSigRes }
  where
    txSigRes : TXSigned (sub→list sub) vecOut
    txSigRes rewrite proofSub = txAux
    where
      txAux : TXSigned (txSigInput txSig) vecOut
      txAux rewrite proofVecOut = TXRaw→TXSig vecOut proofVecOut txSig

```

It has to validate first that the *list of outputs* is a valid *Vector Output*. Second, it validates if the signature of the inputs are valid with the *raw signed transaction*. In the last case, it validates if the time of the *vector output* is equal of the time of this transaction. If all conditions match, it returns a proven signed transaction. If not, it returns nothing.

This function transforms a *raw transaction* into a *signed transaction*:

```

TXRaw→TXSig : {inputs : List TXFieldWithId}
  {outputs : List TXFieldWithId}
  {time : Time}

```

```

{outSize : Nat}
{outAmount : Amount}
(vecOut : VectorOutput time outSize outAmount)
(out≡vec : VectorOutput→List vecOut ≡ outputs)
(txSig : TXSignedRawOutput inputs outputs)
→ TXSigned inputs vecOut
TXRaw→TXSig {inputs} {outputs} {_} {_} {outAmount} vecOut out≡vec
record { nonEmpty = (nonEmptyInp , nonNilOutputs) ;
  signed = signed ; in≥out = in≥out } =
record { nonEmpty = nonEmptyInp ;
  signed = allSigned signed ; in≥out = in≥outProof }
where
  vecOut≡ListAmount :
    {outAmount : Amount}
    {time : Time}
    {outSize : Nat}
    (outputs : List TXFieldWithId)
    (vecOut : VectorOutput time outSize outAmount)
    (out≡vec : VectorOutput→List vecOut ≡ outputs)
    → outAmount ≡ txFieldList→TotalAmount outputs
  vecOut≡ListAmount [] (el tx sameId elStart) ()
  vecOut≡ListAmount [] (cons vecOut tx sameId elStart) ()
  vecOut≡ListAmount _
    (el record { time = time ; position = position ; amount = zero ;
      address = address } sameId elStart) refl = refl
  vecOut≡ListAmount _ (el record { time = time ;
    position = position ; amount = (suc amount) ;
    address = address } sameId elStart) refl = refl
  vecOut≡ListAmount _ (cons vecOut tx sameId elStart) refl =
    let vecProof = vecOut≡ListAmount (VectorOutput→List vecOut) vecOut refl
    in cong (λ x → x + TXFieldWithId.amount tx) vecProof

in≥outProof : txFieldList→TotalAmount inputs ≥ outAmount
in≥outProof rewrite vecOut≡ListAmount outputs vecOut out≡vec = in≥out

sameMessage :
  {outAmount : Amount}
  {time : Time}
  {outSize : Nat}
  (outputs : List TXFieldWithId)

```

```

    (input    : TXFieldWithId)
    (nonNilOut : NonNil outputs)
    (vecOut   : VectorOutput time outSize outAmount)
    (out≡vec  : VectorOutput→List vecOut ≡ outputs)
    → txEls→Msg input outputs (nonEmptyInp , nonNilOut) ≡
        txEls→MsgVecOut input vecOut
  sameMessage _ _ outNotNil (el tx sameId elStart) refl = refl
  sameMessage _ _ outNotNil (cons (el tx1 sameId1 elStart1)
    tx sameId elStart) refl = refl
  sameMessage _ input unit (cons (cons vecOut tx2 sameId2 elStart2)
    tx1 sameId1 elStart1) refl =
    let msgRest = sameMessage _ input unit (cons vecOut tx2 sameId2 elStart2) refl
  in cong (λ x → TX→Msg (removeld tx1) +msg x) msgRest

sigPub : {input : TXFieldWithId}
  (sign : SignedWithSigPbk
    (txEls→Msg input outputs (nonEmptyInp , nonNilOutputs))
    (TXFieldWithId.address input))
  → SignedWithSigPbk (txEls→MsgVecOut input vecOut)
    (TXFieldWithId.address input)
sigPub {input} sign =
  let msgEq = sameMessage outputs input nonNilOutputs vecOut out≡vec
  in transport (λ msg → SignedWithSigPbk msg
    (TXFieldWithId.address input)) msgEq sign

allSigned : {inputs : List TXFieldWithId}
  (allSig : All
    (λ input →
      SignedWithSigPbk
        (txEls→Msg input outputs (nonEmptyInp , nonNilOutputs))
        (TXFieldWithId.address input)) inputs)
  → All
    (λ input →
      SignedWithSigPbk (txEls→MsgVecOut input vecOut)
        (TXFieldWithId.address input))
    inputs
allSigned {[]} allSig = []
allSigned {input :: inputs} (sig :: allSig) = (sigPub sig) :: (allSigned allSig)

```

The first function returns a proof that the *vector output* is equal to the total amount of the *list of transactions*. It is impossible that the *vector output* is equal to an empty

list. In case that the list has just one element, it just has to return *refl*. The another case, it is done recursively.

The proof that the amount of input transaction is greater than the amount of output is just a rewrite from the previous proof.

The function of *same message* returns a proof that the message of *raw transaction* is the same as the message of the *vector output*. In case that *vector output* has just size one or two, it is a trivial case. The other cases are doing it recursively.

sigPub is another function that returns a proof that an input message is signed. It validates it with its public key.

The last function returns a proof that every input was signed. It is done in a recursive way using the function *sigPub*.

This is the function that transforms a list of transactions into a possible *vector output*:

```

listTXField→VecOut : (txs : List TXFieldWithId) → Maybe $ RawVecOutput txs
listTXField→VecOut [] = nothing
listTXField→VecOut (tx :: txs) with listTXField→VecOut txs
... | just vouts = addElementRawVec tx txs vouts
where
  addElementInVectorOut : {time : Time} {outSize : Nat} {amount : Amount}
    (tx : TXFieldWithId)
    (vecOut : VectorOutput time outSize amount)
    → Maybe $ VectorOutput time (suc outSize)
      (amount + TXFieldWithId.amount tx)
  addElementInVectorOut {time} {outSize} tx vecOut
    with TXFieldWithId.time tx == time
... | no ¬p = nothing
... | yes refl with TXFieldWithId.position tx == outSize
... | no ¬p = nothing
... | yes refl = just $ cons vecOut tx refl refl

addElementRawVec : (tx : TXFieldWithId)
  (outs : List TXFieldWithId) (vecOut : RawVecOutput outs)
  → Maybe $ RawVecOutput (tx :: outs)
addElementRawVec tx outs record { time = time ; outSize = outSize ;
                                     vecOut = vecOut ; proof = proof }
  with addElementInVectorOut tx vecOut
... | nothing = nothing

```

```

... | just vec with TXFieldWithId.time tx == time
... | no _ = nothing
... | yes refl with TXFieldWithId.position tx == outSize
...   | no _ = nothing
...   | yes refl = just $ record { time = time ; outSize = suc outSize
    ; vecOut = cons vecOut tx refl refl ; proof = cong (_ :: _ tx) proof }
... | nothing with txs == []
...   | no _ = nothing
...   | yes p rewrite p = createVecOutsize tx

```

The list has to be at least with a size one. Because the *vector output* can not be empty. To add one element into the vector, it has to verify if the time is equal to the first time. Another verification is that the informed position in the vector is right. If all validations are right, it returns the vector output. If it is not, it returns nothing.

The definition of the function that transform a *raw transaction* into a *signed transaction*:

```

raw→TXSigned : ∀ (time : Time) (ftx : RawTransaction)
  → Maybe RawTXSigned
raw→TXSigned time record { inputs = inputs ; outputs = outputs }
  with NonNil? inputs
... | no _ = nothing
... | yes nonNilInp with NonNil? outputs
... | no _ = nothing
... | yes nonNilOut = ans
where
  inpsField : List TXFieldWithId
  inpsField = map raw→TXField inputs

  outsField : List TXFieldWithId
  outsField = addId zero time outputs

  nonNilMap : ∀ {A B : Set} {f : A → B} (lista : List A)
    → NonNil lista → NonNil (map f lista)
  nonNilMap [] ()
  nonNilMap (_ :: _) nla = unit

  nonNilImpTX : NonNil inpsField
  nonNilImpTX = nonNilMap inputs nonNilInp

```

```

nonNilAddId : {time : Time} (outputs : List TXField)
  (nonNilOut : NonNil outputs)
  → NonNil (addId zero time outputs)
nonNilAddId [] ()
nonNilAddId (_ :: outputs) nonNil = nonNil

nonNilOutTX : NonNil outsField
nonNilOutTX = nonNilAddId outputs nonNilOut

nonEmpty : NonNil inpsField × NonNil outsField
nonEmpty = nonNilImpTX , nonNilOutTX

All?Signed : (inputs : List RawInput) →
  Maybe (All (λ input → SignedWithSigPbk
    (txEls→Msg input outsField nonEmpty)
    (TXFieldWithId.address input)) (map raw→TXField inputs))
All?Signed [] = just []
All?Signed (input :: inputs)
  with Signed? (txEls→Msg (raw→TXField input) outsField nonEmpty)
  (RawInput.publicKey input) (RawInput.signature input)
... | no _ = nothing
... | yes signed with All?Signed inputs
... | nothing = nothing
... | just allInputs = just $ (record
  { publicKey = RawInput.publicKey input
  ; pbkCorrect = refl
  ; signature = RawInput.signature input
  ; signed = signed
  }) :: allInputs

in≥out : Dec $ txFieldList→TotalAmount inpsField ≥
  txFieldList→TotalAmount outsField
in≥out = txFieldList→TotalAmount inpsField ≥?p
  txFieldList→TotalAmount outsField

ans : Maybe RawTXSigned
ans with All?Signed inputs
... | nothing = nothing
... | just signed with in≥out
... | no _ = nothing

```

```
... | yes in>out = just $ record { inputs = inpsField ; outputs = outsField ;
  txSig = record { nonEmpty = nonEmpty ; signed = signed ; in≥out = in>out } }
```

The first validation that the function does is verifying that the outputs are not empty. Another validation is verifying if the amount spent on inputs is greater than the amount of the outputs. The function *Signed?*, defined in the crypto library, validates if the message was signed with the input. After, it validates if all inputs are signed. If all validations are right, it returns the *raw transaction signed*. If it is not, it returns nothing.

4.4 Transaction Tree

4.4.1 Definition

The transaction tree is one of the most important data structures in Bitcoin. In the transaction tree, there are all unspent transaction outputs (UTXO). In every new transaction, the UTXOs used as input is removed from the transaction tree.

```
mutual
data TXTree : (time : Time) (block : Nat)
  (outputs : List TXFieldWithId)
  (totalFees : Amount)
  (qtTransactions : tQtTxs) → Set where

genesisTree : TXTree (nat zero) zero [] zero zero
txtree :
  {block : Nat} {time : Time}
  {outSize : Nat} {amount : Amount}
  {inputs : List TXFieldWithId}
  {outputTX : VectorOutput time outSize amount}
  {totalFees : Amount} {qtTransactions : tQtTxs}
  (tree : TXTree time block inputs totalFees qtTransactions)
  (tx : TX {time} {block} {inputs} {outSize} tree outputTX)
  (proofLessQtTX :
    Either
      (IsTrue (lessNat (finToNat qtTransactions) totalQtSub1))
      (isCoinbase tx))
  → TXTree (sucTime time)
    (nextBlock tx)
    (inputsTX tx ++ VectorOutput→List outputTX)
    (incFees tx) (incQtTx tx proofLessQtTX)
```

In this implementation, time is the number of transactions in TXTree. Block is related to which block the transaction tree is. After every new coinbase transaction (the miner transaction), the block size increment in one quantity. Total fees are how much the miner will have in fee of transactions if he makes a block with these transactions. Quantity of transactions is how many transactions there are in the current block. The type is tQtTxs instead of a natural number because, in this implementation, each block can have a number maximum of transactions. In Bitcoin, it is different, each block has a limit size in space of 1 MB.

Genesis tree is the first case. It is when the cryptocurrency was created. *txtree* is created from another tree. *proofLessQtTX* is proof that the last transaction tree has its block size less than the maximum block size minus one or it is a coinbase transaction. It is because it is necessary to verify the size of the last *txtree* so it will not have the size greater than the maximum.

```

data TX {time : Time} {block : Nat} {inputs : List TXFieldWithId}
  {outSize : Nat} {outAmount : Amount}
  {totalFees : Nat} {qtTransactions : tQtTx}
: (tr : TXTree time block inputs totalFees qtTransactions)
  (outputs : VectorOutput time outSize outAmount) → Set where
normalTX :
  (tr : TXTree time block inputs totalFees qtTransactions)
  (SubInputs : SubList inputs)
  (outputs : VectorOutput time outSize outAmount)
  (txSigned : TxsSigned (sub→list SubInputs) outputs)
  → TX tr outputs
coinbase :
  (tr : TXTree time block inputs totalFees qtTransactions)
  (outputs : VectorOutput time outSize outAmount)
  (pAmountFee : outAmount out≡Fee totalFees +RewardBlock block)
  → TX tr outputs

```

TX is related to the transaction done in the cryptocurrency. There are two kinds of transaction. Coinbase transaction is the transaction done by the miner. In coinbase, they have just outputs and do not have any input. *pAmountFee* is proof that the output of the coinbase transaction is equal to the total fees plus a block reward.

Another kind of transaction is the *normalTX*, a regular transaction. *SubInputs* are a sub-list of all unspent transaction outputs of the previous transaction tree. Outputs are the new unspent transaction from this transaction. So who receives the amount from this transaction can spend it after. *TxsSigned* is the signature that proves that every owner of each input approve this transaction. In *TxsSigned*, there is proof that the output amount is greater than the input amount too.

```

isCoinbase : ∀ {block : Nat} {time : Time}
  {inputs : List TXFieldWithId}
  {outSize : Nat} {amount : Amount}
  {totalFees : Nat} {qtTransactions : tQtTx}
  {tr : TXTree time block inputs totalFees qtTransactions}
  {outputs : VectorOutput time outSize amount}

```

```

(tx : TX {time} {block} {inputs} {outSize} tr outputs)
→ Set
isCoinbase (normalTX _ _ _ _) = ⊥
isCoinbase (coinbase _ _ _) = ⊤

```

This function just returns trivial type if coinbase and bot type if not.

```

nextBlock : ∀ {block : Nat} {time : Time}
  {inputs : List TXFieldWithId}
  {outSize : Nat} {amount : Amount}
  {totalFees : Nat} {qtTransactions : tQtTxs}
  {tr : TXTree time block inputs totalFees qtTransactions}
  {outputs : VectorOutput time outSize amount}
  (tx : TX {time} {block} {inputs} {outSize} tr outputs)
  → Nat
nextBlock (normalTX genesisTree _ _ _) = zero
nextBlock {block} (normalTX (txtree _ (normalTX _ _ _ _) _) _ _ _) = block
nextBlock {block} (normalTX (txtree _ (coinbase _ _ _) _) _ _ _) = suc block
nextBlock (coinbase genesisTree _ _) = zero
nextBlock {block} (coinbase (txtree _ (normalTX _ _ _ _) _) _ _ _) = block
nextBlock {block} (coinbase (txtree _ (coinbase _ _ _) _) _ _ _) = suc block

```

If it is a normal transaction, the block continues the same. If it is a coinbase transaction, the next transaction will be in a new block.

```

incQtTx : ∀ {qtTransactions : tQtTxs}
  {block : Nat} {time : Time}
  {inputs : List TXFieldWithId}
  {outSize : Nat} {amount : Amount}
  {totalFees : Nat}
  {tr : TXTree time block inputs totalFees qtTransactions}
  {outputs : VectorOutput time outSize amount}
  (tx : TX {time} {block} {inputs} {outSize} tr outputs)
  (proofLessQtTX :
    Either
      (IsTrue (lessNat (finToNat qtTransactions) totalQtSub1))
      (isCoinbase tx))
  → tQtTxs
incQtTx {qt} (normalTX _ _ _ _) (left pLess) =
  natToFin (suc (finToNat qt)) {{pLess}}

```

```

incQtTx {qt} (normalTX _ _ _ _) (right ())
incQtTx (coinbase _ _ _) _ = zero

```

This function is to increment the number of transactions in the block. It has to receive proof that the quantity of transaction that was before this new transaction was less than then the maximum quantity of transactions allowed. So it is guaranteed that the number of transactions will never be greater than the maximum allowed. If it is a coinbase transaction, it will be a new block. So the number of transactions starts being zero.

```

incFees : ∀ {block : Nat} {time : Time}
  {inputs : List TXFieldWithId}
  {outSize : Nat} {amount : Amount}
  {totalFees : Amount} {qtTransactions : tQtTxs}
  {tr : TXTree time block inputs totalFees qtTransactions}
  {outputs : VectorOutput time outSize amount}
  (tx : TX {time} {block} {inputs} {outSize} tr outputs)
  → Amount
incFees {[]} {[]} {[]} {[]} {amount} {totalFees}
  (normalTX _ SubInputs _ (txsig _ _ in ≥ out)) =
  txFieldList→TotalAmount (sub→list SubInputs)
  - amount p ≥ in ≥ out
  + totalFees
incFees (coinbase tr outputs _) = zero

```

IncFee is a function that increments how much fee the miner will receive. If it is a coinbase transaction, the fee will be received by the miner, so the next miner will not receive this previous fee. Because of that, the new fee will start from zero. If it is a normal transaction, the newest fee will be the amount of input of the transaction minus the output of this transaction plus the last fee of previous transactions.

```

_out≡Fee_+RewardBlock_ : (amount : Amount)
  (totalFees : Amount)
  (block : Nat) → Set
amount out≡Fee totalFees +RewardBlock block =
  amount ≡ totalFees + blockReward block

```

outFee+RewardBlock is proof that the amount of output transactions is equal to total fees of other transactions plus the block reward.

4.4.2 Raw Transaction Tree

The raw transaction tree is the tree without the explicit types. Here, the definition:

```
record RawTXTree : Set where
  field
    time      : Time
    block     : Nat
    outputs   : List TXFieldWithId
    totalFees : Amount
    qtTransactions : tQtTx
    txTree    : TXTree time block outputs totalFees qtTransactions
```

A good utility of raw data types is that it is not necessary to add type arguments in functions. Here, a function that adds a transaction to a transaction tree. If this transaction is compatible with the transaction tree, it returns a new transaction tree. If it is not compatible, it returns nothing. A better solution is a proof that this transaction is invalid with the transaction tree instead of nothing. But defining what is an invalid transaction can be tricky.

```
addTransactionTree : (txTree : RawTXTree) (tx : RawTX) → Maybe RawTXTree
addTransactionTree record { time = time ; block = block ; outputs = outputs ;
  qtTransactions = qtTransactions ; totalFees = totalFees ; txTree = txTree }
  (coinbase record { outputs = outputsTX }) with listTXField→VecOut outputsTX
... | nothing = nothing
... | just record { time = timeOut ; outSize = outSize ; vecOut = vecOut }
  with vecOut→Amount vecOut == totalFees + blockReward block
... | no _ = nothing
... | yes eqBlockReward
  with time == timeOut
... | no _ = nothing
... | yes refl = just $
  record { time = sucTime time ;
    block = nextBlock (coinbase txTree vecOut eqBlockReward) ;
    outputs = outputs ++ VectorOutput→List vecOut ;
    txTree = txtree txTree tx (right unit) }
  where
    tx : TX txTree vecOut
    tx = coinbase txTree vecOut eqBlockReward
```

There are two cases. The first one is if the transaction is a coinbase transaction. It tries first to transform a list of *TXField* into *VecOut*. If it can not transform,

it returns nothing. If it can, it validates if the amount of vector output is equal to total fees plus the block reward. After, it validates if the time of the transaction is equal to the time of the transaction tree. In the end, it adds the outputs of the transaction to the vector of outputs. Because it is a coinbase transaction, there are no inputs to be removed.

```

addTransactionTree record { time = time ; block = block ; outputs = outputs ;
  qtTransactions = qtTransactions ; txTree = txTree }
  (normalTX record { inputs = inputsTX ; outputs = outputsTX })
  with dec< (finToNat qtTransactions) totalQtSub1
... | no _ = nothing
... | yes pLess
  with raw→TXSigned time record { inputs = inputsTX ; outputs = outputsTX }
... | nothing = nothing
... | just txSig with rawTXSigned→TXSigAll time outputs txSig
... | nothing = nothing
... | just record { outSize = outSize ; sub = sub ;
  outputs = outs ; signed = signed } =
  just $ record { time = sucTime time ;
    block = nextBlock (normalTX txTree sub outs signed) ;
    outputs = list-sub sub ++ VectorOutput→List outs ;
    txTree = txtree txTree (normalTX txTree sub outs signed) (left pLess) }

```

The second case, that the transaction is regular, looks like the same. First, it validates if the quantity of transaction is less than the maximum allowed. Second, it validates if this transactions is a valid signed transaction. If all these conditions are true, it returns a new transaction tree with news outputs equal to the outputs of this transaction plus the outputs of the last transaction tree minus the inputs. In case of an invalid transaction, it returns nothing.

4.4.3 Proofs

One of the important proofs is that each output of *outputs transaction* is distinct. This is very important because it guarantees that each input in the transaction could be just related to just one unspent output. This characteristic could be in the type of transaction tree, but it is proven outside of it.

First, it is necessary to define what is a distinct union:

```

unionDistinct : {A : Set} {la lb : List A} (da : Distinct la) (db : Distinct lb)
  (twoDist : twoListDistinct la lb) → Distinct $ la ++ lb

```

```

unionDistinct {__} {[]} {lb} da db twoDist = db
unionDistinct {__} {__} {lb} (cons x da isDistXla) db (isDistXlb , distLaLb) =
  cons x (unionDistinct da db distLaLb) (isDistUnion x isDistXla isDistXlb)

```

The union of distinct lists makes a new distinct list if both are distinct to each other.

Now, to prove that outputs are a distinct list:

```

uniqueOutputs : {time : Time}
  {block : Nat}
  {outputs : List TXFieldWithId}
  {totalFees : Amount}
  {qtTransactions : tQtTxs}
  (txTree : TXTree time block outputs totalFees qtTransactions)
  → Distinct outputs
uniqueOutputs genesisTree = []
uniqueOutputs (txtree {block} {time} {outSize} {inputs} {__} {vecOut} tree tx _) =
  unionDistinct {__} {inputsTX tx} {VectorOutput→List vecOut}
    (distInputs tx) (vecOutDist vecOut)
    (allDistincts (inputsTXTimeLess tx) (allVecOutSameTime vecOut))

```

In the first case, the transaction tree is a genesis tree without any outputs. So an empty list is a distinct list. In the second case, the outputs are the union of inputs of the transaction with the outputs of *vector output*. So, it is necessary to prove that inputs of the transaction are distinct, that elements of *vector output* are also distinct and that both lists are distinct to each other.

```

distInputs : {time : Time}
  {block : Nat}
  {inputs : List TXFieldWithId}
  {outSize : Nat}
  {totalFees : Amount}
  {qtTransactions : tQtTxs}
  {outAmount : Amount}
  {tree : TXTree time block inputs totalFees qtTransactions}
  {outVec : VectorOutput time outSize outAmount}
  (tx : TX tree outVec)
  → Distinct $ inputsTX tx
distInputs (normalTX genesisTree [] outputs txSigned) = []
distInputs (normalTX (txtree {__} {__} {__} {__} {__} {vecOut} tr tx _)
  SubInputs outputs txSigned) =

```

```

distList→distSub { _ } { _ } { SubInputs } (unionDistinct { _ } { inputsTX tx }
(distInputs tx) (vecOutDist vecOut)
(allDistincts (inputsTXTimeLess tx) (allVecOutSameTime vecOut)))
distInputs (coinbase genesisTree outVec _) = []
distInputs (coinbase
(txtree { _ } { _ } { _ } { _ } { _ } { vecOut } tr tx _) outVec _) =
unionDistinct { _ } { inputsTX tx } (distInputs tx)
(vecOutDist vecOut)
(allDistincts (inputsTXTimeLess tx) (allVecOutSameTime vecOut) )

```

There are some cases to prove that inputs are distinct. First, if it is a regular transaction or if it is a coinbase transaction. Second, if the transaction tree of this transaction is a genesis tree or if it is a regular tree.

If the transaction tree of the transaction is a genesis tree, the number of inputs is zero. So they are distinct.

In other cases, it does the same thing as proof of unique outputs. The only difference is that it also does a recursive proof. It assumes that the transaction of the last transaction tree is also distinct.

```

allDistincts : { time : Time } { vec< vec≡ : List TXFieldWithId }
(all< : All (λ tx → tx out<time time) vec<)
(all≡ : All (λ tx → TXFieldWithId.time tx ≡ time) vec≡)
→ twoListDistinct vec< vec≡
allDistincts { time } { .[] } { vec≡ } [] all≡ = unit
allDistincts { time } { (x :: _) } { vec≡ } (p< :: all<) all≡ =
distinctLess all≡ , allDistincts all< all≡
where
sucRemove : ∀ { m n : Nat } (suc≡ : _≡_ { _ } { Nat }
(suc m) (suc n)) → m ≡ n
sucRemove refl = refl

⊥-k+ : (k n : Nat) → ¬ (n ≡ suc k + n)
⊥-k+ k zero ()
⊥-k+ k (suc n) eqs = ⊥-k+ k n let eq = sucRemove eqs in
trans eq (add-suc-r k n)

⊥-< : { n : Nat } → ¬ (n < n)
⊥-< { n } (diff k eq) = ⊥-k+ k n eq

distinctLess : { vec≡ : List TXFieldWithId }

```

```

(all≡ : All (λ tx → TXFieldWithId.time tx ≡ time) vec≡)
→ isDistinct x vec≡
distinctLess [] = unit
distinctLess (refl :: all≡) = (λ{ refl → ⊥-< p<} ) , (distinctLess all≡)

```

Both are distinct to each other because all of the transactions of input has the timeless then the time of the transaction. And because all of the outputs of the current transaction has time equal to the current time of this transaction.

```

outputsTimeLess :
  {time : Time}
  {block : Nat}
  {outputs : List TXFieldWithId}
  {totalFees : Amount}
  {qtTransactions : tQtTx}
  (txTree : TXTree time block outputs totalFees qtTransactions )
  → All (λ output → output out<time time) outputs
outputsTimeLess genesisTree = []
outputsTimeLess {__} {__} {__} {totalFees} {qtTransactions}
  (txtree {block} {time} {amount} {outSize} {outputs} {outVec} txTree tx __) =
  allJoin (inputsTX tx) (VectorOutput→List outVec)
  (inputs≤→inputsTX tx $ outputsTimeLess txTree)
$ vecOutTimeLess outVec
where
  vecOutTimeLess : {time : Time}
    {outSize : Nat}
    {amount : Amount}
    (vecOut : VectorOutput time outSize amount)
    → All (λ output → output out<time (sucTime time))
      (VectorOutput→List vecOut)
  vecOutTimeLess (el tx refl elStart) =
    (diff zero (timeToNatSuc {TXFieldWithId.time tx})) :: []
  vecOutTimeLess (cons {time} vecOut tx refl elStart) =
    (diff zero (timeToNatSuc {time})) :: (vecOutTimeLess vecOut)

≤timeSuc : {t1 : TXFieldWithId} {t2 : Time} (pt : t1 out<time t2)
  → t1 out<time (sucTime t2)
≤timeSuc {txfieldid time position amount address} {t2}
  (diff k eq) = diff (suc k) (trans (eqTimeNat {t2}) eqsuc)
where
  eqsuc : _≡_ {__} {Nat} (suc (timeToNat t2))

```



```

(suc (suc (k + timeToNat time)))
eqsuc = cong suc eq

eqTimeNat : {t2 : Time} → timeToNat (sucTime t2) ≡ suc (timeToNat t2)
eqTimeNat {nat zero} = refl
eqTimeNat {nat (suc x)} = refl

inputs≤→inputsTX : {inputs : List TXFieldWithId}
  {totalFees : Amount}
  {qtTransactions : Fin totalQt}
  {tree : TXTree time block inputs totalFees qtTransactions}
  (tx : TX tree outVec)
  (allInps : All (λ output → output out<time time) inputs)
  → All (λ input → input out<time sucTime time) (inputsTX tx)
inputs≤→inputsTX {[]} (normalTX tr [] outVec txSigned) [] = []
inputs≤→inputsTX {[]} (coinbase tr outputs _) [] = []
inputs≤→inputsTX {input :: inputs} (normalTX tr (input :: SubInputs)
  outVec txSigned) (pt :: allInps) =
  ≤timeSuc {input} {time} pt :: allProofFG (λ y pf → ≤timeSuc {y} {time} pf)
  (allList→allSub SubInputs allInps)
inputs≤→inputsTX {input :: inputs} (normalTX tr (input :: SubInputs)
  outVec txSigned) (x :: allInps) =
  allProofFG (λ y pf → ≤timeSuc {y} {time} pf)
  (allList→allSub SubInputs allInps)
inputs≤→inputsTX {input :: inputs} (coinbase tr outVec _)
  (pt :: allInps) = ≤timeSuc {input} {time} pt
  :: allProofFG (λ y pf → ≤timeSuc {y} {time} pf) allInps

```

The proof that the time of the outputs is less than the current time of the transaction is done recursively. It is both necessary to proof that *inputs* of *tx* and *vector output* have both times less than the current time of this transaction. It is all done recursively.

4.5 Ledger

Ledger in the cryptocurrency is like a wallet. It makes it easier for users to send their coins or to know how much money they have in total.

Here, the definition of how much money the user has in the last tree:

```
ledgerTree : (rawTXTree : RawTXTree) (addr : Address) → Amount
ledgerTree txTree = ledgerOut outputs
  where open RawTXTree.RawTXTree txTree
```

The definition of *ledgerOut*:

```
ledgerOut : ∀ (outputs : List TXFieldWithId) (addr : Address)
  → Amount
ledgerOut [] addr = zero
ledgerOut (output :: outputs) addr with TXFieldWithId.address output == addr
... | yes _ = TXFieldWithId.amount output + ledgerOut outputs addr
... | no _ = ledgerOut outputs addr
```

If there is no output, it returns zero of the amount. If there is at least one output, it verifies if the output address is the same as the address. If it is, it adds the amount to the amount of the rest of the outputs. If it is not, it just returns the result of the recursion of the rest of the outputs.

Here, the same code for list of outputs without id:

```
ledgerOutNold : ∀ (outputs : List TXField) (addr : Address)
  → Amount
ledgerOutNold [] addr = zero
ledgerOutNold (output :: outputs) addr with TXField.address output == addr
... | yes _ = TXField.amount output + ledgerOutNold outputs addr
... | no _ = ledgerOutNold outputs addr
```

4.6 Blockchain

4.6.1 Definition

Block is a chain of transactions that is added in Bitcoin blockchain in every ten minutes. Each block consists of several transactions and a miner transaction. This is how a block is defined in this work:

```
record Block
  {block1 : Nat}
  {time1 : Time}
  {outputs1 : List TXFieldWithId}
  {totalFees1 : Amount}
  {qtTransactions1 : tQtTxs}
  (txTree1 : TXTree time1 block1 outputs1 totalFees1 qtTransactions1)

  {time2 : Time}
  {outputs2 : List TXFieldWithId}
  {totalFees2 : Amount}
  {qtTransactions2 : tQtTxs}
  (txTree2 : TXTree time2 block1 outputs2 totalFees2 qtTransactions2)
  : Set where
constructor blockc
field
  nxTree : nextTXTree txTree1 txTree2
  fstBlock : firstTreesInBlock txTree1
  sndBlockCoinbase : coinbaseTree txTree2
```

nextTXTree assures that the second transaction tree is from the first transaction tree. *firstTreesInBlock* guarantees that the last transaction in the first transaction tree is the first in the block. *coinBaseTree* assures that the last transaction in the second transaction tree is a coinbase transaction.

Blockchain is a chain of valid blocks. Every new block must be a continuation of the previous one. Here is the definition of the blockchain:

```
data Blockchain :
  {block1 : Nat}
  {time1 : Time}
  {outputs1 : List TXFieldWithId}
  {totalFees1 : Amount}
```

```

{qtTransactions1 : tQtTxs}
{txTree1 : TXTree time1 block1 outputs1 totalFees1 qtTransactions1}

{time2 : Time}
{outputs2 : List TXFieldWithId}
{totalFees2 : Amount}
{qtTransactions2 : tQtTxs}
{txTree2 : TXTree time2 block1 outputs2 totalFees2 qtTransactions2}
(block : Block txTree1 txTree2)
→ Set where
  fstBlock :
    {block1 : Nat}
    {time1 : Time}
    {outputs1 : List TXFieldWithId}
    {totalFees1 : Amount}
    {qtTransactions1 : tQtTxs}
    {txTree1 : TXTree time1 block1 outputs1 totalFees1 qtTransactions1}

    {time2 : Time}
    {outputs2 : List TXFieldWithId}
    {totalFees2 : Amount}
    {qtTransactions2 : tQtTxs}
    {txTree2 : TXTree time2 block1 outputs2 totalFees2 qtTransactions2}
    (block : Block txTree1 txTree2)
    → Blockchain block

  addBlock :
    {block-p1 : Nat}
    {time-p1 : Time}
    {outputs-p1 : List TXFieldWithId}
    {totalFees-p1 : Amount}
    {qtTransactions-p1 : tQtTxs}
    {txTree-p1 : TXTree time-p1 block-p1 outputs-p1 totalFees-p1 qtTransactions-p1}

    {time-p2 : Time}
    {outputs-p2 : List TXFieldWithId}
    {totalFees-p2 : Amount}
    {qtTransactions-p2 : tQtTxs}
    {txTree-p2 : TXTree time-p2 block-p1 outputs-p2 totalFees-p2 qtTransactions-p2}
    {block-p : Block txTree-p1 txTree-p2}

```

```

(blockchain : Blockchain block-p)

{outSize : Nat}
{amount : Amount}
{outputTX : VectorOutput time-p2 outSize amount}
{tx : TX {time-p2} {block-p1} {outputs-p2} {outSize} txTree-p2 outputTX}
{proofLessQtTX :
  Either
    (IsTrue (lessNat (finToNat qtTransactions-p2) totalQtSub1))
    (isCoinbase tx)}

{time2 : Time}
{outputs2 : List TXFieldWithId}
{totalFees2 : Amount}
{qtTransactions2 : tQtTxs}
{txTree2 : TXTree time2 (nextBlock tx) outputs2 totalFees2 qtTransactions2}
(block : Block (txtree txTree-p2 tx proofLessQtTX) txTree2)
→ Blockchain block

```

In the first case, blockchain just has one block, called *fstBlock*. In the second case, the blockchain is an addition of a valid block from a previous blockchain.

4.6.2 Creation

To create a blockchain, it is first needed to create the last block. From the last block, it is possible to create all the chain.

```

block→blockchain : ∀
  {block1 time1 outputs1 totalFees1 qtTransactions1}
  {txTree1 : TXTree time1 block1 outputs1 totalFees1 qtTransactions1}
  {time2 outputs2 totalFees2 qtTransactions2}
  {txTree2 : TXTree time2 block1 outputs2 totalFees2 qtTransactions2}
  (block : Block txTree1 txTree2)
  → Blockchain block

block→blockchain {__} {__} {__} {__} {__} {genesisTree}
  (blockc nxTree fstBlock1 sndBlockCoinbase) =
  fstBlock (blockc nxTree unit sndBlockCoinbase)

block→blockchain {__} {__} {__} {__} {__} {txtree tree tx proofLessQtTX}
  (blockc nxTree fstBlock1 sndBlockCoinbase)
  with firstTree tree

```

```

... | fstTreec nxTree1 fstBlockc = addBlock
  (block→blockchain (blockc nxTree1 fstBlockc (fstTree→coinbase fstBlock1)))
  (blockc nxTree fstBlock1 sndBlockCoinbase)

```

In this proof, if the first transaction tree of the block is a genesis tree, it will return a blockchain of just one block. If it is a regular tree, it tries to find the first transaction tree of this block. Using a recursive definition of block to blockchain, it is possible to generate all the rest of this blockchain from this block.

It is not always possible to generate a block from the transaction tree. It is because the last transaction of a transaction tree must be a coinbase transaction. Here, the function that returns a decidable if it is possible to generate a block from the transaction tree.

```

txTree→Block : ∀
  {block time outputs totalFees qtTransactions}
  (tree : TXTree time block outputs totalFees qtTransactions)
  → Dec (RawBlock tree)
txTree→Block genesisTree =
  no λ{(rawBlockc (blockc _ _ sndBlockCoinbase)) → sndBlockCoinbase}
txTree→Block (txtree tree tx proofLessQtTX)
  with isCoinbaseTree (txtree tree tx proofLessQtTX)
... | no ¬isCoinbase =
  no λ{(rawBlockc (blockc _ _ coinbaseTree)) → ¬isCoinbase coinbaseTree}
... | yes isCoinbase = let fTree = firstTree (txtree tree tx proofLessQtTX)
                        nxTree = fstTree.nxTree fTree
                        fBlock = fstTree.fstBlockc fTree
                        in yes (rawBlockc (blockc nxTree fBlock isCoinbase))

```

The definition of the raw block gets just the coinbase transaction tree as an explicit type. The other transaction tree can be founded opening the record.

```

record RawBlock
  {block : Nat}
  {time2 : Time}
  {outputs2 : List TXFieldWithId}
  {totalFees2 : Amount}
  {qtTransactions2 : tQtTx}
  (tree2 : TXTree time2 block outputs2 totalFees2 qtTransactions2)
  : Set where
  constructor rawBlockc

```

```

field
  {time}      : Time
  {outputs}   : List TXFieldWithId
  {totalFees} : Amount
  {qtTransactions} : tQtTxS
  {tree}      : TXTree time block outputs totalFees qtTransactions
  rawBlock    : Block tree tree2

```

The code of the definition of what is a coinbase tree:

```

coinbaseTree : ∀
  {block time outputs totalFees qtTransactions}
  (tree : TXTree time block outputs totalFees qtTransactions)
  → Set
coinbaseTree genesisTree = ⊥
coinbaseTree (txtree _ (normalTX _ _ _ _) _) = ⊥
coinbaseTree (txtree _ (coinbase _ _ _ _) _) = ⊤

```

The definition of a coinbase tree is the one that the last transaction is a coinbase.

The code verifies if the last transaction tree is a coinbase tree:

```

isCoinbaseTree : ∀
  {block time outputs totalFees qtTransactions}
  (tree : TXTree time block outputs totalFees qtTransactions)
  → Dec (coinbaseTree tree)
isCoinbaseTree genesisTree = no λ x → x
isCoinbaseTree (txtree _ (normalTX _ _ _ _) _) = no λ x → x
isCoinbaseTree (txtree _ (coinbase _ _ _ _) _) = yes tt

```

If it is, it returns that it is possible to create a block from that with the block definition. If it is not, it returns that it is impossible to create a block from this transaction tree.

But to create a block from this coinbase transaction tree, it is necessary to find the first tree of the block.

```

record fstTree
  {block : Nat}
  {time2 : Time}
  {outputs2 : List TXFieldWithId}
  {totalFees2 : Amount}

```

```

{qtTransactions2 : tQtTxs}
(txTree2 : TXTree time2 block outputs2 totalFees2 qtTransactions2)
: Set where
constructor fstTreec
field
  {time}           : Time
  {outputs}        : List TXFieldWithId
  {totalFees}      : Amount
  {qtTransactions} : tQtTxs
  {tree}           : TXTree time block outputs totalFees qtTransactions
  nxTree           : nextTXTree tree txTree2
  fstBlockc        : firstTreesInBlock tree

```

The definition of *fstTree* is that it has a tree that is before this tree in the type. And this tree before is the first in the block.

```

firstTreesInBlock : ∀
  {block time outputs totalFees qtTransactions}
  (tree : TXTree time block outputs totalFees qtTransactions)
  → Set
firstTreesInBlock genesisTree = ⊤
firstTreesInBlock (txtree genesisTree _ _) = ⊥
firstTreesInBlock (txtree (txtree _ (normalTX _ _ _)) _ _) = ⊥
firstTreesInBlock (txtree (txtree _ (coinbase _ _ _)) _ _) = ⊤

```

The decidable version of this *Set*:

```

isFirstTreeInBlock : ∀
  {block time outputs totalFees qtTransactions}
  (tree : TXTree time block outputs totalFees qtTransactions)
  → Dec (firstTreesInBlock tree)
isFirstTreeInBlock genesisTree = yes tt
isFirstTreeInBlock (txtree genesisTree (normalTX _ _ _)) = no λ x → x
isFirstTreeInBlock (txtree genesisTree (coinbase _ _ _)) = no λ x → x
isFirstTreeInBlock (txtree (txtree _ (normalTX _ _ _)) _ _) = no λ x → x
isFirstTreeInBlock (txtree (txtree _ (coinbase _ _ _)) _ _) = yes tt

```

In this case, it pattern match trees that are genesis tree or if the last transaction was a coinbase transaction.

```

firstTree : ∀
  {block time outputs totalFees qtTransactions}

```



```

    (tree : TXTree time block outputs totalFees qtTransactions)
    → fstTree tree
firstTree genesisTree = fstTreec (firstTX genesisTree) unit
firstTree {block2} (txtree {block1} tree tx proofLessQtTX)
  with isFirstTreeInBlock (txtree tree tx proofLessQtTX)
... | yes isFirst = fstTreec (firstTX (txtree tree tx proofLessQtTX)) isFirst
... | no ¬first with let fstTree = firstTree tree in block2 == block1
... | yes eq = let ftree = firstTree tree
               nxTree = fstTree.nxTree ftree
               fstBlock = fstTree.fstBlock ftree
               chgType = changeTXType nxTree fstBlock tx proofLessQtTX eq
               in TXChange.fTree chgType
... | no ¬eq = ⊥-elim impossible
      where postulate impossible : ⊥

```

To find the first tree in the block, there are two cases. The first case is that if the tree is a genesis tree, so the result is itself. The second case is if it a regular tree, so it still has to divide it in many cases. If this tree is already the first tree in the block, it will return itself. If this tree is not, it has to verify if the block number of the tree is the same as this tree. If the block number is equal, it can recursively find the first tree. If it is not, it has to provide proof that this tree must be the first and the blocks numbers are different.

To define what it means of one tree is next to another:

```

data nextTXTree :
  {block1 : Nat}
  {time1 : Time}
  {outputs1 : List TXFieldWithId}
  {totalFees1 : Amount}
  {qtTransactions1 : tQtTxs}
  (txTree1 : TXTree time1 block1 outputs1 totalFees1 qtTransactions1)

  {block2 : Nat}
  {time2 : Time}
  {outputs2 : List TXFieldWithId}
  {totalFees2 : Amount}
  {qtTransactions2 : tQtTxs}
  (txTree2 : TXTree time2 block2 outputs2 totalFees2 qtTransactions2)
  → Set where

```

```

firstTX : ∀ {block time outputs totalFees qtTransactions}
  (txTree : TXTree time block outputs totalFees qtTransactions)
  → nextTXTree txTree txTree
nextTX : ∀ {block1 time1 outputs1 totalFees1 qtTransactions1}
  {txTree1 : TXTree time1 block1 outputs1 totalFees1 qtTransactions1}

  {block2 time2 outputs2 totalFees2 qtTransactions2}
  {txTree2 : TXTree time2 block2 outputs2 totalFees2 qtTransactions2}

  (nxTree : nextTXTree txTree1 txTree2)

  {outSize amount}
  {outputTX : VectorOutput time2 outSize amount}
  (tx : TX txTree2 outputTX)
  (proofLessQtTX :
    Either
      (isTrue (lessNat (finToNat qtTransactions2) totalQtSub1))
      (isCoinbase tx))
  → nextTXTree txTree1 (txtree txTree2 tx proofLessQtTX)

```

There are two cases. If both trees are the same, they are next to each other. If there is a proof that both trees are next to each other and if there is one tree that was generated from the last one, so the first tree is next to the last one.

5 Conclusion

This text has shown the definition of Bitcoin protocol. Definitions of transactions, transactions tree, block, and blockchain. In this work, it was also made the code that transforms raw transactions in a possible valid transaction, to incorporate it in the transaction tree.

5.1 Future work

In this work, there was a code that transforms a raw transaction into a possible valid transaction. It is not a decidable function, because there is no definition of what it is an invalid transaction. From future work, it should have a definition of what is an invalid raw transaction. So it will avoid that valid transaction will be discarded.

There is no definition of crypto functions like SHA-256 and elliptic curves in this work. One thing that can be done is importing these functions from some Agda or Haskell packages.

This work does not have any IO operation. So it is not possible to add transactions in the blockchain from the command line or the network.

The cryptocurrency of this work does not have any smart contract. It would be good to define some of them in it.

References

- Back, A., et al. (2002). Hashcash-a denial of service counter-measure.
- Bastiaan, M. (2015). Preventing the 51%-attack: a stochastic analysis of two phase proof of work in bitcoin. In *Available at <http://refraat.cs.utwente.nl/conference/22/paper/7473/preventingthe-51-attack-a-stochasticanalysis-oftwo-phase-proof-of-work-in-bitcoin.pdf>*.
- Beukema, W. (2014). Formalising the bitcoin protocol. In *21th twente student conference on it*.
- Bhargavan, K., Delignat-Lavaud, A., Fournet, C., Gollamudi, A., Gonthier, G., Kobeissi, N., ... others (2016). Formal verification of smart contracts: Short paper. In *Proceedings of the 2016 acm workshop on programming languages and analysis for security* (pp. 91–96).
- Chaudhary, K., Fehnker, A., Van De Pol, J., & Stoelinga, M. (2015). Modeling and verification of the bitcoin protocol. *arXiv preprint arXiv:1511.04173*.
- Chaum, D. (1983). Blind signatures for untraceable payments. In *Advances in cryptology* (pp. 199–203).
- Dai, W. (1998). B-money. *Consulted*, 1, 2012.
- Hopwood, D., Bowe, S., Hornby, T., & Wilcox, N. (2016). Zcash protocol specification. *Tech. rep. 2016–1.10. Zerocoin Electric Coin Company, Tech. Rep.*.
- Kosba, A., Miller, A., Shi, E., Wen, Z., & Papamanthou, C. (2016). Hawk: The blockchain model of cryptography and privacy-preserving smart contracts. In *2016 ieee symposium on security and privacy (sp)* (pp. 839–858).
- Luu, L., Chu, D.-H., Olickel, H., Saxena, P., & Hobor, A. (2016). Making smart contracts smarter. In *Proceedings of the 2016 acm sigsac conference on computer and communications security* (pp. 254–269).
- Melkonian, O. (2019). *Formalizing extended utxo and bitml calculus in agda* (Unpublished master’s thesis).
- Nakamoto, S., et al. (2008). Bitcoin: A peer-to-peer electronic cash system.
- Noether, S. (2015). Ring signature confidential transactions for monero. *IACR Cryptology ePrint Archive*, 2015, 1098.
- Panurach, P. (1996). Money in electronic commerce: Digital cash, electronic fund transfer, and ecash. *Communications of the ACM*, 39(6), 45–51.
- Setzer, A. (2018). Modelling bitcoin in agda. *arXiv preprint arXiv:1804.06398*.
- Wallace, B. (2011). The rise and fall of bitcoin. *Wired*, 19(12).
- Wood, G., et al. (2014). Ethereum: A secure decentralised generalised transaction ledger. *Ethereum project yellow paper*, 151, 1–32.