

# Chapter 3: roadmap

- Transport-layer services
- Multiplexing and demultiplexing
- Connectionless transport: UDP
- Principles of reliable data transfer
- **Connection-oriented transport: TCP**
  - segment structure
  - reliable data transfer
  - flow control
  - connection management
- Principles of congestion control
- TCP congestion control




# TCP: overview

RFCs: 793, 1122, 2018, 5681, 7323

- **point-to-point:**
  - one sender, one receiver
- **reliable, in-order *byte stream*:**
  - no “message boundaries”
- **full duplex data:**
  - bi-directional data flow in same connection
  - MSS: maximum segment size
- **cumulative ACKs**
- **pipelining:**
  - TCP congestion and flow control set window size
- **connection-oriented:**
  - handshaking (exchange of control messages) initializes sender, receiver state before data exchange
- **flow controlled:**
  - sender will not overwhelm receiver

# TCP segment structure



# TCP sequence numbers, ACKs

## Sequence numbers:

- byte stream “number” of first byte in segment’s data

## Acknowledgements:


- seq # of next byte expected from other side
- cumulative ACK

Q: how receiver handles out-of-order segments

- A: TCP spec doesn’t say, - up to implementor

outgoing segment from sender


source port #	dest port #
sequence number	
acknowledgement number	
	rwnd
checksum	urg pointer



outgoing segment from receiver

source port #	dest port #
sequence number	
acknowledgement number	
	A
checksum	urg pointer

# TCP sequence numbers, ACKs



simple telnet scenario

# TCP round trip time, timeout

Q: how to set TCP timeout value?

- longer than RTT, but RTT varies!
- *too short*: premature timeout, unnecessary retransmissions
- *too long*: slow reaction to segment loss

Q: how to estimate RTT?


- **SampleRTT**: measured time from segment transmission until ACK receipt
  - ignore retransmissions
- **SampleRTT** will vary, want estimated RTT “smoother”
  - average several *recent* measurements, not just current **SampleRTT**

# TCP round trip time, timeout

$$\text{EstimatedRTT} = (1 - \alpha) * \text{EstimatedRTT} + \alpha * \text{SampleRT}$$

- exponential weighted moving average (EWMA)
- influence of past sample decreases exponentially fast

typical value:  $\alpha = 0.12$



# TCP round trip time, timeout

- timeout interval: **EstimatedRTT** plus “safety margin”
  - large variation in **EstimatedRTT**: want a larger safety margin

$$\text{TimeoutInterval} = \text{EstimatedRTT} + 4 * \text{DevRTT}$$



↑  
estimated RTT

↑  
“safety margin”

- **DevRTT**: EWMA of **SampleRTT** deviation from **EstimatedRTT**:

$$\text{DevRTT} = (1 - \beta) * \text{DevRTT} + \beta * |\text{SampleRTT} - \text{EstimatedRTT}|$$

(typically,  $\beta = 0.2$ )



# TCP Sender (simplified)

event: data received from application

- create segment with seq #
- seq # is byte-stream number of first data byte in segment
- start timer if not already running
  - think of timer as for oldest unACKed segment
  - expiration interval: **TimeOutInterval**


event: *timeout*

- retransmit segment that caused timeout
- restart timer


event: *ACK received*

- if ACK acknowledges previously unACKed segments
  - update what is known to be ACKed
  - start timer if there are still unACKed segments


# TCP Receiver: ACK generation [RFC 5681]



# TCP: retransmission scenarios




lost ACK scenario



premature timeout

# TCP: retransmission scenarios



# TCP fast retransmit


## *TCP fast retransmit*

if sender receives 3 additional ACKs for same data (“triple duplicate ACKs”), resend unACKed segment with smallest seq #

- likely that unACKed segment lost, so don't wait for timeout



Receipt of three duplicate ACKs indicates 3 segments received after a missing segment – lost segment is likely. So retransmit!




# Chapter 3: roadmap

- Transport-layer services
- Multiplexing and demultiplexing
- Connectionless transport: UDP
- Principles of reliable data transfer
- **Connection-oriented transport: TCP**
  - segment structure
  - reliable data transfer
  - flow control
  - connection management
- Principles of congestion control
- TCP congestion control




# TCP flow control

Q: What happens if network layer delivers data faster than application layer removes data from socket buffers?



# TCP flow control


Q: What happens if network layer delivers data faster than application layer removes data from socket buffers?






# TCP flow control

Q: What happens if network layer delivers data faster than application layer removes data from socket buffers?



flow control: # bytes  
receiver willing to accept

Application removing  
data from TCP socket  
buffers




# TCP flow control

Q: What happens if network layer delivers data faster than application layer removes data from socket buffers?

## —flow control—


receiver controls sender, so sender won't overflow receiver's buffer by transmitting too much, too fast

Application removing data from TCP socket buffers



# TCP flow control


- TCP receiver “advertises” free buffer space in **rwnd** field in TCP header
  - **RcvBuffer** size set via socket options (typical default is 4096 bytes)
  - many operating systems autoadjust **RcvBuffer**
- sender limits amount of unACKed (“in-flight”) data to received **rwnd**
- guarantees receive buffer will not overflow



# TCP flow control

- TCP receiver “advertises” free buffer space in **rwnd** field in TCP header
  - **RcvBuffer** size set via socket options (typical default is 4096 bytes)
  - many operating systems autoadjust **RcvBuffer**
- sender limits amount of unACKed (“in-flight”) data to received **rwnd**
- guarantees receive buffer will not overflow

flow control: # bytes receiver willing to accept




TCP segment format


# TCP connection management

before exchanging data, sender/receiver “handshake”:

- agree to establish connection (each knowing the other willing to establish connection)
- agree on connection parameters (e.g., starting seq #s)





```
Socket clientSocket =  
    newSocket("hostname", "port number");
```



```
Socket connectionSocket =  
    welcomeSocket.accept();
```

# Agreeing to establish a connection


2-way handshake:



Q: will 2-way handshake always work in network?

- variable delays
- retransmitted messages (e.g. req\_conn(x)) due to message loss
- message reordering
- can't "see" other side


# 2-way handshake scenarios



No problem!




# 2-way handshake scenarios



Problem: half open connection! (no client)



# 2-way handshake scenarios




# TCP 3-way handshake

## Server state

## Client state

```
clientSocket = socket(AF_INET, SOCK_STREAM)
LISTEN
clientSocket.connect((serverName, serverPort))
```

```
serverSocket = socket(AF_INET, SOCK_STREAM)
serverSocket.bind(('', serverPort))
serverSocket.listen(1)
connectionSocket, addr = serverSocket.accept()
```



# Closing a TCP connection

- client, server each close their side of connection
  - send TCP segment with FIN bit = 1
- respond to received FIN with ACK
  - on receiving FIN, ACK can be combined with own FIN
- simultaneous FIN exchanges can be handled