TÉCNICO
UNIVERSIDADE
DE LISBOA



# DEPT: Defense via Ensemble and Purification Transformer

**Guilherme Silvério de Carvalho Romeiro Leitão**

Thesis to obtain the Master of Science Degree in

## Computer Science and Engineering

Supervisor: Prof. Fernando Manuel Valente Ramos

**October 2026**

**Declaration**
I declare that this document is an original work of my own authorship and that it fulfills all the requirements of the Code of Conduct and Good Practices of the Universidade de Lisboa.

# Acknowledgments

I would like to thank my parents for their friendship, encouragement and caring over all these years, for always being there for me through thick and thin and without whom this project would not be possible. I would also like to thank my grandparents, aunts, uncles and cousins for their understanding and support throughout all these years.

Quisque facilisis erat a dui. Nam malesuada ornare dolor. Cras gravida, diam sit amet rhoncus ornare, erat elit consectetuer erat, id egestas pede nibh eget odio. Proin tincidunt, velit vel porta elementum, magna diam molestie sapien, non aliquet massa pede eu diam. Aliquam iaculis.

Fusce et ipsum et nulla tristique facilisis. Donec eget sem sit amet ligula viverra gravida. Etiam vehicula urna vel turpis. Suspendisse sagittis ante a urna. Morbi a est quis orci consequat rutrum. Nullam egestas feugiat felis. Integer adipiscing semper ligula. Nunc molestie, nisl sit amet cursus convallis, sapien lectus pretium metus, vitae pretium enim wisi id lectus.

Donec vestibulum. Etiam vel nibh. Nulla facilisi. Mauris pharetra. Donec augue. Fusce ultrices, neque id dignissim ultrices, tellus mauris dictum elit, vel lacinia enim metus eu nunc.

I would also like to acknowledge my dissertation supervisors Prof. Some Name and Prof. Some Other Name for their insight, support and sharing of knowledge that has made this Thesis possible.

Last but not least, to all my friends and colleagues that helped me grow as a person and were always there for me during the good and bad times in my life. Thank you.

To each and every one of you – Thank you.

# Abstract

Network intrusion detection today relies on machine learning, which brought a weakness signatures never had: the detector itself can be evaded. An attacker that reshapes only packet timing and sizes, keeping every packet protocol-compliant, can make an ongoing attack look benign to a deployed detector. Much of the defensive literature measures robustness against perturbations no real packet sequence can produce. This thesis proposes DEPT (Defense via Ensemble and Purification Transformer), a streaming defense trained and evaluated on realizable adversarial traffic from TANTGen, a black-box generator built in a sibling thesis. DEPT turns traffic into a masked, bit-level representation at two temporal granularities; two architecturally different learners, a Random Forest and a Temporal Convolutional Network, fused per packet by an attention-based meta-learner, decide whether a flow was manipulated; flagged flows are corrected by a causal purification Transformer and realized back into sendable packets. Across ten traffic sources from three public datasets, each manipulated in three perturbation modes, DEPT gives a verdict from the first packet, where the fusion is the best model available, and reaches an end-of-flow AUROC of $0.933$; the Random Forest alone is stronger from the second packet on, and the fusion's benefit is earliness and a higher cost to a gradient-guided attacker, which never evades the stack on $74.5\%$ of flows against $45.5\%$ for the sequence model alone. Judged through the independent detector each attack targeted, purification recovers $63\%$ of the destroyed detection and cuts attack success from $21.1\%$ to $11.6\%$, with $97.2\%$ of reconstructed packets parsed cleanly by Wireshark's `tshark`. The evaluation reports the failures with equal prominence: on the size-perturbed reflection floods no model beats chance, and purifying non-evading traffic lowers detection rather than restoring it.

# Keywords

Adversarial Machine Learning; Network Intrusion Detection; Evasion Attacks; Ensemble Learning; Adversarial Purification; Streaming Traffic Analysis

# Resumo

A deteção de intrusões em rede assenta hoje em aprendizagem automática, trazendo uma fragilidade que as assinaturas não tinham: o próprio detetor pode ser enganado. Um atacante que altere apenas tempos e tamanhos de pacotes, sem nunca violar o protocolo, faz um ataque em curso passar por benigno ao detetor. Muita da literatura de defesa mede a robustez contra perturbações que nenhum tráfego real consegue produzir. Esta dissertação propõe o DEPT (Defense via Ensemble and Purification Transformer), uma defesa em streaming treinada e avaliada sobre tráfego adversarial realizável do TANTGen, um gerador black-box de uma dissertação irmã. O DEPT converte o tráfego numa representação mascarada e ao nível do bit, a duas granularidades temporais; uma Random Forest e uma Temporal Convolutional Network, de famílias distintas, fundidas a cada pacote por um modelo de atenção, decidem se o fluxo foi manipulado; os fluxos sinalizados são corrigidos por um Transformer causal de purificação e reescritos como pacotes enviáveis. Em dez fontes de tráfego de três conjuntos de dados públicos, manipuladas em três modos de perturbação, o DEPT dá um veredicto logo no primeiro pacote, onde a fusão é o melhor modelo disponível, e atinge uma AUROC final de 0,933; a Random Forest isolada é superior a partir do segundo pacote, e o benefício da fusão está na precocidade e no maior custo para um atacante guiado por gradiente, que nunca evade a deteção em 74,5% dos fluxos, contra 45,5% no modelo sequencial. Avaliada pelo detetor independente visado por cada ataque, a purificação recupera 63% da deteção destruída e reduz o sucesso do ataque de 21,1% para 11,6%, com 97,2% dos pacotes reconstruídos aceites sem erros pelo `tshark` do Wireshark. A avaliação dá igual destaque às falhas: nos floods de reflexão com perturbação de tamanho nenhum modelo supera os 50%, e purificar tráfego que não evadia baixa a deteção em vez de a restaurar.

# Palavras Chave

Aprendizagem Automática Adversarial; Deteção de Intrusões em Rede; Ataques de Evasão; Métodos de Ensemble; Purificação de Tráfego; Análise de Tráfego em Tempo Real

# Contents


**1 Introduction** **1**

1.1 Context and Motivation . . . 2

1.2 Problem Statement . . . 3

1.3 Work Objectives and Challenges . . . 4

1.4 Rationale and Contributions . . . 4

1.5 Organization of the Document . . . 6

**2 Background** **7**

2.1 Machine Learning for NIDS . . . 8

2.1.1 Learning Paradigms . . . 8

2.1.2 Feature Engineering and Representation . . . 8

2.1.3 Model Architectures Relevant to DEPT . . . 11

A – Random forests. . . . 11

B – One-dimensional and temporal convolutional networks. . . . 11

C – Transformers. . . . 11

2.2 Adversarial Machine Learning . . . 13

2.2.1 Threat Taxonomy . . . 13

2.2.2 Defense Paradigms . . . 15

2.2.3 Realizability and Protocol Constraints . . . 16

2.3 Ensemble Learning for Robustness . . . 17

2.3.1 Bagging, Boosting, Stacking . . . 17

2.3.2 Gradient Masking and Transferability . . . 17

2.4 Summary . . . 19

**3 Related Work** **21**

3.1 Adversarial Attacks against ML-based NIDS . . . 22

A – Feature-space attacks. . . . 22

B – Traffic-space attacks. . . . 22

3.1.1 TANTGen, the Attacker of This Thesis . . . 23

3.1.2 Gradient-guided Evasion, the Second Attacker . . . 23
3.2 Training-time Defenses . . . 24
A – Data sanitization and poisoning defenses. . . . 24
B – Federated and backdoor defenses. . . . 25
C – Ensemble-based hardening. . . . 25
D – Realizable adversarial training. . . . 25
3.3 Inference-time Defenses . . . 26
A – Certified robustness. . . . 26
B – Generative purification. . . . 26
C – Constraint-based and auxiliary detection. . . . 27
3.4 Positioning of DEPT and Gap Analysis . . . 27
**4 Solution: DEPT Architecture** **31**
4.1 Threat Model . . . 32
4.2 System Overview . . . 33
4.3 Dataset Construction and Packet-to-Tensor Pipeline . . . 35
A – Traffic corpus. . . . 35
B – Label convention. . . . 36
C – From packets to tensors. . . . 36
D – Splits and class balance. . . . 36
4.4 Primary Detection: Heterogeneous Stacking Ensemble . . . 37
4.4.1 Random Forest Base Learner . . . 37
4.4.2 Temporal Convolutional Network Base Learner . . . 38
4.4.3 Attention-Based Meta-Learner (the “Mini-Transformer”) . . . 38
4.5 Input Purification: Reconstructor Transformer . . . 39
4.5.1 Purification Model . . . 40
4.5.2 Training on Matched Flow Pairs . . . 41
4.5.3 Traffic-Space Realization and Validation . . . 41
4.6 Implementation and Tools . . . 42
**5 Evaluation** **45**
5.1 Research Questions . . . 46
5.2 Experimental Setup . . . 46
5.2.1 Datasets and Threat Generation . . . 46
5.2.2 Implementation Environment . . . 47
5.3 Metrics . . . 48
A – Static classification. . . . 48

B – Streaming. . . . 48
C – Purification. . . . 48
5.4 Base Learner Results . . . 49
5.5 Meta-Learner Results . . . 51
5.6 Purification Results . . . 53
5.7 Ensemble Robustness under a Gradient-guided Attacker (RQ1) . . . 56
5.7.1 The Attacker . . . 57
5.7.2 How the Numbers Must Be Read . . . 58
5.7.3 Results . . . 58
A – The stack costs the attacker more than either base learner alone, at every budget an attacker would plausibly pay. . . . 58
B – The meta-learner shifts its reliance onto the Random Forest as the TCN is degraded. . . . 60
C – Gradients buy this attacker nothing at all. . . . 60
5.8 End-to-End System Evaluation . . . 61
5.8.1 Detect-then-Purify, End to End . . . 61
5.8.2 One Global Model or Ten Specialists? . . . 64
5.9 Discussion and Limitations . . . 65
A – Answering the research questions. . . . 65
B – Purification without a good gate can subtract as well as add. . . . 66
C – The reflection floods' `size` variants fail below chance, and that is a representation problem. . . . 66
D – A stacker that is beaten by its own base learner. . . . 66
E – Purification is validated through independent NIDS, not only DEPT's own detector. . . . 67
F – The label convention is a modelling choice. . . . 67
G – What the aggregates do and do not summarize. . . . 67
5.9.1 Scope of the Gradient-ablation Result (RQ1) . . . 68
A – RQ1 is only answerable where the base learners detect anything. 68
B – Some flows are unreachable through this surface at any budget. 68
C – The timing channel has a representational floor. . . . 68
D – The attacker that was priced is not a gradient attacker in the end. 68
**6 Conclusion** **71**
6.1 Summary of Contributions . . . 72
6.2 Answers to Research Questions . . . 73

6.3 System Limitations . . . . . 74
6.4 Future Work . . . . . 76

**Bibliography** **78**

# List of Figures


1.1 The adversarial evasion problem. . . . . 2

2.1 The two supervision regimes most relevant to DEPT. . . . . 9
2.2 The nPrint per-packet representation with identity masking. . . . . 10
2.3 The one-dimensional convolutional pipeline. . . . . 12
2.4 Dilated causal convolutions and the TCN receptive field. . . . . 12
2.5 The decoder-only Transformer block. . . . . 14
2.6 Purification as projection onto the benign manifold. . . . . 16
2.7 The three classical ensemble strategies. . . . . 18

3.1 The surveyed defenses on the phase and space axes. . . . . 28

4.1 DEPT's deployment context. . . . . 32
4.2 The DEPT architecture. . . . . 34
4.3 The dual prediction cadence over a flow. . . . . 37
4.4 The purification stage. . . . . 40

5.1 Per-source AUROC distribution. . . . . 51
5.2 Streaming AUROC@$t$ trajectories. . . . . 52
5.3 Purification gain against perturbation footprint. . . . . 56
5.4 A single real packet through the purification pipeline. . . . . 57
5.5 Evasion cost: one perturbation, three targets. . . . . 59
5.6 Deployment baseline: NIDS attack success before vs. after DEPT. . . . . 62

# List of Tables


2.1 The two representations DEPT derives from the same masked nPrint tokens. . . . . 11

3.1 Comparison of the surveyed adversarial defenses. . . . . 28

4.1 The 13-dimensional fusion token. . . . . 39
4.2 Model configuration summary. . . . . 43

5.1 Static classification results . . . . . 49
5.2 Per-source streaming AUROC . . . . . 50
5.3 Streaming comparison . . . . . 52
5.4 Purification results (overall) . . . . . 53
5.5 Purification by source . . . . . 55
5.6 Evasion cost under a gradient-guided attacker. . . . . 59
5.7 Deployment baseline: attack success before vs. after DEPT . . . . . 63
5.8 Global model against per-attack specialists . . . . . 65

# Acronyms

**AML** Adversarial Machine Learning

**ART** Adversarial Robustness Toolbox

**ASR** Attack Success Rate

**AUROC** Area Under the Receiver Operating Characteristic curve

**CNN** Convolutional Neural Network

**DDoS** Distributed Denial of Service

**EDP** Earliest Detection Packet

**FGSM** Fast Gradient Sign Method

**FL** Federated Learning

**GAN** Generative Adversarial Network

**ICMP** Internet Control Message Protocol

**IFM** Inverse Feature Mapping

**IP** Internet Protocol

**IPAT** Inter-Packet Arrival Time

**MDP** Markov Decision Process

**ML** Machine Learning

**MSE** Mean Squared Error

**MTU** Maximum Transmission Unit

**NIDS** Network Intrusion Detection System

**PGD** Projected Gradient Descent

**RF** Random Forest

**RL** Reinforcement Learning

**SMT** Satisfiability Modulo Theories

**TCN** Temporal Convolutional Network

**TCP** Transmission Control Protocol

**TLS** Transport Layer Security

**UDP** User Datagram Protocol

# 1

# Introduction

## Contents


1.1 Context and Motivation . . . . . 2

1.2 Problem Statement . . . . . 3

1.3 Work Objectives and Challenges . . . . . 4

1.4 Rationale and Contributions . . . . . 4

1.5 Organization of the Document . . . . . 6


Network intrusion detection has largely become a machine learning problem. The systems that guard today's networks rely less and less on hand-written signatures and more on learned models, and with that shift they inherited a weakness that signatures never had: the models themselves can be attacked. This thesis is concerned with that weakness in its most realistic form, and with what a defender can actually do about it. It proposes DEPT (Defense via Ensemble and Purification Transformer), a streaming defense that detects adversarially manipulated network traffic and undoes the manipulation before it reaches the detector it was meant to evade.

## 1.1 Context and Motivation

A Network Intrusion Detection System (NIDS) watches the traffic that crosses a network boundary and decides what is malicious. For a long time this decision was made by matching traffic against signatures of known threats, which is precise for catalogued attacks and blind to everything else. Machine Learning (ML) changed the terms of the problem: instead of enumerating what an attack looks like, a model learns the statistical behaviour that separates malicious from benign traffic, and can therefore generalize to variants and to attacks it never saw [1, 2]. Learning-based detection is by now the dominant research direction in the field and an increasingly common deployment choice [3, 4].

The improvement came with a new attack surface. A learned model can be fooled: a small, deliberate perturbation of its input may flip its decision, the phenomenon known as an adversarial example [5, 6]. For a NIDS, adversarial examples take the form of evasion: the attacker reshapes ongoing attack traffic just enough for the detector to label it benign, while the attack keeps doing its work [7]. The threat is not hypothetical. Black-box attacks have reached evasion rates of up to $35.7\%$ against deep detectors that looked nearly perfect on clean benchmarks [8]. Figure 1.1 illustrates the situation this thesis starts from.





**Figure 1.1:** The problem this thesis addresses. In the form the attacker originally generates it, attack traffic is flagged by the ML-based NIDS that guards the network (top path). A black-box generator, TANTGen in this work, reshapes the same attack, altering only packet timing and sizes while every packet remains protocol-compliant, and the detector now labels the traffic benign, so the attack is delivered to the network it was aimed at (bottom path). DEPT exists to close exactly this gap.

Not every adversarial example in the literature is a real threat, however, and this point shapes the whole thesis. In the image domain, where adversarial examples were first studied, any perturbed pixel array is still an image; a perturbed feature vector of network traffic, in contrast, is only a threat if some sendable sequence of packets actually produces it. Recovering concrete traffic from a desired feature vector is the Inverse Feature Mapping (IFM) problem, and it is often intractable, since packets must keep their checksums, lengths, and protocol semantics consistent [9, 10]. A realistic attacker is further confined to the black-box setting: it can probe a deployed detector and observe outcomes, but it holds neither the model's architecture nor its gradients [11, 12]. Much of the defensive literature sidesteps one

or both of these constraints, assuming white-box access or training against feature-space perturbations that no real packet sequence can produce, and so ends up measuring robustness against a threat that cannot occur as measured; Chapter 3 examines this mismatch in detail.

This mismatch is what the present work, together with its sibling thesis, set out to remove. TANTGen [13], developed in the sibling thesis of this one, closes the realism gap on the attack side: it is a Transformer-based generator that manipulates live attack traffic under black-box constraints, altering only packet timing and packet size, and the traffic it emits is protocol-compliant by construction. DEPT is the defense side of the same effort. It is trained on, and evaluated against, the realizable adversarial traffic that TANTGen produces, so that every claim made about the defense refers to an attack that demonstrably exists on the wire, and not to a synthetic worst case.

## 1.2 Problem Statement

The problem this thesis addresses can now be stated. A stream of flows arrives at the boundary of a protected network, where a NIDS is deployed. Part of the traffic is benign; part belongs to conventional attacks, which the deployed NIDS is assumed to handle, since that is precisely its job; and part has been adversarially manipulated so that this NIDS mishandles it. The defense must decide, for each flow and while the flow is still in progress, whether it has been manipulated, and, when it has, neutralize the manipulation before the protected system consumes the flow.

Three constraints qualify an acceptable solution. First, streaming operation: the verdict must be produced packet by packet, as the flow unfolds, because a defense that waits for a flow to complete has already let the attack through, and buffering whole flows at a network boundary is not viable in any case. Second, black-box realism: the defense may not assume any knowledge the attacker would not grant it, which means it must be trained and evaluated against realizable, protocol-compliant adversarial traffic rather than against convenient synthetic perturbations. Third, realizable output: a flow the defense repairs must leave it as valid traffic, packets that parse and keep their protocol semantics, otherwise the defense has merely moved the realizability problem from the attacker to the defender.

Two boundaries complete the statement. DEPT complements the protected NIDS, it does not replace it: recognizing the underlying attacks themselves (a flood, a scan, a brute-force attempt) remains the downstream system's task, and DEPT answers only the narrower question of whether a flow has been tampered with on its way in. And since the defense sits inline, its decisions must fit a real-time latency budget: the per-flow cost of detection, and of purification when it triggers, has to remain compatible with acting on a flow while it is still passing. This budget shapes the design choices of Chapter 4; measuring the delivered system against it is deliberately left to future work (Section 6.4).

## 1.3 Work Objectives and Challenges

The problem statement was broken into four objectives, which structure both the design of Chapter 4 and the research questions that organize the evaluation of Chapter 5:

- **O1 (shared traffic representation).** Find a representation of raw traffic that stays close to the packets themselves, so that model outputs can be turned back into real traffic, and that architecturally different learners can consume at different temporal granularities, from individual packets to aggregated flow statistics.
- **O2 (heterogeneous detection).** Build a detection ensemble whose members belong to different architectural families, so that a perturbation shaped against one member does not automatically transfer to the others, and fuse their asynchronous opinions into a single per-packet verdict.
- **O3 (input purification).** Learn to reconstruct a flagged flow: remove the adversarial manipulation and return the flow to its clean appearance, while keeping the result a valid, sendable packet sequence.
- **O4 (streaming-aware evaluation).** Evaluate the system the way it would be used: on partial flows as they arrive, with metrics that expose how early a verdict becomes reliable, rather than end-of-flow accuracy alone.

The setting makes these objectives harder than they may look, and three difficulties deserve to be named early. The first is imbalance: public attack corpora are dominated by high-rate floods, so a handful of traffic sources contributes the overwhelming majority of flows, and both training and evaluation have to be designed so that these sources neither drown out the rest nor flatter the aggregate numbers. The second is the thinness of the signal: a manipulation confined to packet timing on a high-rate flood barely moves any observable feature, and no detector can find a footprint where almost none exists; Chapter 5 quantifies this limit openly instead of averaging it away. The third is that the defense inherits the attacker's constraint: purification edits traffic, and edited traffic must remain realizable, which rules out treating flows as free-floating feature vectors and directly forces the representation choices of O1. Cutting across all three runs the latency constraint: whatever the pipeline does, it must do at streaming pace.

## 1.4 Rationale and Contributions

The design of DEPT rests on two decisions, whose full justification occupies Chapters 2 and 3 but whose logic can be given in a few lines. The first concerns detection. A black-box attacker's practical weapon

is transferability: perturbations crafted against a substitute model tend to carry over to the target when both expose similar, differentiable decision surfaces [11]. DEPT's detector therefore stacks two learners from different architectural families, a Random Forest (RF), whose decision function offers no gradient at all, and a Temporal Convolutional Network (TCN), which reads the raw packet sequence, fused at every packet by a small attention-based meta-learner [14]. What moves one member's verdict does not necessarily move the other's, and a single gradient signal cannot cross both.

The second decision concerns what to do with a flagged flow. Dropping it would turn every false positive into denial of service for a legitimate client, so DEPT purifies instead, in the input-transformation tradition started by Defense-GAN [15]. The purifier is a causal Transformer that predicts a residual correction over the packet sequence, rather than a Generative Adversarial Network (GAN) or a diffusion model: flows are sequences, which is what self-attention models well; causality preserves the streaming property; a residual head makes "change nothing" the default behaviour; and a single forward pass fits a latency budget that an iterative denoiser does not.

Against this rationale, the thesis makes five contributions:

- A streaming packet-to-tensor pipeline that turns raw captures into a masked, bit-level representation of each flow, emitted at two temporal granularities, so that architecturally different learners share one behaviour-focused view of the same traffic (Section 4.3).

- A heterogeneous detection ensemble, a RF and a TCN fused per packet by an attention meta-learner, together with a like-for-like streaming comparison that scores every model by how early, and not only how well, it separates manipulated from clean flows (Sections 4.4 and 5.5).

- A causal purification Transformer coupled to an explicit realization step: flagged flows are corrected in feature space, written back into protocol-compliant packets, and validated with a standard dissector. On the sources where the manipulation leaves a footprint the protected detector can see, purification recovers most of the detection the attack destroyed, and this is confirmed not through DEPT's own detector but through the independent NIDS each attack was built to evade (Sections 4.5 and 5.6).

- An end-to-end deployment baseline that measures DEPT as what it is, a defense placed in front of a protected NIDS: the full gated detect-then-purify pipeline is run over clean, TANTGen-perturbed, and DEPT-defended traffic, and each is scored through the real NIDS the attack targets, Kitsune for the Kitsune-native attacks and TANTGen's ML-NIDS for the CIC attacks, reporting the attack-success rate the defense removes and the detection it restores (Section 5.8).

- A paired adversarial evaluation corpus and its honest accounting: ten benign traffic sources drawn from three public datasets (Kitsune, CIC-IDS2017, and CIC-DDoS-2019 [16–18]), each manipu-

lated by TANTGen in three perturbation modes, evaluated end to end with an explicit per-source analysis of where the defense works, where it is inert, and why (Section 4.3 and Chapter 5).

## 1.5 Organization of the Document

The remainder of this document is organized as follows. Chapter 2 presents the background this work builds on: learning-based intrusion detection and traffic representation, adversarial machine learning and the realizability constraints that distinguish it in the network domain, and the ensemble concepts behind DEPT's detector. Chapter 3 surveys the related work on both the attack and the defense sides, gives TANTGen the closer treatment its role in this thesis requires, and closes by positioning DEPT against the surveyed defenses and stating the gap it fills. Chapter 4 presents DEPT itself, as a designer would proceed: the threat model, the system overview, the construction of the corpus and of the packet-to-tensor pipeline, the detection ensemble, and the purification and realization stages, together with the implementation. Chapter 5 evaluates the delivered system against two research questions derived from the objectives above, covering streaming detection and purification, and reporting the cases where the system does poorly with the same prominence as those where it excels. Chapter 6 closes with the summary of contributions, the answers to the research questions, the system's limitations, and future work, of which the continuous adaptation of the defense against an evolving attacker is the main direction.

# 2

# Background

## Contents


2.1 Machine Learning for NIDS . . . . . 8

2.2 Adversarial Machine Learning . . . . . 13

2.3 Ensemble Learning for Robustness . . . . . 17

2.4 Summary . . . . . 19


DEPT combines three main ingredients: a bit-level representation of network traffic, a heterogeneous detection ensemble, and a generative purifier. This chapter presents the concepts that each of these components builds upon. Instead of a broad survey of machine learning for security, the focus is kept on the specific concepts that the system relies on, so that the design decisions of Chapter 4 follow from the principles introduced here. Section 2.1 covers learning-based intrusion detection, traffic representation, and the model architectures that DEPT composes. Section 2.2 introduces adversarial machine learning and the realizability constraints that distinguish it in the network domain. Section 2.3 presents ensemble learning and the transferability argument behind DEPT's detector, and Section 2.4 ties the three parts together.

## 2.1 Machine Learning for NIDS

A NIDS inspects network traffic in order to separate benign activity from attacks. Classical systems match traffic against hand-written signatures of known threats, which makes them precise on catalogued attacks but unable to detect anything absent from the rule set, including minor variants of existing malware. ML reformulates detection as a data-driven problem: instead of enumerating signatures, a model learns the statistical structure that separates benign from malicious traffic, and can therefore generalize to variants and to previously unseen attacks [1, 2]. This shift supports a large body of modern detection research [3, 4], and it defines the setting in which DEPT operates: every component of the system is a learned model.


### 2.1.1 Learning Paradigms

Learning-based intrusion detection is usually organized by the kind of supervision a model requires. Four paradigms recur in the literature, of which DEPT draws on two.

Supervised learning trains on labelled data, where each example is marked benign or malicious, and learns a mapping from input features to labels (Figure 2.1). Random forests, support vector machines, and deep neural networks all follow this paradigm [1, 19], and it is the main approach in DEPT: the two base detectors, the meta-learner that fuses them, and the purifier are all trained under supervision. Unsupervised learning uses no attack labels. It models the normal behaviour of a network and flags departures from that baseline as anomalies, which makes it attractive for catching zero-day attacks that a supervised model never saw during training. The canonical example in this domain is Kitsune, an ensemble of autoencoders that scores each packet by how poorly it reconstructs under a model of benign traffic [16]. DEPT does not train a dedicated anomaly detector, but the same principle, learning the distribution of clean traffic and measuring deviation from it, reappears in its purifier. Semi-supervised learning sits between the two, exploiting a small labelled set together with abundant unlabelled data; it is especially relevant in networking, where labelling traffic at scale is expensive. Finally, reinforcement learning replaces the fixed dataset with an agent that learns by interacting with an environment and receiving rewards. DEPT employs neither of the last two, although reinforcement learning is the natural framework for the continuous-adaptation extension discussed in Chapter 6.

### 2.1.2 Feature Engineering and Representation

The performance of a learned detector depends directly on the representation it consumes. Feature engineering, the process of turning raw packets into numerical vectors, places an upper bound on what any model can learn [20, 21]. Before discussing representations, one term should be fixed: throughout this document, a flow is the sequence of packets that share the same five-tuple (source and destination




**(a)** Supervised learning: labelled flows train a model that maps a flow to a label.

**(b)** Unsupervised learning: with no labels, the model learns the structure of the traffic and flags what departs from it.

**Figure 2.1:** The two supervision regimes most relevant to DEPT, illustrated on network flows. All of DEPT's components are trained under supervision; the unsupervised idea of modelling normal behaviour and flagging deviations from it motivates the purification step.

Internet Protocol (IP) addresses, source and destination ports, and transport protocol), ordered by arrival time.

Two axes organize the design space of traffic representations. The first is granularity. Static, packet-level features are read from individual headers (addresses, ports, flags); they are cheap enough to extract at line rate, but they carry no temporal context. Dynamic, flow-level features aggregate a sequence of packets into statistics such as mean packet size, inter-arrival times, or flow duration. These capture behaviour, but at the cost of latency, since the system must wait for the flow to progress [12]. The second axis concerns the space in which a perturbation is expressed: the traffic-space of actual packets on the wire versus the feature-space of derived vectors. This distinction becomes central once adversaries are considered (Section 2.2.3). DEPT works at both granularities, and deliberately keeps its features close to the traffic-space so that its outputs can be turned back into real packets.

Rather than hand-designing features, DEPT represents traffic with **nPrint**, a bit-level encoding of packet headers [22]. Hand-crafted feature sets usually assume in advance which fields matter, and they are tied to particular protocols: a tool that computes flow statistics for Transmission Control Protocol (TCP) says nothing useful about an Internet Control Message Protocol (ICMP) flood. nPrint instead maps each bit of a packet's headers to one feature in a fixed-width vector, using a tri-state encoding: a value of $1$ or $0$ records a header bit that is set or unset, and $-1$ marks a field that belongs to a protocol layer absent from that packet. The representation is uniform across protocols, requires no manual feature design, and can be consumed directly by models that learn their own features. Bit-level encodings of this kind have proven effective for traffic analysis in settings where hand-crafted features generalize poorly [22–24]. DEPT encodes the IPv4, TCP, User Datagram Protocol (UDP), and ICMP headers, producing a $1088$-bit vector ($480 + 480 + 64 + 64$), and appends two derived per-packet scalars, the z-scored Inter-Packet Arrival Time (IPAT) and a direction bit, to obtain a $1090$-dimensional per-packet

token. Figure 2.2 illustrates the encoding. This choice places DEPT within a broader movement towards learned traffic representations, such as the byte-level Deep Packet [24], one-dimensional convolutional encoders over raw flows [23], and pre-trained datagram transformers [25].





**Figure 2.2:** The per-packet representation used by DEPT. Each packet's IPv4, TCP, UDP, and ICMP headers are encoded bit-by-bit into a fixed $1088$-bit vector following nPrint [22]: a cell holds $1$ or $0$ for a set or unset header bit and $-1$ when the corresponding layer is absent. High-entropy identity fields (source and destination IP, transport ports, and the IP identification field) are masked to zero. The z-scored inter-packet arrival time and a direction bit are appended, giving a $1090$-dimensional token.

A bit-level header vector inevitably includes fields that identify the particular hosts and ports of a capture: the source and destination IP addresses, the transport ports, and the IP identification field. If these fields are left intact, a model can reach high benchmark accuracy simply by memorizing which addresses and ports appear in the attack traces, instead of learning the attack behaviour itself; this shortcut inflates test scores but does not survive deployment on a different network [12,26]. DEPT therefore masks these identity fields, zeroing the $144$ bits that encode them (Figure 2.2). Masking forces the detectors to rely on behavioural structure, such as packet sizing and timing, and it directly supports the claim that detection transfers across deployments instead of overfitting to one capture. Field selection of exactly this kind is a first-class feature of the nPrint representation [22].

The same tokens feed two representations at different rates, a design choice matched to the two kinds of base learner that DEPT uses (Table 2.1). The TCN consumes the full per-packet token stream, one $1090$-dimensional vector per packet. The random forest instead consumes prefix-checkpoint statistics: at selected packet positions, six base features (inter-arrival time, packet size, payload length, payload entropy, TCP flags, and direction) are summarized by their mean, standard deviation, minimum, and maximum over the flow prefix seen so far, giving a compact $24$-dimensional vector. Checkpoints are emitted at packet $2$ and then every tenth packet. The early checkpoint is deliberate: some attacks generate extremely short flows. A port scan, for example, averages roughly two packets per flow, typically a single SYN and its RST, so without the checkpoint at packet $2$ the forest would never issue a verdict for precisely the flows that a scan consists of. Feeding one learner a dense per-packet sequence and the other a sparse, aggregated summary is also a source of the ensemble diversity that Section 2.3 argues to be valuable.

**Table 2.1:** The two representations DEPT derives from the same masked nPrint tokens.

| Representation | Consumer | Emission rate | Dimension |
|---|---|---|---|
| Per-packet token | TCN | every packet | $1090$ (nPrint $+$ IPAT $+$ direction) |
| Prefix checkpoint | random forest | packet $2$, then every $10$ | $24$ (mean/std/min/max of $6$ features) |

### 2.1.3 Model Architectures Relevant to DEPT

DEPT combines three architecture families, chosen for complementary properties rather than for raw accuracy alone.

**A – Random forests.** A RF is an ensemble of decision trees trained by bagging (Section 2.3.1): each tree recursively partitions the feature space with axis-aligned threshold tests, and the forest averages their votes [27, 28]. Forests are a strong, low-cost fit for tabular and statistical features and need no feature scaling [29], which is why DEPT applies one to the $24$-dimensional checkpoint vectors. Their decisive property for this work, however, is structural: a forest's decision function is constant over axis-aligned regions and therefore non-differentiable. It exposes no informative gradient that an attacker can follow, a property whose relevance for adversarial robustness is developed in Section 2.3.2.

**B – One-dimensional and temporal convolutional networks.** A Convolutional Neural Network (CNN) slides learnable kernels over its input to detect local patterns; in one dimension it processes sequences, extracting recurring motifs from a packet stream such as header patterns or sizing signatures [23, 24] (Figure 2.3). A TCN specializes this design for long sequences through two devices [30]. Dilated convolutions insert a growing stride between kernel taps, so the receptive field expands with depth without a corresponding blow-up in parameters [31]. Causal convolutions pad the input so that the output at position $t$ depends only on positions $\leq t$, never on future packets. Causality is what makes the model valid for streaming inference: it can emit a verdict after each packet arrives. DEPT's TCN stacks three residual blocks of $128$ channels with kernel size $k = 3$ at dilations $1$, $2$, and $4$, with two convolutions per block. Its receptive field is

$$\mathrm{RF} \;=\; 1 + 2\,(k-1)\sum_{i=0}^{2} 2^{\,i} \;=\; 1 + 2 \cdot 2 \cdot (1+2+4) \;=\; 29 \text{ packets}, \tag{2.1}$$

so a verdict at any packet integrates evidence from up to the preceding $29$ (Figure 2.4).

**C – Transformers.** The self-attention mechanism lets every position in a sequence attend to every other position, weighting them by a learned measure of relevance [32]. Each input position is projected into a query, a key, and a value vector; collecting these as the rows of matrices $Q$, $K$, and $V$, attention





**Figure 2.3:** A one-dimensional convolutional pipeline over a packet sequence: kernels slide along the sequence and produce per-position feature maps, which further layers, pooling, and a classification head turn into a verdict. DEPT's temporal convolutional network specializes this design with dilated, causal convolutions.





**Figure 2.4:** Dilated causal convolutions in a temporal convolutional network. Highlighted nodes trace the dependency cone of the rightmost output: each layer's kernel skips inputs at a growing dilation ($1$, then $2$, then $4$), so the receptive field expands with depth while every output still depends only on the present and past. The figure is schematic (one convolution per block is drawn); DEPT stacks two convolutions per block, giving the $29$-packet receptive field of Equation (2.1).

computes

$$\text{Attention}(Q, K, V) \;=\; \text{softmax}\left(\frac{QK^{\top}}{\sqrt{d_k}}\right) V, \tag{2.2}$$

where $d_k$ is the key dimension, so the output at each position is a weighted combination of the values of the positions it attends to. This captures long-range dependencies that a fixed convolution window cannot. Two arrangements are relevant here. Encoder-only models attend bidirectionally over the entire sequence, which suits classification and representation tasks, including learned traffic analysers [25,33]. Decoder-only models apply a causal mask so that each position attends only to the past, which suits autoregressive and streaming generation (Figure 2.5). Causality also enables key–value caching: since the keys and values of past positions in Equation (2.2) do not change when new tokens arrive, they can be stored and reused, and producing each new token then costs work proportional to the current length instead of reprocessing the whole prefix. This property is what keeps causal, autoregressive inference tractable under tight latency budgets. DEPT adopts the causal arrangement in both of its Transformer components: the meta-learner is a compact, causally-masked encoder that fuses the base detectors' per-packet outputs (Section 2.3.1), and the purifier is a decoder-style sequence model whose causal masking keeps it amenable to key–value caching for streaming deployment (Chapter 4).

## 2.2 Adversarial Machine Learning

The same flexibility that lets a learned model generalize also exposes it to manipulation. An adversarial example is an input perturbed by a small, deliberate amount so that the model misclassifies it, often while remaining nearly indistinguishable from a clean input [5, 6]. For a NIDS, adversarial examples are the mechanism of evasion: an attacker reshapes malicious traffic just enough for it to be labelled benign [7, 34]. Adversarial Machine Learning (AML) studies both how such manipulations are constructed and how models can be hardened against them.

### 2.2.1 Threat Taxonomy

Attacks are classified along two axes: what the adversary knows, and what the adversary wants.

Along the knowledge axis, a white-box attacker has full access to the model, including its architecture and weights, and can compute gradients of the loss with respect to the input to craft precise perturbations. A gray-box attacker knows only part of the pipeline, such as the feature set. A black-box attacker can only query the system and observe its outputs. The black-box setting is the realistic one for a deployed NIDS, which an attacker probes as an oracle, and such attacks typically rely on transferability: an adversarial example crafted against a substitute model often fools the target as well [11]. Along the goal axis, poisoning corrupts the model during training, whereas evasion manipulates inputs at inference





**Figure 2.5:** A decoder-only Transformer block over a stream of packet tokens: masked (causal) self-attention followed by a feed-forward sublayer, with residual connections and layer normalization, stacked $N$ times. The causal mask restricts each position to its past, which makes the design valid for streaming inference and amenable to key–value caching.

time against an already-trained model. DEPT is designed for the black-box evasion threat, which is the case that dominates real deployments (Chapter 4).

Network intrusion detection is harder to attack, and to defend, than the image classification setting where adversarial examples were first studied, because of a constraint with no analogue in the pixel domain. Any pixel of an image can be modified slightly and the result is still a valid image. A network feature vector cannot be modified freely: a perturbation must correspond to a packet or flow that is actually valid on the wire. Recovering a realizable packet from a desired feature vector is the **IFM** problem, and it is frequently constrained or computationally intractable [9, 10, 35]. The IFM problem is the defining difficulty of network adversarial machine learning, and it shapes attacks and defenses alike. In particular, the gradient-based methods that dominate the image setting, such as the Fast Gradient Sign Method (FGSM) and Projected Gradient Descent (PGD) [6, 36], produce feature perturbations that need not correspond to any sendable packet, which limits their direct applicability in this domain.

### 2.2.2 Defense Paradigms

Defenses against evasion fall into a few broad families, with different strengths for traffic data. Adversarial training augments the training set with adversarial examples so that the model learns to classify them correctly [36]. It is effective against the perturbations it is trained on, but it is costly, it can depress accuracy on clean traffic, and in networking it is only meaningful if the adversarial examples are themselves realizable rather than impossible feature vectors. DEPT follows this line in spirit, since its detectors are trained on realizable adversarial traffic rather than on synthetic feature perturbations (Chapter 4); the fundamental difference is that DEPT's goal is to distinguish naturally occurring traffic from adversarially perturbed traffic, not to classify both as malicious.

Input transformation, or purification, is the family DEPT builds its purifier on. Instead of hardening the classifier, it transforms each input before classification in order to remove the perturbation, projecting the sample back onto the manifold of normal traffic, as Figure 2.6 illustrates. The idea originates with Defense-GAN, which projects each input onto the manifold captured by a generative adversarial network [15], and it has since been realized in the network domain with diffusion models [37, 38] and reconstruction-based Transformer autoencoders [33]. DEPT's purifier is a causal Transformer denoiser in this tradition (Chapter 4).

Two further families should be mentioned, although DEPT adopts neither. Defensive distillation trains a second model on the softened probability outputs of a first one, smoothing the decision surface so that useful gradients become harder to find [39]; it has been largely circumvented and does not address realizability. Certified robustness provides provable guarantees that no perturbation within a bounded region can change a prediction, through randomized smoothing [40, 41] or Lipschitz and edit-distance bounds [42]. Such guarantees are valuable, but they are difficult to scale to the high-dimensional,





**Figure 2.6:** Purification as projection onto the benign manifold. An adversarial perturbation $\delta$ moves a clean flow $x$ off the manifold of benign traffic; without purification, the perturbed flow $x'$ is misclassified by the downstream detector. The purifier $g$, trained on the benign distribution, projects $x'$ back onto the manifold, and the detector then receives an input close to the original $x$. The idea originates with generative-model defenses such as Defense-GAN [15].

discrete, and sequential structure of network traffic, and they secure a formal radius rather than the traffic-space validity that is central to this work.

### 2.2.3 Realizability and Protocol Constraints

The gap between a valid feature vector and a valid packet is the central difficulty of network adversarial machine learning. A perturbation can move a feature vector anywhere in $\mathbb{R}^n$, but a packet must satisfy hard structural constraints: checksums must match the bytes they cover, header-length fields must equal the actual lengths, control flags must be mutually consistent, and sequence numbers must be ordered. A perturbation that ignores these constraints is unrealizable: it describes no packet that can be sent, so evaluating a detector against it overstates the real threat [9, 10]. Recent attack research enforces realizability explicitly, whether by verifying every perturbation against protocol constraints with an SMT solver, as in PANTS [43], or by generating traffic that is protocol-compliant by construction, as in GPMT [35] and TANTGen [13].

It is important to note that the constraint applies to both sides, and this is what makes it a design concern for DEPT rather than a property of attacks alone. A defense that edits traffic, as a purifier does, must itself re-emit valid packets; otherwise its output is unusable, or is trivially detected as malformed. The step from feature-space back to traffic-space, which we call realization, is therefore treated as a first-class part of the design rather than a mere afterthought. The nPrint representation is an asset here: because it is close to a bijective, bit-level image of the packet headers, a purified nPrint vector can be decoded back into a concrete packet and checked for on-the-wire validity, which DEPT does

with packet-level tooling (Chapter 4). The same protocol constraints can even be turned into a detector, by flagging inter-field inconsistencies [44]; DEPT does not adopt this approach, but it underlines how central protocol structure is to the problem.

## 2.3 Ensemble Learning for Robustness

An ensemble combines several base models into a single predictor, on the premise that a collective decision is more accurate and more robust than that of any single learner [29, 45]. Beyond accuracy, ensembles are of particular interest for security, because diversity among the base models can be turned directly against adversarial transferability.


### 2.3.1 Bagging, Boosting, Stacking

Three combination strategies dominate (Figure 2.7). Bagging trains homogeneous models in parallel on bootstrap resamples of the data and averages their predictions, which reduces variance; the random forest is bagging applied to decision trees [27, 28]. Boosting trains models sequentially, each one focusing on the examples its predecessors got wrong, which reduces bias [46]. Stacking trains heterogeneous base learners and then trains a separate meta-learner to combine their outputs [14]. Stacking is most effective precisely when the base learners are diverse and make different kinds of error, so that their combination covers more of the input space than any of them alone.

DEPT stacks a random forest and a temporal convolutional network, which is precisely the setting stacking was designed for. The two learners are heterogeneous in architecture and asynchronous in operation: the network emits a dense verdict on every packet, while the forest emits a sparse verdict only at its checkpoints, starting at packet $2$. A fixed combination rule, such as averaging or majority voting, cannot express when each learner should be trusted. A learned meta-learner can: by assigning input- and position-dependent weights to each base output, it acts as a dynamic gating mechanism rather than a static average [47, 48]. DEPT implements this meta-learner as a small attention model over the fused per-packet outputs, a choice that is further motivated by the transferability argument below and detailed in Chapter 4.

### 2.3.2 Gradient Masking and Transferability

Transferability is what makes black-box evasion practical: an attacker who cannot see the target model builds a differentiable substitute, crafts a perturbation against it with a gradient method such as PGD or the FGSM, and relies on that perturbation carrying over to the target [11]. Heterogeneous stacking acts directly on this mechanism. A differentiable member, such as the TCN, exposes a gradient that




**(a)** Bagging: parallel homogeneous models on resampled data, averaged.

**(b)** Boosting: sequential models, each correcting the last.

**(c)** Stacking: heterogeneous models fused by a meta-learner.

**Figure 2.7:** The three classical ensemble strategies. DEPT's detector is a stacking ensemble, chosen because its base learners are architecturally heterogeneous and emit predictions at different rates.

an attacker can follow. An RF does not: its decision function is constant over axis-aligned regions, so there is no gradient direction to exploit. Combining a differentiable and a non-differentiable model yields what the literature calls a rugged decision boundary, in which a perturbation optimized against the differentiable member does not necessarily move the forest's discrete verdict, and therefore transfers poorly across the ensemble, raising the attacker's cost [48–51].

This argument must be stated carefully, because the absence of a usable gradient is a form of gradient masking, and gradient masking is not robustness in the general case. A determined white-box adversary can estimate gradients numerically or fall back on gradient-free search, and masked gradients have repeatedly produced a false sense of security when mistaken for genuine robustness [52]. The argument holds for DEPT precisely because its threat model is black-box: the value of a non-differentiable member is not an absolute barrier, but a measurable reduction in the transferability from whatever substitute the attacker is able to build without direct gradient access. Robustness is therefore treated as a property to be evaluated empirically, not as a guarantee to be assumed, a distinction that Chapter 5 takes up.

## 2.4 Summary

The concepts in this chapter compose into the three pillars of DEPT. Representation: a bit-level nPrint encoding, stripped of identity fields and emitted at two rates, gives heterogeneous learners a shared, behaviour-focused, and realizable view of traffic (Section 2.1.2). Ensembling: heterogeneous stacking, fused by an attention meta-learner, combines a differentiable network with a non-differentiable forest to resist transferable gradient attacks under a black-box threat model (Section 2.3). Purification: an input-transformation defense, built as a causal Transformer, projects flagged traffic back onto the benign manifold while respecting the protocol constraints that keep its output realizable (Sections 2.2.2 and 2.2.3). These three elements are the building blocks of the architecture presented in Chapter 4. The prior work that each of them draws on, and the gap that DEPT's particular combination fills, are the subject of Chapter 3.

# 3

# Related Work

## Contents


3.1 Adversarial Attacks against ML-based NIDS . . . . . 22

3.2 Training-time Defenses . . . . . 24

3.3 Inference-time Defenses . . . . . 26

3.4 Positioning of DEPT and Gap Analysis . . . . . 27


The tension between learning-based detection and adversarial evasion has produced a large body of research on both sides. Chapter 2 introduced the concepts this work builds on; this chapter surveys the concrete systems, and reads each of them against the questions DEPT has to answer: what realistic attacks against a NIDS look like (Section 3.1), what can be done before deployment to harden a model (Section 3.2), and what can be done at inference time on the inputs themselves (Section 3.3). The survey is deliberately selective rather than exhaustive: works are included when they shape a design decision of DEPT, or when DEPT departs from them and the departure needs justification. Section 3.4 closes the chapter by placing the surveyed defenses and DEPT on a common map and stating the gap this thesis addresses.

## 3.1 Adversarial Attacks against ML-based NIDS

A defense is only meaningful relative to the attacks it expects, so the survey starts on the offensive side. Following the distinction of Section 2.1.2, attacks divide by the space in which they operate: the feature-space of derived vectors, or the traffic-space of actual packets.

**A – Feature-space attacks.** The first wave of attacks against learned traffic detectors transplanted the gradient-based methods of the image domain, FGSM and PGD among them [6, 36], onto NIDS feature vectors. Hashemi et al. [10] were among the first to evaluate state-of-the-art network detectors under such manipulations, and Tiki-Taka [8] made the threat concrete at scale: attacking deep learning-based intrusion detectors with a battery of black-box methods, it reached evasion rates of up to $35.7\%$ against models that had looked nearly perfect on clean benchmarks. Two lessons carry over to this work. First, a detector built from a single differentiable architecture inherits a smooth loss surface that gradient-guided search can exploit, directly or through a substitute model [11]; notably, the defenses that Tiki-Taka itself proposed, model voting and ensemble adversarial training, already point towards the ensemble route DEPT takes. Second, most of these attacks perturb feature vectors without asking whether any real packet sequence maps to the perturbed vector, which is exactly the realizability critique of Section 2.2.3 [9, 12]: their reported evasion rates are upper bounds obtained in a space an external attacker does not control.

**B – Traffic-space attacks.** The recent attack literature has therefore moved into the traffic-space, enforcing realizability either by verification or by construction. **GPMT** [35] generates practical malicious traffic with a GAN under little prior knowledge of the target, constraining its perturbations so that the traffic keeps its malicious function. **PANTS** [43] couples adversarial search with an Satisfiability Modulo Theories (SMT) solver, so that every candidate perturbation is formally checked against protocol and semantic constraints before it is accepted; the cost of solving is the price of the guarantee. **DeepRed** [53] embeds a GAN-based generator in a multi-stage command-and-control framework and shows that realizable, protocol-abiding attacks degrade the detection rate of ML-based NIDS by up to $20\%$, which settles that the threat survives the realizability constraint. Most recently, **NetDiffuser** [54] brought diffusion models to the attack side, injecting semantically consistent perturbations into flow features, although still under a white-box assumption. The trend across these works is clear: the attack side has converged on generative sequence models operating under explicit realizability constraints, and it is precisely to this class that the attacker of this thesis belongs.

### 3.1.1 TANTGen, the Attacker of This Thesis

**TANTGen** [13] is a Transformer-based adversarial network traffic generator developed in the sibling thesis of this one, and it deserves a closer treatment than the works above because it is not merely related work: it is the concrete adversary that DEPT is trained against and evaluated on. Where GPMT and DeepRed rely on GANs and PANTS on solver-checked perturbations, TANTGen uses self-attention to model the sequential dependencies between the packets of a flow, and generates its evasions in the traffic-space directly, so that protocol compliance holds by construction rather than by after-the-fact verification. It operates in the black-box setting: it needs no access to the target detector's architecture, weights, or gradients, only to the detection outcomes it can observe while probing, and its evasion capability was demonstrated against the detectors its generation was calibrated on: Kitsune [16], the anomaly-based detector, for its Kitsune-native attacks, and its own suite of ML-NIDS flow classifiers for the CIC attacks. The manipulation itself is confined to two physical quantities of live attack traffic, packet timing and packet size, exposed as the three perturbation modes (`iat`, `size`, `both`) that structure the corpus of Section 4.3.

Taking TANTGen as the adversary has three consequences that run through DEPT's design. First, since the adversarial traffic is protocol-compliant by construction, a defense gains nothing from checking protocol validity; whatever signal exists must be found in the traffic's behaviour, its timing and sizing structure, which is what DEPT's learned detectors consume. Second, because the perturbation touches only timing and size, the detectable footprint can be thin, and in the timing-only mode genuinely faint; Chapter 5 quantifies this honestly. Third, the black-box setting makes transferability the operative attack channel, which is the scenario the heterogeneity argument of Section 2.3.2 is aimed at. The threat model of Section 4.1 formalizes these assumptions.

### 3.1.2 Gradient-guided Evasion, the Second Attacker

TANTGen is the adversary DEPT is trained on, but it cannot be the only one it is evaluated against, and the reason is structural rather than a matter of thoroughness. DEPT's central design claim is that fusing a non-differentiable Random Forest with a differentiable TCN raises the cost of evasion because an attacker's gradient reaches only one of the two. TANTGen has no gradient into either. It can therefore demonstrate that the ensemble detects its perturbations, but it cannot price the mechanism the claim rests on: an attack that never differentiates anything says nothing about what differentiability is worth. Section 5.7 closes that gap with a complementary adversary drawn from the standard adversarial-ML toolkit.

The canonical instrument is PGD [36], which takes repeated gradient steps against a model's loss and projects each iterate back onto a feasible set. Its strength as an evaluation tool is that it makes

the feasible set explicit: whatever the attacker is allowed to change, and by how much, is a projection operator rather than an implicit consequence of the optimizer. Because a hand-tuned attack that underperforms flatters the defense it is measuring, robustness evaluations are conventionally cross-checked against a parameter-free optimizer; AutoPGD [55] adapts its own step size for exactly this purpose, and both it and PGD are available in the Adversarial Robustness Toolbox (ART) library [56]. The literature on this failure mode is unambiguous: many published defenses have been shown to owe their apparent robustness to weak or badly-adapted attacks rather than to any real property [57, 58], which is why the evaluation of Section 5.7 reports its attack-strength controls alongside its results rather than in a footnote.

Two features of the network-traffic setting keep this from being a routine application of those tools. The perturbation is not a free vector in the model's input space: it must remain a sendable packet, so the attacker's variables are bytes of padding and seconds of delay, and the budget must be denominated in those units rather than in an $\ell_p$ ball over a tensor whose channels carry incommensurable scales. And the ensemble's two halves do not even read the same features, so a perturbation crafted against one must be replayed through the other's featurisation to be scored at all. Section 5.7 takes both constraints seriously, and Section 5.9.1 discusses what they imply for how the result should be read.

## 3.2 Training-time Defenses

Training-time defenses harden a model before it is ever deployed, by sanitizing its training data or by shaping its decision surface. Four lines of work are relevant here, in rather different degrees.

**A – Data sanitization and poisoning defenses.** The earliest defensive line protects the integrity of the training set itself. **Antidote** [59] replaces the principal-component subspace of an anomaly detector with robust statistics, so that poisoned flows that deviate from the benign subspace are rejected instead of absorbed; its acknowledged difficulty is telling adversarial poisoning apart from the benign drift that non-stationary network traffic produces naturally. A complementary result concerns bagging: Biggio et al. [50] showed empirically, and Chen et al. [51] later certified, that training each ensemble member on a random subset of the data dilutes the influence of any individual poisoned sample across the collective decision. DEPT excludes poisoning from its threat model (Section 4.1), so these defenses are not competitors; they matter here because they establish, from the training side, the same principle DEPT exploits at inference time, that ensemble diversity is a robustness mechanism and not only an accuracy one.

**B – Federated and backdoor defenses.** As NIDS deployments move towards Federated Learning (FL) for privacy, the defensive focus shifts from the data to the model updates that clients contribute. **FedTGE** [60] detects backdoors in federated graph learning through the topological energy of client models, **AlignIns** [61] inspects the directional alignment of local updates, and **CrowdGuard** [62] has clients validate candidate models against their private data inside trusted execution environments. When a model is found already compromised, unlearning techniques such as **SEAM** [63], **BayBFed** [64], and **PBP** [65] scrub the backdoor from the weights at a fraction of the cost of retraining. All of these defend the training pipeline against an insider or a poisoning adversary, a threat DEPT's threat model explicitly trusts away; they are surveyed for completeness and treated as complementary infrastructure rather than as alternatives.

**C – Ensemble-based hardening.** A third line builds robustness into the model by combining several learners, which is the training-time ancestor of DEPT's detection stage. Beyond Tiki-Taka's voting ensembles [8], **TRS** [49] showed that low transferability among ensemble members can be promoted directly, by regularizing for gradient diversity and model smoothness during training, and **Stewart** [48] demonstrated, in the neighbouring domain of predictive maintenance, that a stacking ensemble with a learned meta-model withstands white-box attacks substantially better than its individual members. **Mateen** [66] takes the ensemble idea in the direction of distribution shift, maintaining an adaptive committee of autoencoders for network anomaly detection, and broader benchmarking frameworks confirm the accuracy benefits of ensembling for intrusion detection in general [45]. What nearly all of these have in common is that their members are drawn from the same differentiable family, so a gradient exists for every member and the ensemble's protection rests on decorrelating those gradients. Heterogeneity across families, mixing a non-differentiable forest with a differentiable network so that part of the ensemble offers no gradient at all, is far less explored, and it is the specific form of diversity DEPT's detector is built on (Section 4.4).

**D – Realizable adversarial training.** Adversarial training [36] hardens a model by folding adversarial examples into its training set, but in the network domain it is only as good as the examples themselves: a model trained against impossible feature perturbations is hardened against a threat that cannot occur, the IFM problem of Section 2.2.1 seen from the defender's side. The works of Section 3.1 close this gap by supplying realizable adversarial data, and PANTS in particular demonstrates that inserting its solver-verified examples into the training loop yields robustness that persists against attacks not seen during training [43], while DeepRed argues the same necessity from the red-team side [53]. DEPT's corpus construction follows this line: its detectors are trained on realizable, black-box adversarial traffic generated by TANTGen, not on synthetic feature noise (Section 4.3). The goal, however, differs in kind. Adversarially trained classifiers aim to keep classifying perturbed attacks as attacks; DEPT aims to

recognize the manipulation itself, and then to undo it, which places its second stage in the inference-time family surveyed next.

## 3.3 Inference-time Defenses

Inference-time defenses act at deployment, on the inputs a model receives. Three groups are relevant: certifying predictions against bounded perturbations, purifying inputs before classification, and detecting adversarial inputs by auxiliary signals.

**A – Certified robustness.** Certification promises that no perturbation within a bounded region can flip a prediction. **CertTA** [41] made randomized smoothing practical for traffic analysis by drawing its smoothing noise jointly over the modalities an attacker actually perturbs, packet timing, sizing, and insertion, and derives robustness regions that are meaningful for traffic models. **LipsLev** [42] obtains deterministic certificates under a bounded Levenshtein distance in a single forward pass, several orders of magnitude faster than smoothing-based verification. The guarantee is valuable but bounded by construction: a certificate covers a radius, and a TANTGen-style manipulation is not constrained to stay inside one, since a flow's timing can be stretched by legitimately large amounts while remaining perfectly realizable. Certification is therefore complementary to what DEPT attempts; it bounds the small-perturbation regime, while DEPT's purification acts on whatever manipulation its ensemble flags, with empirical rather than certified coverage (Section 2.2.2 discussed this trade-off in general terms).

**B – Generative purification.** The purification family goes back to **Defense-GAN** [15], which projects each input onto the manifold captured by a generative model before classification. Its modern descendants are mostly diffusion-based, and mostly proven in the image and text domains: **ADBM** [38] constructs a direct reverse bridge from the adversarial to the clean distribution, **CausalDiff** [67] disentangles attack-specific factors from label-causative ones during generation (its notion of causality concerns factor attribution, not the temporal masking DEPT uses), and **DiffuseDef** [68] iteratively denoises the hidden states of a text classifier. In the network domain the idea has been instantiated more recently: **AdvPurRec** [37] reconstructs traffic features with a diffusion model before they reach the NIDS, Merzouk et al. [69] systematically map the trade-off that governs such purifiers, more diffusion noise removes more of the perturbation but degrades clean accuracy, and **GTAE-IDS** [33] applies a graph-Transformer autoencoder to reconstruct traffic representations for real-time detection.

DEPT's reconstructor (Section 4.5) sits in this family but departs from it on three axes, each a deliberate choice rather than an oversight. The first is architectural: diffusion purifiers pay an iterative denoising chain, tens of forward passes, for every input, which sits poorly with a per-packet latency bud-

get, whereas DEPT uses a causal Transformer that produces its correction in a single pass and defaults to the identity through its residual head. The trade is explicit: DEPT gives up the broad distribution coverage of a diffusion process in exchange for a model that fits streaming deployment. The second axis is supervision: purifiers in the Defense-GAN tradition learn from clean data alone and purify by projection, while DEPT exploits the matched adversarial-to-clean flow pairs its corpus provides, a stronger form of supervision that is unavailable in general but natural in a paired-generator setting. The third axis is the one this thesis considers decisive: every network purifier surveyed above stops at the feature vector, and none of them re-emits traffic. A purified vector that corresponds to no sendable packet sequence has simply moved the realizability problem from the attacker to the defender. DEPT treats the step back into the traffic-space, realization followed by dissector-level validation, as part of the defense itself (Section 4.5.3).

**C – Constraint-based and auxiliary detection.** A final group detects adversarial inputs without generative machinery. **NIDS-CBAD** [44] flags violations of inter-feature domain constraints, for instance a payload size inconsistent with a packet count, on the observation that naive feature-space attacks routinely break such invariants. **AMDS** [70] fuses ensemble disagreement, predictive uncertainty, and distributional anomaly scores into an adversarial-input detector with attack-adaptive weights. DEPT adopts neither as its detection principle, for a reason that follows directly from Section 3.1.1: its adversary emits protocol-compliant traffic by construction, so constraint checks are blind to it, and the constraint family defends against exactly the naive attacks that the realizability literature has already moved past. The disagreement signal of AMDS is closer in spirit to this work; DEPT's meta-learner can in fact be read as a learned, per-packet version of it, fusing the opinions of two deliberately dissimilar base learners (Section 4.4.3).

## 3.4 Positioning of DEPT and Gap Analysis

Figure 3.1 arranges the surveyed defenses along the two axes that organized this chapter, the phase at which a defense acts and the space in which it operates, and Table 3.1 records the same works with their strategies and techniques. Read together, they make the pattern of the literature visible. The training-time corner is well populated, but almost entirely in the feature-space; PANTS is the exception that carries realizability into training. The inference-time work concentrates on purification, yet every network purifier acts on feature vectors and returns feature vectors. Traffic-space thinking at inference time exists, in CertTA's certified regions, but certification bounds a radius rather than undoing a manipulation.

The gap this thesis addresses is the combination. Of the surveyed works, none brings together (a) training data that is realizable and generated under a black-box threat model, (b) an ensemble that is het-





**Figure 3.1:** The surveyed defenses arranged by the phase at which they act (training time against inference time) and the space they operate in (feature-space against traffic-space). Prior defenses cluster in the feature-space row; PANTS brings realizability to training, and CertTA to certification. DEPT spans both phases in the traffic-space row: it is trained on realizable adversarial traffic and purifies flagged flows back into valid packets at inference time.

**Table 3.1:** Comparison of the surveyed adversarial defenses and of DEPT. Phase: $\mathcal{T}$ training-time, $\mathcal{I}$ inference-time. Scope: $\Phi$ feature-space (abstract vectors), $\Psi$ traffic-space (realizable packets).

| System | Year | Strategy | Phase | Scope | Techniques |
|---|---|---|---|---|---|
| Antidote [59] | 2009 | Statistical sanitization | $\mathcal{T}$ | $\Phi$ | Robust statistics |
| Bagging defense [50, 51] | 2011 | Poisoning defense | $\mathcal{T}$ | $\Phi$ | Bagged ensemble |
| Tiki-Taka (defense) [8] | 2020 | Ensemble hardening | $\mathcal{T}$ | $\Phi$ | Voting, adv. training |
| TRS [49] | 2021 | Ensemble hardening | $\mathcal{T}$ | $\Phi$ | Gradient diversity |
| CrowdGuard [62] | 2024 | FL backdoor defense | $\mathcal{T}$ | $\Phi$ | TEE, clustering |
| PBP [65] | 2025 | Backdoor unlearning | $\mathcal{T}$ | $\Phi$ | Neuron masking |
| PANTS [43] | 2025 | Adversarial training | $\mathcal{T}$ | $\Psi$ | SMT-verified examples |
| Defense-GAN [15] | 2018 | Purification | $\mathcal{I}$ | $\Phi$ | GAN projection |
| AdvPurRec [37] | 2024 | Purification | $\mathcal{I}$ | $\Phi$ | Diffusion |
| GTAE-IDS [33] | 2025 | Reconstruction detection | $\mathcal{I}$ | $\Phi$ | Transformer autoencoder |
| CertTA [41] | 2025 | Certified robustness | $\mathcal{I}$ | $\Psi$ | Multi-modal smoothing |
| LipsLev [42] | 2025 | Certified robustness | $\mathcal{I}$ | $\Phi$ | Levenshtein certificates |
| NIDS-CBAD [44] | 2025 | Adversarial detection | $\mathcal{I}$ | $\Phi$ | Domain constraints |
| AMDS [70] | 2026 | Adversarial detection | $\mathcal{I}$ | $\Phi$ | Ensemble signals |
| **DEPT** (this thesis) | 2026 | Detection + purification | $\mathcal{T}+\mathcal{I}$ | $\Psi$ | Realizable corpus, heterogeneous stacking, causal Transformer, traffic-space realization |

erogeneous across architectural families, pairing a non-differentiable with a differentiable learner to resist transfer, and (c) a generative purification stage whose output is realized back into protocol-compliant packets. Each property exists in isolation: PANTS holds (a) but hardens classifiers and performs no purification, TRS and Stewart hold (b) within homogeneous differentiable families or outside the network domain, and AdvPurRec and GTAE-IDS hold (c) up to the feature vector, on single datasets and without a streaming constraint. DEPT composes all three and is evaluated end to end, against a live generative adversary rather than replayed perturbations, on a corpus built over ten benign traffic sources and three perturbation modes, with metrics that respect the streaming setting (Chapter 5). One further line of the literature is acknowledged but not pursued: reinforcement learning is increasingly used to make security responses adaptive [71–73], and a defense that retrains against an evolving generator is the natural continuation of this work; DEPT as delivered is a static defense, and Chapter 6 frames that continuation as future work. The architecture that occupies this gap is the subject of Chapter 4.

# 4

# Solution: DEPT Architecture

## Contents


4.1 Threat Model . . . . . 32
4.2 System Overview . . . . . 33
4.3 Dataset Construction and Packet-to-Tensor Pipeline . . . . . 35
4.4 Primary Detection: Heterogeneous Stacking Ensemble . . . . . 37
4.5 Input Purification: Reconstructor Transformer . . . . . 39
4.6 Implementation and Tools . . . . . 42


This chapter presents DEPT (Defense via Ensemble and Purification Transformer), the system this thesis proposes and builds. DEPT composes the three pillars introduced in Chapter 2 into a single streaming defense: a bit-level traffic representation emitted at two rates, a heterogeneous detection ensemble fused by an attention meta-learner, and a causal purification Transformer whose output is realized back into valid packets. The chapter is organized as a designer would proceed. Section 4.1 fixes the threat model, since every later decision is only justified relative to it. Section 4.2 gives the end-to-end view of the architecture and its two operating phases. Section 4.3 describes how the training corpus is constructed and how raw captures become the tensors the models consume. Sections 4.4 and 4.5 then detail the two functional stages, detection and purification, and Section 4.6 closes with the

implementation. Design decisions and their rationale belong to this chapter; the measured behaviour of the resulting system is the subject of Chapter 5.

## 4.1 Threat Model

The scenario, illustrated in Figure 4.1, involves three parties. A protected NIDS guards a network and is assumed to handle conventional, non-adversarial attack traffic; this is the detector an adversary wants to get past. An attacker manipulates the traffic of an ongoing attack so that this NIDS no longer recognizes it, in the mould of the evasion attacks of Section 2.2. DEPT sits inline, immediately upstream of the protected NIDS: its job is to decide, packet by packet, whether a flow has been adversarially manipulated, and to neutralize the manipulation before the protected system ever consumes the flow.





**Figure 4.1:** DEPT's deployment context. Benign traffic and adversarially manipulated traffic (generated by TANTGen in this work) arrive interleaved. DEPT inspects every flow in streaming fashion: flows judged clean are forwarded unchanged, while flagged flows pass through the purifier first, so that the protected NIDS downstream receives traffic whose adversarial manipulation has been undone.

The attacker is modelled after TANTGen [13], the Transformer-based adversarial traffic generator developed in the sibling thesis and reviewed in depth in Chapter 3. This choice pins the threat model to capabilities that have been demonstrated rather than assumed. The attacker operates in the black-box setting of Section 2.2.1: it has no access to the architecture, parameters, or gradients of DEPT or of the protected NIDS, and can at most observe detection outcomes while probing. It perturbs live attack traffic along two physical axes, the timing of packets (their inter-arrival times) and their size (payload padding), which TANTGen exposes as three perturbation modes: `iat` (timing only), `size` (size only), and `both`. Crucially, the generated traffic is protocol-compliant by construction; it consists of packets that can actually be sent and that a dissector parses without complaint.

We further adopt a functional realizability assumption: attacks that violate protocol semantics, for instance a broken checksum, a length field inconsistent with the bytes on the wire, or a negative inter-arrival time, are out of scope by design. This is a scoping decision rather than a weakness. As discussed in Section 2.2.3, a perturbation that describes no sendable packet is not a working evasion in the first place, and such malformed traffic is trivially rejected by stateless checks well before any learned model

needs to be involved.

TANTGen fixes the threat model to demonstrated capabilities, but it also bounds what that model can be asked. Being gradient-free, it cannot price a gradient path, and the central claim of this design, that fusing a non-differentiable learner with a differentiable one raises the cost of evasion, is a claim precisely about gradient paths. Establishing it needs an adversary that has one.

We therefore admit a second, strictly stronger adversary alongside TANTGen, and evaluate against it in Section 5.7. It is granted white-box access to the TCN: exact architecture, weights and gradients. It is granted nothing at all for the Random Forest, which is not merely withheld but non-differentiable, so no gradient exists to leak. This is the sharpest form of the heterogeneity question rather than a concession: the attacker holds one half of the ensemble exactly and must reach the other half through the traffic they share. Its perturbations obey the same functional realizability assumption as TANTGen's and are further constrained to be increase-only, since packets already on the wire may be padded or delayed but never un-sent, and are measured in the units an attacker actually spends, bytes of padding and seconds of delay, rather than in an abstract norm.

Three non-goals complete the model. First, DEPT does not defend against poisoning: its training data is curated offline from known sources, and the training pipeline is trusted. Second, no claim is made against an adversary with gradient access to every component, which for the Random Forest is not a realistic capability but an impossible one. Third, DEPT does not replace the protected NIDS. Detecting the underlying attacks themselves (a flood, a scan, a brute-force attempt) remains the downstream system's job; DEPT answers only the narrower question of whether a flow has been adversarially tampered with. This division of labour directly shapes the labelling convention of Section 4.3.

## 4.2 System Overview

Figure 4.2 shows the complete architecture. Traffic enters through the Packet-to-Tensor pipeline, which converts each flow into the masked nPrint representation of Section 2.1.2 and emits it at two rates: a dense per-packet token stream and a sparse stream of prefix statistics. The two base learners consume one stream each. The TCN produces a verdict logit at every packet, from the very first one; the RF produces a logit at packet 2 and then every ten packets, on the aggregated prefix. A per-packet fusion token joins the two prediction streams with a small amount of context, and the meta-learner, a compact causal Transformer, turns that token stream into a per-packet probability that the flow is adversarial. Flows that never cross the decision threshold are forwarded untouched. Flows that do are handed to the reconstructor, a causal purification Transformer that undoes the manipulation in feature space; its output is passed on to the protected NIDS, and a separate realization step can materialize the purified flow as an actual PCAP whenever concrete packets are required.





**Figure 4.2:** The DEPT architecture. The Packet-to-Tensor pipeline feeds two representations of the same flow to two architecturally different base learners; their prediction streams are joined into 13-dimensional per-packet fusion tokens and fused by a causal mini-Transformer into a streaming verdict. Only flagged flows pay the cost of purification. Realization (the mapping of the purified flow back onto concrete packets, validated with tshark) runs off the inference path.

The shape of the system follows from the objectives stated in Section 1.3. The shared representation and its dual emission cadence answer O1: both learners see the same masked, behaviour-focused view of a flow, each at the granularity it is suited for. The ensemble answers O2: the two base learners differ in architecture (non-differentiable trees against a differentiable network), in input (aggregated statistics against raw sequences), and in timing (sparse against dense), which is exactly the diversity that the transferability argument of Section 2.3 asks for. The reconstructor answers O3, restoring flagged flows to the benign manifold while keeping them realizable. The streaming discipline that runs through all of it, verdicts at every packet rather than at end of flow, is what O4's evaluation axis is later measured against.

DEPT operates in two phases. In the training phase, all components are fitted offline, in dependency order. The pipeline first tensorizes every source once. The two base learners are then trained independently on the training split. The meta-learner is trained next, not on the training split but on the validation split, where the base learners' predictions are out-of-fold; Section 4.4.3 returns to why this matters. The reconstructor is trained last, on matched pairs of adversarial and clean flows. Its purification effect is then quantified primarily against the independent NIDS each attack was built to evade, Kitsune or TANTGen's ML-NIDS (Section 5.8), with the already-trained TCN kept only as a secondary in-distribution diagnostic; Section 5.6 discusses why the external judge, not DEPT's own detector, carries the end-to-end claim. In the deployment phase the flow of Figure 4.2 runs continuously: tensorize each arriving packet, update both base learners, fuse, and decide. Purification is gated on the ensemble's flag, so the common case, clean traffic, never pays for it, and only the flows the detector marks adversarial are handed to the reconstructor before reaching the protected NIDS. This detect-then-purify cycle is the design point on which the real-time requirement of Section 1.2 rests; measuring it in wall-clock terms is left to future work (Section 6.4).

## 4.3 Dataset Construction and Packet-to-Tensor Pipeline

**A – Traffic corpus.** The corpus pairs ten benign traffic sources with adversarial counterparts generated by TANTGen. Five sources carry over from the datasets most used in the related literature: the Mirai botnet and SSDP flood captures of Kitsune [16], and the Distributed Denial of Service (DDoS), port scan, and FTP/SSH brute-force captures of CIC-IDS2017 [17]. Five more come from CIC-DDoS-2019's reflection and amplification floods (NTP, DNS, SSDP, SYN, and LDAP) [18]. For each source, TANTGen produced one adversarial variant per perturbation mode (`both`, `iat`, `size`), giving thirty adversarial source–mode combinations. Two construction decisions deserve mention. The CIC-DDoS-2019 captures are attack-dominated from their first seconds and offer no clean time window to filter on, so each is truncated to its first million packets instead, the same scale at which the generator caps its own malicious input. And no source without a TANTGen counterpart was admitted into the corpus: benign

flows from unpaired captures would inflate the benign class without contributing any adversarial signal to learn against.

**B – Label convention.** Every flow taken from the raw datasets is labelled benign, including their native attacks, and every TANTGen-generated flow is labelled adversarial. This follows directly from the threat model: detecting a flood or a scan is the protected NIDS's responsibility, while DEPT's task is to recognize whether a flow has been manipulated. The labels therefore encode precisely the question the system must answer, "did the generator touch this flow". The convention has a measurable consequence, namely that a source whose features TANTGen barely moves is close to unlabellable no matter the detector, and Section 5.9 analyses this cost openly rather than folding it into aggregate numbers.

**C – From packets to tensors.** Each capture is processed in a single pass. Packets are grouped into flows by their canonical five-tuple and kept in stable timestamp order, and each packet is encoded into the $1090$-dimensional token of Section 2.1.2: the $1088$ masked nPrint header bits plus the z-scored IPAT and a direction bit (the normalization statistics are computed at tensorization time and stored alongside the tensors, so that training and inference standardize identically). The per-flow token sequences are stored as one large ragged array with an offsets table, which keeps loading cheap and lets every downstream model share the same on-disk artifacts.

The same pass also produces the sparse representation for the RF. At each checkpoint, six base features (inter-arrival time, packet size, payload length, payload entropy, TCP flags, and direction) are summarized by their mean, standard deviation, minimum, and maximum over the whole prefix seen so far, a $24$-dimensional vector. These statistics are defined incrementally, by Welford's online algorithm for means and variances together with running extrema, so that a flow need never be buffered: the cost per packet is constant, and the statistics available at a checkpoint are exactly those the forest would see at the same point of a live flow. Offline, where the whole capture is already in memory, the same quantities are computed by vectorized per-flow cumulative sums, which agree with the incremental form to floating-point round-off and are considerably faster to build; the incremental definition remains the one a deployed ingress would evaluate per live flow. Checkpoints fire at packet $2$ and then every tenth packet, the cadence motivated in Section 2.1.2: without the early checkpoint, flows shorter than ten packets, which include essentially every port-scan flow, would end before the forest ever voted. Figure 4.3 lays the resulting prediction pattern out on the packet axis, including the carry-forward behaviour that the fusion stage of Section 4.4.3 builds on.

**D – Splits and class balance.** All models share a single $70/15/15$ train/validation/test split, drawn with seed $42$. The split is flow-atomic: every row derived from a flow, be it a packet token, a checkpoint vector, or a reconstruction pair, lands on the same side, since splitting per row would leak near-duplicate





**Figure 4.3:** The dual prediction cadence over the first packets of a flow. The TCN (circles) emits a verdict at every packet, starting at the first. The Random Forest (squares) emits only at prefix checkpoints (packet 2, then every tenth packet, shaded); between checkpoints its last logit is carried forward, and before packet 2 it has no verdict at all. The `rf_age` row shows the recency counter that the fusion token exposes to the meta-learner. The meta-learner (diamonds) fuses both streams into a fresh verdict at every packet.

prefixes of the same flow across sets. It is also stratified by source, so each split preserves the corpus's source mixture, and it is reused verbatim by the RF, the TCN, the meta-learner, and the reconstructor. This shared discipline is what later makes their comparison like-for-like, and it guarantees that the meta-learner and reconstructor, which consume the base learners' outputs, are never evaluated on flows any base learner trained on. Class imbalance is treated at two levels. Because the reflection floods contribute vastly more benign flows than the other sources, the benign pool is capped at three benign flows per adversarial flow before training; the residual imbalance is then handled by the learners themselves, with balanced class weighting in both the forest and the neural losses.

## 4.4 Primary Detection: Heterogeneous Stacking Ensemble

The detection stage instantiates the stacking pattern of Section 2.3: two deliberately dissimilar base learners and a learned combiner. The base learners are described first, the fusion afterwards.

### 4.4.1 Random Forest Base Learner

The RF consumes the $24$-dimensional checkpoint vectors and answers, at every checkpoint, whether the prefix statistics look manipulated. The choice of a forest for this role is doubly motivated. Practically, forests are strong learners for small tabular inputs and need neither feature scaling nor much tuning (Section 2.1.3). Strategically, a forest's decision function is piecewise constant and non-differentiable, which makes it the gradient-free member that the transferability argument of Section 2.3.2 requires: even a surrogate-based attacker obtains no smooth loss surface that extends to the forest's verdicts.

The configuration was selected by grid search on the validation split, over $\{200, 400\}$ trees, maxi-

mum depths $\{\text{unbounded}, 20, 40\}$, and minimum leaf sizes $\{1, 2, 5\}$, with $\sqrt{d}$ feature sampling and the `balanced_subsample` class weighting fixed throughout. The selected model uses $200$ trees of maximum depth $20$ with at least $5$ samples per leaf. It is worth noting that the search favoured the most regularized corner of the grid: with only $24$ input dimensions, deeper, unconstrained trees mostly memorize checkpoint idiosyncrasies, while a bounded depth and a non-trivial leaf size force splits that generalize across flows. At inference time the forest is queried exactly at the pipeline's checkpoints, so its verdict stream is sparse, delayed by design, and refreshed at the cadence of Figure 4.3.

### 4.4.2 Temporal Convolutional Network Base Learner

The TCN is the dense half of the ensemble. It consumes the full per-packet token stream and emits a logit pair at every position, so a flow acquires its first verdict with its first packet. The network instantiates the architecture of Section 2.1.3: three residual temporal blocks of $128$ channels each, kernel size $3$, dilations $1$, $2$, and $4$, and dropout of $0.15$, closed by a per-timestep linear head; in total about $0.8$ million parameters. Causal padding keeps every output independent of future packets, which is the property that makes the model legitimate for streaming use, and the dilation schedule gives the receptive field of $29$ packets derived in Equation (2.1), enough context to cover several RF checkpoint intervals without inflating the parameter count.

Training minimizes per-packet cross-entropy with balanced class weights, averaged within each flow before averaging across flows, so that a ten-thousand-packet flood does not drown out two-packet scans in the gradient. Sequences are truncated at $200$ packets during batching to bound the padded batch size; the verdict semantics are unaffected, since a streaming detector is judged on prefixes anyway. Optimization uses AdamW with a cosine learning-rate schedule and early stopping on the validation split. The intended division of labour inside the ensemble is thus clear-cut: the TCN contributes an early, dense, but noisier signal, the forest a delayed, sparse, more conservative one, and neither is expected to be sufficient alone.

### 4.4.3 Attention-Based Meta-Learner (the "Mini-Transformer")

The meta-learner reconciles the two prediction streams. The difficulty is not accuracy but asynchrony: at most packets the forest has no fresh opinion, and before packet $2$ it has none at all, so a fixed rule such as averaging is not even well-defined at every position. DEPT's answer is a small causal Transformer encoder over per-packet fusion tokens, whose $13$ dimensions are listed in Table 4.1. The token gives the model the two base logits, the bookkeeping needed to interpret them (how stale the forest's logit is, whether it was refreshed at this very packet), and a deliberately compact summary of the current packet.

Three design decisions define this component. First, the input is kept minimal on purpose: the

**Table 4.1:** The 13-dimensional per-packet fusion token consumed by the meta-learner.

| Slot | Feature | Meaning |
|---|---|---|
| 0 | RF logit | last checkpoint logit, carried forward; placeholder before packet 2 |
| 1 | TCN logit | dense per-packet logit |
| 2 | `rf_age` | packets since the last RF refresh, clipped at $30$ |
| 3 | `is_rf_checkpoint` | $1$ iff the RF logit was refreshed at this packet |
| 4 | IPAT | z-scored inter-packet arrival time |
| 5 | direction | direction bit of the current packet |
| 6 | packet length | IPv4 total length, normalized by $1500$ |
| 7–12 | TCP flags | URG, ACK, PSH, RST, SYN, FIN bits |


meta-learner is a stacker, not another feature extractor, and withholding the full $1088$-bit representation forces it to combine the base learners instead of bypassing them; it also keeps the model at roughly $68$K parameters (two encoder layers, four heads, $d_{\text{model}} = 64$), negligible next to either base. Second, the pre-checkpoint gap is filled by a learnable placeholder logit rather than an imputed constant. A zero would be read as a genuine "undecided" forest opinion; a trainable parameter lets the model learn its own prior for "the forest has not spoken yet". Third, attention is causally masked and positions are encoded with the standard sinusoidal scheme, so the fused verdict at packet $t$ depends only on packets up to $t$, preserving the streaming property end to end.

The training discipline matters as much as the architecture. Fitting a stacker on the same data its base learners trained on would let it learn their overfit confidence rather than their generalizing behaviour [14], so the meta-learner trains on the validation split, where both base learners' predictions are out-of-fold, and that split is sub-divided (seed $43$) into a meta-train and a meta-val part, the latter driving early stopping on streaming Area Under the Receiver Operating Characteristic curve (AUROC) at packet $10$. The loss is the same balanced per-packet cross-entropy as the TCN's, plus an auxiliary "beat the best base" term (weight $0.5$) that penalizes, at each packet, any shortfall of the meta-learner's true-class confidence against the better of the two base learners. The intent is to make "never worse than the best base" an explicit training signal; what this loss does and does not achieve in practice is reported with the ablations in Section 5.5. At deployment the meta-learner's per-packet probability is compared against a fixed threshold of $0.5$; a flow is flagged the first time its score crosses it, which is also the event the earliest-detection metric of Chapter 5 records.

## 4.5 Input Purification: Reconstructor Transformer

Detection alone would leave only a blunt response to a flagged flow, dropping it, which turns every false positive into denial of service for a legitimate client. DEPT's second stage takes the purification route of Section 2.2.2 instead: undo the manipulation and let the repaired flow proceed. Within the taxonomy

of generative purifiers, the reconstructor is a causal Transformer denoiser operating directly on the per-packet token sequence, trained to map an adversarial flow onto its clean counterpart (Figure 4.4).




**(a)** Feature-space purification: a causal encoder predicts a per-dimension residual correction $\Delta$, and the purified flow is $x + \Delta$.

**(b)** Traffic-space realization: the purified length and timing are written back onto the original packets, and the result is checked with a dissector.

**Figure 4.4:** The purification stage. Purification happens in feature space (a); whenever concrete packets are needed, realization (b) overlays the two purified quantities onto the original adversarial packets, preserving identity and payload content, and recomputes the dependent header fields.

### 4.5.1 Purification Model

The reconstructor shares the meta-learner's scaffold, a pre-norm Transformer encoder under a strict causal mask with sinusoidal positions, scaled up to three layers, four heads, and $d_{\text{model}} = 128$ (about $678$K parameters), with the $1090$-dimensional token as both input and output. Its head, however, does not predict the clean sequence directly: it predicts a per-dimension residual $\Delta$, and the output is the input plus $\Delta$. This residual formulation encodes the right prior for the problem. TANTGen's manipulations touch two physical quantities, timing and size, so out of the $1090$ dimensions of a token only a handful actually need correcting; with a residual head, the identity map is the easy default ($\Delta \approx 0$), the untouched $\sim 1050$ header bits are preserved for free, and the model's capacity is spent on the localized corrections that matter. The causal mask, in turn, keeps the purifier valid for streaming use and, as discussed for decoder-style models in Section 2.1.3, makes it amenable to key–value caching; the present implementation runs whole-prefix forwards, and Chapter 5 measures it as built, so caching remains an available engineering optimization rather than a claimed one.

### 4.5.2 Training on Matched Flow Pairs

Purification is learned from matched pairs. Because TANTGen perturbs a flow without changing its five-tuple identity, every adversarial flow can be aligned with the exact clean flow it was derived from by matching canonical five-tuple keys; the result is a corpus of (adversarial $\rightarrow$ clean) sequence pairs on which reconstruction is supervised directly. Pairs shorter than two packets are dropped, since a single packet carries no inter-arrival interval and thus no timing signal to restore. Pairs follow the same seed-$42$ flow-atomic split as everything else, keeping the test pairs unseen by every base learner.

The loss is a smooth-L1 distance between the reconstructed and the clean sequence, masked over padding and averaged within each flow before averaging across flows, the same length-normalization argument as in Section 4.4.2; smooth-L1 is preferred over a plain squared error for its robustness to the occasional large deviation. One further choice deserves emphasis: the loss weights all $1090$ dimensions uniformly. The training signal contains no hint of where TANTGen's perturbation lives, so the model must discover for itself which dimensions are trustworthy and which have been tampered with. This keeps the purifier attack-agnostic: nothing in its objective is specific to TANTGen's footprint. During development a variant weighted towards the known perturbed dimensions was also explored, and it was dropped from the final design precisely because it ties the defense to one attacker's signature; the honest, deployable configuration is the uniform one.

### 4.5.3 Traffic-Space Realization and Validation

A purifier that edits traffic inherits the realizability obligation of Section 2.2.3: its output must be traffic that can exist on the wire. DEPT discharges this obligation with an explicit realization step (Figure 4.4(b)). Rebuilding packets from scratch out of the purified tensors would be both impossible and unwise, as nPrint encodes only headers and the identity fields are masked to zero. Realization therefore works by overlay: it keeps each original adversarial packet, with its identity and payload content intact, and writes back only the two quantities purification may have changed. The purified IPv4 total length is decoded from its sixteen header bits (rounded back to the tri-state alphabet) and applied by trimming or padding the application payload, which is the inverse of TANTGen's size perturbation; the purified inter-arrival time is de-normalized and applied to the packet's capture timestamp. The packets are then re-serialized with scapy, which recomputes the checksums and length fields that depend on the edit. Alignment between tensor rows and packets reuses the pipeline's canonical flow grouping, giving a one-to-one correspondence; any flow whose packet count fails to match its tensor length is skipped and counted, never silently mangled.

Every realized packet is finally passed through the `tshark` dissector, and protocol compliance is scored as the fraction of packets parsed without a malformed-packet complaint. One structural caveat is

worth stating already here: for application-layer text protocols, such as the SSDP `M-SEARCH` messages that dominate one source, a byte-level size edit necessarily corrupts the L7 grammar even when all IP and UDP fields remain consistent, so such packets cannot be faithfully realized by overlay at all. They are reported separately rather than scored as compliance failures, and Section 5.6 gives the full accounting. Realization runs off the inference path by design: the protected detector consumes the purified flow in feature space, while PCAP emission serves validation, forensics, and any downstream system that requires concrete packets, without adding to the per-packet latency budget.

Finally, the evaluation harness embeds the independent protected detectors that complement the TCN-based purification measurements: a Kitsune instance (KitNET with the damped incremental statistics its reference implementation calls AfterImage [16]) for the two Kitsune-native sources (Mirai and the SSDP flood), and TANTGen's own ML-NIDS flow classifiers for the eight CIC attacks, in every case the very detector TANTGen calibrated that attack's evasion against. The harness realizes matched adversarial, purified, and clean packet triplets of the same flows and scores each through its attack's detector, so that purification can be judged by a judge that shares nothing with DEPT's training loop; the measurement is reported in Section 5.8.1.

## 4.6 Implementation and Tools

DEPT is implemented in Python. The three sequence models (TCN, meta-learner, reconstructor) are built in PyTorch and the RF in scikit-learn. The nPrint encoding is reimplemented natively on top of scapy, following the bit layout of the original tool [22]; folding the encoder into the pipeline avoids an external binary, lets identity masking happen inline, and keeps tensorization a single pass over each capture. Scapy also drives packet parsing and the realization step, while `tshark`, `editcap`, and `tcpdump` handle dissection, time-window filtering of CIC-IDS2017, and the packet-capping of the large CIC-DDoS-2019 captures, respectively.

The system is organized as four model stages behind five configuration files, one per stage plus one for the pipeline, with the two evaluation studies of Chapter 5 (the deployment baseline and the gradient ablation) adding one configuration file each in the same pattern; every file fully determines its stage's data scope, architecture, and training settings, and a small runner script per stage executes it end to end. All stages read the same tensor artifacts and the same stored split, which is how the shared-split discipline of Section 4.3 is enforced in practice, and derived artifacts are cached and fingerprinted against their upstream inputs (for instance, the meta-learner's token cache is invalidated whenever a base learner's checkpoint changes), so any partial re-run stays consistent. Table 4.2 summarizes the learned components. The source layout mirrors the stages, with the feature pipeline under `src/feature_extraction`, the models under `src/models`, per-stage entry points under `scripts`, and

**Table 4.2:** Configuration summary of DEPT's learned components. The Random Forest complements them with $200$ trees of maximum depth $20$ and minimum leaf size $5$, selected by grid search (Section 4.4.1).

| | **TCN** | **Meta-learner** | **Reconstructor** |
|---|---|---|---|
| Input (per packet) | $1090$ | $13$ | $1090$ |
| Blocks / layers | $3$ temporal | $2$ encoder | $3$ encoder |
| Width | $128$ channels | $d_{\text{model}} = 64$ | $d_{\text{model}} = 128$ |
| Attention heads | — | $4$ | $4$ |
| Feed-forward dim | — | $128$ | $256$ |
| Dropout | $0.15$ | $0.1$ | $0.1$ |
| Parameters | $805{,}762$ | $67{,}971$ | $677{,}698$ |
| Loss | balanced CE | balanced CE + aux | smooth-L1 |
| Learning rate | $10^{-3}$ | $3 \cdot 10^{-4}$ | $3 \cdot 10^{-4}$ |
| Batch size | $32$ | $128$ | $32$ |
| Max epochs / early stop | $20$ / val macro-$F_1$ | $20$ / AUROC@10 | $20$ / val loss |

configuration under `config`; further operational detail lives with the repository rather than in this document.

With the architecture in place, what remains is to show that it meets its goals: that the ensemble detects manipulation early, and that purification actually returns flagged flows to the benign manifold while emitting valid packets. These are the questions Chapter 5 takes up.

# 5

# Evaluation

## Contents


5.1 Research Questions . . . . . 46
5.2 Experimental Setup . . . . . 46
5.3 Metrics . . . . . 48
5.4 Base Learner Results . . . . . 49
5.5 Meta-Learner Results . . . . . 51
5.6 Purification Results . . . . . 53
5.7 Ensemble Robustness under a Gradient-guided Attacker (RQ1) . . . . . 56
5.8 End-to-End System Evaluation . . . . . 61
5.9 Discussion and Limitations . . . . . 65


This chapter evaluates DEPT against the threat model of Section 4.1: a black-box, protocol-compliant adversary, concretely the TANTGen generator of Section 4.3 treated as an opaque red team, that manipulates a streaming flow so as to evade a downstream NIDS. The chapter first fixes the research questions (Section 5.1), the corpus and environment (Section 5.2), and the metric definitions (Section 5.3). It then reports the two base learners (Section 5.4), their attention-based fusion (Section 5.5), and the purification stage (Section 5.6), before turning to the end-to-end system (Section 5.8) and to an

explicit accounting of the limitations (Section 5.9). Throughout, the results are reported as measured, including the sources and perturbation modes on which DEPT does poorly.

## 5.1 Research Questions

The evaluation is organized around two research questions, each tied to one of the work objectives of Section 1.3:

- **RQ1 (ensemble robustness).** Does heterogeneous stacking, a non-differentiable Random Forest fused with a differentiable Temporal Convolutional Network, measurably raise the cost of a transferable, gradient-guided evasion attack relative to a single-architecture baseline?
- **RQ2 (purification effectiveness).** Does the reconstructor move a flagged adversarial flow back onto the benign manifold, closing the detection gap seen by the protected NIDS, while emitting a realizable, protocol-compliant packet sequence?

Both questions are answered by measurement. RQ2 is answered through the reconstructor's own metrics (Section 5.6) and, end to end, through the deployment baseline that scores the defense against the independent NIDS each attack was built to evade (Section 5.8).

RQ1 needs an adversary TANTGen cannot supply. TANTGen is black-box and gradient-free by design, so it prices no gradient path and cannot say what heterogeneity is worth against one; taking its success rate as evidence for RQ1 would answer a question about gradients with an attacker that has none. Section 5.7 therefore introduces a second, complementary adversary that differentiates the TCN directly and whose perturbation is then scored, unchanged, against the Random Forest, the TCN, and the fused stack. The asymmetry is the point: the attacker has an exact gradient into one half of the ensemble and none into the other, which is the situation RQ1 describes.

A third natural question, whether the detect-then-purify pipeline stays within a real-time inference budget, is deliberately not addressed here: the wall-clock latency and overhead evaluation of the delivered system is left to future work (Chapter 6).

## 5.2 Experimental Setup

### 5.2.1 Datasets and Threat Generation

The evaluation corpus combines ten benign traffic sources (Mirai and the SSDP flood from Kitsune; DDoS, Port Scan and Brute Force from CIC-IDS2017; and the five CIC-DDoS-2019 reflection and amplification floods, namely NTP, DNS, SSDP, SYN, and LDAP), each paired with three TANTGen adversarial variants: `both` (timing and size), `iat` (inter-arrival timing only), and `size` (payload/size only). The

per-source detection tables of this chapter therefore cover ten sources and thirty source–mode combinations. Under DEPT's label convention (Section 4.3), every raw-capture flow is labelled benign, since the upstream NIDS is responsible for the datasets' native attacks, and every TANTGen-generated flow is labelled adversarial. The task DEPT is measured on is therefore precise: distinguish a flow that TANTGen has manipulated from one it has not, and undo that manipulation. This framing is a deliberate choice, and its consequences (in particular, that a source on which TANTGen barely perturbs the features is essentially unlabelable) are analysed in Section 5.9.

The corpus as tensorized comprises $8{,}624{,}958$ flows and $61{,}516{,}406$ packets across the forty sources (ten benign and thirty adversarial). All models share a single flow-atomic, source-stratified $70/15/15$ split (seed $42$), so that the RF, TCN, meta-learner, and reconstructor are trained, validated, and tested on the same flows and their results are directly comparable. Because the CIC-DDoS-2019 reflection floods contribute the overwhelming majority of adversarial flows, the held-out test pool is adversarial-dominated: of the $1{,}293{,}737$ test flows seen by the TCN and meta-learner, $1{,}082{,}586$ ($83.7\%$) are adversarial and $211{,}151$ are benign. The RF, whose first checkpoint fires at packet $2$, never sees the $6{,}179$ single-packet flows and therefore scores $1{,}287{,}558$ flows on the streaming axis, or $1{,}838{,}798$ rows on its native per-checkpoint axis. This base rate matters when reading accuracy and precision, and it is the reason the cross-model comparison is anchored on threshold-free, base-rate-robust quantities (AUROC and PR AUC) and on the streaming axis rather than on raw accuracy.

### 5.2.2 Implementation Environment

All training and evaluation were run on a single research server: $2\times$ Intel Xeon Gold 5320 CPUs @ $2.2$ GHz ($52$ physical cores, $104$ hardware threads), $160$ GB of RAM, and $2\times$ NVIDIA RTX 6000 Ada GPUs, of which one was used at a time. The software stack is the one described in Section 4.6: PyTorch for the TCN, meta-learner, and reconstructor; scikit-learn for the Random Forest; and Scapy together with `tshark`/`editcap`/`tcpdump` for PCAP handling, feature realization, and protocol-compliance checking.

The full pipeline is expensive to run end to end, and the cost is worth recording since it bounds how much exploration a project of this size can afford. Generating the thirty adversarial captures with TANTGen took $26.7$ h, dominated by the NTP flood alone ($11.9$ h, whose raw capture must be streamed to reach the million-packet cap), and tensorizing the forty sources took a further $11.2$ h. Of the model stages, the RF completed its eighteen-point grid search and final fit in $2.7$ h on CPU (each configuration fitting in $270$–$522$ s); the TCN trained for $24.7$ h on one GPU, early-stopping after ten of twenty planned epochs with the best epoch at $6$; the meta-learner for $3.4$ h, best epoch $17$ of $20$; and the reconstructor for $10.0$ h, best epoch $19$ of $20$. The two comparison studies of Section 5.7 and Section 5.8 cost $4.3$ h and $33.6$ h respectively, the latter because it scores $2{,}704{,}816$ realized flows through the independent detectors. Repeating the four model stages once per attack, as Section 5.8.2 does, adds roughly $28$ h

more.

## 5.3 Metrics

The metrics separate into three families.

**A – Static classification.** Treating each scored unit independently at the end-of-flow (or per-checkpoint) verdict, the evaluation reports ROC AUC and PR AUC (threshold-free ranking quality; PR AUC is the more informative summary under the $\approx 83\%$ adversarial base rate), Macro F1 (the unweighted mean of the benign and adversarial $F_1$ at threshold $0.5$), and the per-class precision and recall. Recall on the adversarial class is reported separately, because a detector that misses adversarial flows is failing at the one task it exists for.

**B – Streaming.** A defense that must act before a flow completes cannot be judged only at end-of-flow. The evaluation therefore reports AUROC@$t$: the ROC AUC computed using, for each flow, only the prediction available after its first $t$ packets. This exposes how quickly a model becomes discriminative. It is paired with the Earliest Detection Packet (EDP), the median packet index at which a flow's streaming score first crosses $0.5$, reported with its inter-quartile range, and with the detection rate, the fraction of adversarial flows that ever cross the threshold. AUROC@$t$ measures ranking quality; EDP and detection rate measure operational timeliness at a fixed operating point.

**C – Purification.** The reconstructor is judged on four quantities. Reconstruction Mean Squared Error (MSE) is computed on the feature dimensions TANTGen actually perturbed, between the flow and its true clean counterpart, measured before (adversarial input) and after (reconstructor output). The headline efficacy quantity is detection restoration through an independent NIDS: the clean, adversarial, and purified (or DEPT-defended) flows are scored through the real NIDS each attack was built to evade, Kitsune or the ML-NIDS, and the restoration ratio, the fraction of the adversarial-to-clean gap recovered, together with the Attack Success Rate (ASR) before and after DEPT, report how much detection the defense returns (Section 5.8). A secondary, in-distribution diagnostic is the purification gain, the drop in DEPT's own TCN's adversarial-probability $\Delta P(\text{adv})$ from the adversarial to the reconstructed flow, with its residual gap to a genuinely clean flow; this is circular by construction (the same detector family the loop trained around) and is read only as a manifold-return sanity check, not as the end-to-end claim. Finally, protocol compliance is the fraction of realized packets that `tshark` parses without a malformed-packet error, computed only over packets the realization step can faithfully emit.

**Table 5.1:** Static classification results on the held-out test set. The Random Forest is scored per checkpoint ($1{,}838{,}798$ units); the TCN and meta-learner are scored once per flow at the last timestep ($1{,}293{,}737$ flows). These columns are not directly comparable across the RF / (TCN, Meta) boundary; see the streaming axis in Table 5.3. Best value in each row in **bold**.

| Metric | RF (per-ckpt) | TCN (per-flow) | Meta (per-flow) |
|---|---|---|---|
| ROC AUC | **0.9852** | 0.8386 | 0.9334 |
| PR AUC | **0.9948** | 0.9592 | 0.9866 |
| Macro $F_1$ | **0.8935** | 0.6608 | 0.6988 |
| Accuracy | **0.9099** | 0.7621 | 0.7544 |
| Precision (adv.) | 0.9939 | 0.9220 | **0.9985** |
| Recall (adv.) | **0.8832** | 0.7820 | 0.7076 |
| $F_1$ (adv.) | **0.9353** | 0.8462 | 0.8282 |
| Recall (benign) | **0.9847** | 0.6606 | 0.9947 |

## 5.4 Base Learner Results

Table 5.1 reports the static classification results for the two base learners and the meta-learner. Two population differences must be kept in mind when reading it. First, the Random Forest is scored on its native per-checkpoint population, one row per prefix checkpoint (packet $2$, then every ten packets), giving $1{,}838{,}798$ scored units, whereas the TCN and meta-learner are scored once per flow at the last timestep. The two are therefore not directly comparable on this table; the like-for-like comparison is the streaming axis of Section 5.5. Second, all figures are computed on the same adversarial-dominated test pool, so the high adversarial recall and PR AUC partly reflect that base rate.

All three models are precision-first at threshold $0.5$, and the differences between them are differences of recall. The Random Forest flags $88.3\%$ of adversarial checkpoints while misclassifying only $1.5\%$ of benign ones. The meta-learner is the most conservative of the three, with the highest adversarial precision ($0.9985$: just $1{,}115$ of $211{,}151$ benign test flows are flagged) but the lowest adversarial recall ($0.7076$). The TCN is the weakest on both sides, and notably weak on the benign class ($0.6606$ recall), which is what drags its macro-$F_1$ to $0.6608$ despite a respectable $0.9592$ PR AUC. Neither ordering should be over-interpreted from this table alone, because the RF's lead is measured on the checkpoint population that most favours it, and because macro-$F_1$ at a fixed threshold conflates ranking quality with calibration.

The more informative view is per source and per perturbation mode. Table 5.2 gives the end-of-flow streaming AUROC@MAX for all $30$ source–mode combinations, and Figure 5.1 plots the same values as one mark per combination. Both are computed against same-source benign flows, which is the axis that matches DEPT's task as posed: separate a manipulated flow of a given source from an unmanipulated flow of that same source, rather than from generic benign traffic drawn from the other nine. It is also the strictest of the three axes the harness records, and the one on which the system's real failure becomes visible.

**Table 5.2:** End-of-flow streaming AUROC@MAX per source and perturbation mode, measured against same-source benign flows. $n_{\text{adv}}$ is the number of adversarial test flows per mode variant, as seen by the Random Forest; the TCN and meta-learner see the same counts except on `mirai`, where they score $1{,}957$ flows against the forest's $867$, because `mirai`'s many very short flows end before the forest's packet-$2$ checkpoint. Values below $0.55$, at or under chance, are marked with †. `b`/`i`/`s` denote the `both`/`iat`/`size` modes.

| Source | $n_{\text{adv}}$ | M. | RF | TCN | Meta |
|---|---|---|---|---|---|
| `brute_force` | $1{,}045$ | b | 0.974 | 0.978 | 0.981 |
| | | i | 0.974 | 0.978 | 0.979 |
| | | s | 0.990 | 0.978 | 0.989 |
| `ddos` | $5{,}781$ | b | 1.000 | 1.000 | 1.000 |
| | | i | 0.999 | 0.924 | 0.967 |
| | | s | 1.000 | 1.000 | 1.000 |
| `dns_ddos` | $1{,}019$ | b | 0.999 | 0.552 | 1.000 |
| | | i | 0.999 | 0.547† | 1.000 |
| | | s | 0.258† | 0.531† | 0.443† |
| `ldap_ddos` | $74{,}710$ | b | 1.000 | 0.500† | 1.000 |
| | | i | 1.000 | 0.500† | 1.000 |
| | | s | 0.476† | 0.501† | 0.476† |
| `mirai` | $867$ | b | 0.926 | 0.680 | 0.724 |
| | | i | 0.919 | 0.680 | 0.719 |
| | | s | 0.829 | 0.723 | 0.734 |
| `ntp_ddos` | $2{,}103$ | b | 0.999 | 0.514† | 0.654 |
| | | i | 0.999 | 0.497† | 0.653 |
| | | s | 0.213† | 0.494† | 0.493† |
| `portscan` | $23{,}800$ | b | 1.000 | 0.997 | 0.998 |
| | | i | 1.000 | 0.652 | 0.757 |
| | | s | 0.998 | 0.997 | 0.997 |
| `ssdp_ddos` | $40{,}446$ | b | 1.000 | 0.499† | 0.927 |
| | | i | 1.000 | 0.502† | 0.927 |
| | | s | 0.409† | 0.497† | 0.497† |
| `ssdp_flood` | $9{,}830$ | b | 1.000 | 0.999 | 1.000 |
| | | i | 1.000 | 1.000 | 1.000 |
| | | s | 1.000 | 0.999 | 1.000 |
| `syn_ddos` | $200{,}483$ | b | 1.000 | 1.000 | 1.000 |
| | | i | 1.000 | 0.647 | 0.806 |
| | | s | 1.000 | 1.000 | 1.000 |

The distribution is emphatically not unimodal. Most combinations are solved: $21$ of the $30$ reach $\geq 0.99$ for the Random Forest and $13$ for the meta-learner. But a cluster of four sits below chance for every model, namely the `size` variants of the DNS, NTP, SSDP, and LDAP reflection floods, where the RF scores $0.214$–$0.476$ and the meta-learner $0.443$–$0.497$. Below chance is a strong statement and it should be read literally: on those source–mode pairs a TANTGen-edited flow looks more like generic benign traffic than that flood's own unedited flows do, so a detector that inverted its verdict there would do better than the one that was trained. Section 5.9 takes up what this means. Two reading caveats: the per-source figures for the reflection floods rest on the RF's aggregate prefix statistics rather than on any single feature, and the `brute_force` rows, at $1{,}045$ adversarial test flows per mode, are the thinnest in the table.

Three cross-cutting regularities emerge, and they are not the ones the design anticipated. First, the `iat`-only mode is hardest for the TCN and easy for the forest: `portscan_iat` (TCN $0.652$ against RF $1.000$), `syn_ddos_iat` ($0.647$ against $1.000$), `ddos_iat` ($0.924$ against $0.999$). Aggregated prefix timing statistics capture a pure timing shift that the per-packet sequence view does not, which is exactly the architectural heterogeneity the ensemble was built on, though in the opposite direction to the one originally expected. Second, the TCN is not merely weak but blind on the four reflection floods: it sits at $0.494$–$0.552$ on every mode of `dns_ddos`, `ldap_ddos`, `ntp_ddos`, and `ssdp_ddos`, and on `ldap_ddos`, the largest of them, it reads $0.500$ to three decimals in all three modes, which is the signature of a model whose score carries no information about the label. These floods are one- and two-packet UDP exchanges, and a receptive field of $29$ packets has nothing to convolve over. Third, `mirai` is the hardest source for every model ($0.83$–$0.93$ RF, $0.68$–$0.72$ TCN, $0.72$–$0.73$ meta), and it will reappear as the hardest case for





**Figure 5.1:** The $30$ source–mode AUROC@MAX values of Table 5.2, one mark per combination and one row per model. The structure is bimodal for all three models: a dense cluster of solved combinations at $\approx 1.0$, and, separated from it, the `size` variants of the four reflection floods, which fall below the chance line rather than merely approaching it. The TCN's row is the widest spread of the three, reflecting that it is at chance on every reflection-flood mode.

the purifier as well.

## 5.5 Meta-Learner Results

The meta-learner is evaluated on the streaming axis, which places all three models on a common footing: each is asked, using only the first $t$ packets of a flow, to rank it as adversarial or benign. Table 5.3 reports AUROC@$t$ for $t \in \{1, 2, 5, 10, \text{MAX}\}$ together with the median EDP and detection rate, and Figure 5.2 plots the full AUROC@$t$ trajectories.

The result on this axis is not the one the design predicted, and it is worth stating plainly before interpreting it. The Random Forest alone is the strongest stream at every point from packet $2$ onward, reaching $0.9805$ at its first checkpoint and $0.9813$ thereafter, against the meta-learner's $0.9099$ to $0.9334$ and the TCN's $0.8225$ to $0.8386$. The meta-learner is not the best model in this system; it is the second-best, and its advantage over the forest is confined to a single packet.

What the fusion does deliver is precise, and it is a real advantage, but it is narrower than "the stack beats its base learners". It is threefold. First, at packet $1$, where the forest is silent by construction, the meta-learner has the best available verdict of any model, at $0.8373$ against the TCN's $0.8191$; a defense that must act on the first packet has only these two options, and fusion is the better one. Second, the

**Table 5.3:** Flow-level streaming comparison (like-for-like across models). AUROC@$t$ uses only each flow's prediction through packet $t$; EDP is the median packet at first threshold crossing; detection rate is the fraction of adversarial flows ever flagged. The RF issues no verdict before packet $2$. Best value in each row in **bold**.

| Metric | RF | TCN | Meta-Learner |
|---|---|---|---|
| First verdict at | packet 2 | **packet 1** | **packet 1** |
| AUROC@1 | — | 0.8191 | **0.8373** |
| AUROC@2 | **0.9805** | 0.8225 | 0.9099 |
| AUROC@5 | **0.9805** | 0.8375 | 0.9319 |
| AUROC@10 | **0.9813** | 0.8371 | 0.9323 |
| AUROC@MAX | **0.9813** | 0.8386 | 0.9334 |
| EDP (median) | 2 pkts | **1 pkt** | **1 pkt** |
| Detection rate | **88.99%** | 78.40% | 77.69% |





**Figure 5.2:** Flow-level AUROC@$t$ as a function of the packets seen, for all measured checkpoints. The TCN and the meta-learner alone have a verdict at packet $1$; the Random Forest joins at packet $2$, immediately at $0.98$, and stays the strongest single stream thereafter. The meta-learner rises steeply between packets $1$ and $5$ and then plateaus between the two base learners.

meta-learner dominates the TCN at every horizon, by $8.7$ to $9.5$ AUROC points from packet $2$ onward, so as a way of using a sequence model it is unambiguously better than using the sequence model alone. Third, and most consequential for RQ1, the fused stack is measurably harder to evade than either component under a gradient-guided attacker, which Section 5.7 quantifies: it is the only one of the three that keeps $74.5\%$ of flows unevaded at every budget. Robustness, not clean-traffic accuracy, is what the second base learner buys.

Two further observations complete the picture, and both cut against the fusion. The meta-learner's per-source behaviour tracks whichever base learner is stronger on that source, but not reliably: on `ssdp_ddos both/iat` it reaches $0.927$ where the forest reaches $1.000$, and on `ntp_ddos both/iat` it reaches $0.653$–$0.654$ against the forest's $0.999$, so on those sources it discards most of a signal it was handed. The mechanism is the one anticipated in Section 4.4.3: the carry-forward RF logit enters the

**Table 5.4:** Purification results on the $384{,}963$-pair test set, overall. Reconstruction MSE is over the perturbed feature dimensions; the purification gain and residual gap are a secondary, in-distribution diagnostic measured through DEPT's own TCN (circular by construction, which is why the independent-NIDS restoration is the headline efficacy quantity); compliance is over realizable packets.

| Family | Quantity | Value |
|---|---|---|
| Reconstruction | MSE on perturbed dims (before $\rightarrow$ after) | $0.918 \rightarrow \mathbf{0.054}$ |
| | Reduction ratio | $17.0\times$ |
| Purification (TCN) | $P(\text{adv})$: adversarial $\rightarrow$ reconstructed | $0.675 \rightarrow 0.428$ |
| | Purification gain $\Delta P(\text{adv})$ | $\mathbf{0.247}$ |
| | Residual gap vs. clean ($0.421$) | $0.007$ |
| Independent NIDS | Detection rate: adversarial $\rightarrow$ purified | $0.781 \rightarrow \mathbf{0.906}$ |
| | Clean-oracle ceiling | $0.980$ |
| | Detection-restoration ratio | $\mathbf{0.630}$ |
| Compliance | `tshark` pass rate (realizable pkts) | $\mathbf{97.22}\%$ ($67{,}106/2{,}412{,}357$ bad) |
| | Unrealizable L7-text packets (reported apart) | $450{,}758$ |

per-packet fusion token as a single, sparsely updated feature, refreshed only at checkpoints and absent before packet $2$, where a learnable placeholder stands in, whereas the dense TCN logit is present and updated at every timestep, so the attention encoder systematically under-weights the intermittent evidence. A stacker should be no worse than its best base learner; this one is worse on several sources and on the aggregate, and that is the clearest single target for future work on the detection stage (Section 5.9).

A note on the auxiliary "beat the best base" loss (weight $0.5$, Section 4.4.3) closes the section. Over training the auxiliary term falls from $0.0267$ to $0.0177$, so the meta-learner does move toward matching its best base learner's confidence; over the same twenty epochs the meta-validation AUROC@$10$ rises from $0.9197$ to $0.9333$, with essentially all of that gain in the first few epochs and under $10^{-3}$ of movement after epoch $10$. The bottleneck is rank ordering, not calibration: a loss that sharpens confidences cannot by itself recover ranking that the $13$-dimensional fusion tokens do not support. This negative result is recorded because it delimits what the auxiliary loss can be expected to do.

## 5.6 Purification Results

The reconstructor was trained on $1{,}796{,}542$ five-tuple-matched (adversarial $\rightarrow$ clean) flow pairs, of $2{,}566{,}489$ paired in total, and evaluated on the held-out $384{,}963$-pair test split (seed $42$, unseen by any base learner). It is an attack-agnostic denoiser: it is trained with uniform-weight reconstruction over all feature dimensions, so it is given no hint of where TANTGen perturbed a flow (a perturbation-weighted variant was explored as an ablation during development and dropped from the final implementation). Table 5.4 summarizes the metric families overall.

The headline is the independent-NIDS row. Scored through the real detector each attack was built to evade, over $370{,}700$ realized flows, purification lifts detection from the evaded floor of $0.781$ to $0.906$ against a clean-oracle ceiling of $0.980$, recovering $63.0\%$ of the gap TANTGen had opened. Split by detector family the two halves behave very differently and the difference is informative: on the Kitsune-native sources detection is restored from $0.019$ to $0.792$ against a ceiling of $0.793$, which is $99.9\%$ of the available gap, while on the eight ML-NIDS sources it moves from $0.808$ to $0.910$ against a ceiling of $0.987$, or $57.1\%$. The Kitsune figure is the cleaner demonstration because TANTGen had genuinely destroyed detection there; the ML-NIDS average is diluted by the many sources where detection was never lost and there was consequently nothing to restore.

The in-distribution diagnostic agrees in direction: through DEPT's own TCN, the mean $P(\text{adv})$ falls from $0.675$ on the adversarial flow to $0.428$ on the reconstruction, against $0.421$ for a genuinely clean flow, a residual gap of $0.007$. This is reported as a sanity check only, since the judge belongs to the family the loop was trained around, and the earlier drafts of this work leaned on it more heavily than it can bear.

As with detection, the effect is strongly attack-dependent, and the per-source view is where the honest reading lives. Table 5.5 gives the rows that carry the argument, and Figure 5.3 plots every source–mode pair by its perturbation footprint (the pre-purification MSE on the perturbed dimensions) against the gain purification achieves on it. Four regimes are visible, three of them anticipated and one not.

Purification is large precisely on the structurally perturbed sources: `ddos` (gain $0.93$ on `both`, $0.94$ on `size`), `syn_ddos` ($0.92$ and $0.93$), `portscan` ($0.84$ on both), and, in independent-NIDS terms, these are the same rows where detection is genuinely rescued: `ddos_both` from $0.080$ to $0.865$, `ddos_size` from $0.005$ to $0.817$, `portscan_both` from $0.011$ to $0.679$, `ssdp_flood_iat` from $0.001$ to $1.000$. It is correctly inert where TANTGen barely moved the features, chiefly the `both` and `iat` variants of the reflection floods, whose pre-purification MSE is already near zero. It is unmeasurable on the `size` variants of those same floods, where the footprint is maximal (MSE $= 1.0$) and substantially reduced, yet the TCN gain stays at $\approx 0$ because that detector assigns adversarial and clean flows the same probability to begin with: the gain metric is bounded by the detection gap, so on detector-blind sources it can neither credit nor discredit the purifier.

The fourth regime is the one the earlier framing missed, and it only becomes visible once an independent judge is used. On sources where TANTGen never succeeded in evading, purification actively harms detection. Through the independent NIDS, `dns_ddos` falls from $0.986$ to $0.762$ on `both` and from $0.993$ to $0.756$ on `iat`; `portscan_iat` falls from $0.994$ to $0.811$; `brute_force_size` from $0.993$ to $0.963$. The denoiser is doing what it was trained to do, moving the flow toward the clean manifold, but on these flows the attack's fingerprint and the clean manifold were never far apart, so what it removes is signal the protected NIDS was still using. This is not a defect of the reconstructor so much as an argument that pu-

**Table 5.5:** Purification by source (representative rows). MSE on perturbed dims (before → after), purification gain $\Delta P(\text{adv})$ through DEPT's own TCN, and the independent NIDS's detection rate on the adversarial and purified streams with the clean-oracle value in parentheses. Rows are grouped by the four regimes of the text. A dash marks a quantity the run does not record for that row: no perturbed cells in the pairing, or, for `ssdp_flood` `size`, a stream whose packets are all L7-unrealizable.

| Source | Mode | MSE (before → after) | Gain | NIDS det. adv → pur. (clean) |
|---|---|---|---|---|
| Footprint erased and detection genuinely restored | | | | |
| `ddos` | size | $1.000 \to 0.117$ | $+0.938$ | $0.005 \to 0.817$ $(0.828)$ |
| `ddos` | both | $0.928 \to 0.124$ | $+0.931$ | $0.080 \to 0.865$ $(0.821)$ |
| `syn_ddos` | size | $1.000 \to 0.144$ | $+0.932$ | $0.879 \to 1.000$ $(1.000)$ |
| `syn_ddos` | both | $0.973 \to 0.129$ | $+0.923$ | $0.973 \to 0.999$ $(0.998)$ |
| `portscan` | both | $0.972 \to 0.105$ | $+0.835$ | $0.011 \to 0.679$ $(0.999)$ |
| `portscan` | size | $1.000 \to 0.104$ | $+0.835$ | $0.013 \to 0.479$ $(0.999)$ |
| `ssdp_flood` | iat | $0.110 \to 0.081$ | $+0.535$ | $0.001 \to 1.000$ $(1.000)$ |
| `ssdp_flood` | both | $0.965 \to 0.003$ | $+0.374$ | $1.000 \to 1.000$ $(1.000)$ |
| No footprint to undo | | | | |
| `ldap_ddos` | both, iat | $\leq 0.18 \to \approx 0$ | $\approx 0$ | $1.000 \to 1.000$ $(1.000)$ |
| `ssdp_ddos` | both, iat | $\approx 0 \to \approx 0$ | $\approx 0$ | $0.998 \to 0.998$ $(0.998)$ |
| `ntp_ddos` | both, iat | $\approx 0 \to \approx 0$ | $\approx 0$ | $0.983 \to 0.986$ $(0.998)$ |
| Footprint, but the TCN cannot see a gap | | | | |
| `dns_ddos` | size | $1.000 \to 0.302$ | $-0.002$ | $0.986 \to 0.765$ $(0.986)$ |
| `ldap_ddos` | size | — | $+0.000$ | $1.000 \to 1.000$ $(1.000)$ |
| `ssdp_flood` | size | $1.000 \to 0.003$ | $+0.549$ | — |
| Purification harms an attack that was not evading | | | | |
| `dns_ddos` | iat | $\approx 0 \to \approx 0$ | $-0.006$ | $0.993 \to 0.756$ $(0.998)$ |
| `dns_ddos` | both | $\approx 0 \to \approx 0$ | $-0.008$ | $0.986 \to 0.762$ $(0.996)$ |
| `portscan` | iat | $\approx 0 \to 0.007$ | $+0.000$ | $0.994 \to 0.811$ $(0.999)$ |
| `brute_force` | size | $1.000 \to 0.188$ | $-0.002$ | $0.993 \to 0.963$ $(0.994)$ |
| `mirai` | size | $1.569 \to 0.973$ | $+0.271$ | $0.257 \to 0.005$ $(0.008)$ |

rification must be gated on whether it will help, which Section 5.8 measures end to end and Section 5.9 takes up as a limitation.

Three realization caveats must be stated, and the second and third are worse than in earlier drafts of this work. First, a size edit on an application-layer text protocol (the SSDP/HTTP `M-SEARCH` messages in `ssdp_flood` `both`/`size`) corrupts the L7 grammar even when the IP and UDP lengths and checksums remain valid, and `tshark` flags these as malformed. Rather than count them as compliance failures, since they are artefacts of byte-overlay realization on a text protocol and not of the purifier, the $450{,}758$ such packets are reported separately as unrealizable at L7, and the $97.22\%$ rate is computed over the $2{,}412{,}357$ realizable ones. For `ssdp_flood` `size` that exclusion is total: every packet of that stream is L7-unrealizable, so it has no compliance or independent-NIDS figure at all. Second, the aggregate compliance rate is pulled down by two sources, `ddos` at $0.84$ (of $140{,}128$ realized packets, $22{,}623$ are flagged, mostly length and checksum corner cases at scale) and `syn_ddos` `iat` at $0.178$; every other source is at or above $0.99$. Third, the `syn_ddos` `iat` figure rests on a thin and unrepresentative slice, since only $927$ of that source's $10{,}748$ test pairs survive the equal-length pairing guard, and of the $2{,}088$ packets realized from them $1{,}716$ carry a bad TCP checksum after the rewrite while none is malformed, which points at the realization step for that slice rather than at the reconstructor. None of these is a claim





**Figure 5.3:** Purification gain against perturbation footprint, one mark per source–mode pair ($27$ of $30$; the three pairs whose pairing records no perturbed-dimension MSE are omitted). Top right: the footprint is erased and the detection gap closed. Bottom left: TANTGen barely moved the features, so purification is correctly inert. Bottom right: the `size` variants of the reflection floods carry a full footprint, but the TCN is near chance on them, so no gain is measurable through this judge. Note that the axis is the in-distribution gain, so the sources on which purification harms independent-NIDS detection are not distinguishable here; Table 5.5 reports that separately.

about purification quality, but they do bound how far the traffic-space results can be pushed.

To make these aggregates concrete, it is worth following a single real packet through the pipeline. Figure 5.4 traces one flow drawn from the held-out test split, a four-packet Mirai SYN-flood burst from `192.168.2.108:35220` to `52.25.66.250:8280` under the `size` variant. In the original capture each datagram is $44$ bytes, a $20$-byte IPv4 header followed by a $24$-byte TCP header with no application payload. TANTGen appends $29$ bytes of payload to every packet, inflating the IPv4 total-length field to $73$ bytes; this length shift is the whole of the perturbation the `size` variant applies, and it is what pushes the flow off the clean manifold. The reconstructor recovers the original length, and the traffic-space realization of Section 4.5.3 trims the appended bytes back off, returning every datagram to $44$ bytes, a residual of exactly zero on the manipulated field. All twelve packets across the three stages pass `tshark` dissection with no malformed frames and no bad checksums, and because the `size` variant perturbs length alone the inter-arrival times are identical between the clean and adversarial captures, so packet size is the only quantity that changes. The $17.0\times$ reduction in perturbed-dimension MSE and the restored detection reported above are, at the granularity of one packet, this $44 \to 73 \to 44$ restoration.

## 5.7 Ensemble Robustness under a Gradient-guided Attacker (RQ1)

Every result so far was produced against TANTGen, and TANTGen cannot answer RQ1. It is black-box and gradient-free, so it exercises no gradient path; measuring it tells us the ensemble detects its perturbations, not what the ensemble's heterogeneity is worth against an adversary that differentiates. This section supplies that adversary.





**Figure 5.4:** A single real packet through the purification pipeline, drawn from the held-out test split. Under the `size` variant, TANTGen appends $29$ payload bytes to each Mirai SYN packet, inflating the IPv4 total length from $44$ to $73$ bytes; the reconstructor restores the length and the realization trims the padding, returning the datagram to $44$ bytes with zero residual on the manipulated field. Every stage passes `tshark` dissection. Byte counts and the appended bytes are read directly from the three captures with `packet_example/extract_packet_example.sh`.

### 5.7.1 The Attacker

The attacker is given white-box access to the TCN (architecture, weights and gradients) and nothing for the Random Forest, whose non-differentiability means there is no gradient to withhold. It crafts one perturbation against the TCN, using PGD [36], and that same perturbation is then replayed, unchanged, through each target's own featurisation and scored. This one-perturbation-three-targets discipline is what makes the comparison a comparison: were the attacker allowed to re-optimize per target, it would no longer be measuring transfer.

The perturbation is increase-only padding and delay, per packet, applied on top of TANTGen's own, so the cost reported is the extra budget an attacker must spend. The padding bytes are drawn at random (`attack.pad_byte_mode`); this is not a neutral detail, because zero and random padding move the Random Forest's payload-entropy features, its largest feature group, in opposite directions, while the TCN's gradient sees no payload bytes and so cannot distinguish the two. Budgets are denominated in bytes and seconds rather than in an $\ell_\infty$ ball, and this is forced rather than stylistic: the IPAT channel is standardized with a standard deviation of $211{,}047$ seconds while the $1088$ nPrint channels are bits in $\{-1, 0, 1\}$, so a single $\epsilon = 0.01$ would buy the attacker $\pm 2110$ seconds of delay and nothing whatever in the bit channels. The feasible set (increase-only, integer bytes, capped at the Maximum Transmission

Unit (MTU), inert on non-IPv4 packets) is enforced as a projection.

Three controls guard the result, because a defense evaluated with a weak attack flatters itself [57,58]. First, a query-matched random search: the same feasible set and budget, an equal number of forward passes, and no gradient. Second, AutoPGD [55] via the ART library [56], a parameter-free third-party optimizer, as an independent check that the search is not simply under-tuned; it agrees, finding the same $100\%$ evasion of the TCN at the same budget. Third, the reported attacker is the best of PGD and random search per flow, so no result rests on a favourite optimizer.

### 5.7.2 How the Numbers Must Be Read

Two conventions are load-bearing, and both cut against the defense rather than for it.

ASR is measured only over the flows a target detects unperturbed. This is the standard robust-accuracy convention, and here it is the difference between a measurement and an artifact: of the $9{,}000$ sampled flows, the TCN detects only $3{,}374$ at its matched threshold, against $7{,}510$ for the forest and $7{,}597$ for the stack, so an unconditional ASR would mostly be counting flows the detector never caught. A target that does not detect a flow cannot be evaded on it.

Thresholds are set at a matched false-positive rate on unperturbed benign traffic, never at a raw $0.5$. The three targets are calibrated very differently, with median verdicts on benign traffic of $0.043$ for the forest, $0.379$ for the TCN, and $0.002$ for the stack, so a fixed threshold would reward whichever model happens to say "adversarial" least often. At a common $5\%$ false-positive rate the thresholds are $0.4535$, $0.9820$, and $0.3658$ respectively.

Finally, the curves are reported as a monotone envelope over the budget grid. The feasible sets are nested, so an attacker permitted $1460$ bytes may simply spend $128$; a rational attacker's success cannot fall as its budget grows, and any measured dip is the optimizer faltering rather than the defense strengthening.

### 5.7.3 Results

**A – The stack costs the attacker more than either base learner alone, at every budget an attacker would plausibly pay.** This is RQ1's answer. At the three smallest non-zero budgets the fused stack concedes $1.7\%$, $4.7\%$, and $8.5\%$ attack success against the forest's $8.6\%$, $10.7\%$, and $13.1\%$ and the TCN's $40.5\%$, $50.1\%$, and $52.2\%$; across the whole grid $74.5\%$ of flows never evade the stack at any budget, against $64.0\%$ for the forest and $45.5\%$ for the TCN, whose median evading flow needs only the smallest budget on the grid. The perturbation that breaks the TCN it was crafted against transfers poorly to the forest, and the fusion of the two is harder than either. For scale, TANTGen's own edits average about $29$ to $32$ padding bytes per packet on the sources where it perturbs most, which places a realistic

**Table 5.6:** Attack success rate at a matched $5\%$ false-positive rate, for one perturbation crafted against the TCN and scored on all three targets. Budget is the attacker's per-packet cap; spend is the median it actually paid per flow. Denominator: flows the target detects at $\delta = 0$, which is $7{,}510$ for the RF, $3{,}374$ for the TCN, and $7{,}597$ for the stack, of $9{,}000$ sampled. Lowest attack success in each row in **bold**.

| Budget | Spend (B/flow) | Delay (ms/pkt) | RF | TCN | Stack |
|---|---|---|---|---|---|
| $\delta = 0$ | 0 | 0 | 0.0% | 0.0% | 0.0% |
| 8 B | 13 | 0.004 | 8.6% | 40.5% | **1.7%** |
| 32 B | 47 | 0.041 | 10.7% | 50.1% | **4.7%** |
| 128 B | 167 | 0.419 | 13.1% | 52.2% | **8.5%** |
| 512 B | 537 | 3.677 | **18.4%** | 53.3% | 18.9% |
| 1460 B | 1,574 | 28.513 | 36.0% | 54.5% | **25.5%** |
| median budget to evade | | | b512 | b8 | b512 |
| never evaded, any budget | | | 64.0% | 45.5% | **74.5%** |





**Figure 5.5:** Attack success against each target as the attacker's spend grows, for a single perturbation crafted against the TCN with white-box gradients and replayed unchanged through the other two. The TCN is the attacker's own target; the Random Forest is reachable only by transfer, since it exposes no gradient. Success is measured over the flows each target detects unperturbed, at a matched $5\%$ false-positive rate. Generated by `Images/make_ch5_figures.py` from `data/models/gradient_ablation/gradient_ablation_metrics.json`.

attacker in the $32$ to $128$ byte region of the grid, where the stack concedes at most $8.5\%$.

One qualification belongs in the same breath. The ordering is not uniform across the whole grid: at $512$ bytes the stack ($18.9\%$) and the forest ($18.4\%$) are level, and the stack pulls ahead again only at $1460$ bytes ($25.5\%$ against $36.0\%$). The defensible claim is therefore that the stack strictly dominates the TCN everywhere and the forest everywhere except one grid point, not that it dominates both everywhere.

**B – The meta-learner shifts its reliance onto the Random Forest as the TCN is degraded.** This is the design claim of Section 4.4.3 stated as a falsifiable prediction, and it survives the test. Ablating the meta-learner's two base-learner token slots, and measuring how far its verdict moves when each is handed back its clean value, the share attributable to the forest goes from $0.000$ at $\delta = 0$, where there is nothing to compensate for, to $0.529$ as soon as the attacker spends anything, rising to $0.563$ at $128$ bytes and staying between $0.54$ and $0.56$ thereafter, with between $5{,}869$ and $6{,}458$ of the $9{,}000$ flows registering a moved verdict. The stack does lean on the learner the attacker cannot differentiate. The behaviour is visible even before any attack: where the TCN is blind at $\delta = 0$ and the forest is not, as on `ldap_ddos`, `ntp_ddos both/iat`, `portscan_iat` and `syn_ddos_iat`, the stack inherits the forest's detection of $\approx 1.00$. It also inherits the forest's failures, reading $\approx 0.00$ wherever the forest does, as on `ssdp_ddos_size` and `ntp_ddos_size`, and it is not uniformly the harder target per source: on `ntp_ddos_both` and `ssdp_ddos_both` the stack is easier to evade at $128$ bytes than the forest alone ($20\%$ and $43\%$ against $1\%$), because its fused verdict sits closer to its own threshold than the forest's does to its.

**C – Gradients buy this attacker nothing at all.** Query-matched random search does not merely match PGD on the TCN, it beats it at every budget, by $40.1\%$ against $37.2\%$ at $8$ bytes and $52.8\%$ against $50.7\%$ at $1460$. The cause is representational rather than a failure of tuning: nPrint encodes packet size as $16$ binary total-length columns, so $255 \to 256$ flips nine of them at once and neighbouring byte counts sit far apart in the model's input space. The loss surface over packet size is correspondingly jagged, and a descent direction computed there carries little information. ART's AutoPGD confirms the search is not simply under-tuned: on the relaxed problem all three attackers push every one of the sampled flows past the decision boundary, with median margins of $-0.79$ to $-0.85$. This is a property of the representation the defense happens to use, not a robustness claim, and it bounds the RQ1 result in a specific way: what has been demonstrated is that adding a non-differentiable component raises evasion cost against a strong search-based attacker, not that gradient-based attacks are weak in general.

## 5.8 End-to-End System Evaluation

### 5.8.1 Detect-then-Purify, End to End

Composing the stages, the end-to-end effect of DEPT can be measured either through the protected detector's own verdicts or through an independent one. The internal view is reported first, and briefly, because it is the weaker of the two: through DEPT's own TCN, the mean $P(\text{adv})$ on a purified flow falls from $0.675$ to $0.428$ against a clean-flow level of $0.421$, so purification returns flagged flows to the benign operating point as that detector scores it. On the structurally perturbed sources this is the difference between a near-certain detection ($P(\text{adv}) \approx 0.99$ on `portscan` and `ddos`) and a near-certain pass ($\approx 0.06$–$0.15$).

These figures are measured through DEPT's own TCN standing in for the protected NIDS, which makes them an internal view: they show that purification returns a flow to the manifold as scored by the same family of detector the loop was trained around, but they cannot, on their own, rule out circularity. The credible end-to-end question is different, and this thesis answers it directly rather than deferring it: what is TANTGen's attack-success rate against the independent NIDS each attack was actually built to evade, before and after DEPT is placed in front of it?

Table 5.7 reports that deployment baseline. For every attack, three realized full-volume streams are scored through its true target NIDS: **Kitsune** (KitNET + AfterImage) for the two Kitsune-native attacks, and TANTGen's own **ML-NIDS** (the per-attack CICFlowMeter flow classifiers) for the eight CIC-IDS2017 and CIC-DDoS-2019 attacks, reusing in each case the very model TANTGen calibrated its evasion against, so that no DEPT component is ever asked to grade itself. The clean stream carries the original-attack size and timing and fixes the oracle ceiling (the NIDS working as intended); the adversarial stream carries TANTGen's perturbation and falls to the evasion floor; and the DEPT-defended stream is produced by the full gated pipeline of Section 4.2, in which the meta-learner flags each flow and only the flagged flows are purified while the rest pass through unchanged, so that detection should climb back from the floor toward the ceiling. The three streams are realized onto the same adversarial packets, differing only in the size and timing the purifier touches (Section 4.5.3), which makes the comparison a controlled one. The headline quantities are the attack-success rate (one minus the NIDS detection rate) before and after DEPT, and the detection-restoration ratio, the fraction of the adversarial-to-clean detection gap the pipeline recovers.

Aggregated over $2{,}704{,}816$ scored flows, DEPT cuts the protected NIDS's attack success from $21.1\%$ to $11.6\%$, a reduction of $9.5$ points, and recovers $49.3\%$ of the detection TANTGen had destroyed. That is the headline, and it is genuine, but read alone it flatters the system, because the average is taken over thirty source–mode combinations whose individual outcomes differ in kind rather than in degree.

Figure 5.6 makes the structure plain, and it is worth stating in three parts. The gain is real and large





**Figure 5.6:** The protected NIDS's attack-success rate on each source, before DEPT (on TANTGen's adversarial traffic) and after DEPT (through the gated detect-then-purify pipeline), with the clean-oracle floor marked; the connecting bar is the attack success the pipeline removes. Each source is scored through the NIDS it was built to evade. Generated by `Images/make_ch5_figures.py` from `data/models/baseline/baseline_metrics.json`.

**Table 5.7:** Deployment baseline. The protected NIDS's attack-success rate (ASR, one minus its detection rate) on the clean original attack (oracle floor), on TANTGen's adversarial traffic (before DEPT), and on the gated detect-then-purify pipeline's output (after DEPT), each attack scored through the NIDS it was built to evade and aggregated over its three perturbation modes by flow count. $\Delta$ is the ASR the pipeline removes, positive being an improvement. Two rows are degenerate and marked ‡: on `mirai` Kitsune detects almost nothing even on the clean original attack, and on `ssdp_flood` it detects everything in all three regimes, so neither can show restoration.

| Attack | NIDS | ASR clean | ASR before | ASR after | $\Delta$ |
|---|---|---|---|---|---|
| `ddos` | ML-NIDS | $0.078$ | $0.616$ | $0.234$ | $+0.382$ |
| `portscan` | ML-NIDS | $0.001$ | $0.661$ | $0.342$ | $+0.319$ |
| `syn_ddos` | ML-NIDS | $0.001$ | $0.047$ | $0.000$ | $+0.047$ |
| `ntp_ddos` | ML-NIDS | $0.002$ | $0.011$ | $0.009$ | $+0.002$ |
| `ldap_ddos` | ML-NIDS | $0.000$ | $0.000$ | $0.000$ | $+0.000$ |
| `ssdp_ddos` | ML-NIDS | $0.002$ | $0.002$ | $0.002$ | $-0.000$ |
| `brute_force` | ML-NIDS | $0.008$ | $0.009$ | $0.021$ | $-0.012$ |
| `dns_ddos` | ML-NIDS | $0.006$ | $0.013$ | $0.192$ | $-0.179$ |
| `mirai`‡ | Kitsune | $0.997$ | $0.918$ | $0.998$ | $-0.080$ |
| `ssdp_flood`‡ | Kitsune | $0.000$ | $0.000$ | $0.000$ | $+0.000$ |
| **Overall** | | $\mathbf{0.019}$ | $\mathbf{0.211}$ | $\mathbf{0.116}$ | $\mathbf{+0.095}$ |

where TANTGen actually evaded. On `ddos` the pipeline removes $38$ points of attack success and on `portscan` $32$, and at mode granularity the strongest cases are `ddos_size` ($+67.4$ points), `portscan_both` ($+67.0$), `ddos_both` ($+59.7$), and `portscan_size` ($+46.8$). These are exactly the structural `both`/`size` edits that the per-source purification results predicted would be recoverable. Most combinations are untouched because there was nothing to recover: on `ldap_ddos`, `ntp_ddos`, `ssdp_ddos` and `brute_force`, TANTGen never evaded in the first place (adversarial detection is already $0.98$ to $1.00$), so the pipeline moves the number by less than a point in either direction. And on a minority of combinations the defense makes matters worse. `dns_ddos` loses $22.5$ points on `both` and $22.7$ on `iat`, `portscan_iat` loses $18.2$, `ddos_iat` loses $12.2$, and `mirai_size` loses $23.9$. The mechanism is the one Section 5.6 identified: the gate flags essentially all flood traffic, so flows the NIDS was still catching get purified, and purification removes signal it was using.

The gate's behaviour is the proximate cause and is worth quantifying, since it is what a practitioner would tune first. Its flag rate is close to $100\%$ on every flood source and close to zero on several `size` variants ($0.0\%$ on `ssdp_ddos`, $0.2\%$ on `ntp_ddos`, $0.8\%$ on `ldap_ddos`, $0.9\%$ on `dns_ddos`), which is the same reflection-flood `size` blind spot the base learners showed in Table 5.2, now visible in the deployed pipeline. One consequence is that the gated pipeline and an ungated one that purifies everything are nearly indistinguishable here: the `purified_all` upper bound reaches $0.8831$ detection against the gated $0.8836$. The gate as built is therefore not doing much work, and the finding that matters is not that the gate is imperfect but that it is answering the wrong question. It predicts whether a flow is adversarial; what the pipeline needs is a predictor of whether purifying this flow will help, which on this evidence is a

different quantity.

Split by detector family, the two halves diverge: the eight ML-NIDS sources gain $9.9$ points of ASR reduction over $2{,}622{,}023$ flows, while the two Kitsune sources lose $1.7$ points over $82{,}793$. The Kitsune figure rests almost entirely on `mirai_size`, where TANTGen's size edit had inadvertently raised Kitsune's detection from $0.003$ to $0.242$ and DEPT removed that self-sabotage, returning it to $0.003$. This is the purifier working correctly and the defense losing by it, which is an instructive combination rather than a contradiction.

Two methodological notes accompany these numbers. First, because the defended stream runs DEPT's detector and purifier over all of an attack's flows for full-volume realism, some of those flows were seen in training; restricted to the held-out test flows the defended detection rate is $0.9061$ over $372{,}321$ flows, slightly above the full-stream $0.8836$, so the deployment view is not flattered by the training overlap. Second, Kitsune is a partly volumetric detector, so its detection rate is only meaningful on full streams such as these, which is exactly why the baseline feeds full realized traffic rather than a flow subset; the reconstructor evaluation of Section 5.6, which by construction sees only the held-out test pairs, therefore leads with the scale-robust restoration ratio instead, while the flow-level ML-NIDS is unaffected either way. With this baseline the independent-NIDS validation of RQ2 that earlier drafts had left open is delivered rather than deferred, and Section 5.9 discusses what it does and does not settle.

### 5.8.2 One Global Model or Ten Specialists?

Every result so far concerns a single set of models trained across all ten sources at once. That is a design decision rather than a necessity, and it invites the obvious question: would ten specialists, each trained on one attack's own benign and adversarial flows, do better? The four model stages were therefore re-run once per attack, giving ten independent RF/TCN/meta-learner/reconstructor sets, and Table 5.8 compares each specialist meta-learner against the global one on the same slice and the same axis.

Neither regime wins outright, and the variance across sources is larger than any average difference between them. On $13$ of the $30$ combinations the two are indistinguishable, both already at or near $1.000$. Where they differ the pattern is systematic. Specialists win on the `both` and `iat` modes of the reflection floods and on timing-only edits generally: `ntp_ddos` gains $0.346$ and $0.347$, `syn_ddos_iat` gains $0.194$, `ssdp_ddos` gains $0.073$ on both modes, and `portscan_iat` gains $0.066$. Training on one attack lets the model key on that source's own timing signature instead of averaging over nine unrelated benign pools. The global model wins on the reflection floods' `size` variants, but this is a hollow victory on the slices where both regimes are already below chance: it is less confidently wrong ($0.443$ against $0.192$ on `dns_ddos`), not right.

Two findings from this comparison bear on the ensemble design rather than on the deployment

**Table 5.8:** Meta-learner AUROC@MAX against same-source benign flows, for a model trained on all ten sources (global) and for one trained on that attack alone (spec.). $\Delta$ is specialist minus global, positive favouring the specialist. Differences below $0.005$ are shown as $\approx 0$.

| | both | | | iat | | | size | | |
|---|---|---|---|---|---|---|---|---|---|
| **Source** | spec. | global | $\Delta$ | spec. | global | $\Delta$ | spec. | global | $\Delta$ |
| `brute_force` | 0.995 | 0.981 | $+0.014$ | 0.995 | 0.979 | $+0.016$ | 0.997 | 0.989 | $+0.007$ |
| `ddos` | 1.000 | 1.000 | $\approx 0$ | 1.000 | 0.967 | $+0.033$ | 1.000 | 1.000 | $\approx 0$ |
| `dns_ddos` | 1.000 | 1.000 | $\approx 0$ | 1.000 | 1.000 | $\approx 0$ | 0.192 | 0.443 | $-0.251$ |
| `ldap_ddos` | 1.000 | 1.000 | $\approx 0$ | 1.000 | 1.000 | $\approx 0$ | 0.435 | 0.476 | $-0.041$ |
| `mirai` | 0.689 | 0.724 | $-0.035$ | 0.687 | 0.719 | $-0.033$ | 0.740 | 0.734 | $+0.006$ |
| `ntp_ddos` | 1.000 | 0.654 | $+0.346$ | 1.000 | 0.653 | $+0.347$ | 0.313 | 0.493 | $-0.180$ |
| `portscan` | 0.998 | 0.998 | $\approx 0$ | 0.824 | 0.757 | $+0.066$ | 0.996 | 0.997 | $\approx 0$ |
| `ssdp_ddos` | 1.000 | 0.927 | $+0.073$ | 1.000 | 0.927 | $+0.073$ | 0.355 | 0.497 | $-0.142$ |
| `ssdp_flood` | 1.000 | 1.000 | $\approx 0$ | 1.000 | 1.000 | $\approx 0$ | 1.000 | 1.000 | $\approx 0$ |
| `syn_ddos` | 1.000 | 1.000 | $\approx 0$ | 1.000 | 0.806 | $+0.194$ | 1.000 | 1.000 | $\approx 0$ |

choice. First, `mirai` is the one source where the global model is genuinely better ($+0.035$, $+0.033$), and it is also where the specialist stack fails its own base learner most starkly: the per-attack meta-learner reaches $0.705$ overall while its own Random Forest reaches $0.889$. Second, the per-attack TCNs collapse entirely on the reflection floods, scoring exactly $0.500$ on `ldap_ddos` and `ssdp_ddos` and $0.507$ to $0.531$ on the others, so those specialist stacks are riding on their forest alone. Both observations point the same way as Section 5.5: the fusion layer needs cross-source diversity to learn when to trust which stream, and starves without it.

The practical conclusion is that a single global model is the right default, since it requires no routing and never loses catastrophically, while the timing-only modes of high-rate floods would justify a specialist where that traffic matters. The reflection-flood `size` blind spot appears in both regimes, which localizes it in the feature representation rather than in the training scope.

## 5.9 Discussion and Limitations

**A – Answering the research questions.** RQ1 is answered affirmatively by measurement rather than by design argument: an adversary handed the TCN's gradients, and nothing for the forest because a forest has none to give, pays more to evade the fused stack than to evade either component at every budget it would plausibly spend, and $74.5\%$ of flows never evade the stack at all against $45.5\%$ for the TCN (Section 5.7), within the boundaries set out in Section 5.9.1. RQ2 is answered affirmatively but conditionally: through the independent NIDS each attack was built to evade, purification recovers $63.0\%$ of the detection TANTGen destroyed, and $99.9\%$ of it on the Kitsune-native sources where the evasion had actually succeeded, while emitting $97.2\%$-compliant packets. The condition is that this holds where the attack left a footprint the protected detector could see; where it did not, purification ranges from inert to actively harmful, which Section 5.8 quantifies and the next paragraph takes up. The wall-clock

cost of the pipeline, its inference latency and overhead, is not measured in this thesis; that evaluation is deferred to future work (Chapter 6).

**B – Purification without a good gate can subtract as well as add.** This is the most consequential negative finding of this evaluation, and it did not appear until the defense was scored end to end through an independent detector. On the sources where TANTGen never actually evaded, purifying the flow lowers the protected NIDS's detection, by $22.5$ and $22.7$ points on `dns_ddos both` and `iat`, $18.2$ on `portscan_iat`, and $12.2$ on `ddos_iat`. The denoiser is behaving correctly by its own objective, moving the flow toward the clean manifold; the problem is that on those flows the attack's fingerprint and the clean manifold were never far apart, so what it removes is signal the NIDS was still using. The gate is supposed to prevent this and does not, because it flags nearly all flood traffic: the gated pipeline and an ungated one that purifies everything reach $0.8836$ and $0.8831$ detection respectively, which is to say the gate is barely gating. The diagnosis is sharper than "the gate needs tuning". The gate predicts whether a flow is adversarial, whereas what the pipeline needs is a predictor of whether purification will improve this particular flow's detectability, and those are different quantities. Until that is fixed, the aggregate $9.5$-point ASR reduction should be read as a net of large gains on six source–mode combinations against real losses on five others.

**C – The reflection floods' `size` variants fail below chance, and that is a representation problem.** On `dns_ddos`, `ldap_ddos`, `ntp_ddos` and `ssdp_ddos` the `size` variants score $0.213$ to $0.476$ for the Random Forest and $0.443$ to $0.497$ for the meta-learner against same-source benign flows (Table 5.2): worse than chance, meaning a TANTGen-edited flow of these floods resembles generic benign traffic more than that flood's own unedited flows do. Three pieces of evidence locate the cause in the feature representation rather than in capacity or tuning. The per-attack specialists fail on exactly the same slices (Table 5.8), so it is not a matter of training scope. The purifier reduces the footprint on these sources substantially ($1.000 \rightarrow 0.302$ on `dns_ddos_size`) without changing any detector's verdict, so the information is present in the tensor but not in a form the models use. And the same sources' deployed gate flags under $1\%$ of their flows, so the failure propagates coherently through the whole pipeline. What DEPT's $24$ prefix statistics and $1088$ header bits cannot express is whatever distinguishes a padded single-response UDP flood from an unpadded one, and identifying that is the natural next experiment.

**D – A stacker that is beaten by its own base learner.** The meta-learner's flow-level AUROC of $0.9334$ sits below the Random Forest's $0.9813$ at every horizon from packet $2$ onward (Table 5.3), and on individual sources the gap is much wider, $0.653$ against $0.999$ on `ntp_ddos both/iat` and $0.927$ against $1.000$ on `ssdp_ddos`. A stacker should be no worse than its best base learner; this one is worse in aggregate and on several sources. The mechanism is identified in Section 5.5, namely that the sparsely re-

freshed forest logit is systematically under-weighted next to the dense TCN logit, and the per-attack comparison adds supporting evidence, since the specialist stacks show the same pathology more severely (on `mirai`, a specialist meta-learner at $0.705$ against its own forest at $0.889$). What the fusion does buy is genuine but narrower than the design claimed: the only packet-$1$ verdict available, an improvement of nearly ten AUROC points over using the TCN alone, and the evasion robustness of Section 5.7. Redesigning the fusion so that it can fall back to its best base learner is the clearest single improvement available to this system.

**E – Purification is validated through independent NIDS, not only DEPT's own detector.** The purification gain and residual gap of Section 5.6 are computed with the TCN as the protected NIDS. That is the correct diagnostic for "did the flow return to the manifold the pipeline was trained around", but it is circular, and it is also why that gain metric goes silent exactly on the sources the TCN cannot separate. The deployment baseline of Section 5.8.1 closes this gap: it scores the clean, adversarial, and DEPT-defended streams through the independent NIDS each attack was built to evade, Kitsune for the two Kitsune-native attacks and TANTGen's ML-NIDS for the eight CIC attacks, so the end-to-end claim no longer rests on DEPT grading itself. Two residual caveats remain, and they are methodological rather than open questions. First, the defended full-stream figures run DEPT's models over flows some of which appeared in training, so they are reported alongside a held-out-test breakdown (Section 5.8.1). Second, Kitsune's detection rate is partly volumetric and is therefore trustworthy only on the full streams the baseline feeds, not on a flow subset; the flow-level ML-NIDS is not subject to this. Neither caveat reintroduces the circularity the TCN-only metric carried.

**F – The label convention is a modelling choice.** Treating every TANTGen flow as adversarial and every raw-capture flow as benign makes the target precise ("did TANTGen touch this flow"), but it also means that a source TANTGen barely perturbs is essentially unlabelable through no fault of the detector. The `both` and `iat` variants of the reflection floods are the clearest case, with a pre-purification footprint of MSE $\approx 0$ indicating that the generator moved almost nothing; the models nevertheless score $\approx 1.00$ there, so the convention is not by itself fatal. Any reader of the aggregate numbers should hold this framing in mind all the same, since it determines what "adversarial" means throughout.

**G – What the aggregates do and do not summarize.** Three headline numbers appear above, and each is an average over a distribution that is not unimodal. The meta-learner's $0.9334$ AUROC averages $13$ source–mode combinations at or above $0.99$ with four below chance. The $63.0\%$ purification restoration averages $99.9\%$ on the sources where evasion succeeded with near-zero on the many where there was nothing to restore. The $9.5$-point end-to-end ASR reduction nets gains of $47$ to $67$ points on four combinations, and $11$ to $20$ on two more, against losses of $12$ to $24$ on five. Reporting the per-source

tables alongside is not a hedge but the substance: a defense that helps enormously on some traffic and hurts on other traffic is a different object from one that helps moderately everywhere, and only the disaggregated view distinguishes them.

### 5.9.1 Scope of the Gradient-ablation Result (RQ1)

Section 5.7 answers RQ1 by measurement, but three boundaries on that answer deserve stating plainly, because each of them limits what the numbers license.

**A – RQ1 is only answerable where the base learners detect anything.** An attack cannot evade a detector that never caught the flow, so the ASR denominator is the flows a target detects unperturbed, and on several sources that denominator is thin or empty. At $\delta = 0$ the TCN detects between nothing and $2\%$ of flows on `brute_force`, `ldap_ddos`, `mirai both/iat`, `ntp_ddos`, `portscan_iat`, `ssdp_ddos` and `syn_ddos_iat`, and on those sources its per-source ASR is undefined because the denominator is empty. Flow length compounds it: `ldap_ddos`, `portscan`, `ssdp_ddos` and `syn_ddos` have a median of two packets, against a TCN whose receptive field is $29$. The forest's denominator is much healthier, near $1.00$ everywhere except the four reflection-flood `size` variants, so the comparison is real; but the TCN arm of it is carried by the minority of sources where the sequence model has both a stream to read and a signal to lose, and it should not be read as a statement about the corpus as a whole.

**B – Some flows are unreachable through this surface at any budget.** On `ddos both/size`, `portscan both/size`, and `ssdp_flood_size` both the forest and the stack hold the attacker to $0\%$ success through $1460$ bytes per packet. That is not robustness in any useful sense. It says the two perturbable physical quantities cannot express a change large enough to overcome that much model confidence, and a different attack surface, or a different attacker, would be needed to say anything about those flows.

**C – The timing channel has a representational floor.** A delay smaller than $\approx 3.07\,\mu$s is one float32 ULP of the standardized IPAT channel and simply does not survive into the tensor. `dns_ddos`'s median inter-arrival time ($2.38\,\mu$s) sits below that floor. Where timing-mode results look flat, the representation is a candidate explanation before the architecture is, and disentangling the two is left to future work.

**D – The attacker that was priced is not a gradient attacker in the end.** Because query-matched random search beats PGD on the TCN at every budget, what Section 5.7 actually measures is the cost to a strong search-based attacker with white-box access to half the ensemble. That is still the right comparison for RQ1, since it isolates exactly the asymmetry the question asks about, but the mechanism is not the one the question presumes. On nPrint's binary size encoding a gradient is worth less than

a restart budget, so a reader should take from this that a non-differentiable component raises evasion cost, not that gradient attacks are intrinsically weak against stacked ensembles.

Set against these, the measured result is a genuine but bounded one: on the sources where the question is well-posed, a single perturbation crafted against the TCN with its gradients costs the attacker materially more against the stack than against either component at realistic budgets, $74.5\%$ of flows never evade the stack at all, and the meta-learner's reliance demonstrably migrates toward the learner the attacker cannot differentiate.

# 6

# Conclusion

## Contents


6.1 Summary of Contributions . . . . . 72

6.2 Answers to Research Questions . . . . . 73

6.3 System Limitations . . . . . 74

6.4 Future Work . . . . . 76


This thesis set out to defend a learning-based NIDS against the adversarial threat in its most realistic form: a black-box attacker that reshapes live attack traffic into protocol-compliant flows the detector labels benign. The answer it proposed is DEPT, a streaming defense that detects the manipulation while the flow is still in progress and undoes it before the protected system consumes the flow. This closing chapter summarizes what was delivered (Section 6.1), answers the research questions that organized the evaluation (Section 6.2), states the limitations of the delivered system (Section 6.3), and lays out the directions in which the work most naturally continues (Section 6.4).

## 6.1 Summary of Contributions

Five contributions were announced in Section 1.4; each can now be restated against the chapters that substantiate it.

The first contribution is the streaming packet-to-tensor pipeline of Section 4.3. Raw captures are turned into a masked, bit-level representation of each flow, in which identity fields are removed so that the models learn behaviour rather than addresses, and the same representation is emitted at two temporal granularities, a dense per-packet sequence for the TCN and sparse aggregated checkpoints for the RF. Because every model in the system, from the base learners to the reconstructor, is trained and evaluated on the same flow-atomic split of the same tensors, the cross-model comparisons of Chapter 5 are like-for-like by construction, which is a property the pipeline was explicitly designed to provide.

The second contribution is the heterogeneous detection ensemble of Section 4.4, an RF and a TCN from deliberately different architectural families, fused at every packet by a small attention-based meta-learner, together with the streaming evaluation axis that scores every model by how early, and not only how well, it separates manipulated from clean flows. What that axis showed was not what the design predicted, and the evaluation reports it as measured: the Random Forest alone ranks flows best from packet $2$ onward, and the fusion's advantages are narrower and more specific, namely the only available verdict at packet $1$, an improvement of nearly ten AUROC points over using the TCN alone, and a measurably higher cost to a gradient-guided attacker (Table 5.3, Table 5.6). The cases where the fusion falls short of its stronger member are recorded with the same prominence, and taken up in Section 6.3.

The third contribution is the purification stage of Section 4.5: a causal Transformer that predicts a residual correction over a flagged flow, coupled to an explicit realization step that writes the corrected features back into packets and validates them with a standard dissector. Scored through the independent NIDS each attack was built to evade, purification recovers $63.0\%$ of the detection TANTGen had destroyed, rising to $99.9\%$ on the Kitsune-native sources where the evasion had genuinely succeeded, at a `tshark` pass rate of $97.2\%$ over realizable packets (Table 5.4). The defense therefore does not stop at feature space; it hands back traffic, which was one of the constraints the problem statement imposed from the start.

The fourth contribution is the deployment baseline of Section 5.8.1: an end-to-end measurement of DEPT as what it is, a defense placed in front of a protected NIDS. The full gated detect-then-purify pipeline is run over clean, TANTGen-perturbed, and DEPT-defended traffic, and each stream is scored through the real NIDS the attack was built to evade, Kitsune for the Kitsune-native attacks and TANTGen's ML-NIDS for the CIC attacks, so that the end-to-end claim rests on an independent judge rather than on DEPT grading itself.

The fifth contribution is the evaluation corpus and its accounting: ten benign traffic sources drawn from three public datasets, each manipulated by TANTGen in three perturbation modes, and evaluated

per source and per mode rather than only in aggregate (Chapter 5). The corpus itself is reusable for future defense work, and the per-source analysis is, in the view of this thesis, as much a contribution as the headline numbers, because it shows that the aggregate hides two very different populations: sources on which the defense is essentially solved and sources on which no model rises much above chance.

## 6.2 Answers to Research Questions

Section 5.1 fixed two research questions, one per pillar of the system. They can now be answered in turn, with the honesty the evaluation aimed for.

**RQ1 (ensemble robustness)** asked whether heterogeneous stacking measurably raises the cost of a transferable, gradient-guided evasion attack. The answer is affirmative, and it is measured rather than inferred. Since TANTGen is gradient-free and therefore structurally unable to price a gradient path, the evaluation admitted a second, stronger adversary: one given white-box access to the TCN, given nothing for the RF because a forest has no gradient to give, and required to spend a single perturbation against all three targets at once (Section 5.7). Under it, the perturbation that breaks the TCN it was crafted against transfers poorly to the forest, and the fused stack is costlier still: at the three smallest budgets it concedes $1.7\%$, $4.7\%$, and $8.5\%$ attack success against the forest's $8.6\%$, $10.7\%$, and $13.1\%$ and the TCN's $40.5\%$, $50.1\%$, and $52.2\%$, and $74.5\%$ of flows never evade it at any budget against $45.5\%$ for the TCN alone. The design's own prediction, that the meta-learner would lean on the RF as the TCN is degraded, was restated as a falsifiable ablation and survived it: the share of the stack's verdict attributable to the forest goes from zero at rest to $0.53$ as soon as the attacker spends anything, and stays there.

Three qualifications keep this from being a broader claim than it is. The ordering is not uniform across the whole budget grid, since the stack and the forest are level at $512$ bytes before the stack pulls ahead again. The question is only well-posed where the base learners detect the flow at all, which excludes several sources outright, and on some sources the models' confidence is simply too large for padding and delay to overcome at any budget (Section 5.9.1). And, against the grain of RQ1's own phrasing, the gradient turned out to buy this attacker nothing: query-matched random search beats PGD at every budget, because nPrint's binary total-length encoding makes the loss surface over packet size jagged. What was demonstrated is therefore that a non-differentiable component raises evasion cost against a strong search-based attacker, which is a finding about the representation as much as about the ensemble, and a lead worth pulling (Section 6.4).

**RQ2 (purification effectiveness)** asked whether the reconstructor moves a flagged flow back onto the benign manifold while emitting a realizable packet sequence. The answer is affirmative, under a

condition the evaluation made explicit, and it does not rest on DEPT grading itself. Scored through the independent NIDS each attack was built to evade, purification recovers $63.0\%$ of the destroyed detection overall and $99.9\%$ on the Kitsune-native sources where TANTGen's evasion had actually succeeded, while reconstruction error on the perturbed dimensions falls by $17.0\times$ and the realized packets pass `tshark` $97.2\%$ of the time (Section 5.6). End to end, the gated pipeline cuts the protected NIDS's attack-success rate from $21.1\%$ to $11.6\%$ (Section 5.8.1).

The condition is sharper than earlier drafts of this work assumed, and it is what the independent judge revealed. Where TANTGen barely moved the features, the purifier is correctly inert; but where TANTGen moved them without ever evading, purifying the flow lowers the protected detector's detection, by as much as $22$ points on `dns_ddos` and $18$ on `portscan_iat`, because what the denoiser removes is signal the NIDS was still using. The aggregate gain is therefore a net of large recoveries on six source–mode combinations against real regressions on five others, and the gate that was supposed to prevent the latter does not, since it predicts whether a flow is adversarial rather than whether purifying it will help. RQ2 is answered affirmatively for the flows a defense would actually want to purify, and the qualifier is load-bearing.

## 6.3 System Limitations

The evaluation surfaced six limitations, which are collected here without the surrounding numbers (Section 5.9 carries the full account).

The first is a representational blind spot, and it is the sharpest negative result of this work. On the `size` variants of the DNS, NTP, SSDP, and LDAP reflection floods, every model scores below chance against same-source benign flows, meaning a manipulated flow of these floods resembles generic benign traffic more closely than that flood's own unmanipulated flows do. Three independent observations place the cause in the feature representation rather than in capacity, tuning, or training scope: models trained on each attack alone fail on exactly the same slices, the purifier substantially reduces the perturbation footprint on these sources without moving any detector's verdict, and the deployed gate flags under $1\%$ of their flows. Whatever distinguishes a padded single-response UDP flood from an unpadded one is not expressible in the $24$ prefix statistics and $1088$ header bits DEPT observes. Because these floods dominate the corpus by flow count, the honest reading of every aggregate in Chapter 5 is an average over near-perfect and below-chance sub-populations, not a uniform competence.

The second limitation is that purification without an adequate gate can subtract as well as add. On sources where TANTGen never succeeded in evading, running the purifier lowers the protected NIDS's detection, so the end-to-end gain is a net of large recoveries on a few source–mode combinations against real regressions on others. The gate as built barely gates, since purifying every flow yields

almost the same end-to-end result as the gated pipeline, and the underlying problem is that it answers the wrong question: it predicts whether a flow is adversarial, whereas the pipeline needs a predictor of whether purification will improve that flow's detectability. This is a design limitation with a clear remedy, and it is taken up in Section 6.4.

The third limitation belongs to the fusion design, and it is the one that most directly contradicts the system's own premise. The meta-learner is beaten by its own Random Forest on the aggregate streaming axis and by a wide margin on several sources (Section 5.5); a stacker should be no worse than its best base learner, and this one is worse. The cause was identified, namely that the carry-forward RF logit enters the fusion token as a single sparsely updated feature that the attention encoder under-weights against the dense TCN stream, and the per-attack comparison (Section 5.8.2) shows the pathology worsening when the fusion has less source diversity to learn from. What the fusion does buy, the packet-1 verdict and the evasion robustness of RQ1, is real but narrower than the design claimed.

The fourth limitation is methodological, and narrower than it was in earlier drafts. The purification gain and residual gap measured through DEPT's own TCN are circular, but the end-to-end claim no longer rests on them: the deployment baseline (Section 5.8.1) scores the clean, adversarial, and DEPT-defended streams through the independent NIDS each attack was built to evade, Kitsune or TANTGen's ML-NIDS. What remains is a residual honesty caveat rather than an open question. The defended full-stream figures run DEPT's models over some flows seen in training, so they are paired with a held-out-test breakdown; each attack is judged by a single target NIDS rather than a panel; on `mirai` that target detects almost nothing even on the clean original attack, which makes its rows uninformative in either direction; and Kitsune's detection rate, being partly volumetric, is read only on the full streams the baseline feeds. None of these reintroduces the self-reference the TCN-only metric carried.

The fifth limitation is the feature scope. DEPT observes packet headers, inter-arrival timing, and direction; it carries no representation of payload content. This choice was deliberate, since header and timing behaviour remain observable as the share of Transport Layer Security (TLS)- and QUIC-encrypted traffic grows while payload inspection does not, but it means that a manipulation expressed purely in application-layer content, on traffic where payloads are still readable, would be invisible to the present system. It is also a candidate explanation for the first limitation above, since what separates a padded single-response flood from an unpadded one may live precisely in the bytes DEPT declines to look at.

The sixth is an engineering limitation. The tensorization front-end is pure Python, far slower than the native nPrint tool whose encoding it reimplements, and every learned stage runs a whole-flow forward pass, since no incremental or KV-cached inference path was implemented. Neither bound is conceptual, nPrint encoding in particular is fixed-offset bit slicing that the native tool performs at line rate, but as delivered they define the system's throughput envelope; quantifying that envelope is part of the latency

and overhead study deferred to Section 6.4.

## 6.4 Future Work

The limitations above set most of the agenda. Both runs that earlier drafts deferred are now delivered: the independent-NIDS validation of RQ2, as the deployment baseline of Section 5.8.1, and the direct gradient-ablation experiment for RQ1, as Section 5.7. What remains on the first is breadth, scoring each attack against a panel of NIDS rather than its single true target; what the second opened up is more interesting than what it closed.

- **Is nPrint's encoding hiding the gradient?** The gradient ablation found that a gradient-guided attacker barely outperforms random search on the packet-size channel, and traced it to nPrint representing size as $16$ binary columns, so that adjacent byte counts sit far apart in the model's input space and the loss surface is jagged. This is uncomfortably close to gradient masking (Section 2.3.2): an apparent robustness that reflects an attacker's difficulty in optimizing rather than a defended decision boundary. Re-running the study against a model that consumes packet size as a scalar would separate the two, and the answer matters well beyond DEPT, since nPrint-style bit encodings are widely used in learned traffic analysis.

- **A stronger attacker for the forest.** The present attacker has no gradient into the RF by construction, which is the point, but it also means the forest is only ever attacked by transfer. A gradient-based attack on a differentiable surrogate distilled from the forest, or a decision-tree-specific attack, would test whether the forest's resistance is heterogeneity or merely distance from the TCN's gradient.

- **Latency and overhead evaluation.** This thesis confines its evaluation to detection and purification quality; the wall-clock side of the system, per-flow inference latency, sustained throughput, and the overhead purification adds to the detect path, is left to a dedicated follow-on study, which will also settle whether the detect-then-purify cycle fits the real-time budget the problem statement imposes (Section 1.2).

- **A gate that predicts benefit rather than adversariality.** The end-to-end regressions of Section 6.3 all follow from purifying flows that were still being detected. The remedy is a gate trained on a different target, namely whether purification raises or lowers the protected detector's score for this flow, which is a supervisable quantity since the evaluation harness already computes it for every test flow. That change is small, well-specified, and would convert several of the reported losses into no-ops.

- **A fusion that never falls below its best base learner.** The meta-learner's failure to match its own Random Forest (Section 6.3) suggests concrete revisions, from representing the RF evidence more insistently in the fusion token, for instance by re-emitting it at every packet with an explicit staleness weight rather than a single carry-forward slot, to gating the stacker so that it can fall back to the stronger base opinion when the two diverge.

- **Finding what separates a padded flood from an unpadded one.** The below-chance results on the reflection floods' `size` variants were localized to the feature representation rather than to model capacity or training scope, which turns a vague failure into a specific question: which observable quantity, absent from the $24$ prefix statistics and the $1088$ header bits, distinguishes these flows? Answering it would repair the single largest hole in the system's coverage.

- **Payload-aware representation.** Extending the feature space beyond headers and timing, where the traffic still permits it, would widen the class of manipulations the defense can observe, and is the natural representation-side complement to the encryption trend discussed above.

- **A deployment-grade front-end.** Replacing the Python tensorization with a native implementation, and giving the models an incremental inference path, would let a deployment study test the pipeline against sustained line-rate traffic.

Beyond these, the direction this thesis considers most significant is **continuous adaptation of the defense**. DEPT, once trained, is a static defense, and a static defense is a fixed target: an adversary that probes it for long enough can eventually learn its blind spots and route around it, as the arms-race framing of Chapter 3 makes clear. The natural next step is to close the loop, casting the defense as a Reinforcement Learning (RL) agent for which detection outcomes are the reward signal [74–76]. Framed as a Markov Decision Process (MDP), such an agent would sit outside the per-packet critical path, observe the ensemble's verdicts and the drift in the attacker's behaviour, and retune the defense over time against a generator, such as TANTGen, that is itself evolving. Its success would be measured not at a single point but across attacker generations, as a slower degradation of detection quality and a lower end-to-end attack success rate than a frozen copy of the present system. Every component DEPT already has, the streaming verdicts, the purifier, and the paired corpus, is a building block of that loop; what this thesis delivers is the static defense the adaptive one would start from.

In closing, this work argued that a defense for learning-based intrusion detection is only worth measuring against an attack that can exist on the wire, and it built and evaluated one under that discipline end to end: a shared traffic representation, architecturally heterogeneous detection, and generative purification that returns real, protocol-compliant packets. Within its stated limits, the delivered system detects a realistic black-box manipulation from the first packet and undoes it before the protected system

consumes the flow, and where it fails, it fails for reasons the evaluation identifies rather than hides. That, for a defense meant to be built upon, seemed the right place to leave it.

# Bibliography


[1] R. Boutaba, M. A. Salahuddin, N. Limam, S. Ayoubi, N. Shahriar, F. Estrada-Solano, and O. M. Caicedo, "A comprehensive survey on machine learning for networking: evolution, applications and research opportunities," *Journal of Internet Services and Applications*, vol. 9, no. 1, pp. 16:1–16:99, 2018.

[2] S. Wang, J. F. Balarezo, S. Kandeepan, A. Al-Hourani, K. G. Chavez, and B. Rubinstein, "Machine learning in network anomaly detection: A survey," *IEEE Access*, vol. 9, pp. 152 379–152 396, 2021.

[3] Z. Xu, Y. Wu, S. Wang, J. Gao, T. Qiu, Z. Wang, H. Wan, and X. Zhao, "Deep learning-based intrusion detection systems: A survey," *arXiv preprint arXiv:2504.07839*, 2025.

[4] F. M. Anis, M. AlAbdullatif, S. Aljbli, and M. Hammoudeh, "A survey on the applications of deep learning in network intrusion detection systems to enhance network security," *IEEE Access*, vol. 13, pp. 185 357–185 373, 2025.

[5] C. Szegedy, W. Zaremba, I. Sutskever, J. Bruna, D. Erhan, I. Goodfellow, and R. Fergus, "Intriguing properties of neural networks," in *2nd International Conference on Learning Representations (ICLR 2014)*, 2014.

[6] I. J. Goodfellow, J. Shlens, and C. Szegedy, "Explaining and harnessing adversarial examples," *arXiv preprint arXiv:1412.6572*, 2014.

[7] K. He, D. D. Kim, and M. R. Asghar, "Adversarial machine learning for network intrusion detection systems: A comprehensive survey," *IEEE Communications Surveys & Tutorials*, vol. 25, no. 1, pp. 538–566, 2023.

[8] C. Zhang, X. Costa-Pérez, and P. Patras, "Tiki-Taka: Attacking and defending deep learning-based intrusion detection systems," in *Proceedings of the 2020 ACM SIGSAC conference on cloud computing security workshop*, 2020, pp. 27–39.

[9] F. Pierazzi, F. Pendlebury, J. Cortellazzi, and L. Cavallaro, "Intriguing properties of adversarial ML attacks in the problem space," in *2020 IEEE symposium on security and privacy (SP)*. IEEE, 2020, pp. 1332–1349.

[10] M. J. Hashemi, G. Cusack, and E. Keller, "Towards evaluation of NIDSs in adversarial setting," in *Proceedings of the 3rd ACM CoNEXT Workshop on Big DAta, Machine Learning and Artificial Intelligence for Data Communication Networks*, 2019, pp. 14–21.

[11] N. Papernot, P. McDaniel, I. Goodfellow, S. Jha, Z. B. Celik, and A. Swami, "Practical black-box attacks against machine learning," in *Proceedings of the 2017 ACM on Asia conference on computer and communications security*, 2017, pp. 506–519.

[12] G. Apruzzese, P. Laskov, and J. Schneider, "SoK: Pragmatic assessment of machine learning for network intrusion detection," in *2023 IEEE 8th European Symposium on Security and Privacy (EuroS&P)*. IEEE, 2023, pp. 592–614.

[13] I. d. A. Pissarra, "TANTGen: Transformer-based adversarial network traffic generator," Master's thesis, Instituto Superior Técnico, Universidade de Lisboa, Lisbon, Portugal, 2026, unpublished Master's Thesis.

[14] D. H. Wolpert, "Stacked generalization," *Neural networks*, vol. 5, no. 2, pp. 241–259, 1992.

[15] P. Samangouei, M. Kabkab, and R. Chellappa, "Defense-GAN: Protecting classifiers against adversarial attacks using generative models," in *International Conference on Learning Representations (ICLR)*, 2018.

[16] Y. Mirsky, T. Doitshman, Y. Elovici, and A. Shabtai, "Kitsune: An ensemble of autoencoders for online network intrusion detection," in *Network and Distributed System Security Symposium (NDSS)*, 2018.

[17] "Intrusion detection evaluation dataset (CIC-IDS2017)," [Online]. Available: https://www.unb.ca/cic/datasets/ids-2017.html, accessed: 2025-12-30.

[18] I. Sharafaldin, A. H. Lashkari, S. Hakak, and A. A. Ghorbani, "Developing realistic distributed denial of service (DDoS) attack dataset and taxonomy," in *2019 International Carnahan Conference on Security Technology (ICCST)*. IEEE, 2019, pp. 1–8.

[19] I. H. Sarker, "Deep cybersecurity: a comprehensive overview from neural network and deep learning perspective," *SN Computer Science*, vol. 2, no. 3, p. 154, 2021.

[20] A. Salim, O. Salim, O. M. Khudhur, S. M. Al-Barzinji, and F. M. Jasem, "Feature selection techniques in intrusion detection systems: A review," *Journal of Cybersecurity and Information Management*, vol. 17, no. 2, pp. 97–112, 2026.

[21] S. Ning, K. Nguyen, S. Bagchi, and Y. Park, “The study of feature engineering in machine learning and deep learning for network intrusion detection systems,” in *2024 Silicon Valley Cybersecurity Conference (SVCC)*. IEEE, 2024, pp. 1–5.

[22] J. Holland, P. Schmitt, N. Feamster, and P. Mittal, “New directions in automated traffic analysis,” in *Proceedings of the 2021 ACM SIGSAC Conference on Computer and Communications Security (CCS)*. ACM, 2021, pp. 3366–3383.

[23] W. Wang, M. Zhu, J. Wang, X. Zeng, and Z. Yang, “End-to-end encrypted traffic classification with one-dimensional convolution neural networks,” in *2017 IEEE international conference on intelligence and security informatics (ISI)*. IEEE, 2017, pp. 43–48.

[24] M. Lotfollahi, M. Jafari Siavoshani, R. Shirali Hossein Zade, and M. Saberian, “Deep packet: A novel approach for encrypted traffic classification using deep learning,” *Soft Computing*, vol. 24, no. 3, pp. 1999–2012, 2020.

[25] X. Lin, G. Xiong, G. Gou, Z. Li, J. Shi, and J. Yu, “ET-BERT: A contextualized datagram representation with pre-training transformers for encrypted traffic classification,” in *Proceedings of the ACM Web Conference 2022*, 2022, pp. 633–642.

[26] D. Arp, E. Quiring, F. Pendlebury, A. Warnecke, F. Pierazzi, C. Wressnegger, L. Cavallaro, and K. Rieck, “Dos and don’ts of machine learning in computer security,” in *31st USENIX Security Symposium (USENIX Security 22)*. USENIX Association, 2022, pp. 3971–3988.

[27] L. Breiman, “Random forests,” *Machine Learning*, vol. 45, no. 1, pp. 5–32, 2001.

[28] ——, “Bagging predictors,” *Machine learning*, vol. 24, no. 2, pp. 123–140, 1996.

[29] T. J. Lucas, I. S. De Figueiredo, C. A. C. Tojeiro, A. M. G. De Almeida, R. Scherer, J. R. F. Brega, J. P. Papa, and K. A. P. Da Costa, “A comprehensive survey on ensemble learning-based intrusion detection approaches in computer networks,” *IEEE Access*, vol. 11, pp. 122 638–122 676, 2023.

[30] S. Bai, J. Z. Kolter, and V. Koltun, “An empirical evaluation of generic convolutional and recurrent networks for sequence modeling,” *arXiv preprint arXiv:1803.01271*, 2018.

[31] A. van den Oord, S. Dieleman, H. Zen, K. Simonyan, O. Vinyals, A. Graves, N. Kalchbrenner, A. Senior, and K. Kavukcuoglu, “WaveNet: A generative model for raw audio,” *arXiv preprint arXiv:1609.03499*, 2016.

[32] A. Vaswani, N. Shazeer, N. Parmar, J. Uszkoreit, L. Jones, A. N. Gomez, Ł. Kaiser, and I. Polosukhin, “Attention is all you need,” in *Advances in Neural Information Processing Systems (NeurIPS)*, vol. 30, 2017.

[33] J. Ghadermazi, S. Hore, A. Shah, and N. D. Bastian, "GTAE-IDS: Graph transformer-based autoencoder framework for real-time network intrusion detection," *IEEE Transactions on Information Forensics and Security*, vol. 20, pp. 4026–4041, 2025.

[34] S. Ennaji, F. De Gaspari, D. Hitaj, A. Kbidi, and L. V. Mancini, "Adversarial challenges in network intrusion detection systems: Research insights and future prospects," *IEEE Access*, vol. 13, pp. 148 613–148 645, 2025.

[35] P. Sun, S. Li, J. Xie, H. Xu, Z. Cheng, and R. Yang, "GPMT: Generating practical malicious traffic based on adversarial attacks with little prior knowledge," *Computers & Security*, vol. 130, p. 103257, 2023.

[36] A. Madry, A. Makelov, L. Schmidt, D. Tsipras, and A. Vladu, "Towards deep learning models resistant to adversarial attacks," in *6th International Conference on Learning Representations (ICLR)*, 2018.

[37] N. Alhussien and A. Aleroud, "AdvPurRec: Strengthening network intrusion detection with diffusion model reconstruction against adversarial attacks," in *2024 IEEE 23rd International Conference on Trust, Security and Privacy in Computing and Communications (TrustCom)*. IEEE, 2024, pp. 1638–1646.

[38] X. Li, W. Sun, H. Chen *et al.*, "ADBM: Adversarial diffusion bridge model for reliable adversarial purification," in *International Conference on Learning Representations (ICLR)*, 2025.

[39] N. Papernot, P. McDaniel, X. Wu, S. Jha, and A. Swami, "Distillation as a defense to adversarial perturbations against deep neural networks," in *2016 IEEE Symposium on Security and Privacy (SP)*. IEEE, 2016, pp. 582–597.

[40] J. Cohen, E. Rosenfeld, and Z. Kolter, "Certified adversarial robustness via randomized smoothing," in *International Conference on Machine Learning (ICML)*. PMLR, 2019, pp. 1310–1320.

[41] J. Yan, Z. Liu, Y. Xie, S. Liang, L. Liu, and K. Xu, "CertTA: Certified robustness made practical for learning-based traffic analysis," in *34th USENIX Security Symposium (USENIX Security 25)*. USENIX Association, 2025, pp. 7349–7368.

[42] E. Abad Rocamora, G. G. Chrysos, and V. Cevher, "Certified robustness under bounded Levenshtein distance," in *International Conference on Learning Representations (ICLR)*, 2025.

[43] M. Jin and M. Apostolaki, "Robustifying ML-powered network classifiers with PANTS," in *34th USENIX Security Symposium (USENIX Security 25)*, 2025, pp. 7291–7310.

[44] V. Kumar, K. Kumar, and M. Singh, "NIDS-CBAD: detecting adversarial attacks in network intrusion detection systems using domain constraints," *International Journal of Machine Learning and Cybernetics*, vol. 16, no. 7-8, pp. 4213–4234, 2025.

[45] I. Bibers, O. Arreche, W. Alayed, and M. Abdallah, "Ensemble-IDS: An ensemble learning framework for enhancing AI-based network intrusion detection tasks," *Applied Sciences*, vol. 15, no. 19, p. 10579, 2025.

[46] Y. Freund and R. E. Schapire, "A decision-theoretic generalization of on-line learning and an application to boosting," *Journal of computer and system sciences*, vol. 55, no. 1, pp. 119–139, 1997.

[47] X. Yang, Y. Zhao, and X. Chen, "A novel transformer-based stacking ensemble method with multi-model integration for cancer classification," *PeerJ Computer Science*, vol. 11, p. e3314, 2025.

[48] O. Gungor, T. Rosing, and B. Aksanli, "STEWART: Stacking ensemble for white-box adversarial attacks towards more resilient data-driven predictive maintenance," *Computers in Industry*, vol. 140, p. 103660, 2022.

[49] Z. Yang, L. Li, X. Xu, S. Zuo, Q. Chen, P. Zhou, B. I. P. Rubinstein, C. Zhang, and B. Li, "TRS: Transferability reduced ensemble via promoting gradient diversity and model smoothness," in *Advances in Neural Information Processing Systems (NeurIPS)*, 2021, pp. 17 642–17 655.

[50] B. Biggio, I. Corona, G. Fumera, G. Giacinto, and F. Roli, "Bagging classifiers for fighting poisoning attacks in adversarial classification tasks," in *Multiple Classifier Systems: 10th International Workshop (MCS 2011)*. Springer, 2011, pp. 350–359.

[51] R. Chen, Z. Li, J. Li, J. Yan, and C. Wu, "On collective robustness of bagging against data poisoning," in *International Conference on Machine Learning*. PMLR, 2022, pp. 3299–3319.

[52] A. Athalye, N. Carlini, and D. Wagner, "Obfuscated gradients give a false sense of security: Circumventing defenses to adversarial examples," in *International Conference on Machine Learning (ICML)*. PMLR, 2018, pp. 274–283.

[53] M. Hajizadeh, P. Golchin, E. Nowroozi, M. Rigaki, V. Valeros, S. García, M. Conti, and T. Bauschert, "DeepRed: A deep learning-powered command and control framework for multi-stage red teaming against ML-based network intrusion detection systems," in *19th USENIX WOOT Conference on Offensive Technologies (WOOT 25)*, 2025, pp. 103–127.

[54] P. Kumar, A. S. M. Tayeen, S. Misra, H. Cao, J. Liu, Q. Gong, and J. Harikumar, "NetDiffuser: Deceiving DNN-based network attack detection systems with diffusion-generated adversarial traffic," *arXiv preprint arXiv:2603.08901*, 2026.

[55] F. Croce and M. Hein, “Reliable evaluation of adversarial robustness with an ensemble of diverse parameter-free attacks,” in *Proceedings of the 37th International Conference on Machine Learning (ICML)*, ser. Proceedings of Machine Learning Research, vol. 119, 2020, pp. 2206–2216.

[56] M.-I. Nicolae, M. Sinn, M. N. Tran, B. Buesser, A. Rawat, M. Wistuba, V. Zantedeschi, N. Baracaldo, B. Chen, H. Ludwig, I. M. Molloy, and B. Edwards, “Adversarial robustness toolbox v1.0.0,” arXiv, Tech. Rep. arXiv:1807.01069, 2018.

[57] N. Carlini, A. Athalye, N. Papernot, W. Brendel, J. Rauber, D. Tsipras, I. Goodfellow, A. Madry, and A. Kurakin, “On evaluating adversarial robustness,” arXiv, Tech. Rep. arXiv:1902.06705, 2019.

[58] F. Tramèr, N. Carlini, W. Brendel, and A. Madry, “On adaptive attacks to adversarial example defenses,” in *Advances in Neural Information Processing Systems 33 (NeurIPS)*, 2020, pp. 1633–1645.

[59] B. I. Rubinstein, B. Nelson, L. Huang, A. D. Joseph, S.-h. Lau, S. Rao, N. Taft, and J. D. Tygar, “ANTIDOTE: understanding and defending against poisoning of anomaly detectors,” in *Proceedings of the 9th ACM SIGCOMM Conference on Internet Measurement*, 2009, pp. 1–14.

[60] G. Wan, Z. Shi, W. Huang, G. Zhang, D. Tao, and M. Ye, “Energy-based backdoor defense against federated graph learning,” in *The Thirteenth International Conference on Learning Representations*, 2025.

[61] J. Xu, Z. Zhang, and R. Hu, “Detecting backdoor attacks in federated learning via direction alignment inspection,” in *Proceedings of the Computer Vision and Pattern Recognition Conference*, 2025, pp. 20 654–20 664.

[62] P. Rieger, T. Krauß, M. Miettinen, A. Dmitrienko, and A.-R. Sadeghi, “CrowdGuard: Federated backdoor detection in federated learning,” in *Network and Distributed System Security Symposium (NDSS)*, 2024.

[63] R. Zhu, D. Tang, S. Tang, X. Wang, and H. Tang, “Selective amnesia: On efficient, high-fidelity and blind suppression of backdoor effects in trojaned machine learning models,” in *2023 IEEE Symposium on Security and Privacy (SP)*. IEEE, 2023, pp. 682–700.

[64] K. Kumari, P. Rieger, H. Fereidooni, M. Jadliwala, and A.-R. Sadeghi, “BayBFed: Bayesian backdoor defense for federated learning,” in *2023 IEEE symposium on security and privacy (SP)*. IEEE, 2023, pp. 737–754.

[65] D. T. Nguyen, N. N. Tran, T. T. Johnson, and K. Leach, “PBP: Post-training backdoor purification for malware classifiers,” in *Network and Distributed System Security Symposium (NDSS)*, 2025.

[66] F. Alotaibi and S. Maffeis, “Mateen: Adaptive ensemble learning for network anomaly detection,” in *Proceedings of the 27th International Symposium on Research in Attacks, Intrusions and Defenses*, 2024, pp. 215–234.

[67] M. Zhang, K. Bi, W. Chen, Q. Chen, J. Guo, and X. Cheng, “CausalDiff: Causality-inspired disentanglement via diffusion model for adversarial defense,” *Advances in Neural Information Processing Systems*, vol. 37, pp. 124 791–124 819, 2024.

[68] Z. Li, H. Zhou, M. Rei, and L. Specia, “DiffuseDef: Improved robustness to adversarial attacks via iterative denoising,” in *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, 2025, pp. 9259–9274.

[69] M. A. Merzouk, E. Beurier, R. Yaich, N. Boulahia-Cuppens, F. Cuppens, and F. Khomh, “Diffusion-based adversarial purification for intrusion detection,” in *Data and Applications Security and Privacy XXXIX: 39th Annual IFIP WG 11.3 Conference (DBSec 2025)*. Springer, 2025, pp. 351–370.

[70] O. Olukola and N. Rahimi, “AMDS: Attack-aware multi-stage defense system for network intrusion detection with two-stage adaptive weight learning,” *arXiv preprint arXiv:2603.00859*, 2026.

[71] S. Ren, J. Jin, G. Niu, and Y. Liu, “ARCS: Adaptive reinforcement learning framework for automated cybersecurity incident response strategy optimization,” *Applied Sciences*, vol. 15, no. 2, p. 951, 2025.

[72] G. Wilson, G. Goh, Y. Jiang, A. Gupta, J. Wang, D. Freeman, and F. Dinuzzo, “Predictive response optimization: Using reinforcement learning to fight online social network abuse,” in *34th USENIX Security Symposium (USENIX Security 25)*, 2025, pp. 3239–3256.

[73] W. Qiao, Y. Feng, T. Li, Z. Ma, Y. Shen, J. Ma, and Y. Liu, “Slot: Provenance-driven APT detection through graph reinforcement learning,” in *Proceedings of the 2025 ACM SIGSAC Conference on Computer and Communications Security*, 2025, pp. 963–977.

[74] R. S. Sutton and A. G. Barto, *Reinforcement Learning: An Introduction*, 2nd ed. Cambridge, MA: MIT Press, 2018.

[75] T. T. Nguyen and V. J. Reddi, “Deep reinforcement learning for cyber security,” *IEEE Transactions on Neural Networks and Learning Systems*, vol. 34, no. 8, pp. 3779–3795, 2023.

[76] G. Caminero, M. Lopez-Martin, and B. Carro, “Adversarial environment reinforcement learning algorithm for intrusion detection,” *Computer Networks*, vol. 159, pp. 96–109, 2019.