

# Reliable and Interpretable Artificial Intelligence

## project report

Simone BARBARO, Guillaume WANG

December 2019 (HS2019)

## 1 Zonotope representation and transformation

We represent a zonotope  $Z$  by its center  $a_0 \in R^d$  and a non-negative tensor  $A \in R^{k \times d}$  representing the coefficient of the  $k$  error terms.

Zonotope propagation through the neural network is straightforward using the transformations presented during the course. For convolutional layers, it suffices to apply the convolution to  $A$  itself (excluding bias). The proof is not reproduced here due to space restrictions.

## 2 Loss function

Let  $[o_0, o_2, \dots, o_9]$  be the output layer of the neural network (the logits for the MNIST digit classification). Let  $Z$  be the zonotope region at the output layer, for a given input region, and for given ReLU-transformation parameters  $\lambda$ .

Then the network is verifiably robust on the input region if:

$$\begin{aligned} \forall (o_0, \dots, o_9) \in Z, \forall i \in \{0, \dots, 9\}, o_i &\leq o_t \\ \forall (x_0, \dots, x_9) \in Z', \forall i \in \{0, \dots, 9\}, x_i &\leq 0 \\ \max_{x \in Z'} \max_i x_i &\leq 0 \\ \max_i \max_{x \in Z'_i} x_i &\leq 0 \end{aligned}$$

where  $Z'$  is the zonotope of the "violations"  $[o_0 - o_t, \dots, o_9 - o_t]$ , and  $Z'_i$  is the zonotope of  $o_i - o_t$ .

Since  $Z'_i$  are one-dimensional zonotopes, the innermost max can be computed in  $O(1)$  by assigning all the error terms to the sign of the corresponding coefficients.

Recall that  $Z'_i$  depends on the ReLU-transformation parameters  $\lambda$ . The loss function:

$$L(\lambda) = \max_i \max_{x_i \in Z'_i} x_i$$

can be computed by propagating the input zonotope through the network. The network is verifiably robust if there exists  $\lambda$  such that  $L(\lambda) \leq 0$ .

## 3 Learning lambda

$L(\lambda)$  is differentiable, so we use gradient-based methods to minimize it.