

Chapter 1: Meta-labeling

Guillermo Creus

HKUST - UPC

6th November 2020

Imagine you were dealing with a financial time series and you wanted to predict the **side** (long/short or pass) and **size** of your investment. If the explanatory variables of **side** are different, then meta-labeling is useful:

Primary Model (M1)

- Labels: $y_{M1} \in \{-1, 1\}$. A positive is understood as the model telling you to open a position.

Secondary Model (M2)

Its main function is to decide if a positive from the primary model is a true positive (i.e. whether to trade with the side of M1)

- Features: \hat{y}_{M1} and same or different set of features than model 1.
- Labels: $y_{M2} = 1$ if $\hat{y}_{M1} = y_{M1}$, 0 otherwise.
- **TP**: profitable investment, **FP**: losing investment, **TN**: M2 predicts correctly that M1 was wrong, **FN**: M2 predicts M1 was wrong when the latter was right.

Toy Project

The main idea of this project was to determine how meta-labeling works with synthetic data. In this case, 5 features have been used: $\mathbf{X}_{\cdot,1}$, $\mathbf{X}_{\cdot,2}$ (M1) and $\mathbf{X}_{\cdot,3}$, $\mathbf{X}_{\cdot,4}$, $\mathbf{X}_{\cdot,5}$ (M2).

- $\mathbf{X}_{k,i} \sim N(\mu_i, \sigma^2)$
- $\omega_k = \text{sigmoid} \left(\alpha + \sum_{i=1}^5 \mathbf{X}_{k,i} \cdot \beta_i + \epsilon_k \right)$ where $\epsilon_k \sim N(0, \sigma_\epsilon^2)$ and $\text{sigmoid}(z) = \frac{1}{1+e^{-z}}$

The labels are defined as:

$$y_k^{\text{M1}} = \begin{cases} -1 & \text{if } \omega_k < 0.5 \\ 1 & \text{otherwise} \end{cases}$$

Toy Project

Definition of Models

Primary Model

- **Features:** $\mathbf{X}_1, \mathbf{X}_2$
- **Labels:** y^{M1}
- **Model:** Neural Network (1 layer) for Binary Classification

Secondary Model

- **Features:** $\mathbf{X}_3, \mathbf{X}_4, \mathbf{X}_5, \hat{y}^{M1}$
- **Labels:** y^{M2}
$$y_k^{M2} = \begin{cases} 1 & \text{if } \hat{y}_k^{M1} = y^{M1} = -1 \text{ or } \hat{y}_k^{M1} = y^{M1} = 1 \\ 0 & \text{otherwise} \end{cases}$$
- **Model:** Neural Network (1 hidden layer - Leaky ReLU) for Binary Classification

Toy Project

Results

Primary Model

		Prediction outcome		Total
		1	0	
Actual value	1	TP 115	FN 0	115
	0	FP 85	TN 0	85
Total		200	0	


Secondary Model

		Prediction outcome		Total
		1	0	
Actual value	1	TP 105	FN 10	115
	0	FP 49	TN 36	85
Total		154	46	

Remember that Actual Value = 1 \Rightarrow Trade and Actual Value = 0 \Rightarrow Don't trade

Toy Project

Metrics



The high recall of the Primary Model brought many False Positives which have been corrected in the Meta Model (Primary + Secondary Model). That is why the F1-Score of the Meta Model is higher.

Labeling in financial time series

Triple Barrier Method

- **Horizontal barriers:** Dynamic levels that depend on the 10 day rolling volatility and the price at the first day considered. They can be symmetric or not.
- **Vertical barrier:** Set as a fixed time horizon. In this case, 10 days.



Figure: Symmetrical horizontal barriers




Figure: Non-symmetrical horizontal barriers (Side = -1)

Triple Barrier Method

Noting t_{hit} , t_{start} as the time the barriers start and get hit, respectively, the realized return can be computed as:



$$r_k = \left(\frac{p_{t_{\text{hit}}}}{p_{t_{\text{start}}}} - 1 \right) \cdot \mathbf{signal}_{t_{\text{start}}}$$

Combining everything, the observations are labeled as:

$$y_k = \begin{cases} 1 & \text{if } r_k > 0 \\ 0 & \text{otherwise} \end{cases}$$

Results

Moving Average (MA) & ML Models



Model	Max. Drawdown (Test)	SR (Test)
B&H	15.20%	0.9682
M1	34.41%	-0.7467
MM	5.02%	0.4887

Model	Max. Drawdown (Test)	SR (Test)
B&H	15.20%	0.9682
M1	16.66%	0.7069
MM	14.57%	0.7302