

Ejercicio 5 - API'S

The screenshot displays the Postman application interface. The top bar shows the user 'Guillermo Simón Villanueva Rold...' and the workspace 'API Network'. The main area is divided into a left sidebar with 'Collections' and 'My Collection', and a central workspace. The workspace shows a GET request to the URL 'http://127.0.0.1:8000/tiendas/domicilio/Calle%20Falsa%20123'. The request is saved and has a 'Send' button. Below the URL bar, the 'Query Params' section is empty. The 'Body' tab is selected, showing a JSON response with a status of '200 OK', a response time of '18 ms', and a size of '211 B'. The JSON response is as follows:

```
1 [
2   {
3     "id": 1,
4     "domicilio": "Calle Falsa 123",
5     "telefono": 123456789,
6     "precio_alquiler": 1500.0
7   }
8 ]
```

The bottom status bar includes options for 'Online', 'Find and replace', 'Console', 'Runner', 'Start Proxy', 'Cookies', 'Vault', 'Trash', and a help icon.

API Network

GET http://127.0.0.1:8000/tiendas

Params Authorization Headers (6) Body Scripts Settings

Query Params

Key	Value	Description
Key	Value	Description

Body Cookies Headers (4) Test Results

200 OK - 6 ms - 812 B

```
{
  "id": 1,
  "domicilio": "Avenida Siempre Viva 742",
  "telefono": 987654321,
  "precio_alquiler": 2000.0
},
{
  "id": 2,
  "domicilio": "Plaza Mayor 1",
  "telefono": 856666777,
  "precio_alquiler": 1800.0
},
{
  "id": 3,
  "domicilio": "Calle Luna 45",
  "telefono": 445555666,
  "precio_alquiler": 1600.0
},
{
  "id": 4,
  "domicilio": "Calle Sol 67",
  "telefono": 334444555,
  "precio_alquiler": 2200.0
},
{
  "id": 5,
  "domicilio": "Avenida del Mar 89",
  "telefono": 22333444,
  "precio_alquiler": 3000.0
}
```

Activar Windows
Ve a Configuración para activar Windows.

API Network

GET http://127.0.0.1:8000/tiendas/precio_alquiler/2000.0

Params Authorization Headers (6) Body Scripts Settings

Query Params

Key	Value	Description
Key	Value	Description

Body Cookies Headers (4) Test Results

200 OK - 6 ms - 478 B

```
[
  {
    "id": 1,
    "domicilio": "Calle Falsa 123",
    "telefono": 123456789,
    "precio_alquiler": 1500.0
  },
  {
    "id": 2,
    "domicilio": "Avenida Siempre Viva 742",
    "telefono": 987654321,
    "precio_alquiler": 2000.0
  },
  {
    "id": 4,
    "domicilio": "Calle Luna 45",
    "telefono": 445555666,
    "precio_alquiler": 1800.0
  },
  {
    "id": 7,
    "domicilio": "Calle Montaña 18",
    "telefono": 111222333,
    "precio_alquiler": 1600.0
  }
]
```

Activar Windows
Ve a Configuración para activar Windows.

Postman interface showing a GET request to `http://127.0.0.1:8000/tiendas/id/1`. The response is a 200 OK status with a JSON body:

```
{
  "id": 1,
  "domicilio": "Calle Falsa 123",
  "telefono": 123456789,
  "precio_alquiler": 1500.0
}
```

The interface includes a sidebar with Collections, Environments, Flows, and History. The main panel shows the request details, including Headers (6), Body, and Test Results.

Postman interface showing a GET request to `http://127.0.0.1:8000/tiendas/telefono/123456789`. The response is a 200 OK status with a JSON body:

```
{
  "id": 1,
  "domicilio": "Calle Falsa 123",
  "telefono": 123456789,
  "precio_alquiler": 1500.0
}
```

The interface includes a sidebar with Collections, Environments, Flows, and History. The main panel shows the request details, including Headers (6), Body, and Test Results.

Activar Windows
Ve a Configuración para activar Windows.