

Diagram and Data Dictionary

Internal database structure of the Data Management Portal

Generated on: 06/08/2026

Tables: 20 Columns: 228

1. How to read this document

Every table is created by migrate() in backend/db.php, idempotently. The real name carries the configured prefix (default gdt).

No FOREIGN KEYs — integrity is enforced in application code, keeping the schema portable across MySQL, PostgreSQL, SQL Server and SQLite.

2. Overview

Accounts, session and security

Table	Cols	Description
usuarios	18	Portal accounts.
usuarios_foto	3	Profile photo, separate table.
tentativas_login	7	Failed login counters.
tokens_revogados	2	Tokens invalidated before expiry.
mfa_codigos	9	Verification codes (HMAC only).
auditoria_log	9	Audit trail.

Governance modules

Table	Cols	Description
bancos	14	Central database registry.
acessos	17	Inventory of access to databases and systems.
mudancas	16	Log of structural changes.
mudancas_objetos	5	Objects affected by each change.
backup_politicas	14	Backup policy per database.
restore_testes	11	Restore tests.
dicionario_dados	15	Business dictionary of columns.
integracoes	22	Integrations between systems.
jobs	17	Scheduled routines.
inventario	18	Inventory of applications and DBMS installed on servers, with version, patch and end of support.

Configuration and administration

Table	Cols	Description
config_tipos	4	Editable form lists.
config_email	10	SMTP settings (password in AES-256-GCM).
config_projeto	5	Portal identity and retention.
certificacoes	12	Access Certification history: summary of each cross-check between a database real permissions and what is registered in Acessos. Does not store the raw CSV -- only counters and the exceptions list.

3. Dictionary

usuários

Portal accounts.

Column	Type	Description
id	integer, primary key, auto-increment	Unique identifier.
username	VARCHAR(50) NOT NULL UNIQUE	Portal login.
nome_completo	VARCHAR(120)	Display name.
password_hash	VARCHAR(255) NOT NULL	bcrypt password.
role	VARCHAR(20) NOT NULL DEFAULT 'leitura'	Role: leitura, escrita, admin, master.
criado_em	date and time	Creation date.
atualizado_em	date and time	Last change.
modulos_permitidos	long text (TEXT / NVARCHAR(MAX))	Allowed modules, comma separated.
email	VARCHAR(150)	E-mail.
login_rede	VARCHAR(150)	Network login (AD/domain).
departamento	VARCHAR(120)	Department.
funcao	VARCHAR(120)	Role/position.
mfa_ativo	INT NOT NULL DEFAULT 0	1 = two-step on.
cor_tema	VARCHAR(20) NOT NULL DEFAULT 'padrao'	User palette.
estilo_side	VARCHAR(20) NOT NULL DEFAULT 'claro'	Sidebar look.
ativo	INT NOT NULL DEFAULT 1	0 disables the account.
must_change_password	INT NOT NULL DEFAULT 0	1 forces password change.
tokens_valid_after	date and time	Mass revocation cutoff.

usuários_foto

Profile photo, separate table.

Column	Type	Description
usuario_id	INT NOT NULL PRIMARY KEY	Photo owner (PK).
foto	very long text (MEDIUMTEXT on MySQL)	Image as data URI.
atualizado_em	date and time	Last change.

tentativas_login

Failed login counters.

Column	Type	Description
id	integer, primary key, auto-increment	Unique identifier.
usuario	VARCHAR(150) NOT NULL	Related login.
ip	VARCHAR(45) NOT NULL	Source IP.
tentativas	INT NOT NULL DEFAULT 0	Attempts (max 5).
primeira_tentativa	date and time	Module field.
ultima_tentativa	date and time	Module field.
bloqueado_ate	date and time	Module field.

tokens_revogados

Tokens invalidated before expiry.

Column	Type	Description
jti	VARCHAR(64) NOT NULL PRIMARY KEY	Revoked token.
expira_em	date and time	Code validity.

mfa_codigos

Verification codes (HMAC only).

Column	Type	Description
id	integer, primary key, auto-increment	Unique identifier.
usuario	VARCHAR(150) NOT NULL	Related login.
token	VARCHAR(64) NOT NULL	Verification token.
codigo_hash	VARCHAR(64) NOT NULL	HMAC of "token code".
tentativas	INT NOT NULL DEFAULT 0	Attempts (max 5).
expira_em	date and time	Code validity.
criado_em	date and time	Creation date.
reenvios	INT NOT NULL DEFAULT 0	Module field.
ultimo_reenvio	DATETIME	Module field.

auditoria_log

Audit trail.

Column	Type	Description
id	integer, primary key, auto-increment	Unique identifier.
tabela	VARCHAR(60) NOT NULL	Table.
registro_id	INT	Module field.
acao	VARCHAR(40) NOT NULL	Module field.
usuario	VARCHAR(150)	Related login.
dados_antes	long text (TEXT / NVARCHAR(MAX))	Module field.
dados_depois	long text (TEXT / NVARCHAR(MAX))	Module field.
ip	VARCHAR(45)	Source IP.
criado_em	date and time	Creation date.

bancos

Central database registry.

Column	Type	Description
id	integer, primary key, auto-increment	Unique identifier.
nome	VARCHAR(150) NOT NULL	Record name.
servidor	VARCHAR(150)	Server hostname.
motor	VARCHAR(40)	Database engine.
ambiente	VARCHAR(40)	Environment.
host	VARCHAR(200)	IPv4 address.
porta	VARCHAR(10)	IPv4 port.
ipv6	VARCHAR(200)	IPv6 address.
porta_ipv6	VARCHAR(10)	IPv6 port.
responsavel	VARCHAR(150)	Responsible.
obs	long text (TEXT / NVARCHAR(MAX))	Notes.
criado_por	VARCHAR(150)	Login of the creator (server).
criado_em	date and time	Creation date.
atualizado_em	date and time	Last change.

acessos

Inventory of access to databases and systems.

Column	Type	Description
id	integer, primary key, auto-increment	Unique identifier.
data	DATE	Module field.
usuario	VARCHAR(150)	Related login.
tipo	VARCHAR(50)	Classification.
objeto	VARCHAR(200)	Database (from the Bancos registry).
nivel	VARCHAR(100)	Module field.
justificativa	long text (TEXT / NVARCHAR(MAX))	Module field.
solicitante	VARCHAR(150)	Module field.
aprovador	VARCHAR(150)	Module field.
revisao	DATE	Module field.
status	VARCHAR(30) DEFAULT 'Ativo'	Status (from Registry).
obs	long text (TEXT / NVARCHAR(MAX))	Notes.
criado_em	date and time	Creation date.
atualizado_em	date and time	Last change.
servidor	VARCHAR(150)	Server hostname.
natureza	VARCHAR(20)	Account nature: User or Service.
criado_por	VARCHAR(150)	Login of the creator (server).

mudancas

Log of structural changes.

Column	Type	Description
id	integer, primary key, auto-increment	Unique identifier.
codigo	VARCHAR(30)	Module field.
data	DATE	Module field.
ambiente	VARCHAR(30)	Environment.
tipo	VARCHAR(50)	Classification.
descricao	long text (TEXT / NVARCHAR(MAX))	Free-text description.
script	VARCHAR(200)	Module field.
rollback	long text (TEXT / NVARCHAR(MAX))	Module field.
solicitante	VARCHAR(150)	Module field.
aprovador	VARCHAR(150)	Module field.
status	VARCHAR(30)	Status (from Registry).
resultado	long text (TEXT / NVARCHAR(MAX))	Module field.
criado_em	date and time	Creation date.
atualizado_em	date and time	Last change.
criado_por	VARCHAR(150)	Login of the creator (server).
bancos	long text (TEXT / NVARCHAR(MAX))	Affected databases (multiple, comma separated).

mudancas_objetos

Objects affected by each change.

Column	Type	Description
id	integer, primary key, auto-increment	Unique identifier.
mudanca_id	INT NOT NULL	Module field.
nome	VARCHAR(200) NOT NULL	Record name.
tipo	VARCHAR(50)	Classification.
criado_em	date and time	Creation date.

backup_politicas

Backup policy per database.

Column	Type	Description
id	integer, primary key, auto-increment	Unique identifier.
banco	VARCHAR(150)	Related database.
criticidade	VARCHAR(30)	Criticality (from Registry).
tipo	VARCHAR(50)	Classification.
frequencia	VARCHAR(100)	Frequency.
horario	VARCHAR(50)	Frequency time.
retencao	VARCHAR(100)	Module field.
local	VARCHAR(250)	Module field.
rpo	VARCHAR(50)	Module field.
rto	VARCHAR(50)	Module field.
responsavel	VARCHAR(150)	Responsible.
criado_em	date and time	Creation date.
atualizado_em	date and time	Last change.
criado_por	VARCHAR(150)	Login of the creator (server).

restore_testes

Restore tests.

Column	Type	Description
id	integer, primary key, auto-increment	Unique identifier.
data	DATE	Module field.
banco	VARCHAR(150)	Related database.
backup	VARCHAR(150)	Module field.
tempo	VARCHAR(50)	Module field.
resultado	VARCHAR(30)	Module field.
por	VARCHAR(150)	Module field.
obs	long text (TEXT / NVARCHAR(MAX))	Notes.
criado_em	date and time	Creation date.
atualizado_em	date and time	Last change.
criado_por	VARCHAR(150)	Login of the creator (server).

dicionario_dados

Business dictionary of columns.

Column	Type	Description
id	integer, primary key, auto-increment	Unique identifier.
banco	VARCHAR(150)	Related database.
schema_nome	VARCHAR(150)	Table schema.
tabela	VARCHAR(150)	Table.
coluna	VARCHAR(150)	Column.
tipo_dado	VARCHAR(100)	Module field.
permite_nulo	VARCHAR(10)	Module field.
descricao	long text (TEXT / NVARCHAR(MAX))	Free-text description.
classificacao	VARCHAR(50)	Module field.
origem	VARCHAR(150)	Module field.
obs	long text (TEXT / NVARCHAR(MAX))	Notes.
criado_em	date and time	Creation date.
atualizado_em	date and time	Last change.
servidor	VARCHAR(150)	Server hostname.
criado_por	VARCHAR(150)	Login of the creator (server).

integracoes

Integrations between systems.

Column	Type	Description
id	integer, primary key, auto-increment	Unique identifier.
nome	VARCHAR(200)	Record name.
origem	VARCHAR(150)	Module field.
ip_origem	VARCHAR(45)	Module field.
destino	VARCHAR(150)	Module field.
ip_destino	VARCHAR(45)	Module field.
tipo	VARCHAR(60)	Classification.
direcao	VARCHAR(30)	Module field.
mecanismo	VARCHAR(150)	Module field.
frequencia	VARCHAR(30)	Frequency.
dados_trafegados	long text (TEXT / NVARCHAR(MAX))	Module field.
classificacao	VARCHAR(50)	Module field.
criticidade	VARCHAR(30)	Criticality (from Registry).
resp_tecnico	VARCHAR(150)	Module field.
resp_negocio	VARCHAR(150)	Module field.
ambiente	VARCHAR(30)	Environment.
status	VARCHAR(30)	Status (from Registry).
ultima_revisao	DATE	Module field.
obs	long text (TEXT / NVARCHAR(MAX))	Notes.
criado_em	date and time	Creation date.
atualizado_em	date and time	Last change.
criado_por	VARCHAR(150)	Login of the creator (server).

jobs

Scheduled routines.

Column	Type	Description
id	integer, primary key, auto-increment	Unique identifier.
nome	VARCHAR(200)	Record name.
tipo	VARCHAR(60)	Classification.
servidor	VARCHAR(150)	Server hostname.
banco	VARCHAR(150)	Related database.
descricao	long text (TEXT / NVARCHAR(MAX))	Free-text description.
comando	long text (TEXT / NVARCHAR(MAX))	Job steps as JSON.
frequencia	VARCHAR(60)	Frequency.
horario	VARCHAR(60)	Frequency time.
agendamentos	long text (TEXT / NVARCHAR(MAX))	Windows (start/end) as JSON.
criticidade	VARCHAR(30)	Criticality (from Registry).
status	VARCHAR(30)	Status (from Registry).
responsavel	VARCHAR(150)	Responsible.
obs	long text (TEXT / NVARCHAR(MAX))	Notes.
criado_por	VARCHAR(150)	Login of the creator (server).
criado_em	date and time	Creation date.
atualizado_em	date and time	Last change.

inventario

Inventory of applications and DBMS installed on servers, with version, patch and end of support.

Column	Type	Description
id	integer, primary key, auto-increment	Unique identifier.
nome	VARCHAR(200)	Application / DBMS.
banco	VARCHAR(150)	Related database.
servidor	VARCHAR(150)	Server hostname.
categoria	VARCHAR(60)	Category (from Registry).
fabricante	VARCHAR(150)	Vendor.
versao	VARCHAR(100)	Installed version.
edicao	VARCHAR(100)	Edition (Enterprise, Standard...).
patch_atual	VARCHAR(150)	Current service pack / patch.
data_instalacao	DATE	Install date.
fim_suporte	DATE	Vendor end of support.
status	VARCHAR(40)	Status (from Registry).
historico_patches	long text (TEXT / NVARCHAR(MAX))	Patch history as JSON (date, type, version, ticket, installed by).
responsavel	VARCHAR(150)	Responsible.
obs	long text (TEXT / NVARCHAR(MAX))	Notes.
criado_por	VARCHAR(150)	Login of the creator (server).
criado_em	date and time	Creation date.
atualizado_em	date and time	Last change.

config_tipos

Editable form lists.

Column	Type	Description
id	integer, primary key, auto-increment	Unique identifier.
categoria	VARCHAR(40) NOT NULL	Module field.
nome	VARCHAR(120) NOT NULL	Record name.
criado_em	date and time	Creation date.

config_email

SMTP settings (password in AES-256-GCM).

Column	Type	Description
id	integer, primary key, auto-increment	Unique identifier.
host	VARCHAR(150)	IPv4 address.
porta	INT	IPv4 port.
seguranca	VARCHAR(10) DEFAULT 'tls'	Module field.
usuario	VARCHAR(150)	Related login.
senha_cifrada	long text (TEXT / NVARCHAR(MAX))	Module field.
remetente_nome	VARCHAR(120)	Module field.
remetente_email	VARCHAR(150)	Module field.
testado_ok	INT NOT NULL DEFAULT 0	1 after a send test.
atualizado_em	date and time	Last change.

config_projeto

Portal identity and retention.

Column	Type	Description
id	integer, primary key, auto-increment	Unique identifier.
nome_projeto	VARCHAR(160)	Module field.
logo_data	very long text (MEDIUMTEXT on MySQL)	Logo as data URI (MEDIUMTEXT on MySQL).
atualizado_em	date and time	Last change.
timeout_inatividade_min	INT NOT NULL DEFAULT 30	Minutes until session ends.

certificacoes

Access Certification history: summary of each cross-check between a database real permissions and what is registered in Acessos. Does not store the raw CSV -- only counters and the exceptions list.

Column	Type	Description
id	integer, primary key, auto-increment	Unique identifier.
banco	VARCHAR(150)	Related database.
servidor	VARCHAR(150)	Server hostname.
motor	VARCHAR(40)	Database engine.
periodo	VARCHAR(80)	Certification reference period (e.g., 2nd half 2026).
executor	VARCHAR(150)	Login of who ran the certification.
usuarios_banco	INT NOT NULL DEFAULT 0	Number of users found in the database.
conformidade	INT NOT NULL DEFAULT 0	Permissions matching on both sides.
nao_documentados	INT NOT NULL DEFAULT 0	Access in the database with no record in the portal.
defasados	INT NOT NULL DEFAULT 0	Records in the portal missing in the database.
excecoes	long text (TEXT / NVARCHAR(MAX))	Exception lists (undocumented and outdated) as JSON.
criado_em	date and time	Creation date.

4. Relationships

From	To	Rule
acessos.objeto / servidor	bancos.nome / servidor	Bank picked from the registry fills both.
mudancas.bancos	bancos.nome	Databases affected, comma separated.
inventario.banco / servidor	bancos.nome / servidor	Application linked to the registered database.
certificacoes.banco / servidor	bancos.nome / servidor	Certified database (snapshot at run time).
usuarios_foto.usuario_id	usuarios.id	One photo per user; removed with the user.
auditoria_log.usuario	usuarios.username	By login, so the trail survives deletion.