

API Manual

Reference of the HTTP routes of the Data Management Portal

Generated on: 28/07/2026

Base: /api

Authentication: JWT HS256 (Bearer)

1. Fundamentals

Every route lives under /api. Works in a subfolder. Bodies and responses are JSON; errors carry the message in erro.

```
{ "erro": "Usuario ou senha invalidos." }
```

Authentication

Login returns a JWT token that accompanies the other calls:

```
Authorization: Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJIUzI1NiJ9...
```

Roles

Role	Can do
leitura	Read the allowed modules.
escrita	Read and maintain records.
admin	Plus users, lists and configuration.
master	Plus audit and actions on another master.

2. Session and account

POST /auth/login

Access: public

Authenticates and returns the token. With two-step verification, e-mails a code and returns a temporary token.

Request

```
{ "usuario": "admin", "senha": "SenhaForte1" }
```

Response

```
{
  "token": "eyJ0...",
  "usuario": { "id": 1, "username": "admin", "role": "master" }
}
```

GET /auth/me

Access: authenticated

Data of the current account, including whether it has a photo.

Response

```
{ "id": 1, "username": "admin", "role": "master", "tem_foto": true }
```

3. Users

POST /usuarios

Access: admin

Creates a user. Besides login, name, e-mail and role, it accepts the organizational data network login, department and position. A blank password generates a temporary one with a change on first sign-in.

Request

```
{
  "username": "bdias",
  "nome_completo": "Bruno Dias",
  "email": "bruno.dias@empresa.com",
  "login_rede": "CORP\\bdias",
  "departamento": "TI - Banco de Dados",
  "funcao": "DBA Pleno",
  "role": "leitura",
  "modulos": ["acessos", "bancos"]
}
```

Response

```
{ "id": 7 }
```

The bulk user import (Users screen > Import) uses this same route, one call per CSV row, with the Leitura role and no modules.

PUT /usuarios/{id}

Access: admin

Updates the account. Absent fields stay unchanged; network login, department and position can be cleared by sending an empty value.

Request

```
{ "departamento": "Infraestrutura", "funcao": "DBA Senior" }
```

Response

```
{ "id": 7, "username": "bdias" }
```

4. Databases and governance modules

The modules share the same set of routes, only the name in the path changes. Available: acessos, bancos, mudancas, backup, restore, dicionario, integracoes, jobs.

Route	Does
GET /{modulo}	Lists, with search and pagination.
POST /{modulo}	Creates a record.
PUT /{modulo}/{id}	Updates a record.
DELETE /{modulo}/{id}	Removes a record.

POST /bancos

Access: write access to the module

Registers a database, unique by server (hostname) + name. host/porta are the IPv4; ipv6/porta_ipv6 the IPv6.

Request

```
{
  "nome": "SOMA",
  "servidor": "SRV-SOMADB",
  "motor": "SQL Server",
  "host": "10.0.0.5",
  "porta": "1433",
  "ipv6": "2001:db8::5",
  "porta_ipv6": "1433"
}
```

Response

```
{ "id": 3 }
```

5. Configuration and support

Route	Access	Does
GET /dashboard/stats	authenticated	Home screen figures.
GET /tipos	authenticated	Cadastro lists.
GET /config/projeto	authenticated	Name, logo and session.
GET /auditoria	master	Audit trail.
GET /documentacao/api	authenticated	This manual as PDF.

The documentation routes have an English version with the -en suffix.