


Textures



Where we Are



Textured Sphere



Textures

- A texture is an image painted on a surface
 - reduces geometric complexity of object
 - requires more complex processing
- Textures are made of texels
 - need to specify texel for each point
 - a mapping from the surface to the image



Surface Parametrization

- Images are parametrized
 - each texel has an (i,j) location in texture
- Surfaces can also be parametrized
 - each point on surface has (s,t) location
- So the mapping converts from (s,t) to (i,j)




Texture Steps

- Start with a point p
- Convert to surface parameters (s,t)
- Convert to texel indices (i,j)
- Retrieve texel colour
- Use texel colour for shading



Parametric Sphere



COMP 30020: Intro Computer Graphics

Computing Parameters

- Given point (x,y,z) on sphere
 - Find parameters (Φ,θ) on surface
 - Then find texel coordinates



Computing Parameters

$$x = r \cos \phi \cos \theta$$

$$y = r \cos \phi \sin \theta$$

$$\frac{y}{x} = \frac{r \cos \phi \sin \theta}{r \cos \phi \cos \theta} = \frac{\sin \theta}{\cos \theta} = \tan \theta$$

so:

$$\theta = \arctan \frac{y}{x} \quad \left(\text{Use C function } \text{atan2}(y, x) \right)$$

And:

$$z = r \sin \phi$$


so

$$\phi = \arcsin \frac{z}{r}$$




Cylindrical Projection


- Simplest map projection: lat. vs. long.



From Map to Globe



Code in your Assignment 3




Texture Coordinates

Assume that texture has height h , width w

Point	(ϕ, θ)	(s, t)	(i, j)
Top Left	$(\frac{\pi}{2}, -\pi)$	$(1, 0)$	$(h, 0)$
Top Right	$(\frac{\pi}{2}, \pi)$	$(1, 1)$	(h, w)
Bottom Left	$(-\frac{\pi}{2}, -\pi)$	$(0, 0)$	$(0, 0)$
Bottom Right	$(-\frac{\pi}{2}, \pi)$	$(0, 1)$	$(0, w)$

$\frac{\pi}{2} / 1 / h$



$-\frac{\pi}{2} / 0 / 0$

$-\pi / 0 / 0$

$\pi / 1 / w$

We can compute (i, j) as follows:

$$s = \frac{(\theta + \pi)}{2\pi} = \frac{\theta}{2\pi} + \frac{1}{2} \quad i = h \cdot s = h \left(\frac{\theta}{2\pi} + \frac{1}{2} \right)$$

$$t = \frac{(\phi + \frac{\pi}{2})}{\pi} = \frac{\phi}{\pi} + \frac{1}{2} \quad j = w \cdot t = w \left(\frac{\phi}{\pi} + \frac{1}{2} \right)$$



Problems

- This works very well if:
 - i & j are both integers
 - s & t are in range $[0..1]$
- So we need to deal with
 - interpolation - non-integer i, j
 - clamping / repeating - s, t outside range




Clamping

- Texture coordinates are 0 ... 1
- For other values, we clamp or we repeat:
 - clamp coords to 0 ... 1 (use edge pixels)
 - repeat texture (duplicates textures)
- Set separately for horizontal & vertical



Clamping Example

- Horizontal clamp
- Vertical repeat



Interpolation

- Texture coordinates are rarely exact
 - land between the texels (texture pixels)
- So interpolate texel values:
 - nearest neighbour
 - bilinear interpolation
 - trilinear interpolation




Nearest Neighbour

- Simplest form of interpolation:
 - take the nearest available texel
 - e.g. $(2.5, 1.38765)$ maps to $(3, 1)$
 - preserves sharp edges
 - good for geometric patterns




Bilinear Interpolation

- Texels are arranged on a square grid
- We want to interpolate at (i,j)
- Based on the 4 nearest grid points
- Linear interpolation in s then t



Development



$$f(i, [j]) = (1 - \Delta i) f([i], [j]) + \Delta i f([i] + 1, [j])$$

$$f(i, [j] + 1) = (1 - \Delta i) f([i], [j] + 1) + \Delta i f([i] + 1, [j] + 1)$$

$$f(i, j) = (1 - \Delta j) f(i, [j]) + \Delta j f(i, [j] + 1)$$

Pseudo Code

```
RGBValue BilinearLookup(Image tex, float s, float t)
{ // BilinearLookup()
    int i = s;                // truncates s to get i
    int j = t;                // truncates t to get j
    float sParm = s - i;      // compute s parameter for interpolation
    float tParm = t - j;      // compute t parameter for interpolation


    // grab four nearest texel colours
    RGBValue colour00 = tex[i][j];
    RGBValue colour01 = tex[i][j+1];
    RGBValue colour10 = tex[i+1][j];
    RGBValue colour11 = tex[i+1][j+1];

    // compute colours on edges
    RGBValue colour0 = colour00 + tParm * (colour01 - colour00);
    RGBValue colour1 = colour10 + tParm * (colour11 - colour10);

    // compute colour for interpolated texel
    return colour1 + sParm * (colour1 - colour0);
} // BilinearLookup()
```



Geometric Texture




Nearest
Neighbour

Bilinear


COMP 30020: Intro Computer Graphics



Non-Geometric Texture



Nearest
Neighbour



Bilinear



Texture Modulation

- Colour can be used with or without lighting
 - Texture can replace lighting calculation

$$Colour_{out} = Colour_{texture}$$

- Or it can modulate lighting calculation

$$Colour_{out} = Colour_{texture} \cdot Colour_{shading}$$

- Surface colour usually white for this



Texture Mode



Replace



Modulate

Texture Operations

- *Input* from file to RAM to VRAM
- *Pixel Operations:*
 - *scaling, biasing, & mapping*
 - *clamping*
 - *rasterization*
- *Readback*



Image Coordinates

- OpenGL indexes texels with $[0..1]$
 - assumes image size is $2^m \times 2^n$
 - actually allows 1, 2, or 3 texture coords
- Surface parameters don't always match
 - so OpenGL has a *texture* matrix
 - for transforming texture coordinates
 - defaults to the identity matrix



Specifying Parameters

- Give surface parameters for each vertex
 - `glTexCoord2f()`;
- Then interpolate between vertices
 - using barycentric coordinates
 - generates parameters for each pixel



Setting the Texture

- Using LWJGL & OpenGL state applies as usual

myTexture.bind();


```
GL11.glBegin(GL11.GL_QUADS);  
    GL11.glTexCoord2f(0,0); // odd bug , sometimes not needed  
    GL11.glVertex2f(100,100);  
    GL11.glTexCoord2f(1,0);  
    GL11.glVertex2f(100+texture.getTextureWidth(),100);  
    GL11.glTexCoord2f(1,1);  
    GL11.glVertex2f(100+texture.getTextureWidth(),100+texture.getTextureHeight());  
    GL11.glTexCoord2f(0,1);  
    GL11.glVertex2f(100,100+texture.getTextureHeight());  
GL11 glEnd();
```



Texture Clamping

- Horizontal clamp
- Vertical repeat

```
GL11.glTexParameteri(  
    GL11.GL_TEXTURE_2D,  
    GL11.GL_TEXTURE_WRAP_S,  
    GL11.GL_CLAMP);  
GL11.glTexParameteri(  
    GL11.GL_TEXTURE_2D,  
    GL11.GL_TEXTURE_WRAP_T,  
    GL11.GL_REPEAT);
```




Interpolation

- Texture coordinates are rarely exact
 - land *between* the *texels* (texture pixels)
- So *interpolate* texel values:
 - GL_NEAREST (best if geometric tex.)
 - GL_LINEAR (best if organic tex.)
- GL_MAG_FILTER: for magnification
- GL_MIN_FILTER: for “minification”



GL_MAG_FILTER



GL_NEAREST GL_LINEAR

COMP 30020: Intro Computer Graphics