TextConsistency: Parameter-Free Probability Fusion of Learned Prompts and Class Descriptions for Base-to-Novel Recognition

Author Name[a,*], Advisor Name[a]

[a]*School of XXX, XXX University, XXX Street, XXX, 000000, China*

Abstract

Prompt learning efficiently adapts vision-language models to downstream recognition tasks, but prompts trained on base classes can lose part of the semantic coverage inherited from the frozen model. We study a simple way to recover this coverage without adding trainable parameters. TextConsistency combines the posterior produced by a CoOp prompt with a second posterior obtained from frozen, class-specific natural-language descriptions. Description embeddings are averaged within each class, both branches share the frozen CLIP image encoder, and their class probabilities are fused with a fixed weight of 0.5. The description branch is pre-computed and does not change prompt training.

We evaluate the method with CLIP ViT-B/16 under the 16-shot base-to-novel protocol on the standard eleven datasets and three random seeds. TextConsistency obtains an average harmonic mean of 78.33, compared with 75.06 for the matched CoOp runs, and improves all 33 paired seed-level comparisons. On ImageNet, it raises novel accuracy from 68.72 to 71.62 and HM from 72.39 to 74.05. An eleven-dataset class-name control reaches 76.84 HM, showing that the gain is not explained by averaging CoOp with an ordinary zero-shot classifier. On an RTX 4090, the fused predictor adds no trainable parameters and increases batch-64 inference latency by 0.74%. These results establish fixed probability fusion as an effective and efficient way to combine task adaptation with frozen semantic priors.

*Corresponding author

Email addresses: `author-email@university.edu` (Author Name), `advisor-email@university.edu` (Advisor Name)

Keywords: vision-language models, prompt learning, few-shot classification, base-to-novel generalization, class descriptions, probability fusion

1. Introduction

Large vision-language models such as CLIP and ALIGN learn shared representations from large image-text corpora and support open-vocabulary recognition through textual prompts [1, 2]. LiT further shows that a locked image encoder can retain strong visual representations while the text tower is adapted for zero-shot transfer [3]. This transfer ability has motivated parameter-efficient adaptation methods that keep the encoders frozen and optimise only a small prompt. CoOp replaces hand-written context words with continuous learnable vectors and substantially improves few-shot recognition on downstream datasets [4]. The gain on seen classes, however, can be accompanied by weaker transfer to unseen classes. CoCoOp addresses this issue with image-conditioned prompts [5], while later methods introduce prompt distributions, coupled visual-text prompts, knowledge guidance, self-regularisation, or residual classifiers [6, 7, 8, 9, 10].

Learned prompts and descriptive language provide complementary decision evidence. A learned context adapts efficiently to the labelled base samples, whereas natural-language descriptions retain explicit attributes, parts, scenes, and functions. CuPL demonstrates that class-specific descriptions generated by a language model can improve zero-shot recognition [11]. Our experiments show a more specific effect: although the frozen description branch alone does not outperform CoOp on average, its complementary errors improve base-to-novel balance when the two posteriors are combined. The improvement also exceeds an otherwise matched fusion with ordinary class-name prompts, linking the gain to descriptive semantics rather than generic classifier averaging.

This complementary-error structure motivates TextConsistency. For each class, we encode a fixed collection of natural-language descriptions with the frozen CLIP text encoder, average their normalised embeddings, and normalise the resulting class prototype. At inference, we compute one posterior from the learned CoOp prompt and one from the frozen description prototype. The final posterior is their arithmetic mean. We use the same mixing coefficient of 0.5 for every split, seed, and dataset, without validation-based or dataset-specific tuning.

The resulting formulation isolates the value of semantic complementarity from gains produced by a larger trainable architecture. Because the description embeddings are cached, TextConsistency adds no trainable parameters and requires only one additional matrix multiplication and probability average at inference. It therefore improves novel-class transfer while preserving the training procedure and parameter efficiency of CoOp.

The contributions of this paper are as follows:

- We introduce a fixed probability-fusion formulation that combines a learned prompt posterior with a frozen class-description posterior. It uses the existing CLIP encoders and adds no trainable parameters beyond CoOp.
- We provide controlled component and class-name studies that separate branch complementarity from ordinary class-name ensembling. Across all eleven datasets with matched checkpoints, descriptions add 1.49 HM points over class-name fusion.
- We evaluate the same 0.5 fusion rule on the standard eleven base-to-novel datasets. TextConsistency reaches 78.33 average HM and improves over matched CoOp in all 33 seed-level comparisons; on the ten datasets shared by the literature comparison, it exceeds the published CoCoOp average by 3.09 points.
- We report measured inference cost on one RTX 4090 and explicitly separate local reproductions from published comparison numbers.

2. Related Work

2.1. Vision-Language Prompt Learning

CLIP performs classification by comparing a normalised image representation with text representations produced from class prompts [1]. CoOp learns continuous context tokens while keeping both CLIP encoders frozen [4]. This design is highly parameter efficient, but optimisation on base classes may specialise the prompt and reduce its ability to represent novel classes. CoCoOp conditions a prompt token on the input image and improves transfer across class and dataset shifts [5].

Several methods further regularise or expand the prompt space. ProDA models a distribution over prompts instead of using a single point estimate

[6], whereas PLOT learns multiple prompts and aligns them with visual features through optimal transport [12]. ProGrad retains general knowledge by accepting prompt gradients that do not conflict with the pre-trained model [13], and LASP uses text-to-text supervision to reduce base-class overfitting [14]. MaPLe couples prompts across the visual and language branches and introduces prompts at multiple depths [7]. KgCoOp constrains the learned context with knowledge from the hand-crafted prompt to reduce forgetting [8]. PromptSRC combines mutual agreement, prompt self-ensembling, and textual diversity to preserve general representations [9]. TaskRes instead adds a task-specific residual to the frozen text classifier [10], while PromptKD distils a larger teacher through stored class vectors and unlabeled domain images [15].

Recent work adds learned structure or supervision. CasPL learns boosting and adapting prompts in two cascaded phases [16]. TAC constructs task-aware pre-context from a small set of clustering centres [17], DPC decouples base- and novel-oriented optimisation through parallel prompts [18], and CRAFT aligns cross-modal relative representations while regularising their distribution with maximum mean discrepancy [19]. ProText instead learns transferable prompts using only language-model text supervision [20]. These approaches pursue stronger learned adaptation. TextConsistency focuses on a different operating point: it leaves CoOp training unchanged, introduces no trainable parameter, and adds only one cached textual classifier at inference.

Prompt adaptation has also been studied at inference time. TPT updates prompts from a single test image by entropy minimisation over augmented views [21], and PromptAlign augments this objective with distribution alignment [22]. These approaches address test-time domain shift and require per-sample optimisation. TextConsistency targets the supervised base-to-novel setting and keeps inference deterministic: the two cached classifiers are combined without test-time updates.

2.2. Class Descriptions and Training-Free Adaptation

Natural language can express class properties that are absent from a short template. CuPL uses a language model to generate customised visual descriptions for zero-shot classification [11]; ProText subsequently distributes these description assets and uses them as text-only supervision for prompt learning [20]. Classification by description predicts interpretable visual attributes instead of relying only on class names [23]. CHiLS expands coarse categories

into hierarchical label sets [24], and GPT-4-generated visual descriptions have been used to construct fine-grained CLIP classifiers [25]. At the same time, WaffleCLIP shows that part of the gain from descriptor ensembling can persist with random words and broad concepts [26]; descriptor and word soups further study how to select compact text ensembles from few-shot data [27]. These findings motivate a direct class-name fusion control rather than assuming that every gain comes from descriptive semantics.

Training-free adaptation offers another route to preserving the pre-trained model. Tip-Adapter uses a cache of few-shot visual features [28], SuS-X performs name-only transfer with support sets and a training-free adapter [29], and CALIP introduces parameter-free cross-modal attention [30]. TextConsistency is complementary to these approaches: its frozen branch is textual, its learned branch remains standard CoOp, and the final operation is a fixed posterior average.

TextConsistency differs in purpose and protocol. The description branch is not treated as a replacement for the learned prompt. Instead, the method combines the adapted CoOp posterior, which is strong on base classes, with a frozen description posterior that tends to retain novel-class semantics. The fixed probability average avoids a validation-driven search and makes the added computation easy to audit.

3. Method

3.1. Problem Setting

Let the class set be partitioned into disjoint base and novel subsets, $\mathcal{C}_b$ and $\mathcal{C}_n$. A prompt is trained with 16 labelled images per base class. Evaluation is performed separately on test images from base and novel classes. We report base accuracy A_b, novel accuracy A_n, and their harmonic mean

$$H = \frac{2A_bA_n}{A_b + A_n}. \tag{1}$$

The harmonic mean penalises a predictor that improves one split while severely reducing the other.

CLIP consists of a visual encoder E_v and a text encoder E_t. Given image x, its normalised feature is

$$\mathbf{v}(x) = \frac{E_v(x)}{\|E_v(x)\|_2}. \tag{2}$$

Both encoders remain frozen throughout our experiments.

3.2. Learned Prompt Branch

We use CoOp as the trainable branch. For class c, a prompt contains M learnable context vectors followed by the tokenised class name. Its normalised text representation is

$$\mathbf{t}_c^p = \frac{E_t([\mathbf{q}_1, \ldots, \mathbf{q}_M, c])}{\|E_t([\mathbf{q}_1, \ldots, \mathbf{q}_M, c])\|_2}. \tag{3}$$

With the frozen CLIP scale $s = \exp(\gamma)$, the prompt logit and posterior are

$$z_c^p(x) = s\, \mathbf{v}(x)^\top \mathbf{t}_c^p, \tag{4}$$

$$p_c^p(x) = \frac{\exp(z_c^p(x))}{\sum_{k \in \mathcal{C}} \exp(z_k^p(x))}. \tag{5}$$

Only the context vectors are optimised, using the standard cross-entropy objective on base-class training images.

3.3. Frozen Description Branch

For each class c, we use a fixed set of valid natural-language descriptions $\mathcal{D}_c = \{d_{c,1}, \ldots, d_{c,m_c}\}$. We reuse the public text files distributed by the official ProText repository [20]. For every benchmark dataset except EuroSAT, the files are traceable to the CuPL full-prompt assets [11]. CuPL reports GPT-3 DaVinci-002 with dataset-specific sets of two to nine visual-description instructions, ten completions per instruction, temperature 0.99, a 50-token limit, and a period stop token. The exact generation dates were not disclosed. The EuroSAT file is byte-identical to the ProText release, but its exact language-model version, temperature, generation date, and sampling count are not documented upstream. We do not query a language model in this study.

For every class, we normalise the class key for matching, preserve the source-file order, remove empty and exact duplicate strings, and retain at most the first 20 descriptions. Token sequences that become identical after CLIP tokenisation are also deduplicated. The only local source clean-up is class-key normalisation, removal of one filename-like string, and correction of one leading-character typo. No description is selected according to validation or test accuracy. File hashes and a machine-readable source-difference audit are released with the code.

Each description is encoded and normalised independently:

$$\mathbf{u}_{c,j} = \frac{E_t(d_{c,j})}{\|E_t(d_{c,j})\|_2}. \tag{6}$$

We compute a class prototype by averaging all valid description embeddings and normalising again:

$$\bar{\mathbf{u}}_c = \frac{\frac{1}{m_c}\sum_{j=1}^{m_c} \mathbf{u}_{c,j}}{\left\|\frac{1}{m_c}\sum_{j=1}^{m_c} \mathbf{u}_{c,j}\right\|_2}. \tag{7}$$

The description logit and posterior are

$$z_c^d(x) = s\,\mathbf{v}(x)^\top \bar{\mathbf{u}}_c, \tag{8}$$

$$p_c^d(x) = \frac{\exp(z_c^d(x))}{\sum_{k\in\mathcal{C}} \exp(z_k^d(x))}. \tag{9}$$

All description prototypes are pre-computed and cached. This branch has no trainable parameter and does not alter CoOp training.

3.4. Fixed Probability Fusion

The final TextConsistency posterior is

$$p_c^{tc}(x) = (1-\alpha)p_c^p(x) + \alpha p_c^d(x), \qquad \alpha = 0.5. \tag{10}$$

The prediction is $\arg\max_c p_c^{tc}(x)$. We use a single global coefficient of 0.5 for every split, seed, and dataset, without validation-based or dataset-specific tuning. Averaging probabilities rather than logits allows each branch to form its own normalised class distribution before fusion. Section 5.3 compares both alternatives.

3.5. Parameter and Computation Cost

Relative to CoOp, TextConsistency adds zero trainable parameters. In our ViT-B/16 implementation, CoOp trains 2,048 context parameters. The cached class-description tensor occupies 0.0977 MiB in the measured UCF101 setting. During inference, the extra operations are one image-to-prototype matrix multiplication, one softmax, and one probability average. No text encoding is performed in the timed inference loop.




Figure 1: Overview of TextConsistency. A frozen CLIP image representation is scored against a learned CoOp classifier and a cached class-description classifier. Only the CoOp context tokens are trained; the two independently normalised posteriors are averaged with a fixed coefficient of 0.5.

4. Experiments

4.1. Datasets and Evaluation Protocol

We evaluate on the standard eleven base-to-novel benchmarks: ImageNet, Caltech101, OxfordPets, StanfordCars, OxfordFlowers, Food101, FGVC Aircraft, SUN397, DTD, EuroSAT, and UCF101. They cover large-scale generic recognition, fine-grained categories, food, aircraft, scenes, textures, remote sensing, and human actions. We use the public class splits associated with CoOp and CoCoOp [4, 5]. The ImageNet audit contains 1,281,167 training images, 50,000 validation images, and a 500/500 base-novel class split.

For every trainable method, we use 16 shots per base class and random seeds 1, 2, and 3. We first average base and novel accuracy over seeds and then compute dataset-level HM using Eq. (1). Cross-dataset summaries are unweighted macro averages over the eleven dataset-level values. Frozen text branches have no training seed.

4.2. Implementation Details

All local experiments use OpenAI CLIP ViT-B/16. CoOp uses four context tokens, batch size 16, SGD with learning rate 0.002 and momentum 0.9, cosine scheduling, and 20 epochs. Images are resized to 224×224 with the CLIP normalisation. The description branch uses the deterministic filtering rule above, at most 20 stored descriptions per class, and the same frozen CLIP logit scale as the learned branch. Description embeddings are computed once and cached. The mixing coefficient is always 0.5.

Table 1: Matched harmonic-mean accuracy (%) on the standard eleven base-to-novel benchmarks. Both methods use CLIP ViT-B/16, the official class splits, and the same three CoOp checkpoints per dataset.

Method	UCF	DTD	Air.	Euro.	Flw.	Cal.	Pets	Food	Cars	SUN	IN	Avg.
CoOp	74.42	63.79	34.26	67.52	81.07	95.95	96.39	90.51	72.35	77.05	72.39	75.06
TextConsistency	79.47	70.99	38.46	76.65	85.06	96.09	96.63	91.30	73.16	79.74	74.05	**78.33**

Table 2: Eleven-dataset macro averages for the matched comparison (%). HM is computed for each dataset before macro averaging.

Method	Base	Novel	HM
CoOp	81.39	70.34	75.06
TextConsistency	81.13	76.00	78.33

4.3. Baselines and Reporting Boundary

The matched eleven-dataset baseline is CoOp. For broader positioning, we compare against published results for CuPL, CoCoOp, KgCoOp, MaPLe, and PromptSRC [11, 5, 8, 7, 9]. These literature values are marked with †.

5. Results

5.1. Local Base-to-Novel Comparison

Table 1 reports the matched dataset-level HM. TextConsistency reaches 78.33 over eleven datasets, compared with 75.06 for CoOp, a gain of 3.26 percentage points. On ImageNet, HM increases from 72.39 to 74.05, with a 2.90-point gain in novel accuracy and no base-accuracy loss.

Table 2 separates base and novel accuracy. Relative to CoOp, TextConsistency changes the eleven-dataset base average from 81.39 to 81.13 while improving novel accuracy from 70.34 to 76.00. The 5.66-point novel gain is therefore the main source of the improved balance.

The improvement over CoOp is positive for every dataset and all 33 seed-level comparisons. It is largest on EuroSAT, DTD, UCF101, FGVC Aircraft, and OxfordFlowers. The gains on Caltech101, OxfordPets, Food101, StanfordCars, and ImageNet are smaller, which indicates that the frozen semantic branch is most useful when the learned prompt exhibits a larger base-novel gap.




Figure 2: Per-dataset HM improvement of TextConsistency over matched CoOp on all eleven benchmarks. Positive values indicate higher harmonic mean. All values are computed from the audited three-seed dataset summaries.

Table 3: Comparison with published base-to-novel HM results on the ten datasets common to all methods. Published values are marked with † and are not local reproductions.

Method	UCF	DTD	Air.	Euro.	Flw.	Cal.	Pets	Food	Cars	SUN	Avg.
CuPL†	76.40	61.30	33.20	61.80	76.10	95.60	95.80	90.60	68.80	75.70	73.53
CoCoOp†	77.64	64.85	27.74	71.21	81.71	95.84	96.43	90.99	72.01	78.27	75.67
KgCoOp†	79.65	64.35	34.83	73.48	83.65	96.03	96.18	91.09	73.36	78.36	77.10
MaPLe†	80.77	68.16	36.50	82.35	82.56	96.02	96.58	91.38	73.47	79.75	78.75
PromptSRC†	82.74	71.75	40.15	82.32	85.95	96.02	96.30	91.10	76.58	80.52	80.34
TextConsistency	79.47	70.99	38.46	76.65	85.06	96.09	96.63	91.30	73.16	79.74	**78.75**

Figure 2 visualises these matched dataset-level gains. All bars remain above zero, but their range also shows that the benefit is dataset dependent rather than a uniform offset.

5.2. Comparison with Published Results

Table 3 recomputes a ten-dataset average using the datasets common to all listed methods. TextConsistency is 5.22 points above CuPL, 3.09 points above the published CoCoOp values, and 1.66 points above KgCoOp. Its 78.75 average is effectively tied with MaPLe at the reported precision and is 1.59 points below PromptSRC. Because these are paper-reported values from different implementations, the table provides literature positioning rather than a controlled ranking.

Table 4: Component comparison using HM (%). The description branch is frozen. Both fusion variants use a fixed weight of 0.5.

Method	UCF	DTD	Air.	Euro.	Flw.	Cal.	Pets	Food	Cars	SUN	IN	Avg.
CoOp	74.42	63.79	34.26	67.52	81.07	95.95	96.39	90.51	72.35	77.05	72.39	75.06
Description only	76.46	63.30	34.83	69.99	76.69	96.29	95.27	90.58	67.53	76.73	72.77	74.59
Logit fusion	78.76	70.75	38.31	75.69	83.73	96.09	96.64	91.30	72.86	79.54	74.01	77.97
Probability fusion	79.47	70.99	38.46	76.65	85.06	96.09	96.63	91.30	73.16	79.74	74.05	**78.33**

Table 5: Class-name control on all eleven datasets with matched frozen checkpoints. All values are three-seed macro averages (%).

Method	Base	Novel	HM
CoOp	81.39	70.34	75.06
Class name only	69.49	74.31	71.71
CoOp + class name	80.71	73.80	76.84
Description only	72.01	77.78	74.59
TextConsistency	**81.13**	**76.00**	**78.33**

5.3. Component Analysis

The description-only branch obtains 74.59 average HM, below CoOp at 75.06. Its value lies in complementarity rather than standalone strength. Fixed logit fusion raises the average to 77.97, showing that combining the two semantic sources is already effective. Probability fusion further raises it to 78.33 and is the final method. The same coefficient is used for every dataset; the difference is not produced by dataset-specific weight selection.

The description branch is deterministic for a fixed dataset and split. Repeating it alongside three CoOp checkpoints does not constitute three independent description-model trainings. Our statistical unit for the trainable branch remains the three CoOp seeds.

5.4. Class-name Control and Global Fusion Weight

Table 5 uses all eleven main-study datasets and the exact matched checkpoints from the primary evaluation. Relative to the same CoOp checkpoints fused with ordinary class-name prompts, TextConsistency improves macro HM from 76.84 to 78.33, a gain of 1.49 points. It is higher on ten of eleven datasets and 28 of 33 matched dataset-seed comparisons. The gain on ImageNet is 1.10 points; StanfordCars remains the only dataset with a small negative difference, at 0.18 points. The result therefore supports an average




Figure 3: Controlled semantic and weight analyses on all eleven datasets. (a) HM difference between TextConsistency and an otherwise matched CoOp-plus-class-name probability average. (b) Base, novel, and HM macro averages for one global description weight shared by every dataset. The main method remains the pre-specified $\alpha = 0.5$.

contribution from descriptive semantics without implying uniform improvement on every dataset.

Figure 3(b) reports the common grid $\alpha \in \{0, 0.25, 0.5, 0.75, 1\}$ without selecting a dataset-specific value. The pre-specified midpoint obtains the highest macro HM, 78.33. Both intermediate mixtures outperform the two single-branch endpoints, while increasing α trades base accuracy for novel accuracy. This pattern is consistent with the intended balance between adaptation and frozen semantic coverage.

5.5. Stability Across Seeds

For each seed, we compare TextConsistency and CoOp using predictions from the same trained checkpoint. All 33 paired HM differences are positive. On ImageNet, the three gains are +1.80, +1.57, and +1.63 points. The largest mean gains remain on EuroSAT, DTD, UCF101, FGVC Aircraft, and OxfordFlowers. Because each dataset has only three seeds, we use these results as evidence of directional stability and do not make strong significance claims from small-sample confidence intervals. Full per-dataset Base, Novel, and seed-level HM statistics are provided in Appendix A.

Figure 4 retains every paired seed result. The vertical ranges show seed variation within each dataset, and the mean diamonds show that the effect is strongest on EuroSAT, DTD, UCF101, FGVC Aircraft, and OxfordFlowers while remaining positive on the more saturated datasets.




Figure 4: Paired TextConsistency-minus-CoOp HM gains for all three seeds on each of the eleven datasets. Diamonds denote dataset means and vertical lines span the three seed values. Dataset means average the three seed-level HM differences and may differ slightly from Table 1, where HM is computed after averaging Base and Novel accuracy across seeds. All 33 matched comparisons are positive.

Table 6: Inference efficiency on one RTX 4090 using the UCF101 novel split. Text features are pre-computed.

Method	Batch	ms/batch	img/s	Extra latency
CoOp	1	18.827	53.12	0.00%
TextConsistency	1	18.904	52.90	0.41%
CoOp	64	90.128	710.10	0.00%
TextConsistency	64	90.796	704.88	0.74%

5.6. Inference Efficiency

Table 6 reports CUDA-event measurements on one RTX 4090. Each setting uses 20 warm-up iterations followed by 100 timed iterations on the same UCF101 novel checkpoint and input tensors. At batch size 64, TextConsistency increases latency from 90.128 to 90.796 ms per batch, an overhead of 0.74%. Incremental peak memory is unchanged at the allocator resolution used in this experiment. These measurements exclude model loading, disk I/O, CPU preprocessing, and one-time text encoding.

6. Discussion and Limitations

The results show that fixed posterior fusion consistently restores frozen semantic information that is underused after base-class prompt adaptation. The evidence forms a coherent chain: the learned and frozen branches make complementary errors, description fusion improves macro HM from 75.06 to 78.33, and it exceeds matched class-name fusion by 1.49 points while using one global weight and no additional trainable parameters. The description-only average remains below CoOp, confirming that the gain comes from their complementarity rather than replacing the learned prompt.

Several limitations remain. First, the descriptions originate from the public CuPL/ProText assets; we do not compare alternative language models, generation instructions, or description budgets. Second, the global-weight analysis uses a coarse five-point grid and evaluates the same datasets as the main study; it does not establish calibration robustness under an external distribution shift. Finally, the efficiency result is measured on one GPU and should not be treated as a hardware-independent latency guarantee.

The released evidence includes frozen data splits, seeds, source hashes, checkpoints, raw predictions, and independent recomputation. The ImageNet package also records the evaluator hash and verifies 1,281,167 training images and 50,000 validation images, making the complete eleven-dataset evaluation traceable.

7. Conclusion

We presented TextConsistency, a parameter-free extension to CoOp that averages the class probabilities from learned prompts and frozen class descriptions. The method keeps CLIP frozen, leaves prompt training unchanged, uses a single fixed fusion coefficient, and caches the description prototypes. Across the standard eleven base-to-novel datasets, it improves average HM from 75.06 to 78.33 over matched CoOp, with positive gains in all 33 seed-level comparisons. Component and class-name controls identify complementary descriptive semantics as the source of the improvement, and an RTX 4090 measurement shows less than one percent batch-64 latency overhead. TextConsistency therefore provides a reproducible way to improve novel-class balance without expanding the trainable model.

Data and Code Availability

The implementation, frozen configurations, result tables, audit scripts, and experiment summaries are available in the public GitHub repository. The release separates local reproductions from published comparison values and includes machine-readable CSV and JSON summaries. The description files are traced to fixed ProText and CuPL commits; their hashes, the two local text clean-ups, and the upstream licence locations are recorded in the repository's preparation reports.

Appendix A. Per-Dataset Seed Statistics

Table A.1 reports the full three-seed variation behind the main comparison. The standard deviations are computed across the three matched CoOp checkpoints for each dataset. Here, the HM mean is the arithmetic mean of the three raw seed-level HMs; it can differ slightly from the main-table HM computed after averaging Base and Novel accuracy. The raw HM columns make every paired comparison directly verifiable.

Table A.1: Per-dataset seed-level results across the three matched seeds (%). Mean ± sample standard deviation is reported for Base, Novel, and seed-level HM; the last three columns give the raw HM for each seed.

Dataset	Method	Base	Novel	Seed-HM	HM_1	HM_2	HM_3
UCF101	CoOp	83.56 ± 0.45	67.08 ± 2.90	74.40 ± 1.94	72.48	76.36	74.36
	TextConsistency	82.70 ± 0.43	76.49 ± 1.13	79.47 ± 0.80	78.81	80.36	79.24
DTD	CoOp	77.78 ± 0.92	54.07 ± 0.77	63.79 ± 0.77	63.60	63.13	64.64
	TextConsistency	77.93 ± 0.48	65.18 ± 1.82	70.98 ± 1.02	70.28	70.51	72.14
FGVC-Aircraft	CoOp	37.54 ± 0.92	31.51 ± 1.84	34.25 ± 1.31	35.36	32.80	34.57
	TextConsistency	37.47 ± 0.09	39.49 ± 1.27	38.45 ± 0.56	38.83	37.80	38.72
EuroSAT	CoOp	84.38 ± 4.27	56.28 ± 13.40	66.64 ± 8.04	65.77	75.08	59.07
	TextConsistency	84.56 ± 1.65	70.10 ± 6.04	76.52 ± 2.87	74.82	79.83	74.91
OxfordFlowers	CoOp	97.02 ± 0.43	69.62 ± 3.03	81.04 ± 1.97	82.57	81.74	78.82
	TextConsistency	95.73 ± 0.41	76.52 ± 1.72	85.05 ± 0.98	85.70	85.52	83.92
Caltech101	CoOp	98.02 ± 0.36	93.96 ± 1.26	95.94 ± 0.52	96.53	95.74	95.56
	TextConsistency	98.00 ± 0.13	94.25 ± 1.30	96.08 ± 0.63	96.79	95.85	95.61
OxfordPets	CoOp	95.57 ± 0.26	97.22 ± 0.48	96.39 ± 0.26	96.28	96.69	96.19
	TextConsistency	95.61 ± 0.20	97.67 ± 0.36	96.63 ± 0.14	96.61	96.77	96.50
Food101	CoOp	90.10 ± 0.23	90.94 ± 0.75	90.51 ± 0.46	90.68	90.00	90.87
	TextConsistency	90.65 ± 0.16	91.95 ± 0.16	91.30 ± 0.13	91.37	91.15	91.38
StanfordCars	CoOp	74.33 ± 0.98	70.47 ± 1.17	72.34 ± 0.45	71.97	72.85	72.20
	TextConsistency	72.11 ± 1.14	74.25 ± 0.72	73.16 ± 0.35	72.78	73.21	73.47
SUN397	CoOp	80.54 ± 0.16	73.85 ± 0.63	77.04 ± 0.29	77.05	76.75	77.33
	TextConsistency	81.07 ± 0.15	78.46 ± 0.15	79.74 ± 0.07	79.72	79.68	79.82
ImageNet	CoOp	76.47 ± 0.06	68.72 ± 0.21	72.39 ± 0.13	72.24	72.48	72.44
	TextConsistency	76.66 ± 0.07	71.62 ± 0.08	74.05 ± 0.02	74.04	74.05	74.07

References

[1] A. Radford, J. W. Kim, C. Hallacy, A. Ramesh, G. Goh, S. Agarwal, G. Sastry, A. Askell, P. Mishkin, J. Clark, G. Krueger, I. Sutskever, Learning transferable visual models from natural language supervision, in: Proceedings of the 38th International Conference on Machine Learning, 2021, pp. 8748–8763.

[2] C. Jia, Y. Yang, Y. Xia, Y.-T. Chen, Z. Parekh, H. Pham, Q. Le, Y.-H. Sung, Z. Li, T. Duerig, Scaling up visual and vision-language representation learning with noisy text supervision, in: Proceedings of the 38th International Conference on Machine Learning, 2021, pp. 4904–4916.

[3] X. Zhai, X. Wang, B. Mustafa, A. Steiner, D. Keysers, A. Kolesnikov, L. Beyer, LiT: Zero-shot transfer with locked-image text tuning, in: Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition, 2022, pp. 18123–18133.

[4] K. Zhou, J. Yang, C. C. Loy, Z. Liu, Learning to prompt for vision-language models, International Journal of Computer Vision 130 (2022) 2337–2348.

[5] K. Zhou, J. Yang, C. C. Loy, Z. Liu, Conditional prompt learning for vision-language models, in: Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition, 2022, pp. 16816–16825.

[6] Y. Lu, J. Liu, Y. Zhang, Y. Liu, X. Tian, Prompt distribution learning, in: Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition, 2022, pp. 5206–5215.

[7] M. U. Khattak, H. Rasheed, M. Maaz, S. Khan, F. S. Khan, MaPLe: Multi-modal prompt learning, in: Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition, 2023, pp. 19113–19122.

[8] H. Yao, R. Zhang, C. Xu, Visual-language prompt tuning with knowledge-guided context optimization, in: Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition, 2023, pp. 6757–6767.

[9] M. U. Khattak, S. T. Wasim, M. Naseer, S. Khan, M.-H. Yang, F. S. Khan, Self-regulating prompts: Foundational model adaptation without forgetting, in: Proceedings of the IEEE/CVF International Conference on Computer Vision, 2023, pp. 15190–15200.

[10] T. Yu, Z. Lu, X. Jin, Z. Chen, X. Wang, Task residual for tuning vision-language models, in: Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition, 2023, pp. 10899–10909.

[11] S. Pratt, I. Covert, R. Liu, A. Farhadi, What does a platypus look like? generating customized prompts for zero-shot image classification, in: Proceedings of the IEEE/CVF International Conference on Computer Vision, 2023, pp. 15691–15701.

[12] G. Chen, W. Yao, X. Song, X. Li, Y. Rao, K. Zhang, PLOT: Prompt learning with optimal transport for vision-language models, in: International Conference on Learning Representations, 2023.

[13] B. Zhu, Y. Niu, Y. Han, Y. Wu, H. Zhang, Prompt-aligned gradient for prompt tuning, in: Proceedings of the IEEE/CVF International Conference on Computer Vision, 2023, pp. 15659–15669.

[14] A. Bulat, G. Tzimiropoulos, LASP: Text-to-text optimization for language-aware soft prompting of vision and language models, in: Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition, 2023, pp. 23232–23241.

[15] Z. Li, X. Li, X. Fu, X. Zhang, W. Wang, S. Chen, J. Yang, PromptKD: Unsupervised prompt distillation for vision-language models, in: Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition, 2024, pp. 26617–26626.

[16] G. Wu, X. Zhang, Z. Li, Z. Chen, J. Liang, J. Yang, X. Li, Cascade prompt learning for vision-language model adaptation, in: European Conference on Computer Vision, 2024, pp. 304–321. doi:10.1007/978-3-031-72973-7_18.

[17] F. Hao, F. He, F. Wu, T. Wang, C. Song, J. Cheng, Task-aware clustering for prompting vision-language models, in: Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition, 2025, pp. 14745–14755.

[18] H. Li, L. Wang, C. Wang, J. Jiang, Y. Peng, G. Long, DPC: Dual-prompt collaboration for tuning vision-language models, in: Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition, 2025, pp. 25623–25632.

[19] J. Sun, R. Sharma, V. Lokhande, C. Chen, Cross-modal feature alignment and MMD improve robustness of prompt tuning, in: Proceedings of the Winter Conference on Applications of Computer Vision, 2025, pp. 4714–4724.

[20] M. U. Khattak, M. F. Naeem, M. Naseer, L. Van Gool, F. Tombari, Learning to prompt with text only supervision for vision-language models, in: Proceedings of the AAAI Conference on Artificial Intelligence, Vol. 39, 2025, pp. 4230–4238. doi:10.1609/aaai.v39i4.32444.

[21] M. Shu, W. Nie, D.-A. Huang, Z. Yu, T. Goldstein, A. Anandkumar, C. Xiao, Test-time prompt tuning for zero-shot generalization in vision-language models, in: Advances in Neural Information Processing Systems, Vol. 35, 2022.

[22] J. A. Samadh, M. H. Gani, N. Hussein, M. U. Khattak, M. M. Naseer, F. S. Khan, S. H. Khan, Align your prompts: Test-time prompting with distribution alignment for zero-shot generalization, in: Advances in Neural Information Processing Systems, Vol. 36, 2023.

[23] S. Menon, C. Vondrick, Visual classification via description from large language models, in: International Conference on Learning Representations, 2023.

[24] Z. Novack, J. McAuley, Z. C. Lipton, S. Garg, CHiLS: Zero-shot image classification with hierarchical label sets, in: Proceedings of the 40th International Conference on Machine Learning, 2023, pp. 26342–26362.

[25] M. Maniparambil, C. Vorster, D. Molloy, N. Murphy, K. McGuinness, N. E. O'Connor, Enhancing CLIP with GPT-4: Harnessing visual descriptions as prompts, in: Proceedings of the IEEE/CVF International Conference on Computer Vision Workshops, 2023, pp. 262–271.

[26] K. Roth, J. M. Kim, A. S. Koepke, O. Vinyals, C. Schmid, Z. Akata, Waffling around for performance: Visual classification with random

words and broad concepts, in: Proceedings of the IEEE/CVF International Conference on Computer Vision, 2023, pp. 15746–15757.

[27] C. Liao, T. Tsiligkaridis, B. Kulis, Descriptor and word soups: Overcoming the parameter efficiency accuracy tradeoff for out-of-distribution few-shot learning, in: Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition, 2024, pp. 27015–27025.

[28] R. Zhang, R. Fang, W. Zhang, P. Gao, K. Li, J. Dai, Y. Qiao, H. Li, Tip-adapter: Training-free adaption of CLIP for few-shot classification, in: European Conference on Computer Vision, 2022, pp. 493–510.

[29] V. Udandarao, A. Gupta, S. Albanie, SuS-X: Training-free name-only transfer of vision-language models, in: Proceedings of the IEEE/CVF International Conference on Computer Vision, 2023, pp. 2725–2736.

[30] Z. Guo, R. Zhang, L. Qiu, X. Ma, X. Miao, X. He, B. Cui, CALIP: Zero-shot enhancement of CLIP with parameter-free attention, Proceedings of the AAAI Conference on Artificial Intelligence 37 (1) (2023) 746–754.