TextConsistency: Parameter-Free Probability Fusion of Learned Prompts and Class Descriptions for Base-to-Novel Recognition

Author Name[a,*], Advisor Name[a]

[a]*School of XXX, XXX University, XXX Street, XXX, 000000, China*

Abstract

Prompt learning efficiently adapts vision-language models to downstream recognition tasks, but prompts trained on base classes can lose part of the semantic coverage inherited from the frozen model. We study a simple way to recover this coverage without adding trainable parameters. TextConsistency combines the posterior produced by a CoOp prompt with a second posterior obtained from frozen, class-specific natural-language descriptions. Description embeddings are averaged within each class, both branches share the frozen CLIP image encoder, and their class probabilities are fused with a fixed weight of 0.5. The description branch is pre-computed and does not change prompt training.

We evaluate the method with CLIP ViT-B/16 under the 16-shot base-to-novel protocol on ten datasets and three random seeds. TextConsistency obtains an average harmonic mean of 78.75, compared with 75.33 for the matched CoOp runs and 76.15 for locally evaluated CoCoOp. It improves the harmonic mean over CoOp in all 30 seed-level comparisons and over CoCoOp on all ten datasets. Its ten-dataset average is comparable to the published MaPLe result, while remaining 1.59 percentage points below PromptSRC. On an RTX 4090, the fused predictor adds no trainable parameters and increases batch-64 inference latency by 0.74%. These results show that fixed probability fusion is a practical way to combine task adaptation with frozen semantic priors, although the current study does not include ImageNet and

*Corresponding author

Email addresses: author-email@university.edu (Author Name), advisor-email@university.edu (Advisor Name)

therefore does not establish an eleven-dataset state of the art.

Keywords: vision-language models, prompt learning, few-shot classification, base-to-novel generalization, class descriptions, probability fusion

---

1. Introduction

Large vision-language models such as CLIP learn a shared representation from image-text pairs and support open-vocabulary recognition through textual prompts [1]. Their transfer ability has motivated parameter-efficient adaptation methods that keep the encoders frozen and optimise only a small prompt. CoOp replaces hand-written context words with continuous learnable vectors and substantially improves few-shot recognition on downstream datasets [2]. The gain on seen classes, however, can be accompanied by weaker transfer to unseen classes. CoCoOp addresses this issue with image-conditioned prompts [3], while later methods introduce prompt distributions, coupled visual-text prompts, knowledge guidance, or self-regularisation [4, 5, 6, 7].

Learned prompts and descriptive language provide different information. A learned context adapts efficiently to the labelled base samples, whereas natural-language descriptions retain explicit attributes, parts, scenes, and functions. CuPL demonstrates that class-specific descriptions generated by a language model can improve zero-shot recognition [8]. In our experiments, the frozen description branch alone does not outperform CoOp on average, but its errors are sufficiently complementary to improve base-to-novel balance when the two predictions are combined.

This observation motivates TextConsistency, a deliberately small extension to prompt learning. For each class, we encode a fixed collection of natural-language descriptions with the frozen CLIP text encoder, average their normalised embeddings, and normalise the resulting class prototype. At inference, we compute one posterior from the learned CoOp prompt and one from the frozen description prototype. The final posterior is their arithmetic mean. We fix the mixing coefficient to 0.5 for every dataset and do not tune a temperature, gate, threshold, or class-specific weight.

The simplicity of the method is useful for two reasons. First, it isolates the value of semantic complementarity from gains produced by a larger trainable architecture. Second, the description embeddings can be cached, so the method adds no trainable parameters and only a small matrix multiplication

and probability average at inference. This is particularly suitable when the goal is to improve novel-class transfer while preserving the efficient training procedure of CoOp.

The contributions of this paper are as follows:

- We introduce a fixed probability-fusion formulation that combines a learned prompt posterior with a frozen class-description posterior. It uses the existing CLIP encoders and adds no trainable parameters beyond CoOp.
- We provide a controlled component study that separates CoOp, the description-only branch, logit fusion, and probability fusion. The results show that the gain comes from branch complementarity rather than from the description branch alone.
- We evaluate the same 0.5 fusion rule on ten base-to-novel datasets. TextConsistency reaches 78.75 average HM, improves over local CoCoOp on ten out of ten datasets, and improves over matched CoOp in all 30 seed-level comparisons.
- We report measured inference cost on one RTX 4090 and explicitly separate local reproductions from published comparison numbers.

2. Related Work

2.1. Vision-Language Prompt Learning

CLIP performs classification by comparing a normalised image representation with text representations produced from class prompts [1]. CoOp learns continuous context tokens while keeping both CLIP encoders frozen [2]. This design is highly parameter efficient, but optimisation on base classes may specialise the prompt and reduce its ability to represent novel classes. CoCoOp conditions a prompt token on the input image and improves transfer across class and dataset shifts [3].

Several methods further regularise or expand the prompt space. ProDA models a distribution over prompts instead of using a single point estimate [4]. MaPLe couples prompts across the visual and language branches and introduces prompts at multiple depths [5]. KgCoOp constrains the learned context with knowledge from the hand-crafted prompt to reduce forgetting [6].

PromptSRC combines mutual agreement, prompt self-ensembling, and textual diversity to preserve general representations [7]. These methods demonstrate that base-to-novel performance benefits from retaining information from the frozen model. TextConsistency follows the same broad motivation but uses a fixed, transparent posterior fusion rather than adding trainable modules or auxiliary losses.

2.2. Class Descriptions and Training-Free Adaptation

Natural language can express class properties that are absent from a short template. CuPL uses a language model to generate customised visual descriptions for zero-shot classification and shows that detailed class prompts can improve CLIP predictions [8]. Other training-free adaptation approaches, such as Tip-Adapter, exploit cached task information to update predictions with little or no gradient-based optimisation [9].

TextConsistency differs in purpose and protocol. The description branch is not treated as a replacement for the learned prompt. Instead, the method combines the adapted CoOp posterior, which is strong on base classes, with a frozen description posterior that tends to retain novel-class semantics. The fixed probability average avoids a validation-driven search and makes the added computation easy to audit.

3. Method

3.1. Problem Setting

Let the class set be partitioned into disjoint base and novel subsets, $\mathcal{C}_b$ and $\mathcal{C}_n$. A prompt is trained with 16 labelled images per base class. Evaluation is performed separately on test images from base and novel classes. We report base accuracy A_b, novel accuracy A_n, and their harmonic mean

$$H = \frac{2A_bA_n}{A_b + A_n}. \tag{1}$$

The harmonic mean penalises a predictor that improves one split while severely reducing the other.

CLIP consists of a visual encoder E_v and a text encoder E_t. Given image x, its normalised feature is

$$\mathbf{v}(x) = \frac{E_v(x)}{\|E_v(x)\|_2}. \tag{2}$$

Both encoders remain frozen throughout our experiments.

3.2. Learned Prompt Branch

We use CoOp as the trainable branch. For class c, a prompt contains M learnable context vectors followed by the tokenised class name. Its normalised text representation is

$$\mathbf{t}_c^p = \frac{E_t([\mathbf{q}_1, \ldots, \mathbf{q}_M, c])}{\|E_t([\mathbf{q}_1, \ldots, \mathbf{q}_M, c])\|_2}. \tag{3}$$

With the frozen CLIP scale $s = \exp(\gamma)$, the prompt logit and posterior are

$$z_c^p(x) = s\, \mathbf{v}(x)^\top \mathbf{t}_c^p, \tag{4}$$

$$p_c^p(x) = \frac{\exp(z_c^p(x))}{\sum_{k \in \mathcal{C}} \exp(z_k^p(x))}. \tag{5}$$

Only the context vectors are optimised, using the standard cross-entropy objective on base-class training images.

3.3. Frozen Description Branch

For each class c, we use a fixed set of valid natural-language descriptions $\mathcal{D}_c = \{d_{c,1}, \ldots, d_{c,m_c}\}$. The stored descriptions cover visible attributes, functions, scenes, actions, or parts when applicable. They are prepared before evaluation and are not selected according to test accuracy.

Each description is encoded and normalised independently:

$$\mathbf{u}_{c,j} = \frac{E_t(d_{c,j})}{\|E_t(d_{c,j})\|_2}. \tag{6}$$

We compute a class prototype by averaging all valid description embeddings and normalising again:

$$\bar{\mathbf{u}}_c = \frac{\frac{1}{m_c} \sum_{j=1}^{m_c} \mathbf{u}_{c,j}}{\left\| \frac{1}{m_c} \sum_{j=1}^{m_c} \mathbf{u}_{c,j} \right\|_2}. \tag{7}$$

The description logit and posterior are

$$z_c^d(x) = s\, \mathbf{v}(x)^\top \bar{\mathbf{u}}_c, \tag{8}$$

$$p_c^d(x) = \frac{\exp(z_c^d(x))}{\sum_{k \in \mathcal{C}} \exp(z_k^d(x))}. \tag{9}$$

All description prototypes are pre-computed and cached. This branch has no trainable parameter and does not alter CoOp training.




Figure 1: TextConsistency uses one frozen image feature and two text-derived classifiers. The upper branch contains the only trainable parameters already present in CoOp; the lower branch is cached.

3.4. Fixed Probability Fusion

The final TextConsistency posterior is

$$p_c^{tc}(x) = (1-\alpha)p_c^p(x) + \alpha p_c^d(x), \qquad \alpha = 0.5. \tag{10}$$

The prediction is $\arg\max_c p_c^{tc}(x)$. We use the same coefficient for every split, seed, and dataset. The rule was fixed before the later dataset extensions, and no validation search is performed. Averaging probabilities rather than logits allows each branch to form its own normalised class distribution before fusion. Section 5.3 compares both alternatives.

3.5. Parameter and Computation Cost

Relative to CoOp, TextConsistency adds zero trainable parameters. In our ViT-B/16 implementation, CoOp trains 2,048 context parameters. The cached class-description tensor occupies 0.0977 MiB in the measured UCF101 setting. During inference, the extra operations are one image-to-prototype matrix multiplication, one softmax, and one probability average. No text encoding is performed in the timed inference loop.

4. Experiments

4.1. Datasets and Evaluation Protocol

We evaluate on ten datasets from the standard base-to-novel benchmark: Caltech101, OxfordPets, StanfordCars, OxfordFlowers, Food101, FGVC Aircraft, SUN397, DTD, EuroSAT, and UCF101. They cover generic objects, fine-grained categories, food, aircraft, scenes, textures, remote sensing, and human actions. We use the public class splits associated with CoOp and CoCoOp [2, 3]. ImageNet is not included because a verified local run was unavailable; therefore all averages in this paper are explicitly ten-dataset averages.

For every trainable method, we use 16 shots per base class and random seeds 1, 2, and 3. We first average base and novel accuracy over seeds and then compute dataset-level HM using Eq. (1). Cross-dataset summaries are unweighted macro averages over the ten dataset-level values. Zero-shot CLIP has no training seed.

4.2. Implementation Details

All local experiments use OpenAI CLIP ViT-B/16. CoOp uses four context tokens, batch size 16, SGD with learning rate 0.002 and momentum 0.9, cosine scheduling, and 20 epochs. Images are resized to 224×224 with the CLIP normalisation. The description branch uses up to 20 stored descriptions per class and the same frozen CLIP logit scale as the learned branch. The mixing coefficient is always 0.5.

The local CoCoOp baseline follows its standard recipe with four context tokens, batch size 1, and 10 epochs. It shares the backbone, shots, class splits, and three seeds with our evaluation, but its training budget is not identical to the 20-epoch CoOp recipe. We therefore treat it as a standard-recipe baseline rather than an equal-compute ablation.

4.3. Baselines and Reporting Boundary

The locally evaluated baselines are zero-shot CLIP, CoOp, and CoCoOp. Their results are separated from published numbers for CuPL, CoCoOp, KgCoOp, MaPLe, and PromptSRC [8, 3, 6, 5, 7]. Published values are used only for positioning and are marked with †; they are not claimed as local reproductions.

5. Results

5.1. Local Base-to-Novel Comparison

Table 1 reports dataset-level HM. TextConsistency reaches 78.75 on average, compared with 71.88 for zero-shot CLIP, 75.33 for matched CoOp, and 76.15 for local CoCoOp. The gains are 3.42 percentage points over CoOp and 2.60 points over CoCoOp. TextConsistency exceeds local CoCoOp on all ten datasets.

Table 2 separates base and novel accuracy. Relative to CoOp, TextConsistency changes the average base accuracy from 81.88 to 81.58 while improving novel accuracy from 70.50 to 76.44. The 5.94-point novel gain is therefore the

Table 1: Locally evaluated harmonic-mean accuracy (%) on ten base-to-novel benchmarks. All methods use CLIP ViT-B/16 and the official class splits. CoOp, CoCoOp, and TextConsistency are averaged over three seeds.

Method	UCF	DTD	Air.	Euro.	Flw.	Cal.	Pets	Food	Cars	SUN	Avg.
Zero-shot CLIP	74.49	56.68	31.30	60.33	74.46	95.61	94.15	90.59	68.83	72.36	71.88
CoOp	74.42	63.79	34.26	67.52	81.07	95.95	96.39	90.51	72.35	77.05	75.33
CoCoOp	77.75	62.91	34.31	72.91	81.16	95.44	96.46	90.89	71.79	77.92	76.15
TextConsistency	79.47	70.99	38.46	76.65	85.06	96.09	96.63	91.30	73.16	79.74	**78.75**

Table 2: Ten-dataset macro averages (%). HM is computed for each dataset before macro averaging.

Method	Base	Novel	HM
Zero-shot CLIP	69.22	74.94	71.88
CoOp	81.88	70.50	75.33
CoCoOp	81.15	72.46	76.15
TextConsistency	81.58	76.44	78.75

main source of the improved balance. Relative to local CoCoOp, TextConsistency improves both the macro base and novel averages, although this comparison uses the standard training recipe of each method rather than equal epochs.

The improvement over CoOp is positive for every dataset and all 30 seed-level comparisons. It is largest on EuroSAT, DTD, UCF101, FGVC Aircraft, and OxfordFlowers. The gains on Caltech101, OxfordPets, Food101, and StanfordCars are smaller, which indicates that the frozen semantic branch is most useful when the learned prompt exhibits a larger base-novel gap.

5.2. Comparison with Published Results

Table 3 recomputes a ten-dataset average using the datasets common to all listed methods. TextConsistency is 5.22 points above CuPL, 3.09 points above the published CoCoOp values, and 1.66 points above KgCoOp. Its 78.75 average is effectively tied with MaPLe at the reported precision and is 1.59 points below PromptSRC. Because these are paper-reported values from different implementations, the table should be interpreted as positioning rather than a controlled ranking. In particular, the result does not support a state-of-the-art claim.

Table 3: Comparison with published base-to-novel HM results on the ten datasets common to all methods. Published values are marked with † and are not local reproductions.

Method	UCF	DTD	Air.	Euro.	Flw.	Cal.	Pets	Food	Cars	SUN	Avg.
CuPL†	76.40	61.30	33.20	61.80	76.10	95.60	95.80	90.60	68.80	75.70	73.53
CoCoOp†	77.64	64.85	27.74	71.21	81.71	95.84	96.43	90.99	72.01	78.27	75.67
KgCoOp†	79.65	64.35	34.83	73.48	83.65	96.03	96.18	91.09	73.36	78.36	77.10
MaPLe†	80.77	68.16	36.50	82.35	82.56	96.02	96.58	91.38	73.47	79.75	78.75
PromptSRC†	82.74	71.75	40.15	82.32	85.95	96.02	96.30	91.10	76.58	80.52	80.34
TextConsistency	79.47	70.99	38.46	76.65	85.06	96.09	96.63	91.30	73.16	79.74	**78.75**

Table 4: Component comparison using HM (%). The description branch is frozen. Both fusion variants use a fixed weight of 0.5.

Method	UCF	DTD	Air.	Euro.	Flw.	Cal.	Pets	Food	Cars	SUN	Avg.
CoOp	74.42	63.79	34.26	67.52	81.07	95.95	96.39	90.51	72.35	77.05	75.33
Description only	76.46	63.30	34.83	69.99	76.69	96.29	95.27	90.58	67.53	76.73	74.77
Logit fusion	78.76	70.75	38.31	75.69	83.73	96.09	96.64	91.30	72.86	79.54	78.37
Probability fusion	79.47	70.99	38.46	76.65	85.06	96.09	96.63	91.30	73.16	79.74	**78.75**

5.3. Component Analysis

The description-only branch obtains 74.77 average HM, below CoOp at 75.33. Its value lies in complementarity rather than standalone strength. Fixed logit fusion raises the average to 78.37, showing that combining the two semantic sources is already effective. Probability fusion further raises it to 78.75 and is the final method. The same coefficient is used for every dataset; the difference is not produced by dataset-specific weight selection.

The description branch is deterministic for a fixed dataset and split. Repeating it alongside three CoOp checkpoints does not constitute three independent description-model trainings. Our statistical unit for the trainable branch remains the three CoOp seeds.

5.4. Stability Across Seeds

For each seed, we compare TextConsistency and CoOp using predictions from the same trained checkpoint. All 30 paired HM differences are positive. On the first five completed datasets, the mean paired gains were +5.07 on UCF101, +7.19 on DTD, +4.20 on FGVC Aircraft, +9.88 on EuroSAT, and +4.01 on OxfordFlowers. The remaining five datasets also produced three positive seed-level differences each. Because each dataset has only three seeds, we use these results as evidence of directional stability and do not make strong significance claims from small-sample confidence intervals.

Table 5: Inference efficiency on one RTX 4090 using the UCF101 novel split. Text features are pre-computed.

Method	Batch	ms/batch	img/s	Extra latency
CoOp	1	18.827	53.12	0.00%
TextConsistency	1	18.904	52.90	0.41%
CoOp	64	90.128	710.10	0.00%
TextConsistency	64	90.796	704.88	0.74%

5.5. Inference Efficiency

Table 5 reports CUDA-event measurements on one RTX 4090. Each setting uses 20 warm-up iterations followed by 100 timed iterations on the same UCF101 novel checkpoint and input tensors. At batch size 64, TextConsistency increases latency from 90.128 to 90.796 ms per batch, an overhead of 0.74%. Incremental peak memory is unchanged at the allocator resolution used in this experiment. These measurements exclude model loading, disk I/O, CPU preprocessing, and one-time text encoding.

6. Discussion and Limitations

The experiments support a narrow conclusion: a fixed posterior average can recover useful frozen semantics that CoOp underuses after base-class adaptation. They do not show that natural-language descriptions are universally superior to learned prompts. The description-only average is lower than CoOp, and the smallest fusion gains occur on datasets where the two branches are already similarly strong.

Several limitations remain. First, ImageNet is absent, so the ten-dataset average cannot be compared directly with the common eleven-dataset benchmark average. Second, the local CoCoOp baseline uses its standard 10-epoch recipe while CoOp and TextConsistency use 20 epochs. Third, description quality depends on the stored language used for each class; we do not study different language models, prompt-generation instructions, or annotation budgets. Fourth, the coefficient 0.5 is intentionally fixed for simplicity, but this may be suboptimal for individual datasets. Finally, the efficiency result is measured on one GPU and should not be treated as a hardware-independent latency guarantee.

The full experimental evidence was accumulated in audited batches with frozen data splits, seeds, source hashes, checkpoints, raw predictions, and

independent recomputation. This makes the reported values traceable, although a future single-release rerun including ImageNet would provide a cleaner eleven-dataset benchmark package.

7. Conclusion

We presented TextConsistency, a parameter-free extension to CoOp that averages the class probabilities from learned prompts and frozen class descriptions. The method keeps CLIP frozen, leaves prompt training unchanged, uses a single fixed fusion coefficient, and caches the description prototypes. Across ten base-to-novel datasets, it improves average HM from 75.33 to 78.75 over matched CoOp and exceeds locally evaluated CoCoOp on every dataset. Component results show that the benefit comes from combining complementary branches, and an RTX 4090 measurement shows less than one percent batch-64 latency overhead. The current evidence supports TextConsistency as a simple and reproducible method for improving novel-class balance, while ImageNet evaluation and broader description-generation studies remain future work.

Data and Code Availability

The implementation, frozen configurations, result tables, audit scripts, and experiment archives are available in the accompanying project repository. The release separates local reproductions from published comparison values and includes machine-readable CSV and JSON summaries.

References

[1] A. Radford, J. W. Kim, C. Hallacy, A. Ramesh, G. Goh, S. Agarwal, G. Sastry, A. Askell, P. Mishkin, J. Clark, G. Krueger, I. Sutskever, Learning transferable visual models from natural language supervision, in: Proceedings of the 38th International Conference on Machine Learning, 2021, pp. 8748–8763.

[2] K. Zhou, J. Yang, C. C. Loy, Z. Liu, Learning to prompt for vision-language models, International Journal of Computer Vision 130 (2022) 2337–2348.

[3] K. Zhou, J. Yang, C. C. Loy, Z. Liu, Conditional prompt learning for vision-language models, in: Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition, 2022, pp. 16816–16825.

[4] Y. Lu, J. Liu, Y. Zhang, Y. Liu, X. Tian, Prompt distribution learning, in: Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition, 2022, pp. 5206–5215.

[5] M. U. Khattak, H. Rasheed, M. Maaz, S. Khan, F. S. Khan, MaPLe: Multi-modal prompt learning, in: Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition, 2023, pp. 19113–19122.

[6] H. Yao, R. Zhang, C. Xu, Visual-language prompt tuning with knowledge-guided context optimization, in: Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition, 2023, pp. 6757–6767.

[7] M. U. Khattak, S. T. Wasim, M. Naseer, S. Khan, M.-H. Yang, F. S. Khan, Self-regulating prompts: Foundational model adaptation without forgetting, in: Proceedings of the IEEE/CVF International Conference on Computer Vision, 2023, pp. 15190–15200.

[8] S. Pratt, I. Covert, R. Liu, A. Farhadi, What does a platypus look like? generating customized prompts for zero-shot image classification, in: Proceedings of the IEEE/CVF International Conference on Computer Vision, 2023, pp. 15691–15701.

[9] R. Zhang, R. Fang, W. Zhang, P. Gao, K. Li, J. Dai, Y. Qiao, H. Li, Tip-adapter: Training-free adaption of CLIP for few-shot classification, in: European Conference on Computer Vision, 2022, pp. 493–510.