JAVA PROGRAMMING PRACTICES

Employee Constructor Overloading

Basic Information

Week	Week 4–5
Source file	EmployeeConstructorOverloading.java
Concepts	Constructors, constructor overloading, classes, objects.

Objective / Aim

To implement employee constructor overloading using the concepts listed in the R23 Java Programming Practices syllabus.

System Requirements

JDK (Java Development Kit) and a text editor or Java IDE.

Algorithm / Logic Description

1. Define employee fields.
2. Create overloaded constructors.
3. Create employee objects and display their details.

UML / Program Structure

```
Employee
+ Employee(name, id)
+ Employee(all fields)
+ display()
```

Source Code

```
class Employee
{
    String name, designation;
    int id;
    double salary;
    boolean promotionStatus;
    Employee(String name, int id)
    {
        this(name, id, "Trainee", 18000, false);
    }
    Employee(String name, int id, String designation, double salary, boolean promotionStatus)
    {
        this.name = name;
        this.id = id;
        this.designation = designation;
        this.salary = salary;
        this.promotionStatus = promotionStatus;
    }
    void display()
    {
        System.out.println("Name: " + name + ", ID: " + id);
        System.out.println("Designation: " + designation + ", Salary: " + salary);
        System.out.println("Promoted: " + promotionStatus + "\n");
    }
}
public class EmployeeConstructorOverloading
{
    public static void main(String[] args)
    {
        Employee e1 = new Employee("Ravi", 101);
        Employee e2 = new Employee("Priya", 102, "Developer", 42000, true);
        e1.display();
        e2.display();
    }
}
```

Compilation and Execution

```
javac EmployeeConstructorOverloading.java
java EmployeeConstructorOverloading
```

Output Screen

```
Name: Ravi, ID: 101
Designation: Trainee, Salary: 18000.0
Promoted: false

Name: Priya, ID: 102
Designation: Developer, Salary: 42000.0
Promoted: true
```

Result

The program demonstrates the listed syllabus concepts. The sample output is based on a compiled execution.