


PL/SQL Introduction

By
Parteek Bhatia
Assistant Professor
Dept of Comp Sc & Engg
Thapar University
Patiala

Procedural Language/Structured Query Language

- PL/SQL is an extension of the SQL language.
- It eliminates many restrictions of the SQL Language.
- PL/SQL extends SQL by adding control structures found in the other procedural languages.
- Procedural constructs blend seamlessly with Oracle SQL, resulting in a structured, powerful language.
- PL/SQL combines the SQL's language's ease of data manipulation and the procedural language's ease of programming.

Benefits of PL/SQL



Benefits of PL/SQL

Modularize program development


```

DECLARE
...
BEGIN
...
EXCEPTION
...
END;
  
```

Features of PL/DQL

- Supports the declaration and manipulation of object types and collections.
- Exception Handling
- Allows the calling of external functions and procedures.
- Triggers
- Cursors
- Support for SQL
- Support for Object-Oriented Programming

Architecture of PL/SQL



Arithmetic operators

Operator	Examples	Description
+	2+5; x+y;	Adds two operands
-	8-2; x-y;	Subtracts the second operand from the first
*	2*5; x*y	Multiplies two operands
/	12/2; x/y;	Divides the first operand by the second
**	3**2; x**2;	Raises the first operand to the exponent of the second

Expression operators

Operator	Examples	Description
:=	x:=y;a:=b*c;	Assigns the value of the operand or expression on the right to the operand on the left.
..	1..5; 4..d ; 4..d-1;	Defines an integer range from the first operand to the second.
	'kit' 'kat'; x y	Concatenates two or more strings.

Comments

- Comments can be single line or multiple lines.
- Single line comment:
Begins with -- can appear within a statement, at end of line.
Example: a number; --variable declaration
- Multi line comment
Begin with /* and end with an asterisk-slash (/).
Example
/* Statements to select rate and quantity into variables and calculate value */

Declaration of Variables

Declare
age number (4) ;
Done Boolean ;

Variable Value Assignment

Three ways:

- With Assignment operator
a := b * c ;
increase := sal * 1.5 ;
OK := false ;
- With substitute variables
a:=&enter_number;
b:=&b;
- With Select into statement
Select col_name into var_name where cond;

Variable Value Assignment

- Select ename into e from emp where empno=100;
- SELECT sal * 0.15 INTO increased FROM emp where empno = emp_id ;
- In this case SELECT statement must return a single record, if it returns no record or more than one record then an error is raised.

Wap to calculate total sal of emp having empno 100. Table emp1 having empno, ename, bp, da, hra, total columns.

Constant Declaration

It may be useful for you to declare constants in the declaration section of the PL/SQL blocks developed as well. Constants are named elements whose values do not change.

For example, pi can be declared as a constant whose value 3.14 is never changed in the PL/SQL block. The declaration of a constant is similar to that of declaration of a variable. We can declare constants in the declaration section and use it elsewhere in the executable part. To declare the constant we must make use of the keyword constant. This keyword must precede the data type as shown below.

```
pi constant number := 3.14;
```

Variable Attributes

- Attributes allow us to refer to data types and objects from the database. PL/SQL variables and constants can have attributes. The following are the types of attributes, which are supported by PL/SQL.

- %TYPE
- %ROWTYPE

Variable Attributes


- %type
DECLARE
eno emp.emp_no%type;
- %rowtype
rec emp%rowtype;

Displaying user messages

- DBMS_OUTPUT.PUT_LINE('ENTER THE NUMBER');
- DBMS_OUTPUT.PUT_LINE('Result of Sum operation is: ' || sum);
- To display messages to the user the SERVEROUTPUT should be set to ON. Here, DBMS_OUTPUT is a package name and PUT_LINE is a function.
- Syntax:
- SET SERVEROUTPUT [ON/OFF];

Control structures of PL/SQL

- Conditional Control
- Iterative Control
- Sequential Control



Conditional Control

- IF-THEN END IF; STATEMENT
- IF- THEN – ELSE STATEMENT
- IF-THEN-ELSIF STATEMENT (LADDER IF)

Conditional Control

```

IF a > b THEN
  dbms_output.put_line('a is greater');
END IF;
IF A > B THEN
  DBMS_OUTPUT.PUT_LINE(' A IS GREATER ');
ELSE
  DBMS_OUTPUT.PUT_LINE(' B IS GREATER ');
END IF;

```

```

IF A > B THEN
ELSIF COND THEN
ELSIF COND THEN
ELSIF COND THEN
ELSE
END IF;

```

Illustration of IF-THEN-ELSIF, PL/SQL block to calculate addition, subtraction, multiplication and division of two numbers according to user choice.

Iterative Control

- Simple Loop Statement
- While Loop Statement
- For Loop Statement

Iterative Control

■ Simple LOOP Statement

LOOP

sequence_of_statements;

END LOOP;

Need to use EXIT or EXIT WHEN to exit out of loop.

IF c > 5 THEN		EXIT WHEN c > 5;
EXIT;		
END IF;		

Loop Labels

```

<<label_name>>
LOOP
  sequence_of_statements;
END LOOP;
<<my_loop>>
LOOP
  ...
END LOOP my_loop;

<<outer>>
LOOP
  ...
  LOOP
    ...
    EXIT outer WHEN ... /* exit both loops, if we only use EXIT WHEN
                        without label it exit only the inner loop */
  END LOOP;
  ...
END LOOP outer;

```

WHILE-LOOP

WHILE condition LOOP

sequence_of_statements;

END LOOP;

WHILE i <= 10 LOOP

a:=n*i;

i:=i+1;

END LOOP;

Illustration of WHILE LOOP, PL/SQL block to print multiplication table any number

FOR-LOOP Statement

```
FOR counter IN [REVERSE] lower_bound..higher_bound LOOP
    sequence_of_statements;
END LOOP;

FOR i IN 1..3 LOOP -- assign the values 1,2,3 to i
    sequence_of_statements; -- executes three times
END LOOP;

FOR i IN 3..1 LOOP -- assign the value 3 to i
    sequence_of_statements; -- executes one time
END LOOP;

FOR i IN REVERSE 1..3 LOOP -- assign the values 3,2,1 to i
    sequence_of_statements; -- executes three times
END LOOP;
```

To design a for loop that execute for multiple of n only

```
FOR j IN 5..15 LOOP
    IF MOD(j, 5) = 0 THEN -- pass multiples of 5
        sequence_of_statements; -- j has values 5,10,15
    END IF;
END LOOP;
```

Scope Rules

```
FOR ctr IN 1..10
    LOOP
        ...
    END LOOP;
sum := ctr - 1; -- illegal

DECLARE
    ctr INTEGER;
BEGIN
    ...
    FOR ctr IN 1..25 LOOP
        ...
        IF ctr > 10 THEN
            ... -- refers to loop counter
        END LOOP;
    END;
END;
```

Scope Rules

```
<<main>>
DECLARE
    ctr INTEGER;
BEGIN
    ...
    FOR ctr IN 1..25 LOOP
        IF main.ctr > 10 THEN
            ... -- refers to global variable
            ctr --local
        END LOOP;
    ctr
END main;
```

Sequential Control

- GOTO statement
- NULL statement
- **GOTO Statement**

```
BEGIN
    ...
    GOTO insert_row;
    .....
    <<insert_row>>
    INSERT INTO emp VALUES
    ...
    -END;
```

Null Statement

```
LOOP
    ....
    IF done THEN
        GOTO end_loop;
    END IF;
    ...
    <<end_loop>> -- illegal
END LOOP; -- not an executable statement

Solution is:
LOOP
    ...
    IF done THEN
        GOTO end_loop;
    END IF;
    ...
    <<end_loop>> -- illegal
    NULL; -- an executable statement
END LOOP; -- not an executable statement
END;
```

Thanks

Lets Implement it in Lab Session