Session Transcripts - README

Session Transcripts (for submission)

This directory stores the OpenCode session records for each stage of this assignment (Markdown format, exported by OpenCode). Each file name is the session ID; the "Stages covered / related bug_log" column below was annotated after manually checking the transcript contents.

File	Machine	Model	Stages covered	Related `bug_log`
`session_ses_ecfe1d76cffeFXkR4UhF919VsK.md`	macOS (`/Users/gu/...`)	big-pickle (opencode free model)	**Main experiment session**: Step 0 EDA → Step 1 data processing → Step 2 LSTM v1 → Step 2b LSTM v2 → Step 3 Transformer → Step 4 generalizable pipeline → export this session	`#1`–`#5`, `#7`
`session_ses_ecf6aab1dffe9TrI5dirH4narT.md`	Windows	big-pickle (opencode free model)	**Step 4b feature selection** (fixing `#6`) + Advanced A local LLM installation attempt and actual deployment	`#6`
`session_ses_ecf6cf53effeDP3ie6Gr4zOzp3.md`	Windows	big-pickle (opencode free model)	Continued session: Step 4b result acceptance + Advanced A discussion (local LLM plan)	`#6`
`session_ses_ed05f4596ffeupDaEUn3uolw38.md`	Windows	big-pickle (opencode free model)	Initialize git and push the remote repository	— (engineering process)
`session_ses_ecf6daf88ffe8Pc7Istneu3XqR.md`	Windows	big-pickle (opencode free model)	Pull the content of the remote repository	— (engineering process)

Notes

- The **3 erroneous/suboptimal code suggestions** required by the report correspond respectively to:
  - `#5` (no validation set / no early stopping → overfitting) and `#7` (test-set leakage) — see the macOS main session `ses_ecfe1d76...`;
  - `#6` (generalizable pipeline without feature selection) — see `ses_ecf6aab1...` and `ses_ecf6cf53...`.
- The sessions preserve the complete "going astray → correction" process, corresponding entry by entry to `report/bug_log.md`.
- The main experiment took place on a macOS machine (path `/Users/gu/Desktop/assignment_2`), then migrated to Windows (this repository's path) to continue Step 4b and Advanced A.

- To re-export: use `opencode session list` to find the sessionID, then `opencode export <sessionID>`.