

ES7411 Specifications

OKI

Open up your dreams



Superior performance with low cost of ownership for enterprise workgroups

When productivity in the workplace really matters, and your team is taking on tight deadlines and demanding workloads, you need a network colour printer you can really depend on. The ES7411 with ultra-reliable digital LED technology, rapid throughput and a robust yet compact design, delivers enterprise-class performance that won't let you down.

And that's not all. With its superb print quality, exceptional media flexibility, superior energy efficiency and a genuinely low total cost of ownership, the ES7411 is a solid investment in the future of your business.

Print more, faster

- Enterprise-class colour print speeds of 34ppm and 36ppm black & white
- First colour page prints in just 9 seconds (8 seconds black & white)
- Generous 256MB RAM and 533MHz processor for rapid throughput
- Large paper supply, extendable to 1,690 sheets

Handle heavy workloads with ease

- Flat paper path copes more easily with high print volumes
- Heavy-duty materials, rugged components and ultra-reliable digital LED technology
- User-replaceable, quick-change toners for maximum uptime

Reduce and control your print costs

- Attractive price tag and low cost per page
- High-yield toners and long-life image drums
- Consumes just 1.2 watts in sleep mode, reducing energy bills
- Print Control software helps you manage print volumes by restricting usage
- PrintSuperVision software lets you track usage and monitor and manage your printers
- Colour Access Policy Manager lets you control and monitor the use of colour

Professional print quality

- ProQ2400 Multi-level output quality, 1200 x 600dpi print resolution
- Microfine High Definition toner ensures documents are sharper, crisper and glossier, even on ordinary office paper

First class media flexibility

- Paper sizes from A6 to A4, plus 210 x 1200mm banners
- Print on stock from 64 to 250gsm
- Print on specialist media including business cards, CD labels and polyester film

Impeccable security

Now you can remove the risk of sensitive information falling into the wrong hands with the Secure Print² utility. A print run can only start when you enter your private PIN at the printer, and data is encrypted before sending and securely erased after use.



EXECUTIVE
SERIES

ES7411 - Colour and Mono Printer

PRINTER	
A4 Print speed	34ppm colour, 36ppm mono
Time to first print	9 seconds colour, 8 seconds mono
Warm up time	Up to 60 seconds from power on & up to 35 seconds from power save
Processor speed	533MHz
PRINT QUALITY	
Resolution	ProQ2400 Multi-level technology, 1200 x 600dpi, 600 x 600dpi
Enhancements	Auto Colour Balance, Photo Enhance via driver (excludes Mac and PostScript drivers)
TYPEFACES	
Printer fonts	Scalable: 87 PCL fonts and 136 PostScript fonts, PCL Bitmap fonts, OCR-A/B, USPS ZIP Barcode
Barcode	Barcode with Checksum support
INTERFACE AND SOFTWARE	
Connectivity	Hi-Speed USB, 10/100-TX Ethernet, IEEE 1284 Bi-directional Parallel
Printer languages	PCL 6 (XL3.0) and PCL5c, PostScript 3 emulation, SIDM (IBM-PPR, EPSON-FX), PDF Direct Print v1.7, XPS
Network & protocols	All major network protocols supported via ethernet card with internal web server for printer and network card set-up and management. TCP/IP: ARP, IPv4/v6, ICMPv4/v6, TCP, UDP, LPR, FTP, TELNET, HTTP(IPP), BOOTP, DHCP, SNMPv1/v3, DNS, DDNS, UPnP, Bonjour, WINS, SSL/TLS, SMTP, POP3, SNT, WSDPrint, JetDirect protocols. NetBIOSoverTCP, NetWare 3.x, 4.x, 5.x and 6 with full NDS and NDPS support:- PServer, RPrinter, NDPS supported via dedicated OKI NDPS Gateway. AppleTalk:- ELAP, AARP, DDP, AEP, NBP, ZIP, RTMP, ATP, PAP. NetBEUI:- SMB, NetBIOS. Other:EAP
OS Compatibility¹	Windows 2000 / XP Home / XP Professional / XP Professional x64 / Server 2003 / Server 2003 x64 / Server 2008 / Server 2008 x64 / Vista (32-bit & 64-bit); Mac OS X 10.3.9 - 10.6.1
Advanced networking and security	IPv6, 802.1x authentication, SNMPv3, SSL/TLS HTTPS encryption, Secure Print ² , Secure Erase ² , Data encryption ² , MAC filtering, IP filtering, IPSec
Utility Suite³	Color Correct, OKI LPR ³ , PrintSuperVision.net ³ , Swatch Utility, Template Manager ³ , Web Driver Installer ³ , Print Control Server ³ , Print Control Client, Storage Device Manager ^{2&3} , Gamma Utility, Profile Assistant ² , Color Access Policy Manager ³

¹ Check local OKI Executive Series website for latest driver releases and OS compatibility; ²SDHC Memory Card required; ³Windows only; ⁴Secure Digital High Capacity (SDHC) Memory Card supports up to 32GB. OKI is not responsible for any compatibility risk using non OKI genuine SDHC Memory Card; ⁵Including all consumables.

Consumables Information: For the protection of your printer, and in order to ensure that you benefit from its full functionality, this model has been designed to operate only with genuine OKI toner cartridges. These can be identified by the OKI trademark. Any other toner cartridge may not operate at all, even if it is described as "compatible", and if it does work, your printer's performance and print quality may be degraded.

PAPER HANDLING	
Paper capacity	Tray 1: 530 sheets of 80gsm; Multi-purpose tray: 100 sheets of 80gsm
Paper capacity optional trays	Tray 2: 530 sheets of 80gsm; Tray 3: 530 sheets of 80gsm;
Maximum paper capacity	1,690 sheets of 80gsm
Paper sizes	Tray 1/2/3: A4, A5, B5; Multi-purpose tray: A4, A5, B5, A6; 10 Envelopes (Com-9, Com-10, DL, Monarch, C5); Labels (Avery 7162, 7664, 7666); Custom size (up to 1200mm length including Banner); Duplex: A4, A5, B5; Custom Size: Width 148-215.9mm Length 210-355.6mm
Paper weight	Tray 1/2/3: 64 to 220gsm; Multi-purpose tray: 64 to 250gsm Duplex: 64 to 220gsm
Duplex	Optional
Paper output	350 sheets face down tray, 100 sheets face up tray (80gsm)

GENERAL FEATURES	
Memory	Standard RAM: 256MB; Maximum RAM: 768MB Optional SDHC Memory Card⁴: 16GB
Operating conditions	Temperature/Humidity: 10°C to 32°C (17°C to 27°C recommended) / 20% to 80% RH (50% to 70% RH recommended) Storage: -10°C to 43°C, 10% to 90% RH
Power supply	Single phase 220 to 240VAC, frequency 50/60Hz +/- 2%
Power consumption	Typical: 600W; Max: 1300W; Idle: 100W (average); Power Save: <15W Sleep: 1.2W
Noise level	Operating: 54dB(A) Standby: 37dB(A) Power save: Background level
Dimensions (HxWxD)	389 x 435 x 604mm
Weight⁵	31kg
Warranty	3 years extended warranty upon registration within 30 days of purchase ⁶
Product order number	ES7411: 44205415; ES7411dn: 44205415dn; ES7411dtn: 44205415dtn

ACCESSORIES (ORDER NUMBERS)

2nd paper tray	44274503
3rd paper tray	44274503
Duplex	44274303
Memory	512MB: 44302207
SDHC Memory Card⁴	16GB: 44301003

CONSUMABLES (ORDER NUMBERS)

Toner cartridges* (11,500 pages)	Cyan: 44318639; Magenta: 44318638; Yellow: 44318637
Toner cartridge* (11,000 pages)	Black: 44318640
Image drum** (20,000 pages)	Cyan: 44318523; Magenta: 44318522; Yellow: 44318521; Black: 44318524
Transfer Belt (60,000 pages)	44341903
Fuser Unit (60,000 pages)	44289104

*Toners: A4 pages yield compliant with ISO/ISC 19798. Printer shipped with toner for 2,100 A4 pages yield compliant with ISO/ISC 19798.

**Drum: Average number of A4 pages printed.

Scan here to find out more



3 Year On-site Warranty⁶

⁶Our devices are manufactured to the highest standards of quality and technology, which has been confirmed by independent tests. We are so convinced of the high quality of our products that we are offering you an extension of the standard warranty period to 3 years at no extra cost to you. Simply register your product within 30 days of purchase to be eligible for our unique all inclusive offer. Fully covered by OKI! For further information please visit: [HTTP://WARRANTY.OKI.COM.AU](http://warranty.oki.com.au) Without registration, the standard Australian 1 year warranty applies.

OKI DATA AUSTRALIA PTY. LTD.

Level 1, 67 Epping Road
Macquarie Park, NSW 2113
Australia

T 1800 800 140

F 02 8071 0010

WWW.OKIEXECUTIVESERIES.COM.AU

OKI