Maximising Productivity

- Modular in design to meet your business demands
- XML open interface allows virtually any application to be delivered to your phone.
- Wideband CODEC for superior speech quality
- Built-in VPN (IP-Sec) support allows employees to work virtually anywhere, in or outside your organisation.

NEC's UNIVERGE Desktop IP Terminals provide all the features and functionality of traditional phones with the seamless integration of advanced IP applications. Integration of voice and data is no longer limited to the network or the PC desktop; it is now in the end-users' hands.

As an integral part of UNIVERGE360, Desktop IP Terminals connect people with the information, applications and tools that they need to drive business success. These intelligent terminals help your business take service and performance to newer, more profitable heights.

UNIVERGE Desktop IP Terminals are ergonomically designed for natural comfort and facilitate use through an array of menu-driven soft key functions and easy-access function keys. Together, these aspects of the terminal deliver power, versatility and programmability to all users, maximising efficiency and productivity.

Because the entire desktop surface is crafted for user productivity it fosters better speed, service and performance- the UNIVERGE Desktop IP Terminal delivers exactly what your business needs.

Features		DT750	DT730	DT710
Display	Display Size	Touch screen 320x240 dot TFT (65536 colour) LCS backlit	224×96 dot matrix gray scale Optional LCD backlit Optional 2nd display	6D: 168×41dot matrix Grey-scale LCD, not backlit
	Characters x Lines	Supports 2 proportional font sizes, 12 and 16 dot	Alphanumeric: 28×6 (7×16font) or 34×8 (6×12font) DESI-less line key display area: 12×1 & icon/line key	6D: 28×3 (6×12font)
	Tiltable	Yes	Yes	N/A
Keypad	Backlit Keypad	Yes	Yes	N/A
	Line Keys	LCD	24,32 DESI-less: 8x4 pages	2, 6
	Softkeys	4, help, exit	4, help, exit	4, help, exit
	Cursor keys	Yes	Yes	No
Built in applications	XML open interface	Yes	Yes	Yes (limited)
	Personal directory	Yes	Yes	Yes (speed dial)
	System directory	Yes	Yes	No
	Corporate directory	Yes	Yes	No
	Call history	Yes	Yes	Yes (last number)
Sound	Full duplex hands-free	Yes	Yes	Yes
	Downloadable ring tone	Yes	Yes	N/A
	Hold music	Yes	Yes	N/A
	CODEC	G.711, G.729A, G.722 (Wideband)		
Network	NAT traversal support	Yes	Yes	Yes
	VPN access	Yes	Yes	Yes
	Power	802.3af or AC	802.3af or AC	802.3af or AC
Optional adaptors & headsets	Bluetooth handset w hub adaptor	Future	Future	N/A
	Gigabit adapter	Yes	Yes	N/A
	Recording adapter	Yes	Yes	N/A
	PSTN survivable adapter	Yes	Yes	N/A
	Wired headset	Yes	Yes	N/A
Security	Authentication	Yes	Yes	Yes
	Encryption	Yes	Yes	Yes
Maintenance	Auto-configuration	Yes	Yes	Yes
	Network management	Yes	Yes	Yes
Characteristics	Dimensions (w x d x h) cm	22.7 × 25 × 11.2	24D: 17.91 × 25.8 × 11.2 32D (24D+8LK): 8.31 × 25.8 × 11.2 DESI-less: 17.91 × 27.2 × 11.2	2D: 17.9 × 22.5 × 11.2 6D: 17.9 × 22.5 × 11.2
	Weight (approx kg)	1.2	24D: 1 32D (24D+8LK): 1.2 DESI-less: 1.2	2D: 0.9 6D: 0.9
	Power (exl. Options) Ethernet IEEE802.3af	6.49 W	24D: 6.49 W DESI-less: 6.49 W	2D: 3.84 W 6D: 3.84 W
	AC Adaptor (optional)	27V 750mA	27V 750mA	27V 750mA

For more information, visit www.nec.com.au, email contactus@nec.com.au or call 131 632

If it can be imagined, it is possible.

Empowered by Innovation

NEC