



Features

Plastic IR Dome Camera
SONY/SHARP Colour CCD
3-Axis bracket built-in
IR LED: ϕ 5X21PCS IR LED working distance: 20M
Lens: 4-9mm Manual Zoom
Dimension : ϕ 149 x 99(H) mm

Specifications

Model	ID111
Image Sensor	1/3"SONY ICX639BK CCD
Horizontal Resolution	600TV Lines Low Illumination, WDR, OSD
Pixels	PAL:795 (H) \times 596(V) NTSC :811 (H) \times 508 (V)
TV System	PAL/NTSC
Lens	4-9mm Manual Zoom
Sync System	Internal
Usable Illumination	0.001Lux/F2.0
S/N Ratio	\geq 54dB (AGC OFF)
Gamma Correction	0.45
Video Out	Composite Signal (1.0Vp-p, 75 Ω)
Scanning System	PAL:625 Lines, 50 Field/Sec;NTSC:525 Lines, 60 Field/Sec
Electronic Shutter Time	Auto:PAL 1/50-1/100,000Sec;NTSC 1/60-1/100,000Sec
Operation Temperature	-10 $^{\circ}$ C \sim +50 $^{\circ}$ C RH95% Max
Storage Temperature	-20 $^{\circ}$ C \sim +60 $^{\circ}$ C RH95% Max
White Balance	Auto
Power Source	DC12V 450mA
Dimension	ϕ 149 x 99(H) mm
Weight	450g