



Features

Vandal proof Mini PTZ Speed Dome camera

Pan range: 0°~360° Continue (Not 355°)

Tilt range: 0°~90° Flip

Pan Speed: Max 50°/sec Pre-set: 16

Weatherproof Outdoor IP66

RS485, Pelco D/P supported

10X optical zoom lens(f=3.8~38mm)

Specifications

Model	PTZ10
Image Sensor	SAMSUNG 10X SDM-100, 1/4" Super HAD Color CCD, ICR, 10X(f=3.8~38mm)
Horizontal Resolution	Colour 500TVL,Black 570TVL
Pixels	PAL:795 (H)× 596(V) NTSC :811 (H) ×508 (V)
TV System	PAL/NTSC
Lens	10X optical zoom lens(f=3.8~38mm)
Sync System	Internal
Usable Illumination	
S/N Ratio	≥54dB (AGC OFF)
Gamma Correction	0.45
Video Out	Composite Signal (1.0Vp-p, 75Ω)
Scanning System	PAL:625 Lines, 50 Field/Sec;NTSC:525 Lines, 60 Field/Sec
Electronic Shutter Time	Auto:PAL 1/50-1/100,000Sec;NTSC 1/60-1/100,000Sec
Operation Temperature	-10°C ~ +50°C RH95% Max
Storage Temperature	-20°C ~ +60°C RH95% Max
White Balance	Auto
Power Source	DC12V 700mA
Dimension	138x212mm
Weight	2500g