



Features

Vandal proof IR Dome Camera
SONY/SHARP Colour CCD
IR LED: \varnothing 5X36PCS ,IR LED working Distance: 30M
Back Light Compensation(BLC)
Auto White Balance(AWB)
Lens: 2.8-10mm Manual Zoom Lens
Dimension : \varnothing 131 x 93(H) mm

Specifications

Model	VID222
Image Sensor	1/3" SONY ICX639BK CCD
Horizontal Resolution	600TV Lines Low Illumination, DWDR, OSD
Pixels	PAL:795 (H) \times 596(V) NTSC :811 (H) \times 508 (V)
TV System	PAL/NTSC
IR LED	\varnothing 5 X 36 PCS
IR Series Distance	30 M
Lens	4-9mm Manual Zoom Lens
Sync System	Internal
IR Status	Under 10 Lux By CDS
Usable Illumination	0.001Lux/F2.0
IR Power On	CDS Auto Control
S/N Ratio	\geq 54dB (AGC OFF)
Gamma Correction	0.45
Video Out	Composite Signal (1.0Vp-p, 75 Ω)
Scanning System	PAL:625 Lines, 50 Field/Sec;NTSC:525 Lines, 60 Field/Sec
Electronic Shutter Time	Auto:PAL 1/50-1/100,000Sec;NTSC 1/60-1/100,000Sec
Operation Temperature	-10 $^{\circ}$ C \sim +50 $^{\circ}$ C RH95% Max
Storage Temperature	-20 $^{\circ}$ C \sim +60 $^{\circ}$ C RH95% Max
White Balance	Auto
Power Source	DC12V 400mA
Dimension	\varnothing 131 x 93(H) mm
Weight	800g