ES7170 MFP Specifications





The ES7170 MFP mono A4 multifunction product (MFP) offers the tools you need to ensure the efficient use of resources within your organisation, improving communication and document workflow using the embedded open platform sXP (smart Extendable Platform). Combining print, copy, scan and fax^ functionality in one high speed, ergonomic device, the smart ES7170 MFP offers efficient and secure document management and output where only mono printing is required

Ultimate flexibility

The ES7170 MFP provides the configuration flexibility required to meet your current and future business needs.

- 3rd party software connectivity for seamless network integration
- Customisable 23cm backlit colour LCD touch

Improving business productivity

Robust and efficient, the ES7170 MFP has been designed to deliver an extensive range of high value features as standard to improve productivity.

- Up to 52ppm print speed in mono
- Paper capacity of up to 3,160 sheets
- Built-in convenience stapler

- Internal finisher for collating and stapling (dfn models)
- 1.2GHz processor and 2GB RAM memory
- Standard 160GB HDD
- 10/100/1000 baseT Ethernet

Highest level document and data security

Including security and encryption to the highest industry standards, the ES7170 MFP provides sophisticated user authentication that prevents unauthorised access and protects your corporate data, whilst user access can be customised, allowing you to enable or disable functions easily.

- Secure print job encryption
- SNMPv3 and optional IPSec secure networking
- PIN/IC Card/LDAP/Kerberos access control
- Secure print with PIN or with optional card reader (MIFARE /HID)

High definition LED scanning

For high definition scanning, the ES7170 MFP combines advanced LED technology with a full range of features that improve productivity and document workflow.

Fast scan and copy speeds of up to 55ipm and 52ipm

- Duplex scanning
- Scan to filing box, scan to shared folder, scan to email, scan to USB memory
- Blank page skipping

Clearer and sharper copying

The ES7170 MFP combines advanced LED technology with a full range of features that improve productivity and document workflow.

- Fast copy speeds of up to 52ppm
- ID Card copy, repeat copy, job build copy
- Duplex copying (1 to 2, 2 to 1, 2 to 2)
- Job Macro stores frequent tasks

Reducing your impact on the environment

The ES7170 MFP is the first full LED A4 large workgroup MFPs on the market.

- Duplex print, copy and scan or reduced paper usage
- High capacity toner cartridges
- Toner save function
- 2W or less in Deep Sleep mode
- Energy Star certified





ES7170dnMFP / ES7170dfnMFP - Mono Multifunction Product

PRINT		PAPER HANDLING	
A4 Print speed		Standard Paper capacity	Tray 1: 530 sheets of 80gsm; Multi-purpose tray: 100 sheets of 80gsm; RADF: 100 sheets of 80gsm
Time to first print Warm up time	5 seconds 35 seconds or less from power on, 19 seconds or less from power save	Optional Paper capacity	Tray 2: 530 sheets of 80gsm; Tray 3: 530 sheets of 80gsm; Tray 4: 530 sheets of 80gsm;
Processor speed	1.2GHz	Paper Input capacity	Large Capacity Feeder (LCF): 2,000 sheets of 80gsm Standard: Up to 630 sheets of 80gsm; Maximum: Up to 3,160
Resolution Printer fonts	600 x 600dpi, 1200 x 1200dpi Scalable: 80 PCL fonts & 138 PostScript fonts		sheets of 80gsm
SCAN	Calaba	Internal finisher	Internal finisher: Offset stacking, stapling - up to 50 sheets of 80gsm (dfn model only); Convenience stapler: Stapling - up to 20 sheets of 80gsm
Resolution	Up to 600 x 600dpi		Tray 1: A4, A5, B5; Tray 2/3/4: A4, A5, B5; Large Capacity Feeder: A4; Multi-purpose tray: A4, B5, A5, A6. Envelopes
Speed	Up to 40ipm/55ipm (Colour/Mono)	Paper sizes	(Com-9, Com10, DL, C5), Labels (Avery 7162, 7664, 7666).
Colour depth	Output 24 bit (8 bit x 3 RGB)	Paper Sizes	Support Custom size: Width 64-216mm Length 127-1321mm RADF: A4, A5, A6(simplex), B5; Duplex: A4, A5, B5. Supports
Document input Contrast	Up to 100 sheet Reverse-Automatic Document Feeder (RADF) 9 Levels		custom size: Width 148.5-216mm Length: 210-356mm
Format	PPEG, TIFF (multi/single page), PDF (multi/single page), Slim PDF, Secure PDF, XPS (multi/single page)	Paper weight	Tray 1: 64 to 220gsm; Tray 2/3/4: 64 to 220gsm; Large Capacit Feeder: 64 to 220gsm; Multi-purpose tray: 64 to 250gsm; RADI 60 to 105gsm; Duplex: 64 to 220gsm
Address book	LDAP & internal address book	Duplex	Standard
Scan to	SMB, FTP, FTPS, Netware, FilingBox, USB Memory, E-mail	Paper output	Face up: 100 sheets of 80gsm, Face down: 500 sheets of 80gsn (dn model); Face up: 100 sheets of 80gsm, Face down: 100
COPY	0		sheets of 80gsm, Finisher: 500 sheets of 80gsm (dfn model)
First copy out Speed		GENERAL FEATURES	
Resolution	600dpi		Standard RAM: 2GB
Reduction / Enlargement	25-400%	Memory	High Performance Secure HDD: 160GB
Maximum copies	999	Environment	Operating temperature/ humidity: 10°C to 32°C (17°C to 27°C recommended) / 20% to 80% RH (50% to 70% RH recommended)
FAX (OPTIONAL)		Power supply	Storage temperature/ humidity: -10°C to 43°C / 10% to 90% F Single phase 220–240VAC, frequency 50/60Hz +/- 2%
Connectivity Speed	RJ11 x 2 (Line/Tel), PSTN, PBX Line ITU-T G3(Super G3) up to 33.6kbps, 3 seconds/page		Typical: 870W; Max: 1500W; Idle: 120W; Power Save: 40W;
Internet faxing	ITU-T T.37	Power consumption	Deep Sleep: 2W or less
Fast dialing	Address book up to 3000 numbers	Noise level	Operating: 58dB(A) or less; Standby: 30dB(A) or less; Power save: Background level
Groups	Up to 200	Dimensions (HxWxD)	675 x 522 x 564mm (dn model); 811 x 522 x 564mm (dfn model)
Broadcast	Maximum 400	Weight ³	50kg approx (dn model); 60kg approx (dfn model)
Page memory	100 jobs, 1000 pages/job, and up to 1GB on HDD	Warranty	3 years extended warranty upon registration within 30 days of purchase^
INTERFACE AND SOFTWARE		Product order number	ES7170dnMFP: 45387314; ES7170dfnMFP: 45387414
Connectivity	10/100/1000 baseT, USB 2.0/ Hi Speed USB, Optional Wireless (802.11 b/g)	Accessories (Order Numb	ERS)
Embedded Open Platform Printer languages	sXP (smart Extendable Platform) PCL5e, PCL6, Postscript 3 Emulation, PDF emulation, XPS	Paper Feeders	2nd/3rd/4th paper tray: 45479002;
Fillitei taliguages	All major network protocols supported via ethernet card with	Castor base	Large Capacity Feeder: 45393302 45466602
Network & protocols	internal web server for printer and network card set-up and man- agement. TCP/IPv4&v6, SMTP, POP3, HTTP, SNMPv1&v3, DHCP, DNS, LPR, Port9100, ARP, FTP, SMB, LDAP, Bonjour, NetWare,	Engineer installed options	Fax: 45036923; Wireless: 45517901; Antenna: 45518001
	EtherTalk, LLTD, Web Service for Devices	Security	Data Overwrite enabler: 45518101; IPSec enabler: 45518401;
OS Compatibility¹	Windows 8 (32-bit & 64-bit) / Windows 7 (32-bit & 64-bit) / Vista SP1 & SP2 (32-bit & 64-bit) / XP SP2 or later / Server	Open platform	IC Card reader (HID): 45518501; IC Card reader (Mifare): 4551860 Meta scan enabler: 45518201
	2008 SP1 or later (32-bit & 64-bit) / Server 2003 SP2(32-bit & 64-bit) / Server 2008 R2 (64-bit) / Server 2012 (64-bit); Mac	CONSUMABLES (ORDER NUMBERS)	
Utility suite ¹	OS X 10.4/10.5/10.6/10.7/10.8; PPDs for Linux/Unix File Downloader, Address Book Viewer, Remote Scan Driver,	Toner cartridges* (36,000 pages)	Black: 45460503
	e-Filing Backup/Restore, Print Job Accounting ² , Print Job Accounting Enterprise ² , PrintSuperVision.NET ² , Output Manager, Fleet Manager, Template Manager ²	Image drum* (72,000 pages)	Black: 45456303
SECURITY		Fuser unit (200,000 pages)	45435104
	IP Filtering, MAC Filtering, IPSec (option), Secure Print, Secure	Convenience Stapler (3,000 staples)	45513301
Device Security	Print job encryption (by secure HDD), SMTP server authentication, POP before SMTP authentication, SSL Security for SMTP Protocol, SMMPv3, SSL/TLS Encryption, Port Change, Storage Device Encryption, Secure Erase, Disable Host USB feature		ା ଡୁ ISO/IEC 19752 coverage. Printer shipped with toner for 752.
Access Security	LDAP authentication	^Fax is optional engineer install	
Certification	CE Mark, Energy Star, GS Mark		es website for latest driver releases and OS compatibility;
OPERATOR PANEL		Consumables Information: For t	he protection of your printer, and in order to ensure that you
User Interface	23cm Colour backlit LCD touch screen & key top; 28 Hard Keys, 6 LED's	benefit from its full functionality, this model has been designed to operate only with genuine OKI toner cartridges. These can be identified by the OKI trademark. Any other toner cartridge may not operate at all, even if it is described as "compatible", and if it does work, your printer's performance and print quality may be degraded.	
	12 numeric, 6 main function buttons (Menu, Copy, Scan, Print, FilingBox, Fax), Power, Power save, Reset, Stop, Start Key,		

Optional Paper capacity	Tray 2: 530 sheets of 80gsm; Tray 3: 530 sheets of 80gsm; Tray 4: 530 sheets of 80gsm; Large Capacity Feeder (LCF): 2,000 sheets of 80gsm			
Paper Input capacity	Standard: Up to 630 sheets of 80gsm; Maximum: Up to 3,160 sheets of 80gsm			
Internal finisher	Internal finisher: Offset stacking, stapling - up to 50 sheets of 80gsm (dfn model only); Convenience stapler: Stapling - up to 20 sheets of 80gsm			
Paper sizes	Tray 1: A4, A5, B5; Tray 2/3/4: A4, A5, B5; Large Capacity Feeder: A4; Multi-purpose tray: A4, B5, A5, A6. Envelopes (Com-9, Com10, DL, C5), Labels (Avery 7162, 7664, 7666). Support Custom size: Width 64-216mm Length 127-1321mm; RADF: A4, A5, A6(simplex), B5; Duplex: A4, A5, B5. Supports custom size: Width 148.5-216mm Length: 210-356mm			
Paper weight	Tray 1: 64 to 220gsm; Tray 2/3/4: 64 to 220gsm; Large Capacity Feeder: 64 to 220gsm; Multi-purpose tray: 64 to 250gsm; RADF: 60 to 105gsm; Duplex: 64 to 220gsm			
Duplex	Standard			
Paper output	Face up: 100 sheets of 80gsm, Face down: 500 sheets of 80gsm (dn model); Face up: 100 sheets of 80gsm, Face down: 100 sheets of 80gsm, Finisher: 500 sheets of 80gsm (dfn model)			
GENERAL FEATURES				
	Standard RAM: 2GB			
Memory	High Performance Secure HDD: 160GB			
Environment	Operating temperature/ humidity: 10°C to 32°C (17°C to 27°C recommended) / 20% to 80% RH (50% to 70% RH recommended)			
Power supply	Storage temperature/ humidity: -10°C to 43°C / 10% to 90% RH Single phase 220–240VAC, frequency 50/60Hz +/- 2%			
	Typical: 870W; Max: 1500W; Idle: 120W; Power Save: 40W;			
Power consumption	Deep Sleep: 2W or less			
Noise level	Operating: 58dB(A) or less; Standby: 30dB(A) or less; Power save: Background level			
Dimensions (HxWxD)	675 x 522 x 564mm (dn model); 811 x 522 x 564mm (dfn model)			
Weight ³	50kg approx (dn model); 60kg approx (dfn model)			
Warranty	3 years extended warranty upon registration within 30 days of purchase [^]			
Product order number	ES7170dnMFP: 45387314; ES7170dfnMFP: 45387414			
Accessories (Order Numb	ers)			
Paper Feeders	2nd/3rd/4th paper tray: 45479002; Large Capacity Feeder: 45393302			
Castor base	45466602			
Engineer installed options	Fax: 45036923; Wireless: 45517901; Antenna: 45518001			
t	Data Overwrite enabler: 45518101; IPSec enabler: 45518401;			
Security	IC Card reader (HID): 45518501; IC Card reader (Mifare): 45518601			
Open platform	Meta scan enabler: 45518201			
Consumables (Order Numbers)				
Toner cartridges* (36,000 pages)	Black: 45460503			



3 Year On-site Warranty[^]

Our devices are manufactured to the highest standards of quality and technology, which has been confirmed by independent tests. We are so convinced of the high quality of our products that we are offering you an extension of the standard warranty period to 3 years at no extra cost to you. Simply register your product within 30 days of purchase to be eligible for our unique all inclusive offer. Fully covered by OKI! For further information please visit: HTTP://WARRANTY.OKI.COM.AU Without registration, the standard Australian 1 year warranty applies.

> Scan here to find out more



OKI DATA AUSTRALIA PTY. LTD.

Level 1, 67 Epping Road Macquarie Park, NSW 2113 Australia T 1800 800 140

F 02 8071 0010

WWW.OKIEXECUTIVESERIES.COM.AU



