



Features

Waterproof proof IR Dome Camera
IR Distance: 40M
IP66 design of the lens inside the outlet: 2.8-10mm manual focus zoom lens designed outside
DC12V/AC24V dual voltage option (plus 25RMB)
Size: 200 (W) x171 (H) x83 (D) mm
Weight: 1.3Kg

Specifications

Model	BIL555
Image Sensor	1 / 3 "SONY
Effective Pixels	600TV Line
Effective Pixels	PAL: 795 (H) × 596 (V) NTSC: 811 (H) × 508 (V)
TV standard	PAL / NTSC
IR infrared light	¢ 5 X42 PCS
IR Distance	40 M
Lens	4-9mm manual zoom lens
Synchronization system	Internal
IR Status	Under 10 Lux By CDS
Illumination can be used	0.001 Lux/F2.0 (IR LED ON)
IR Power On	CDS Auto Control
SNR	≥ 54dB (AGC OFF)
Gamma characteristics	0.45
Screen output	Composite Signal (1.0Vp-p, 75Ω)
Scanning System	PAL: 625 Lines, 50 Field / Sec; NTSC: 525 Lines, 60 Field / Sec
Electronic Shutter	Auto: PAL 1/50-1/100, 000Sec; NTSC 1/60-1/100, 000Sec
Operating Temperature	-10 °C ~ +50 °C RH95% Max
Storage temperature	-20 °C ~ +60 °C RH95% Max
White Balance	Auto
Power Consumption	DC12V 600mA
Size	200 (W) x171 (H) x83 (D) mm
Weight	1300g