NOTES

DATE

MCQ assessment

Q1 ans a, b, c

Q2 ans b

Q3 ans all the answer or option are valid.

Q4 ans a

Q5 ans a, b

Q6 ans d

Q7 ans c (plt. savefig)

Q8 ans a

Q9 ans b

Q10 ans a, c

Q11 ans b, c

Q12 ans c

Q13 ans all the above option are correct.

i) np.random.randint()

ii) np.random.rand(), np.random.randn().

iii) np.random.shuffle().

PAGE

NOTES

DATE

Q14 ans a , b , c

Q15 ans a

Q16 ans c

Q17 ans a

Q18 ans a

Q19 ans a

Q20 ans b

Q21 ans b

Q22 ans b

Q23 ans a

Q24 ans d

Q25 ans a

Q26 ans a

Q27 ans a

Q29 ans b

Q30 ans c

PAGE

NOTES

DATE

Scenario based Question

Q 1

- First I load the dataset
- then print to number of null value using isnull().sum() func
- and print those ~~value~~ column that doesn't have null value or using a dropnal function along will inplace=True and then perform on dataset.

Q2 in the churn prediction model I would suggest to use Logistic Regression model because it is provide probabilities and It is easy to find factors that influencing churn.

Q3 In this kind of problem statement I would try to find the region from where customers interacting or not interacting with retailers.

- reason ~~that~~ behind the interaction ~~or~~ not interaction

- Division of products that slightly in demanding for the reason and ~~not~~ demanding on the reason and why. full the requirement along with the not in demanding and increase in the sale
- option or need or requirement that effecting sales or behavior of a customer.

PAGE

NOTES DATE

Q1 firstly categorical variable has to be converted into numerical format such that ML algorithm can work effectively there are some encoding methods that can be used
Label Encoding, Mean Encoding

★ Concept BASSED QUESTIONS.

Q1 It is a regression analysis where two or more independent variable in a regression model are highly correlated with each other

To handle ~~colinearity~~ multicolinearity in regression analysis there are few ~~ste~~ techniques

correlation Analysis
Variable selection
feature Engineering
Collect more data.

Q2 Outliers are the datapoints that are from the rest of the data in dataset, where in regression modeling outliers impact on model, or leading to biased parameters or reduce model accuracy

To find outlier ~~ep.~~ or to handle outlier we can use
Model fit.
visual inspection
Z-score
Data transformation

PAGE

NOTES DATE

Q3 overfitting is common challenge in regression modeling and ML in general. It caught when a model is over complex poor generalization, Model complexity, Increased in error

Q4 when dealing with non-linear relationship b/w the target variable, regression model may not find the underlying concepts effectively. To enhance regression model in such cases polynomial regres is a valuable technique.

polynomial regression.

$$Y = \beta_0 + \beta_1 X + \beta_2 X^2 + \ldots + \beta_n X^n + \varepsilon$$

where β is a cofficient
X is predictor variable
n is the degree of the polynomial.

Concept and consideration.
Overfitting
feature engineering
visualization
Model evaluation