

# Triage Against the Machine: Can AI Reason Deliberatively?

Francesco Veri, Gustavo Umbelino

2025-04-17

## Large-Language Models (LLMs) Preview

Table 1: LLMs

	Provider	Model	Series	Parameters (B)	Context Length	Architecture	Version
1	anthropic	claude-3-5-haiku-20241022	claude	-	200000	-	2
2	anthropic	claude-3-5-sonnet-20241022	claude	-	200000	-	2
3	anthropic	claude-3-7-sonnet-20250219	claude	-	200000	-	3
4	anthropic	claude-3-haiku-20240307	claude	-	200000	-	1
5	anthropic	claude-3-opus-20240229	claude	-	200000	-	1
6	anthropic	claude-3-sonnet-20240229	claude	-	200000	-	1
7	cohere	command	command	-	4096	-	1
8	cohere	command-a-03-2025	command	111	288000	dense, decoder-only	3
9	cohere	command-r-08-2024	command	32	128000	-	2
10	cohere	command-r-plus-08-2024	command	104	128000	dense, decoder-only	2
11	cohere	command-r7b-12-2024	command	7	128000	-	2
12	deepseek	deepseek-chat	deepseek-chat	671	128000	MoE	3
13	deepseek	deepseek-reasoner	deepseek-reasoner	671	128000	MoE	1
14	deepseek	deepseek-v2	deepseek-chat	NA	128000	-	1
15	deepseek	deepseek-v2.5	deepseek-chat	NA	128000	-	2
16	google	gemini-1.5-flash	gemini	-	1000000	MoE	1
17	google	gemini-1.5-flash-8b	gemini	8	1048576	MoE	1
18	google	gemini-1.5-pro	gemini	-	2000000	MoE	1
19	google	gemini-2.0-flash	gemini	-	1000000	-	2
20	google	gemini-2.0-flash-thinking-exp	gemini	NA	NA	NA	2
21	google	gemini-2.5-pro-preview-03-25	gemini	-	1048576	-	3

	Provider	Model	Series	Parameters (B)	Context Length	Architecture	Version
22	google	gemma	gemma	-	-	dense, decoder-only	1
23	google	gemma-3-27b-it	gemma	27	NA	NA	3
24	google	gemma2:27b	gemma	27	8190	dense, decoder-only	2
25	google	gemma3:12b	gemma	12	128000	-	3
26	ibm	granite3.3	granite	8	131072	dense	3
27	meta	llama2:13b	llama	13	4100	-	1
28	meta	llama2:70b	llama	70	4100	-	1
29	meta	llama3.1:405B-turbo	llama	405	128000	-	3
30	meta	llama3.2	llama	3	131072	-	4
31	meta	llama3.3:70b	llama	70	128000	-	5
32	meta	llama3:70b	llama	70	8190	-	2
33	meta	llama4-maverick	llama	17	1000000	MoE	6
34	meta	llama4-scout	llama	17	1000000000	MoE	6
35	microsoft	phi	phi	NA	NA	-	1
36	microsoft	phi2	phi	NA	NA	-	2
37	microsoft	phi3	phi	NA	NA	-	3
38	microsoft	phi3.5	phi	NA	NA	-	4
39	microsoft	phi4	phi	14	16000	dense, decoder-only	5
40	mistralai	ministral-3b-latest	ministral	3	128000	-	1
41	mistralai	ministral-8b-latest	ministral	8	128000	-	1
42	mistralai	mistral-large-latest	mistral	123	128000	-	1
43	mistralai	mistral-small-latest	mistral	22	32800	-	1
44	mistralai	open-mistral-7b	mistral	7	NA	-	NA
45	mistralai	open-mistral-nemo	mistral	12	128000	-	1
46	mistralai	open-mixtral-8x22b	mixtral	39	65400	SMoE	1
47	mistralai	open-mixtral-8x7b	mixtral	7	NA	SMoE	NA
48	openai	gpt-3.5-turbo	gpt	-	16385	-	1
49	openai	gpt-4	gpt	-	8192	-	3
50	openai	gpt-4-turbo	gpt	-	128000	-	3
51	openai	gpt-4.5-preview	gpt	-	128000	-	4
52	openai	gpt-4o	gpt	-	128000	-	2
53	openai	gpt-4o-mini	gpt	-	128000	-	2
54	openai	o1	o	-	200000	-	1
55	openai	o1-mini	o	NA	NA	-	1
56	openai	o3-mini	o	-	200000	-	2
57	qwen	qwen-max	qwen	-	32768	-	1
58	qwen	qwen-plus	qwen	-	131072	-	1
59	qwen	qwen-turbo	qwen	-	1000000	-	1
60	qwen	qwen1.5-110b-chat	open-qwen	110	NA	-	1
61	qwen	qwen1.5-72b-chat	open-qwen	72	8000	-	1
62	qwen	qwen2-72b-instruct	open-qwen	72	131072	-	2
63	qwen	qwen2.5-72b-instruct	open-qwen	72	131072	-	3
64	qwen	qwq-plus	qwq	-	131072	-	1
65	xai	grok-2-1212	grok	-	131072	-	2
66	xai	grok-3-beta	grok	-	131072	-	3
67	xai	grok-3-mini-beta	grok	-	131072	-	3
68	xai	grok-beta	grok	314	131072	MoE	1

We started the analysis with 68 models, but some models were dropped after data collection. The models and reason for dropping are discussed later on Excluded Models.

## Surveys

Table 2: Surveys

	survey	considerations	policies	scale_max	q_method
1	acp	48	5	11	FALSE
2	auscj	45	8	7	FALSE
3	bep	43	7	7	FALSE
4	biobanking_mayo_ubc	38	7	11	FALSE
5	biobanking_wa	49	7	11	FALSE
6	ccps	33	7	11	FALSE
7	ds_aargau	33	7	7	FALSE
8	ds_bellinzona	32	7	7	FALSE
9	energy_futures	45	9	11	FALSE
10	fnqcj	42	5	12	FALSE
11	forestera	45	7	11	FALSE
12	fremantle	36	6	11	TRUE
13	gbr	35	7	7	FALSE
14	swiss_health	24	6	7	FALSE
15	uppsala_speaks	42	7	7	FALSE
16	valsamoggia	36	4	11	TRUE
17	zh_thalwil	31	7	7	FALSE
18	zh_uster	31	7	7	FALSE
19	zh_winterthur	30	6	7	FALSE
20	zukunft	20	7	7	FALSE

## LLM Data Collection

We collected a total of 35365 valid LLM responses across 20 surveys.

### Cost


We spent a total of 411.3 USD. The cost breakdown per API is below.

Table 3: Costs by API

api	num_models	credits_paid
OpenAI API	9	225.52
Anthropic API	6	75.00
xAI API	4	29.95
Cohere API	5	20.34
Mistral AI API	8	20.00
Alibaba Cloud	8	17.49
Together AI	8	13.00
DeepSeek API	2	10.00
Google Cloud	7	NA
ollama	10	NA

## Time

It took a total of 174 hours<sup>1</sup> across 28 days to complete data collection. Most of it was done in parallel. The first LLM response was collected on Thursday, Mar 20, 2025 and latest on Thursday, Apr 17, 2025.



## Excluded Models

18 out of 70 were excluded from the analysis for the following reasons.

Table 4: Excluded models and reasons


Provider	Model	Reason for exclusion
anthropic	claude-3-sonnet-20240229	not available in Anthropic API anymore
cohere	command-r-plus-08-2024	uniform aggregated considerations (1s)
deepseek	deepseek-v2	high fail rate (85%)
deepseek	deepseek-v2.5	too big to run locally; not available through APIs
google	gemma-3-27b-it	low rate limit (15K tokens/min)
google	gemma3:12b	uniform aggregated considerations (1s)
ibm	granite3.3	testing
meta	llama2:13b	does not respond to prompts correctly
meta	llama2:70b	does not respond to prompts correctly
meta	llama3.2	3% success rate on auscj
microsoft	phi	does not respond to prompts correctly
microsoft	phi2	same model as phi

<sup>1</sup>Execution data is mostly accurate. Only a few (3-5) executions failed and, as a result, we have no record of it.


Provider	Model	Reason for exclusion
microsoft	phi3	does not respond to prompts correctly
microsoft	phi3.5	10% success rate for biobanking_wa
mistralai	open-mistral-7b	11% success rate for auscj, uppsala_speaks, and biobanking_wa
mistralai	open-mixtral-8x7b	6% success rate on fremantle only
openai	o1-mini	0% success rate on uppsala_speaks only; responds with “I’m sorry, but I can’t help with that.”
qwen	qwen1.5-110b-chat	has API limit of 10 RPM; too slow

## Execution Summary Plots


### Fail rate




## Cost per completion




## Total cost



## Time per completion



## Cost/Time per completion



Zoomed in to cost < 0.01 USD and time < 12 s.





	provider	model	N	all	considerations	policies
21	xai	grok-2-1212	600	0.78	0.89	0.47
22	cohere	command-a-03-2025	600	0.79	0.86	0.51
23	cohere	command-r-08-2024	600	0.79	0.81	0.50
24	deepseek	deepseek-chat	600	0.79	0.86	0.52
25	google	gemini-1.5-flash-8b	600	0.79	0.84	0.50
26	meta	llama3:70b	600	0.79	0.79	0.52
27	qwen	qwen-turbo	600	0.79	0.83	0.48
28	anthropic	claude-3-7-sonnet-20250219	600	0.80	0.84	0.53
29	meta	llama4-scout	600	0.80	0.85	0.51
30	qwen	qwen-plus	600	0.80	0.82	0.49
31	qwen	qwen2-72b-instruct	600	0.80	0.86	0.48
32	qwen	qwen2.5-72b-instruct	600	0.80	0.84	0.51
33	xai	grok-3-mini-beta	600	0.80	0.78	0.67
34	anthropic	claude-3-5-haiku-20241022	600	0.81	0.86	0.47
35	microsoft	phi4	600	0.81	0.82	0.55
36	xai	grok-3-beta	600	0.81	0.84	0.53
37	mistralai	ministral-8b-latest	600	0.82	0.83	0.51
38	qwen	qwen-max	600	0.82	0.84	0.51
39	anthropic	claude-3-opus-20240229	600	0.83	0.87	0.50
40	mistralai	mistral-large-latest	600	0.83	0.86	0.54
41	google	gemini-2.0-flash	600	0.84	0.84	0.62
42	openai	gpt-3.5-turbo	600	0.84	0.87	0.48
43	openai	gpt-4.5-preview	201	0.84	0.87	0.70
44	meta	llama3.1:405B-turbo	600	0.85	0.88	0.49
45	mistralai	ministral-3b-latest	600	0.85	0.86	0.53
46	cohere	command-r7b-12-2024	600	0.86	0.87	0.46
47	mistralai	open-mixtral-8x22b	600	0.87	0.90	0.52
48	openai	o1	100	0.92	0.92	0.77
49	openai	o3-mini	100	0.92	0.91	0.80

## Aggregation

We then aggregated LLM data into 1 response per model/survey. Based on (Motoki, Pinho Neto, and Rodrigues 2024), we bootstrap considerations 1000 times.

## Aggregate considerations and preferences

We aggregated 31016 LLM responses into 980 responses: 1 response per model per survey.

## Human Data

Table 6: Number of participants in each case study

	Case	Survey	Participants
1	Citizen Parliamentarian	acp	45
2	HGE Control Group	auscj	19
3	HGE Deliberative Group	auscj	23
4	BEP	bep	16
5	Mayo	biobanking_mayo_ubc	17
6	UBC Bio	biobanking_mayo_ubc	17

	Case	Survey	Participants
7	WA Citizens	biobanking_wa	9
8	WA Stakeholder	biobanking_wa	15
9	CCPS ACT Deliberative	ccps	31
10	Aargau	ds_aargau	16
11	Bellinzona	ds_bellinzona	8
12	CSIRO NSW	energy_futures	12
13	CSIRO WA	energy_futures	17
14	FNQCJ	fnqcj	11
15	Forest Lay Citizen	forestera	9
16	Forest Stakeholder	forestera	11
17	Fremantle	fremantle	41
18	GBR	gbr	7
19	Activate	uppsala_speaks	26
20	Standard	uppsala_speaks	22
21	UPSA Control Group	uppsala_speaks	20
22	Valsamoggia	valsamoggia	16
23	Thalwil	zh_thalwil	14
24	USTER	zh_uster	15
25	Winterthur	zh_winterthur	16
26	Zukunft	zukunft	63

We collected 1032 human responses across 26 case studies, including pre-post deliberation responses.

## Randomly Generated Data

Then, we generated 20 random reseponses, one for each survey.

## DRI Analysis

We begin by defining DRI calculation functions.

```
# original DRI formula
dri_calc <- function(data, v1, v2) {
  lambda <- 1 - (sqrt(2) / 2)
  dri <- 2 * (((1 - mean(abs((data[[v1]] - data[[v2]])) / sqrt(2)
))) - (lambda)) / (1 - (lambda))) - 1

  return(dri)
}

# updated DRI formula
# FIXME: only accounts for negligible positive correlations, but not negative ones
dri_calc_v2 <- function(data, v1, v2) {
  # Calculate orthogonal distance for each pair
  d <- abs((data[[v1]] - data[[v2]])) / sqrt(2))

  # Define lambda as in the original
  lambda <- 1 - (sqrt(2) / 2)

  # Calculate penalty: 0.5 if both correlations are in [0, 0.2], 1 otherwise
  penalty <- ifelse(data[[v1]] >= 0 & data[[v1]] <= 0.2 & #0.3
```

```

        data[[v2]] >= 0 & data[[v2]] <= 0.2, # 0.3
        0, 1)

# Adjusted consistency per pair
consistency <- (1 - d) * penalty

# Average consistency across all pairs
avg_consistency <- mean(consistency)

# Scale to [-1, 1] as in the original
dri <- 2 * ((avg_consistency - lambda) / (1 - lambda)) - 1

return(dri)
}

# updated DRI formula: penalizes both negligible
# positive and negative correlations in a scalar way.
dri_calc_v3 <- function(data, v1, v2) {
  d <- abs((data[[v1]] - data[[v2]]) / sqrt(2))
  lambda <- 1 - (sqrt(2) / 2)

  # Scalar penalty based on strength of signal (|r| and |q|)
  penalty <- ifelse(pmax(abs(data[[v1]]), abs(data[[v2]])) <= 0.2, pmax(abs(data[[v1]]), abs(data[[v2]])) * 0.2, 1)

  consistency <- (1 - d) * penalty
  avg_consistency <- mean(consistency)

  dri <- 2 * ((avg_consistency - lambda) / (1 - lambda)) - 1
  return(dri)
}

```

## Warning: Missing swiss\_health from DRIInd.LLMs!

## Hypotheses Testing

**H1. DRI scores of LLMs do not significantly differ from those produced by a random generation process.**

### Testing assumptions


We employed a one-way ANOVA (or a Kruskal-Wallis test, depending on the results of the exploratory analysis) between subjects to analyze our results. If normality and homogeneity of variance assumptions are met, we will use ANOVA followed by Tukey's HSD post-hoc test for pairwise comparisons between LLM/version DRI and random DRI. If assumptions are violated, we will use the non-parametric Kruskal-Wallis test, followed by Dunn's post-hoc test with Bonferroni correction.

The independent variable is be the type of participant (e.g., random, model). The dependent variable is the individual-level DRI score.

Distribution of DRIPostV3 for Each Source Type



Distribution of DRIPostV3 for Each Source Type



## Testing hypothesis

```
##
## Kruskal-Wallis rank sum test
##
## data: DRIPostV3 by source
## Kruskal-Wallis chi-squared = 69.022, df = 49, p-value = 0.03118
```

## Post-hoc tests

```
##
## alpha = 0.05
## Reject Ho if p <= alpha/2
```

Table 7: Models compared to random

Model	P-adjusted
claude-3-5-sonnet-20241022	0.009*
qwen-plus	0.016*
gemini-2.0-flash	0.024*
claude-3-7-sonnet-20250219	0.026*
deepseek-chat	0.028*
grok-3-beta	0.041*
gemma2:27b	0.045*
qwen2.5-72b-instruct	0.055
claude-3-opus-20240229	0.093
grok-beta	0.097
command-r7b-12-2024	0.145
qwen1.5-72b-chat	0.191
llama4-scout	0.192
gpt-4-turbo	0.214
mistral-large-latest	0.276
open-mistral-nemo	0.35
gemini-2.5-pro-preview-03-25	0.364
claude-3-haiku-20240307	0.479
claude-3-5-haiku-20241022	0.639
llama3.3:70b	0.659
qwen-turbo	0.719
qwen2-72b-instruct	0.806
grok-3-mini-beta	0.829
llama3:70b	0.916
o3-mini	0.964
open-mixtral-8x22b	0.986
command	1
command-a-03-2025	1
command-r-08-2024	1
deepseek-reasoner	1
gemini-1.5-flash	1
gemini-1.5-flash-8b	1
gemini-1.5-pro	1
gemma	1
gpt-3.5-turbo	1
gpt-4	1
gpt-4.5-preview	1
gpt-4o	1
gpt-4o-mini	1
grok-2-1212	1
llama3.1:405B-turbo	1
llama4-maverick	1
ministral-3b-latest	1
ministral-8b-latest	1
mistral-small-latest	1


Model	P-adjusted
o1	1
phi4	1
qwen-max	1
qwq-plus	1

Some models, 7 out of 49, are significantly different than random.


## H2. LLMs' DRI scores will be significantly lower than those obtained from human participants after deliberation.

### Testing assumptions

Distribution of DRIPostV3 for Each Source Type



Distribution of DRIPostV3 for Each Source Type



### Testing hypothesis

##

```
## Kruskal-Wallis rank sum test
##
## data:  DRIPostV3 by source
## Kruskal-Wallis chi-squared = 51.167, df = 49, p-value = 0.3886
```


#### Post-hoc tests

```
## Kruskal-Wallis test is not significant; no need for post-hoc testing.
```

### H3

## DRI Benchmark


```
## `geom_smooth()` using formula = 'y ~ x'
```




```
## `summarise()` has grouped output by 'provider', 'model'. You can override using
## the `.groups` argument.
```




Comparison PRE and POST DRI by Provider




Comparison PRE and POST DRI by Model



## Heatmap of DRI Scores by Case and Model



## Boxplot of LLM DRI Post by Case




## LLM Performance Metrics Against Human DRI Post-Scores

Table 8: LLM Performance Metrics Against Human DRI Post-Scores

Model	MAE	RMSE	MAPE (%)	Human Range	NMAE	NRMSE	Spearman	Delta
command-r7b-12-2024	0.197	0.344	85.810	0.744	0.265	0.463	0.538	-0.041
command	0.283	0.387	89.798	0.744	0.381	0.521	0.406	-0.187
gpt-3.5-turbo	0.310	0.414	128.487	0.744	0.417	0.557	-0.010	-0.185
gemma	0.245	0.424	76.739	0.744	0.330	0.570	0.339	-0.129
claude-3-haiku-20240307	0.254	0.462	98.213	0.744	0.341	0.622	0.475	-0.102
gpt-4o-mini	0.255	0.469	100.318	0.744	0.342	0.631	0.398	-0.137
gpt-4-turbo	0.227	0.478	80.697	0.744	0.306	0.643	0.547	-0.080
ministral-3b-latest	0.289	0.491	111.081	0.744	0.388	0.660	0.220	-0.131
grok-beta	0.270	0.494	134.830	0.744	0.363	0.664	0.543	-0.088
claude-3-5-haiku-20241022	0.268	0.495	76.615	0.744	0.360	0.666	0.371	-0.108
o1	0.318	0.505	92.257	0.744	0.427	0.679	0.309	-0.301
o3-mini	0.292	0.510	95.798	0.744	0.393	0.686	0.454	-0.139
llama3.3:70b	0.275	0.514	111.403	0.744	0.369	0.691	0.521	-0.124
llama3.1:405B-turbo	0.260	0.521	92.533	0.744	0.349	0.701	0.537	-0.155
llama3:70b	0.298	0.526	129.718	0.744	0.400	0.707	0.380	-0.135
qwen2.5-72b-instruct	0.277	0.527	84.711	0.744	0.373	0.709	0.525	-0.092
mistral-small-latest	0.284	0.527	119.671	0.744	0.382	0.709	0.483	-0.172
grok-2-1212	0.317	0.528	109.056	0.744	0.426	0.710	0.063	-0.221
qwen-plus	0.293	0.529	157.093	0.744	0.395	0.711	0.474	-0.067
gemini-2.0-flash	0.283	0.530	142.756	0.744	0.381	0.713	0.469	-0.060
command-r-08-2024	0.279	0.534	122.313	0.744	0.375	0.718	0.394	-0.143
qwq-plus	0.282	0.541	90.107	0.744	0.379	0.728	0.543	-0.153
qwen-turbo	0.267	0.548	85.491	0.744	0.360	0.737	0.562	-0.131
deepseek-reasoner	0.375	0.549	123.108	0.744	0.504	0.739	0.282	-0.258
gemini-2.5-pro-preview-03-25	0.301	0.553	110.210	0.744	0.404	0.744	0.381	-0.138
gemini-1.5-flash-8b	0.328	0.561	97.684	0.744	0.442	0.755	0.227	-0.198
gemma2:27b	0.285	0.567	103.724	0.744	0.383	0.762	0.570	-0.101
phi4	0.287	0.571	83.983	0.744	0.385	0.767	0.426	-0.151
llama4-scout	0.287	0.575	86.507	0.744	0.386	0.773	0.513	-0.127
open-mistral-nemo	0.276	0.580	104.933	0.744	0.371	0.780	0.516	-0.120
grok-3-beta	0.279	0.582	96.493	0.744	0.376	0.783	0.555	-0.093
gpt-4o	0.357	0.586	158.169	0.744	0.481	0.788	0.258	-0.252
ministral-8b-latest	0.309	0.587	109.421	0.744	0.415	0.789	0.208	-0.186
claude-3-opus-20240229	0.284	0.588	92.192	0.744	0.382	0.790	0.548	-0.114
claude-3-5-sonnet-20241022	0.289	0.589	115.990	0.744	0.388	0.791	0.573	-0.072
gemini-1.5-flash	0.307	0.592	102.964	0.744	0.413	0.797	0.521	-0.176
qwen-max	0.313	0.596	111.424	0.744	0.420	0.801	0.390	-0.162
qwen1.5-72b-chat	0.298	0.600	103.533	0.744	0.400	0.807	0.480	-0.117
claude-3-7-sonnet-20250219	0.291	0.601	99.713	0.744	0.391	0.808	0.551	-0.097
qwen2-72b-instruct	0.331	0.602	142.072	0.744	0.445	0.809	0.443	-0.166
grok-3-mini-beta	0.325	0.602	101.669	0.744	0.438	0.809	0.482	-0.179
mistral-large-latest	0.305	0.616	99.385	0.744	0.410	0.828	0.420	-0.124
open-mixtral-8x22b	0.308	0.623	108.671	0.744	0.415	0.838	0.436	-0.165
gpt-4	0.360	0.624	141.193	0.744	0.484	0.839	0.388	-0.213
deepseek-chat	0.315	0.625	129.052	0.744	0.423	0.840	0.471	-0.106
command-a-03-2025	0.375	0.659	140.325	0.744	0.504	0.887	0.227	-0.196
llama4-maverick	0.358	0.672	98.374	0.744	0.482	0.904	0.212	-0.254
gemini-1.5-pro	0.389	0.672	138.578	0.744	0.524	0.904	0.179	-0.221
gpt-4.5-preview	0.459	0.727	160.975	0.744	0.617	0.977	0.286	-0.348



## Human-Normalized Performance




## LLM Performance by Reasoner Classification

Architecture types:

- Transformer-based models (Vaswani et al. 2017).

Some models are considered “reasoning” models, like , reason using chain-of-thought (CoT) – this is not a difference in architecture, but in how



## References

- Motoki, Fabio, Valdemar Pinho Neto, and Victor Rodrigues. 2024. "More Human Than Human: Measuring ChatGPT Political Bias." *Public Choice* 198(1): 3–23. doi:10.1007/s11127-023-01097-2.
- Vaswani, Ashish, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Łukasz Kaiser, and Illia Polosukhin. 2017. "Attention Is All You Need." In Curran Associates, Inc. [https://papers.nips.cc/paper\\_files/paper/2017/hash/3f5ee243547dee91fbd053c1c4a845aa-Abstract.html](https://papers.nips.cc/paper_files/paper/2017/hash/3f5ee243547dee91fbd053c1c4a845aa-Abstract.html).