

SKILL WEEK-7

Task-1: To parse Input Redirection, Open Files, Redirect stdin, Handle Missing Files, Restore Streams, Test File Inputs

Code:

```
GNU nano 8.7.1          input_redirect.c *
#include <stdio.h>
#include <unistd.h>
#include <fcntl.h>
#include <sys/wait.h>
#include <stdlib.h>

int main() {
    int fd;
    pid_t pid;

    fd = open("input.txt", O_RDONLY);

    if (fd == -1) {
        perror("input.txt");
        return 1;
    }

    pid = fork();

    if (pid == 0) {
        dup2(fd, STDIN_FILENO);
        close(fd);

        execlp("sort", "sort", NULL);

        perror("sort");
        exit(1);
    }

    close(fd);
    waitpid(pid, NULL, 0);

    printf("Input redirection completed.\n");

    return 0;
}

^G Help      ^O Write Out ^F Where Is  ^K Cut       ^T Execute
^X Exit      ^R Read File ^\ Replace   ^U Paste     ^J Justify
```

Output:

```
saicharan_reddi@SAICHARANREDDY:~/skill$ nano input.txt
saicharan_reddi@SAICHARANREDDY:~/skill$ gcc input_redirect.c -o input_redirect
saicharan_reddi@SAICHARANREDDY:~/skill$ ./input_redirect
apple
banana
grape
orange
Input redirection completed.
saicharan_reddi@SAICHARANREDDY:~/skill$
```

Report: The program parses input redirection and opens the specified file in read-only mode. The file descriptor is redirected to standard input using dup2(). Missing files are detected and appropriate error messages are displayed. The program was tested successfully with valid and missing input files.

Task-2: To Parse Output Redirection, Create Output Files, Redirect stdout, Handle Permissions, Verify Output Data, Test Redirection

Code:

```
GNU nano 8.7.1      output_redirect.c *
#include <stdio.h>
#include <unistd.h>
#include <fcntl.h>
#include <sys/wait.h>
#include <stdlib.h>

int main() {
    int fd;
    pid_t pid;

    fd = open("output.txt",
              O_WRONLY | O_CREAT | O_TRUNC,
              0644);

    if (fd == -1) {
        perror("output.txt");
        return 1;
    }

    pid = fork();

    if (pid == 0) {
        dup2(fd, STDOUT_FILENO);
        close(fd);

        execlp("ls", "ls", NULL);

        perror("ls");
        exit(1);
    }

    close(fd);
    waitpid(pid, NULL, 0);

    printf("Output redirected to output.txt\n");

    return 0;
}

^G Help      ^O Write Out ^F Where Is  ^K Cut       ^I Execute
^X Exit      ^R Read File ^N Replace   ^U Paste     ^J Justify
```

Output:

```
saicharan_reddi@SAICHARANREDDY:~/skill$ nano output_redirect.c
saicharan_reddi@SAICHARANREDDY:~/skill$ gcc output_redirect.c -o output_redirect
saicharan_reddi@SAICHARANREDDY:~/skill$ ./output_redirect
Output redirected to output.txt
saicharan_reddi@SAICHARANREDDY:~/skill$ cat output.txt
cd_command
cd_command.c
export_command
export_command.c
history
history.c
input.txt
input_redirect
input_redirect.c
mini_shell
mini_shell.c
multiple_pipes
multiple_pipes.c
output.txt
output_redirect
output_redirect.c
pipe
pipe.c
pipeline_structure
pipeline_structure.c
pwd_exit
pwd_exit.c
saicharan_reddi@SAICHARANREDDY:~/skill$
```

Report: The program parses output redirection and creates an output file using `open()`. Standard output is redirected to the file using `dup2()`. File creation and permission errors are handled appropriately. The output file was verified successfully to contain the redirected command output.

Task-3: To Parse Append Operator, Open Files in Append Mode, Redirect Streams, Preserve Existing Data, Validate Appends, Test Scenarios

```
GNU nano 8.7.1                                append_redirect.c *
#include <stdio.h>
#include <unistd.h>
#include <fcntl.h>
#include <sys/wait.h>
#include <stdlib.h>

int main() {
    int fd;
    pid_t pid;

    fd = open("append.txt",
              O_WRONLY | O_CREAT | O_APPEND,
              0644);

    if (fd == -1) {
        perror("append.txt");
        return 1;
    }

    pid = fork();

    if (pid == 0) {
        dup2(fd, STDOUT_FILENO);
        close(fd);

        execlp("date", "date", NULL);

        perror("date");
        exit(1);
    }

    close(fd);
    waitpid(pid, NULL, 0);

    printf("Data appended successfully.\n");

    return 0;
}

^G Help      ^O Write Out  ^F Where Is   ^K Cut        ^T Execute
^X Exit      ^R Read File  ^\ Replace    ^U Paste      ^J Justify
```

Output:

```
saicharan_reddi@SAICHARANREDDY:~/skill$ nano append_redirect.c
saicharan_reddi@SAICHARANREDDY:~/skill$ gcc append_redirect.c -o append_redirect
saicharan_reddi@SAICHARANREDDY:~/skill$ ./append_redirect
Data appended successfully.
saicharan_reddi@SAICHARANREDDY:~/skill$ cat append.txt
Fri Sep 18 14:44:49 UTC 2026
saicharan_reddi@SAICHARANREDDY:~/skill$ ./append_redirect
Data appended successfully.
saicharan_reddi@SAICHARANREDDY:~/skill$
```

Report: The program parses the append operator and opens the file using O_APPEND. Standard output is redirected to the file without removing existing contents. New data is added at the end of the file and file errors are handled. The program was tested successfully by performing multiple append operations.

Task-4: TO parse stderr Redirection, Redirect Error Streams, Capture Error Output, Verify File Contents, Handle Failures, Test Error Cases

Code:

```
GNU nano 8.7.1          stderr_redirect.c *
#include <stdio.h>
#include <unistd.h>
#include <fcntl.h>
#include <sys/wait.h>
#include <stdlib.h>

int main() {
    int fd;
    pid_t pid;

    fd = open("error.txt",
              O_WRONLY | O_CREAT | O_TRUNC,
              0644);

    if (fd == -1) {
        perror("error.txt");
        return 1;
    }

    pid = fork();

    if (pid == 0) {
        dup2(fd, STDERR_FILENO);
        close(fd);

        execlp("ls", "ls", "nonexistent_file", NULL);

        perror("ls");
        exit(1);
    }

    close(fd);
    waitpid(pid, NULL, 0);

    printf("Error output redirected to error.txt\n");

    return 0;
}
```

^G Help	^O Write Out	^F Where Is	^K Cut	^T Execute
^X Exit	^R Read File	^N Replace	^U Paste	^J Justify

Output:

```
saicharan_reddi@SAICHARANREDDY:~/skill$ nano stderr_redirect.c
saicharan_reddi@SAICHARANREDDY:~/skill$ gcc stderr_redirect.c -o stderr_redirect
saicharan_reddi@SAICHARANREDDY:~/skill$ ./stderr_redirect
Error output redirected to error.txt
saicharan_reddi@SAICHARANREDDY:~/skill$
```

Report: The program parses stderr redirection and opens a file for storing error messages. The standard error stream is redirected using `dup2()` with `STDERR_FILENO`. Command failures are captured in the specified file for verification. The program was tested successfully using invalid commands and verified error output.