

```
#include <stdio.h>
#include <unistd.h>
#include <sys/wait.h>

int main()
{
    int pid = fork();

    if (pid == 0)
    {
        printf("Child PID: %d\n", getpid());
        printf("Parent PID: %d\n", getppid());

        sleep(10);

        printf("Child finished\n");
    }
    else
    {
        printf("Parent PID: %d\n", getpid());
        printf("Child PID: %d\n", pid);

        sleep(5);
        wait(NULL);

        printf("Parent finished\n");
    }

    return 0;
}
```

Last login: Sun Aug 30 17:38:56 on ttys000

[sarveswarareddy@sarveswaras-MacBook-Air ~ % nano q3.c

[sarveswarareddy@sarveswaras-MacBook-Air ~ % gcc q3.c -o q3

[sarveswarareddy@sarveswaras-MacBook-Air ~ % ./q3

Parent PID: 5000

Child PID: 5001

Child PID: 5001

Parent PID: 5000

Child finished

Parent finished

[sarveswarareddy@sarveswaras-MacBook-Air ~ % ps -l

UID	PID	PPID	F	CPU	PRI	NI	SZ	RSS	WCHAN	S	ADDR	TTY	TIME	CMD
501	4962	4961		4006	0	31	0	435312608	3968	-		0 ttys001	0:00.03	-zsh

sarveswarareddy@sarveswaras-MacBook-Air ~ %