

```
Linux PID 5.09 File: q1.c
#include <stdio.h>
#include <unistd.h>
#include <sys/wait.h>

int main()
{
    char cmd[100];
    printf("Enter Linux command: ");
    scanf("%s", cmd);
    int pid = fork();
    if (pid == 0)
    {
        printf("Child PID: %d\n", getpid());
        execlp(cmd, cmd, NULL);
    }
    else
    {
        printf("Parent PID: %d\n", getpid());
        wait(NULL);
        printf("Child completed\n");
    }
    return 0;
}
```

Get Help WriteOut Read File Prev Pg Cut Text Cur Pos
Exit Justify Where is Next Pg UnCut Text To Spell

Caption

```
last login: Sat Aug 29 14:55:38 on tty000
gautamvemu@gautams-MacBook-Pro Linux % nano q1.c
gautamvemu@gautams-MacBook-Pro Linux % gcc q1.c -o q1
./q1
Enter Linux command: ls
Parent PID: 2909
Child PID: 2910
.out first.c p2.c process.c ps switch case.c week3
ll.c hello.c pid process2 q1 t1.txt week3.c
ll.c open pid.c process2.c q1 t2.txt week32
ecsc open.c process_id processmanagement read week1 week32.c
ecsc.c p2 process_id.c processmanagement.c read.c week1.c
Child Completed
gautamvemu@gautams-MacBook-Pro Linux %
```

Caption

Caption