

```
#include <stdio.h>
#include <unistd.h>
#include <sys/wait.h>

int main()
{
    int pid = fork();

    if (pid == 0)
    {
        printf("Child PID: %d\n", getpid());
        printf("Parent PID: %d\n", getppid());

        sleep(10);

        printf("Child finished\n");
    }
    else
    {
        printf("Parent PID: %d\n", getpid());
        printf("Child PID: %d\n", pid);

        sleep(5);
        wait(NULL);

        printf("Parent finished\n");
    }

    return 0;
}
```

```
Last login: Sun Aug 30 17:38:56 on ttys000
[rohith@rohith-MacBook-Air ~ % nano q3.c
[rohith@rohith-MacBook-Air ~ % gcc q3.c -o q3
[rohith@rohith-MacBook-Air ~ % ./q3
Parent PID: 5000
Child PID: 5001
Child PID: 5001
Parent PID: 5000
Child finished
Parent finished
```

```
[rohith@rohith-MacBook-Air ~ % ps -l
  UID   PID  PPID      F  CPU PRI  NI       SZ    RSS WCHAN    S        ADDR  TTY        TIME CMD
   501  4962  4961      0    31  0  435312608  3968  -      S          0  ttys001    0:00.03 -zsh
rohith@rohith-MacBook-Air ~ %
```