

Intrinsic-Noise Consolidation: A Doob-Barrier-Conditioned Diffusion Turns Analog Device Noise into a Continual-Learning Resource

Gunner Levi Howe
gunnerlevihowe@gmail.com

July 2026

Abstract

On analog neuromorphic hardware, intrinsic device noise is normally an accuracy tax. We ask whether it can instead be made to *consolidate* memories. We cast per-synapse consolidation as a *Doob h -transform*: condition each weight’s stochastic dynamics on the event of never crossing a memory-critical barrier around its consolidated value. The conditioned diffusion acquires an extra drift $\sigma^2 \partial_w \log h$ — a restoring force toward the memory that is *amplified by the noise variance itself*, and diverges at the barrier. We are explicit about what is and is not new. The anchored-consolidation drift $-s(w-\mu)$ that our rule also contains is *not* ours: it is the small-noise limit of Ornstein–Uhlenbeck Adaptation [Garcia Fernandez et al., 2024], the variance-scaled anchor of MESU [Bonnet et al., 2025], and the Fisher penalty of EWC [Kirkpatrick et al., 2017], and we surrender it as a re-derivation. Our claim is the conjunction of (a) the Doob barrier-conditioning as a synaptic rule — to our knowledge unclaimed; every h -transform use we found is generative modeling or Schrödinger bridges, *none* synaptic — and (b) a falsifiable, load-bearing prediction: increasing the intrinsic noise *non-monotonically* improves sequential-task retention, an inverted-U these anchored-drift methods cannot produce. We pre-registered this as a go/no-go gate and it passes: on single-head Split-MNIST (8 seeds) the barrier-conditioned rule lifts retention by 10.9 percentage points at an interior optimum $\sigma^* = 0.02$ (paired Wilcoxon $p = 0.004$ vs. zero noise and vs. high noise), while the matched OU, EWC and MESU anchors are monotone-decreasing in noise. Ablating the conditioning removes the effect; the optimum tracks the barrier; the inverted-U survives a device-faithful BrainScaleS-2 noise model (colored, multiplicative, fixed-pattern, 6-bit) and reproduces on a second task stream. At its optimum the rule is the strongest *rehearsal-free* consolidation method we test — matching MESU and significantly beating OU, EWC and Benna–Fusi; plain replay, which stores data, scores higher but exhibits none of the mechanism. We do *not* claim measured silicon: our BrainScaleS-2 result is an emulation, and an on-chip reproduction with measured energy is the pre-registered remaining step. Within these limits the mechanism reframes analog noise from a tax into a consolidation dividend that a von-Neumann accelerator must spend energy to fake.

1 Introduction

Catastrophic forgetting — the overwriting of old memories when a network learns something new — is usually fought with regularizers that anchor important weights to their consolidated values [Kirkpatrick et al., 2017, Benna and Fusi, 2016]. On digital hardware, stochasticity is something you add deliberately and pay for. On *analog* neuromorphic substrates such as BrainScaleS-2 (BSS-2) the situation is inverted: the hardware is *intrinsically* noisy — thermal fluctuations, crosstalk, analog-storage drift [Weis et al., 2020, Pehle et al., 2022] — and this noise is normally treated as an accuracy tax to be calibrated away. This paper asks a contrarian question: can that same intrinsic noise be *steered* so that it consolidates memories rather than degrading them?

One idea, stated as an identity plus a conjecture. Consider a single synaptic weight w that, after learning a task, should stay near a consolidated value μ to preserve that task’s function. Model its dynamics as a diffusion. If we simply pull it back — $dw = -s(w - \mu) dt + \sigma dW$ — we recover a mean-reverting Ornstein–Uhlenbeck (OU) process whose stationary spread $\sigma^2/2s$ *grows* with the noise: more noise is strictly worse. This anchored drift is exactly the rule already published as OU Adaptation [Garcia Fernandez et al., 2024], the variance-scaled Bayesian anchor of MESU [Bonnet et al., 2025], and the small-step limit of EWC [Kirkpatrick et al., 2017]; we claim no novelty for it and say so throughout. Our move is different: we *condition* the diffusion on the event that w never crosses a memory-critical barrier at $\mu \pm b$. By Doob’s h -transform, the conditioned process gains an extra drift $\sigma^2 \partial_w \log h(w)$, where h is the survival probability. This term (i) points *into* the safe region, (ii) *diverges* at the barrier, and — crucially — (iii) scales with σ^2 : *the more intrinsic noise, the stronger the noise-powered restoring force*. The competition between this σ^2 steering (which, at moderate noise, best resists interference) and the raw σ diffusion (which, at high noise, overwhelms the steering) predicts a non-monotone, inverted-U relationship between noise and retention with an optimum at $\sigma > 0$.

The claim split (and why it matters). The mechanism has three pieces and intellectual honesty requires separating them. We **surrender** the drift: $-s(w - \mu)$ is a known limit of OUA/MESU/EWC, proven so, not merely “similar.” We **keep**, as the entire contribution, the conjunction of two things: (a) casting per-synapse consolidation as a Doob / barrier-conditioned diffusion — an unclaimed framing (every h -transform use we located is generative modeling, Schrödinger bridges, or transition-path sampling [Du et al., 2025, Nguyen et al., 2025, Deng et al., 2024], *zero* synaptic) — and (b) the falsifiable hardware curve: intrinsic noise non-monotonically improving sequential-task retention. Absent (a) the rule is OUA/MESU; absent (b) it is repackaged Bayesian-online continual learning. The paper lives or dies on (a) *and* (b). We therefore pre-registered (b) as a hard go/no-go gate before running it: if noise did not help retention beyond the unconditioned anchor, the mechanism reduces to OUA/MESU/EWC and there is no paper. It helps.

Contributions.

1. **A synaptic Doob h -transform (novel framing).** We derive the per-synapse barrier-conditioned rule from the ground-state h -transform of the iso-loss interval, with the memory-critical barrier read off the Fisher metric (§3). The steering is a noise-amplified, barrier-divergent restoring force with a finite-bandwidth (physical) cap.
2. **A pre-registered falsifier that passes (load-bearing).** On Split-MNIST (8 seeds) the rule produces a retention inverted-U, lift 10.9 pts at $\sigma^* = 0.02$ ($p = 0.004$), while matched OU, EWC and MESU anchors are monotone in noise (§4.1, Fig. 1).
3. **Mechanism isolation.** Ablating the conditioning ($\kappa : 1 \rightarrow 0$) flattens the curve; the optimum tracks the barrier scale (§4.2). The effect is the conditioning, not generic noise.
4. **Device-faithful robustness and a second modality.** The inverted-U survives a BSS-2 intrinsic-noise emulation (colored + multiplicative + fixed-pattern + 6-bit) and reproduces on continual Yin-Yang (§4.3,4.5). We are explicit that this is emulation, not silicon.
5. **Baselines and an energy argument.** At its optimum the rule is the strongest *rehearsal-free* consolidation method we test (ties MESU, beats OU/EWC/Benna–Fusi); replay, which stores data, does better but lacks the mechanism. Because the diffusion is the device’s own

noise, an analog substrate pays no energy to generate it, whereas a digital accelerator does (§4.4).

The distinguishing statement. We re-derive the anchored-consolidation drift as a known limit of OUA/MESU/EWC, and claim novelty only in (i) casting per-synapse consolidation as a Doob h -transform barrier-conditioned diffusion, and (ii) demonstrating that increasing intrinsic analog noise non-monotonically improves sequential-task retention — a signature these anchored-drift methods cannot produce.

2 Related work

The anchored drift is not ours. OUA [Garcia Fernandez et al., 2024] frames learning as the mean-reverting OU diffusion $d\theta = \lambda(\mu - \theta)dt + \Sigma dW$ — exactly our anchored drift — but as a reward-modulated learning rule; it names catastrophic forgetting only as future work and uses no barrier or first-passage conditioning. MESU [Bonnet et al., 2025] is Bayesian continual learning whose update (their Eq. 11) is a variance-scaled pull toward a prior mean; it treats device read-noise as a *sampling* resource for Monte-Carlo Bayesian updates, never as a retention optimum, and uses no Doob transform. EWC [Kirkpatrick et al., 2017] is the static Fisher-weighted quadratic anchor, the deterministic ancestor. All three are the drift’s origin; none contains (a) or (b).

Noise as a resource, but not this one. Kolesnikov and Semenova [2025] show internal hardware noise can *help* — but with resilience to test-time noise in *single-task* feedforward/echo-state nets, not sequential-task retention, and with no inverted-U over retention. Shaham et al. [2022] consolidate lifelong memory with stochastic *rehearsal* (a replay mechanism), not intrinsic per-synapse device noise, and with no hardware or barrier. NADO [Manneschi et al., 2025] trains *through* device stochasticity with neural-SDE digital twins for single-task temporal tasks. Probabilistic Metaplasticity [Zohora et al., 2024] consolidates on memristors by modulating update *probability* (a stochastic gate) while treating device noise as an obstacle. None claims that raising intrinsic noise non-monotonically improves cross-task retention. **Benna–Fusi** complex synapses [Benna and Fusi, 2016] consolidate without a barrier via a deterministic multi-timescale cascade — an incumbent we compare against.

Doob’s h -transform lives in generative modeling. Conditioning a diffusion on a rare event via the h -transform underlies transition-path sampling [Du et al., 2025], diffusion-based image editing [Nguyen et al., 2025], constrained/reflected Schrödinger bridges [Deng et al., 2024], and diffusion-bridge simulation [Heng et al., 2021]. We found *no* use of Doob’s h -transform as a synaptic, plasticity, or continual-learning rule. That absence is the moat for claim (a); we cite the generative corpus precisely to delimit it.

3 Method

Setup. A network with weights θ learns a sequence of tasks. After task t we store an anchor $\mu = \theta_t$ and an importance $s =$ online-EWC running sum of the model-sampled (true) diagonal Fisher. During a later task each weight follows, under Euler–Maruyama,

$$dw_i = \underbrace{\left[-\partial_{w_i} \mathcal{L}_{\text{task}} \right]}_{\text{learning}} \underbrace{- s_i (w_i - \mu_i)}_{\text{anchored drift (surrendered)}} + \underbrace{\sigma_i^2 \partial_{w_i} \log h_i(w)}_{\text{Doob steering (ours)}} dt + \underbrace{\sigma_i dW_i}_{\text{intrinsic noise}}. \quad (1)$$

Every method we compare shares the first term and receives the *identical* injected noise at matched σ ; methods differ only in their drift. That is what makes the gate a fair isolation of the barrier conditioning rather than of “noise.”

The barrier-conditioned (Doob) steering. We condition each weight to remain in the memory-critical interval $(\mu_i - b_i, \mu_i + b_i)$. The ground-state (quasi-stationary) h -transform of Brownian motion killed at the interval ends has $h_i(w) = \cos(\frac{\pi(w-\mu_i)}{2b_i})$, so

$$\partial_w \log h_i = -\frac{\pi}{2b_i} \tan\left(\frac{\pi(w-\mu_i)}{2b_i}\right), \quad (2)$$

a restoring force toward the anchor that diverges at $\mu_i \pm b_i$ and, in Eq. (1), is multiplied by σ_i^2 : the intrinsic noise powers the confinement. The barrier half-width is the softened iso-loss radius $b_i = b_0/\sqrt{1 + s_i/\text{median}(s)}$, so important (high-Fisher) synapses get a tight barrier and unimportant ones a loose one at $\sim b_0$; the same global noise is thereby *steered per synapse* by the memory geometry. We cap the per-step Doob move at a fraction of b_i (a finite-bandwidth analog restoring force; this also stabilises the discretization of the singular drift).

Matched controls and incumbents. *OU* is Eq. (1) with the Doob term deleted (the ablation; steering strength $\kappa=0$). *EWC* is a stronger static anchor; *MESU* a variance-scaled anchor (Eq. 11 of Bonnet et al., 2025, in spirit); *naive* is plain SGD. All receive the same injected noise. As E3 incumbents we add the Benna–Fusi cascade synapse and plain reservoir replay.

Testbeds. Primary: *Split-MNIST*, domain-incremental — five binary tasks (0v1, ..., 8v9) on one shared 2-way head (later tasks overwrite the readout unless consolidation intervenes), an MLP 784–100–100–2. Second modality: *continual Yin-Yang* [Kriener et al., 2022], the BrainScaleS group’s own procedural benchmark, as five rotations of the pattern on a shared 3-way head. Task 0 is learned by plain SGD (nothing to protect yet); consolidation and the swept noise act on tasks 1 onward. Retention is the mean final accuracy on the past tasks; we also report plasticity (accuracy just after learning each task) and forgetting.

BrainScaleS-2 noise model and the honesty boundary. For E2 we replace the white diffusion in Eq. (1) with a device-faithful BSS-2 noise model built from the published characterization [Weis et al., 2020, Pehle et al., 2022]: temporally *colored* (AR(1)) trial-to-trial variability, a *multiplicative* (signal-dependent) component, a static *fixed-pattern* per-synapse offset, and 6-bit weight quantization. This is an *emulation* on a GPU. We measure no silicon and no joules. Our energy statements come from a transparent operation-count model (per-operation constants from Horowitz, 2014); the load-bearing point is a ratio, robust to the constants: on a digital accelerator the diffusion noise must be *generated* (an RNG draw and a scaled add per weight per step) and the barrier drift computed, whereas on analog silicon the same stochastic term is the device’s own physics — free. The on-chip reproduction with measured energy, via the port outlined in our code (hxtorch/pynn onto the analog array), is the pre-registered remaining step; the software stack is absent in our environment, so we neither run it nor claim it.

4 Experiments

We pre-registered the operating point (one coarse calibration, before the gated seeds), the noise grid, the seed counts, the inverted-U test, and the kill conditions K1–K3 in `PLAN.md`, committed




Figure 1: **GATE F (Split-MNIST, 8 seeds, mean±sd)**. The barrier-conditioned rule (Doob, red) rises from 57.4% at zero noise to 68.3% at an interior optimum $\sigma^* = 0.02$ (a 10.9-point lift; paired Wilcoxon $p = 0.004$ vs. zero, $p = 0.004$ vs. the high-noise end), then falls. The matched OU, EWC, MESU and naive anchors are monotone-decreasing in noise. Noise is a *resource* only when steered by the barrier.

before any results.

4.1 E0 — GATE F: the pre-registered falsifier

We sweep the intrinsic-noise amplitude σ over 10 levels and measure retention for the barrier-conditioned rule and the matched anchored-drift controls, 8 seeds. GATE F passes iff the rule’s retention- σ curve is an inverted-U (interior optimum $\sigma^* > 0$; peak beats both the zero-noise and high-noise ends by one-sided paired Wilcoxon; lift exceeds the seed spread) and no control is.

Result (Fig. 1). The rule is an inverted-U: retention rises from 57.4% (zero noise) to 68.3% at $\sigma^* = 0.02$, a lift of 10.9 points, then falls; both paired Wilcoxon tests give $p = 0.004$ (all 8 seeds agree). Every matched control is monotone-decreasing in σ (fraction of decreasing steps ≥ 0.78), peaking at zero noise. **GATE F passes: GO.** Because $\sigma^* > 0$ and the controls share the drift and the injected noise, the retention gain is attributable to the σ^2 barrier steering, not to noise per se — the mechanism does not reduce to OUA/MESU/EWC (kill condition K1 does not fire).

4.2 E1 — mechanism isolation

Ablating the conditioning is the pre-registered K3 test. Sweeping the steering strength κ from 1 down to 0 (which is exactly the OU control) flattens the curve: the lift falls from 13.0 points ($\kappa=1$) to 0.0 points ($\kappa=0$), and the inverted-U test fails at $\kappa=0$ (Fig. 2a). Varying the barrier scale b_0 moves the optimum σ^* (Fig. 2b), as expected if the barrier geometry sets the operating point. The effect is the barrier conditioning; K3 does not fire.




Figure 2: **Isolation.** (a) Interpolating the steering strength κ from 0 (unconditioned OU) to 1 (full h -transform): the inverted-U *emerges* with the conditioning (lift at $\kappa=0$ is 0.0 pts; at $\kappa=1$, 13.0 pts). (b) Varying the barrier scale b_0 : the retention optimum σ^* tracks the barrier, evidence the optimum is set by the conditioning geometry, not a generic noise sweet-spot.

4.3 E2 — BrainScaleS-2 intrinsic-noise emulation

Re-running the sweep with the device-faithful BSS-2 noise model, the inverted-U survives (Fig. 3a): lift 11.0 points at $\sigma^* = 0.005$, colored/multiplicative/fixed-pattern noise and 6-bit weights notwithstanding. A scan over the temporal color ρ (Fig. 3b) maps the boundary. We stress the boundary of the claim: this is an *emulation*. Whether the *measured* intrinsic noise of a physical BSS-2 chip has the right structure to consolidate is kill condition K2, resolvable only on hardware, which we did not run.

4.4 E3 — matched-budget baselines

At σ^* the rule reaches retention 68.3%. Among rehearsal-free consolidation methods (which store no data) it is the best: it matches the strongest, MESU (65.2%; ours–MESU = +3.1 pts, paired Wilcoxon $p = 0.25$, not significant), and significantly beats unconditioned OU 57.4%, EWC 59.1%, Benna–Fusi 50.6% and naive 57.4% (all $p \leq 0.008$; Fig. 4a). We are explicit about the honest comparison: *plain reservoir replay*, which stores 250 raw exemplars, reaches 83.0% — 14.6 points above ours. Replay is a memory-based method in a different budget class, and, more to the point, it neither exhibits nor exploits the noise-consolidation mechanism that is our subject: our contribution is the noise→retention *signature*, and the rule’s standing is realized *at its optimum*, exploiting a resource the anchored-drift methods are only harmed by. On the energy axis (Fig. 4b), generating the diffusion noise costs a digital accelerator a 23% fraction of each consolidation step; on analog silicon that fraction is physics, not compute — the dividend a von-Neumann machine must pay to fake.

4.5 E4 — second modality and the noise-optimum vs. task similarity

On continual Yin-Yang — a very different, procedural, BSS-2-native stream — the inverted-U reproduces (Fig. 5a), lift 7.4 points at $\sigma^* = 0.035$, with the OU control flat. Sweeping task similarity




Figure 3: **Device-faithful noise (emulation, not silicon).** (a) With the diffusion replaced by the BSS-2 model (colored + multiplicative + fixed-pattern + 6-bit), the inverted-U survives (lift 11.0 pts at $\sigma^* = 0.005$). (b) Scanning the temporal color ρ of the device noise maps where the mechanism holds — the concrete content of kill condition K2, to be settled on silicon.

(Fig. 5b) shows the optimum shifting with interference, sketching where noise-as-consolidator is most useful. Figure 6 locates the mechanism: the retention optimum coincides with a *forgetting minimum* at σ^* , while plasticity (accuracy just after learning each task) is roughly noise-insensitive — the per-synapse steering suppresses interference with old memories without blocking new learning. The inverted-U is thus a protection effect: too little noise under-powers the σ^2 steering, too much lets the raw diffusion overwhelm it.

5 What we do not claim

- **The drift is not novel.** $-s(w - \mu)$ is a re-derived limit of OUA/MESU/EWC [Garcia Fernandez et al., 2024, Bonnet et al., 2025, Kirkpatrick et al., 2017]. Our contribution is the Doob barrier-conditioning (a) and the inverted-U (b), only in conjunction.
- **No measured silicon.** The BSS-2 result is a device-faithful *emulation*. We report no measured on-chip retention and no measured joules; the energy numbers are an operation-count model. On-silicon validation (K2) is pre-registered and remains.
- **Benefit only at the optimum.** We do not claim the mechanism helps at arbitrary noise; it helps in an inverted-U window and hurts outside it. We report the whole curve, including the down-slope.
- **Not a retention SOTA claim.** The result is a mechanism and a signature, not a leaderboard entry. In particular plain replay, which stores raw exemplars, retains more than our rule (83.0% vs. 68.3%); we report this openly. Our comparison of record is against *rehearsal-free* anchored-drift methods under identical noise injection, where the signature and the standing are.




Figure 4: **Baselines (Split-MNIST, 8 seeds)**. (a) At its noise optimum the barrier-conditioned rule (Doob*, 68.3%) is the strongest *rehearsal-free* method: it matches MESU (65.2%) and significantly beats OU, EWC, Benna-Fusi and naive. Plain replay stores exemplars and scores higher (83.0%) — a different, memory-based budget class, shown for reference. (b) Retention vs. modelled compute-energy: a digital accelerator pays a 23% per-step energy tax to *fabricate* the diffusion noise; on BSS-2 (emulated energy) the same noise is intrinsic and free.

6 Limitations

Small single-head MLP testbeds; a diagonal-Fisher barrier; a ground-state (infinite horizon) h -transform rather than a finite-horizon survival function; a finite-force cap that softens the exact barrier divergence; an emulated rather than measured device. Each is a place the on-silicon step (K2) or a larger study could overturn or extend the result; the pre-registered kill conditions name the failure modes.

7 Reproducibility

All code, the pre-registered `PLAN.md` (committed before results), the committed `results/*.json`, and the figure/number generators are released. Every number in this paper is a machine-generated macro (`numbers.tex` from `gen_paper_numbers.py`); `verify_regen.py` checks that `numbers.tex` is byte-identical on regeneration. Seeds, the noise grid, the operating point, and the inverted-U test are fixed in `PLAN.md`. DOI at submission.

8 Conclusion

Casting per-synapse consolidation as a Doob h -transform makes a sharp, falsifiable prediction — intrinsic noise should non-monotonically improve retention — that the anchored-drift methods whose drift we share cannot make. The prediction holds, in simulation and in a device-faithful emulation, and is isolated to the barrier conditioning. If it survives on silicon, intrinsic analog noise becomes a consolidation resource that gets *cheaper* as devices get noisier — the opposite of the usual tax. That last step is the one we have not taken, and we have been careful to say so.




Figure 5: **Second modality.** (a) On continual Yin-Yang the inverted-U reproduces (lift 7.4 pts at $\sigma^* = 0.035$); the OU control is flat. (b) As tasks become less similar (larger per-task rotation, more interference) the noise optimum shifts, mapping the mechanism’s operating regime.

References

- Marcus K. Benna and Stefano Fusi. Computational principles of synaptic memory consolidation. *Nature Neuroscience*, 19:1697–1706, 2016. doi: 10.1038/nn.4401.
- Djohan Bonnet, Kellian Cottart, Tifenn Hirtzlin, Tarcisius Januel, Thomas Dalgaty, Elisa Vianello, and Damien Querlioz. Bayesian continual learning and forgetting in neural networks. *Nature Communications*, 16, 2025. doi: 10.1038/s41467-025-64601-w. arXiv:2504.13569; introduces MESU (Metaplasticity from Synaptic Uncertainty), Eq. 11.
- Wei Deng, Yu Chen, Nicole Tianjiao Yi, Ye Yuan, et al. Reflected schrödinger bridge for constrained generative modeling. In *Uncertainty in Artificial Intelligence (UAI)*, 2024. arXiv:2401.03228.
- Yuanqi Du, Michael Plainer, Rob Brekelmans, Chenru Duan, Frank Noé, Carla P. Gomes, Alán Aspuru-Guzik, and Kirill Neklyudov. Doob’s lagrangian: A sample-efficient variational approach to transition path sampling. In *International Conference on Learning Representations (ICLR)*, 2025. arXiv:2410.07974.
- Jesus Garcia Fernandez, Nasir Ahmad, and Marcel van Gerven. Ornstein-uhlenbeck adaptation as a mechanism for learning in brains and machines. *Entropy*, 26(12):1125, 2024. doi: 10.3390/e26121125. arXiv:2410.13563.
- Jeremy Heng, Valentin De Bortoli, Arnaud Doucet, and James Thornton. Simulating diffusion bridges with score matching. *arXiv preprint arXiv:2111.07243*, 2021.
- Mark Horowitz. 1.1 computing’s energy problem (and what we can do about it). *IEEE International Solid-State Circuits Conference (ISSCC)*, pages 10–14, 2014. doi: 10.1109/ISSCC.2014.6757323.
- James Kirkpatrick, Razvan Pascanu, Neil Rabinowitz, Joel Veness, Guillaume Desjardins, Andrei A. Rusu, Kieran Milan, John Quan, Tiago Ramalho, Agnieszka Grabska-Barwinska, Demis Hassabis, Claudia Clopath, Dharshan Kumaran, and Raia Hadsell. Overcoming catastrophic forgetting in neural networks. *Proceedings of the National Academy of Sciences*, 114(13):3521–3526, 2017. doi: 10.1073/pnas.1611835114.
- Ivan Kolesnikov and Nadezhda Semenova. Internal noise in hardware deep and recurrent neural networks helps with learning. *arXiv preprint arXiv:2504.13778*, 2025.




Figure 6: **Mechanism.** (a) The Doob steering drift $\sigma^2 \partial_w \log h$ for several noise levels: a barrier-divergent restoring force whose strength scales with the noise variance. (b) The retention optimum coincides with a forgetting minimum (1–forgetting peak) at σ^* ; plasticity is roughly noise-insensitive. The inverted-U is a protection effect, not a plasticity tradeoff.

Laura Kriener, Julian Göltz, and Mihai A. Petrovici. The yin-yang dataset. *Neuro-Inspired Computational Elements (NICE)*, 2022. arXiv:2102.08211.

Luca Manneschi, Ian T. Vidamour, Kilian D. Stenning, et al. Noise-aware training of neuromorphic dynamic device networks. *Nature Communications*, 16, 2025. doi: 10.1038/s41467-025-64232-1. arXiv:2401.07387.

Toan Nguyen, Kien Do, Duc Kieu, and Thin Nguyen. h-edit: Effective and flexible diffusion-based editing via doob’s h-transform. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2025. arXiv:2503.02187.

Christian Pehle, Sebastian Billaudelle, Benjamin Cramer, Jakob Kaiser, Korbinian Schreiber, Yannik Stradmann, Johannes Weis, Aron Leibfried, Eric Müller, and Johannes Schemmel. The brainscales-2 accelerated neuromorphic system with hybrid plasticity. *Frontiers in Neuroscience*, 16:795876, 2022. doi: 10.3389/fnins.2022.795876.

Nimrod Shaham, Jay Chandra, Gabriel Kreiman, and Haim Sompolsky. Stochastic consolidation of lifelong memory. *Scientific Reports*, 12:13107, 2022. doi: 10.1038/s41598-022-16407-9.

Johannes Weis, Philipp Spilger, Sebastian Billaudelle, Yannik Stradmann, Arne Emmel, Eric Müller, Oliver Breitwieser, Andreas Grübl, Joscha Ilmberger, Vitali Karasenko, Mitja Kleider, Korbinian Schreiber, Christian Weilbach, and Johannes Schemmel. Inference with artificial neural networks on analog neuromorphic hardware. In *IoT Streams for Data-Driven Predictive Maintenance / ITEM (Springer CCIS 1325)*, 2020. arXiv:2006.13177.

Fatima Tuz Zohora, Vedant Karia, Nicholas Soures, and Dhireesha Kudithipudi. Probabilistic metaplasticity for continual learning with memristors. *Scientific Reports*, 14, 2024. doi: 10.1038/s41598-024-78290-w. arXiv:2403.08718.