NTIRE 2026 Mobile Real-World Image Super-Resolution Challenge Factsheet Perceptual Score-Guided Image Super-resolutuon for Mobile Real-World Applications

Tongqi Guo, Ruhan Liu, Sangzi Shi, Huazhang Deng, Jie Yang
Wenzhuo Ma, Yuantong Zhang, Daiqin Yang, Zhenzhong Chen*
Wuhan University
{2024302131019,ruhan.liu,2024302131080,2023302131136,yang-jie}@whu.edu.cn
{mwzgorgeous,yuantongzhang,dqyang,zzchen}@whu.edu.cn
*Corresponding author

1. Factsheet Information

1.1. Team details

- Team name: Antman
- Team leader name: Zhenzhong Chen
- Team leader address, phone number, and email: School of Remote Sensing and Information Engineering, Wuhan University, Wuhan, 430079, China, +86 18162614523, zzchen@whu.edu.cn
- Rest of the team members: Tongqi Guo, Ruhan Liu, Sangzi Shi, Huazhang Deng, Jie Yang, Wenzhuo Ma, Yuantong Zhang, Daiqin Yang
- Affiliation: Wuhan University, China
- Affiliation of the team and/or team members with NTIRE 2026 sponsors (check the workshop website): None
- User names and entries on the NTIRE 2026 CodaBench competitions (development/validation and testing phases): ant-man, https://www.codabench.org/profiles/user/ant-man/
- Best scoring entries of the team during the testing phase: https://www.codabench.org/competitions/13509/detailed_results/628600/
- Link to the codes/executables of the solution(s): https://github.com/gunshi3/NTIRE2026_Mobile_RealWorld_ImageSR
- Link to the final results of the solution(s) on the testing data: https://drive.google.com/file/d/1MvjM8NUqXavxYdJzVJTlnridStCoa1ct/view?usp=drive_link

1.2. Method details

Method. Our solution is built on the RRDBNet(Fig.1) generator in ESRGAN[5], and we initialize the model with the pretrained Real-ESRGAN_x4plus weights[6]. The network keeps the standard Real-ESRGAN_x4plus configuration, including 3 input and output channels, 64 feature channels, 32 growth channels, and 23 RRDB blocks. This design provides sufficient representation capacity for restoring real-world degradations while maintaining a practical inference cost for the challenge setting.



Figure 1. The pipeline of RRDBNet.

Optimization. To adapt the pretrained generator to the target track, we combine a pixel reconstruction objective with perceptual score guidance. The reconstruction term is the L_1 loss between the restored image and the ground truth. In addition, we introduce a weighted score-guided loss composed of three no-reference quality predictors, namely MANIQA[8], MUSIQ[3], and CLIPIQA[4], together with two full-reference perceptual distance metrics, LPIPS[9] and DISTS[1]. During optimization, the model is encouraged to produce higher MANIQA, MUSIQ, and CLIPIQA scores while reducing LPIPS and DISTS. All quality scores are computed on clamped outputs in the range $[0, 1]$ for stable training.

Training Details. We fine-tune the model on DIV2K[2] and DRealSR[7]. Specifically, we use the 800-image unknown-degradation training split of DIV2K and the training split of DRealSR collected with five DSLR cameras. During each epoch, the model is trained on all 800 DIV2K images together with 800 images randomly sampled from DRealSR. HR patches of size 192×192 are randomly cropped, and random flipping is used for data augmentation. The mini-batch size is set to 4. We optimize the network with Adam for 10,000 iterations, starting from a learning rate

of 5×10^{-6} and halving it at 9,000 iterations. An exponential moving average (EMA) strategy is used throughout training.

References

[1] Keyan Ding, Kede Ma, Shiqi Wang, and Eero P Simoncelli. Image quality assessment: Unifying structure and texture similarity. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 44(5):2567–2581, 2020. 1

[2] ETH Zurich Computer Vision Laboratory. DIV2K Dataset. https://data.vision.ee.ethz.ch/cvl/DIV2K/, 2017. 1

[3] Junjie Ke, Qifei Wang, Yilin Wang, Peyman Milanfar, and Feng Yang. Musiq: Multi-scale image quality transformer. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 5148–5157, 2021. 1

[4] Jianyi Wang, Kelvin CK Chan, and Chen Change Loy. Exploring clip for assessing the look and feel of images. In *Proceedings of the AAAI Conference on Artificial Intelligence*, pages 2555–2563, 2023. 1

[5] Xintao Wang, Ke Yu, Shixiang Wu, Jinjin Gu, Yihao Liu, Chao Dong, Yu Qiao, and Chen Change Loy. ESRGAN: Enhanced super-resolution generative adversarial networks. In *Proceedings of the European Conference on Computer Vision Workshops*, pages 0–0, 2018. 1

[6] Xintao Wang, Liangbin Xie, Chao Dong, and Ying Shan. Real-ESRGAN: Training real-world blind super-resolution with pure synthetic data. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 1905–1914, 2021. 1

[7] Pengxu Wei, Ziwei Xie, Hannan Lu, Zongyuan Zhan, Qixiang Ye, Wangmeng Zuo, and Liang Lin. Component divide-and-conquer for real-world image super-resolution. In *Proceedings of the European Conference on Computer Vision*, pages 101–117. Springer, 2020. 1

[8] Sidi Yang, Tianhe Wu, Shuwei Shi, Shanshan Lao, Yuan Gong, Mingdeng Cao, Jiahao Wang, and Yujiu Yang. Maniqa: Multi-dimension attention network for no-reference image quality assessment. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 1191–1200, 2022. 1

[9] Richard Zhang, Phillip Isola, Alexei A Efros, Eli Shechtman, and Oliver Wang. The unreasonable effectiveness of deep features as a perceptual metric. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 586–595, 2018. 1