Aeolus Renewables

Drivetrain condition assessment using 10-minute SCADA measurements

131,760
sensor records

15
turbines

3.00%
recorded faults

Predictive Modeling with Machine Learning and Neural Networks | Low-Code Path

Submission date: October 11, 2026

Proprietary content. © Great Learning. All Rights Reserved. Unauthorized use or distribution prohibited.

Contents / Agenda

01 Executive summary and business problem

02 Exploratory analysis and preprocessing

03 Model comparison and final selection

04 Actionable recommendations

A Appendix: data, baselines, tuning and evidence

Proprietary content. © Great Learning. All Rights Reserved. Unauthorized use or distribution prohibited.

Executive Summary

VALIDATION RECALL	TEST RECALL	TEST PRECISION	TEST F1
92.49%	**86.40%**	**49.48%**	**62.93%**
Tuned ANN selected	1,245 / 1,441 faults	False-alert tradeoff	Balance of P and R

The operational decision

Use the ANN as analyst decision support, not an automatic turbine shutdown trigger.

1,271 false-positive records require remote triage; 196 fault records were missed.


Proprietary content. © Great Learning. All Rights Reserved. Unauthorized use or distribution prohibited.

Business Problem Overview and Solution Approach

WHY IT MATTERS

Missed drivetrain faults can lead to extended downtime, emergency repairs and lost energy production.

CONDITION-BASED WORKFLOW





Method: timestamp-grouped chronological split, training-only preprocessing, five baseline models, two tuned candidates, validation-driven selection.

Proprietary content. © Great Learning. All Rights Reserved. Unauthorized use or distribution prohibited.

EDA Results — Class Balance and Asset Patterns

131,760 readings • 15 turbines • 3.00% recorded faults






The minority fault class makes accuracy alone misleading; turbine-level rates support prioritised investigation.

Proprietary content. © Great Learning. All Rights Reserved. Unauthorized use or distribution prohibited.

EDA Results — Sensor Evidence




KEY OBSERVATIONS

Vibration, gearbox temperature and oil particles are visibly elevated in fault-state records.

Wind speed alone provides weaker separation, supporting multi-signal evaluation.

Proprietary content. © Great Learning. All Rights Reserved. Unauthorized use or distribution prohibited.

EDA Results — Multivariate Sensor Relationships



What the heatmap shows

Fault-state correlation (r):

- Drivetrain vibration: +0.54
- Oil-particle count: +0.47
- Bearing-frequency vibration: +0.23
- Oil pressure: −0.17
- Gearbox bearing temperature: +0.10

Insight: Condition signals are related but not interchangeable. Combining them is more defensible than a single alarm threshold.

Proprietary content. © Great Learning. All Rights Reserved. Unauthorized use or distribution prohibited.

Data Preprocessing and Leakage Prevention

DATA QUALITY

0 duplicate rows; missing gearbox-oil (645), generator-bearing (690), oil-pressure (636).

TREATMENT

Training-median imputation; ANN StandardScaler fit using training rows only.

FEATURE ENGINEERING

Time cycles, power utilisation and temperature-rise variables.

EVALUATION DESIGN

Timestamp-grouped chronological 70% / 15% / 15%; test reserved until final evaluation.

Proprietary content. © Great Learning. All Rights Reserved. Unauthorized use or distribution prohibited.

Model Performance Summary and Final Selection

Tuned model	Validation recall	F1	Precision
ANN (selected)	92.49%	53.54%	37.67%
XGBoost	69.10%	69.34%	69.57%

Selection rule

Maximise validation recall; F1 and precision are secondary tie-breakers.

ANN catches more recorded fault states. XGBoost offers better precision and F1, so the false-alert tradeoff must be managed.

Proprietary content. © Great Learning. All Rights Reserved. Unauthorized use or distribution prohibited.

Actionable Business Recommendations

01 Triage

Review persistent model alerts and corroborating sensor signals remotely.

02 Dispatch

Prioritise technician inspections when risk persists across successive intervals.

03 Learn

Link alerts to work orders; track false alarms, missed faults, and operational workload.

04 Validate

Run prospective field validation before promising lead time or cost savings.

Pilot evidence: 196 missed fault-state records support recall-first selection; 1,271 false-positive records are not 1,271 visits. Triage remotely; monitor confirmations, workload, downtime and drift.

Proprietary content. © Great Learning. All Rights Reserved. Unauthorized use or distribution prohibited.

APPENDIX — Data Background and Contents

SCADA panel

8,784 timestamp groups, recorded at 10-minute intervals across 15 turbines.

Environment

Wind, ambient conditions

Operation

Power and rotational speeds

Condition

Bearing heat, vibration, oil particles

Asset history


Hours, load cycles and maintenance

Target: failure = 1 denotes a recorded fault condition, not a future failure horizon.

Proprietary content. © Great Learning. All Rights Reserved. Unauthorized use or distribution prohibited.

Model Building — Five Baseline Classifiers


Model	Accuracy	Precision	Recall	F1
Decision Tree	90.70%	27.74%	47.93%	35.14%
Random Forest	95.35%	82.87%	14.44%	24.59%
Gradient Boosting	94.54%	46.96%	29.74%	36.42%
XGBoost	96.64%	71.01%	60.83%	65.53%
ANN	94.79%	50.28%	68.05%	57.83%



ANN and XGBoost have the highest baseline recall and were selected for tuning.

Proprietary content. © Great Learning. All Rights Reserved. Unauthorized use or distribution prohibited.

Model Improvement — Hyperparameter Tuning



XGBOOST

6 randomized configurations; 2 expanding time folds, recall objective.
Best: 160 trees, depth 3, rate 0.07, row sample 0.85, column sample 1.0, min child weight 3.
CV recall 48.45%; validation recall 69.10%.

ANN

Baseline versus regularized 64/24-unit network; BatchNorm, dropout 0.30/0.15, Adam and early stopping.
No multi-configuration search recorded.
Validation recall 92.49%.

Proprietary content. © Great Learning. All Rights Reserved. Unauthorized use or distribution prohibited.

Tuning Comparison — Recall and Precision

Candidates chosen by baseline validation recall; test data excluded from tuning and selection.

Model	Baseline P / R / F1	Tuned P / R / F1	Configuration / method
ANN	50.28 / 68.05 / 57.83	37.67 / 92.49 / 53.54	64/24 units; regularization; early stopping
XGBoost	71.01 / 60.83 / 65.53	69.57 / 69.10 / 69.34	6 configurations; 2 expanding time folds

Selection rationale
Tuned ANN wins on validation recall (92.49% versus 69.10%). XGBoost provides higher precision and F1, reducing false alerts. Both tradeoffs should be monitored in a field pilot.

Proprietary content. © Great Learning. All Rights Reserved. Unauthorized use or distribution prohibited.

Final Model Performance — Untouched Test


TEST RECALL
86.40%

TEST PRECISION
49.48%

TEST ACCURACY
92.58%


TEST F1
62.93%

1,245 detected • 196 missed
1,271 false alerts • 17,058 true normals



Proprietary content. © Great Learning. All Rights Reserved. Unauthorized use or distribution prohibited.

Feature Interpretation and Limitations



KEY DRIVERS

Drivetrain vibration and oil particle count show the largest validation-recall impacts.

Permutation importance measures association, not causation or a future-failure lead time.

Proprietary content. © Great Learning. All Rights Reserved. Unauthorized use or distribution prohibited.

Timestamp-Grouped Split Verification

TRAIN

92,220

6,148 timestamps

VALIDATION


19,770

1,318 timestamps

TEST

19,770

1,318 timestamps



LEAKAGE CHECK

All 15 turbine records at a timestamp remain in the same partition. Failure prevalence changes over time.

Proprietary content. © Great Learning. All Rights Reserved. Unauthorized use or distribution prohibited.

Operational Use Case and Next Steps

STAGE 1

Model flags current abnormal condition.

STAGE 2

Analyst checks persistence and supporting sensors.

STAGE 3

Maintenance team prioritises planned inspection.

DEPLOYMENT GUARDRAILS

Retrospective proof of concept: prospectively validate alert value, technician workload, model drift and downtime outcomes before automated action or savings claims.

Proprietary content. © Great Learning. All Rights Reserved. Unauthorized use or distribution prohibited.