

Descripción del Producto	Broca SDS-MAX de 3 cortadores. Cabezal geometría simétrica.																																																																																																							
Imagen referencial																																																																																																								
Medidas disponibles	Ø: 12 a 42 mm; Longitud 180 a 450 mm. Ø 12-28 mm Ø 30-42 mm  Single Piece Carbide  Segmented Carbide																																																																																																							
Dureza	47 +/-7 HRC																																																																																																							
Superficie	Gris granallado; Protección antioxidante.																																																																																																							
Toma	SDS-MAX																																																																																																							
DIN	8035																																																																																																							
Composición de la placa	Carburo Tungsteno, certificación PGM.																																																																																																							
Usos	Hormigón armado, Hormigón, Piedra natural, Ladrillos y Mampostería.																																																																																																							
Energía de impacto recomendada	<table><tr><th>Rotary hammer drill class</th><th>Impact energy</th><th colspan="13">Drilling diameter in concrete [mm]</th></tr><tr><th>[kg]</th><th>[J]</th><th>4</th><th>5</th><th>6</th><th>8</th><th>10</th><th>12</th><th>14</th><th>16</th><th>18</th><th>20</th><th>22</th><th>24</th><th>26</th></tr><tr><td>2</td><td>< 2</td><td>Recommended application range</td><td>Recommended application range</td><td>Recommended application range</td><td>Recommended application range</td><td>Recommended application range</td><td>Recommended application range</td><td>Recommended application range</td><td>Recommended application range</td><td>Recommended application range</td><td>Recommended application range</td><td>Recommended application range</td><td>Recommended application range</td><td>Recommended application range</td></tr><tr><td>2</td><td>> 2</td><td>Recommended application range</td><td>Recommended application range</td><td>Recommended application range</td><td>Recommended application range</td><td>Recommended application range</td><td>Recommended application range</td><td>Recommended application range</td><td>Recommended application range</td><td>Recommended application range</td><td>Recommended application range</td><td>Recommended application range</td><td>Recommended application range</td><td>Recommended application range</td></tr><tr><td>3</td><td>> 3</td><td>Recommended application range</td><td>Recommended application range</td><td>Recommended application range</td><td>Recommended application range</td><td>Recommended application range</td><td>Recommended application range</td><td>Recommended application range</td><td>Recommended application range</td><td>Recommended application range</td><td>Recommended application range</td><td>Recommended application range</td><td>Recommended application range</td><td>Recommended application range</td></tr><tr><td>4</td><td>> 4</td><td>Recommended application range</td><td>Recommended application range</td><td>Recommended application range</td><td>Recommended application range</td><td>Recommended application range</td><td>Recommended application range</td><td>Recommended application range</td><td>Recommended application range</td><td>Recommended application range</td><td>Recommended application range</td><td>Recommended application range</td><td>Recommended application range</td><td>Recommended application range</td></tr></table> Recommended application range Recommended based on concrete														Rotary hammer drill class	Impact energy	Drilling diameter in concrete [mm]													[kg]	[J]	4	5	6	8	10	12	14	16	18	20	22	24	26	2	< 2	Recommended application range	Recommended application range	Recommended application range	Recommended application range	Recommended application range	Recommended application range	Recommended application range	Recommended application range	Recommended application range	Recommended application range	Recommended application range	Recommended application range	Recommended application range	2	> 2	Recommended application range	Recommended application range	Recommended application range	Recommended application range	Recommended application range	Recommended application range	Recommended application range	Recommended application range	Recommended application range	Recommended application range	Recommended application range	Recommended application range	Recommended application range	3	> 3	Recommended application range	Recommended application range	Recommended application range	Recommended application range	Recommended application range	Recommended application range	Recommended application range	Recommended application range	Recommended application range	Recommended application range	Recommended application range	Recommended application range	Recommended application range	4	> 4	Recommended application range	Recommended application range	Recommended application range	Recommended application range	Recommended application range	Recommended application range	Recommended application range	Recommended application range	Recommended application range	Recommended application range	Recommended application range	Recommended application range	Recommended application range
Rotary hammer drill class	Impact energy	Drilling diameter in concrete [mm]																																																																																																						
[kg]	[J]	4	5	6	8	10	12	14	16	18	20	22	24	26																																																																																										
2	< 2	Recommended application range	Recommended application range	Recommended application range	Recommended application range	Recommended application range	Recommended application range	Recommended application range	Recommended application range	Recommended application range	Recommended application range	Recommended application range	Recommended application range	Recommended application range																																																																																										
2	> 2	Recommended application range	Recommended application range	Recommended application range	Recommended application range	Recommended application range	Recommended application range	Recommended application range	Recommended application range	Recommended application range	Recommended application range	Recommended application range	Recommended application range	Recommended application range																																																																																										
3	> 3	Recommended application range	Recommended application range	Recommended application range	Recommended application range	Recommended application range	Recommended application range	Recommended application range	Recommended application range	Recommended application range	Recommended application range	Recommended application range	Recommended application range	Recommended application range																																																																																										
4	> 4	Recommended application range	Recommended application range	Recommended application range	Recommended application range	Recommended application range	Recommended application range	Recommended application range	Recommended application range	Recommended application range	Recommended application range	Recommended application range	Recommended application range	Recommended application range																																																																																										
Características del producto	Roto-percutor, Punta Auto-centrante, Chaflanes de barras de refuerzo patentados, 3 estrías con resistencia central optimizada.																																																																																																							
País de origen	Alemania.																																																																																																							