Accumulator models of response time

Joachim Vandekerckhove Spring 2025

Accumulator models describe the process that generates speeded CRTs

Accumulator models describe the process that generates speeded CRTs

These models start from a number of representation assumptions:

 Deciders accumulates small bits of evidence, sequentially over time, from the stimulus they were exposed to

Accumulator models describe the process that generates speeded CRTs

These models start from a number of representation assumptions:

- Deciders accumulates small bits of evidence, sequentially over time, from the stimulus they were exposed to
- Most stimuli are at least somewhat ambiguous (noisy)

Accumulator models describe the process that generates speeded CRTs

These models start from a number of representation assumptions:

- Deciders accumulates small bits of evidence, sequentially over time, from the stimulus they were exposed to
- Most stimuli are at least somewhat ambiguous (noisy)
- Deciders aggregates this evidence with the evidence already accumulated

Accumulator models describe the process that generates speeded CRTs

These models start from a number of representation assumptions:

- Deciders accumulates small bits of evidence, sequentially over time, from the stimulus they were exposed to
- Most stimuli are at least somewhat ambiguous (noisy)
- Deciders aggregates this evidence with the evidence already accumulated
- After each accumulation step, deciders evaluate whether the total amount of information in favor of a decision is enough to execute a response

There exist many accumulator models for response times

There exist many accumulator models for response times

They differ in, among other things:

• Whether they allow for two, many, or only one choice

There exist many accumulator models for response times

- Whether they allow for two, many, or only one choice
- Whether time is treated as discrete or continuous

There exist many accumulator models for response times

- Whether they allow for two, many, or only one choice
- Whether time is treated as discrete or continuous
- Whether the accumulation of evidence is at a constant rate

There exist many accumulator models for response times

- Whether they allow for two, many, or only one choice
- Whether time is treated as discrete or continuous
- Whether the accumulation of evidence is at a constant rate
- Whether the evidence 'leaks' over time


There exist many accumulator models for response times

- Whether they allow for two, many, or only one choice
- Whether time is treated as discrete or continuous
- Whether the accumulation of evidence is at a constant rate
- Whether the evidence 'leaks' over time
- Whether evidence for one choice counts as evidence against the other


There exist many accumulator models for response times

- Whether they allow for two, many, or only one choice
- Whether time is treated as discrete or continuous
- Whether the accumulation of evidence is at a constant rate
- Whether the evidence 'leaks' over time
- Whether evidence for one choice counts as evidence against the other
- ..


Evidence is accumulated over short periods of time



The evidence accumulation process occurs at each trial of an experiment, with each process hitting one or the other boundary at some time point



On repeated runs, the first passage times can form a smooth distribution



This distribution is sometimes called the Wiener distribution:

$$p(t, a) = W(\delta, \alpha, \tau, \beta)$$

Cognitive models that use assumptions like these are usually called accumulator models

Cognitive models that use assumptions like these are usually called accumulator models


A particularly popular case of this category of models are the diffusion models for two-choice response times

Cognitive models that use assumptions like these are usually called accumulator models

A particularly popular case of this category of models are the diffusion models for two-choice response times

Diffusion models are popular for a few reasons: they are mathematically somewhat convenient, they seem to fit data well in practice, and they have a small number of easy-to-interpret parameters


	parameter	interpretation
δ	drift rate	dominance (η, d')
α	boundary separation	caution
au	nondecision time	time for encoding and responding
β	initial bias	a priori response bias



Diffusion model parameters in delta plots

Diffusion model parameter effects become tell-tale patterns in delta plots


	parameter	interpretation
δ	drift rate	dominance (η, d')
α	boundary separation	caution
au	nondecision time	time for encoding and responding



Diffusion model parameters in delta plots

Effects on the initial bias often only show when you split the delta plot by error/correct — they can cancel out if you don't!

parameterβ, initial biasinterpretationa priori response bias



Diffusion model parameter estimation

While a quick look at delta plots can be informative, ultimately we want to estimate model parameters from data

Diffusion model parameter estimation

While a quick look at delta plots can be informative, ultimately we want to estimate model parameters from data

Often, we will perform constrained parameter estimation so that, for example each participant has one α_p and τ_p , independent of condition

Diffusion model parameter estimation

While a quick look at delta plots can be informative, ultimately we want to estimate model parameters from data

Often, we will perform constrained parameter estimation so that, for example each participant has one α_p and τ_p , independent of condition

person p	condition c	RT	accuracy		α_p	δ_{pc}	$ au_p$
1	3	0.71	correct		1.61	0.45	0.24
1	5	0.49	correct		1.61	1.17	0.24
:	:	:	:		:	:	÷
1	3	0.43	error	\rightarrow	1.61	0.53	0.24
2	4	0.67	error		2.14	0.08	0.31
:	:	:	:		:	:	:

Weekly assignment: Generate delta plots for diffusion models

Recreate the delta plots in the slides

- Using the 3-ddm/src/diffusion_simulator.py script to generate data from a diffusion model, write your own script to generate delta plots
- Use as baseline parameters:
 - $-\delta = 2.00$ (and as contrast use $\delta = 1.00$)
 - $\alpha = 1.00$ (and as contrast use $\alpha = 2.00$)
 - $-\tau = 0.25$ (and as contrast use $\tau = 0.50$)
 - $-\beta = 0.35$ (and as contrast use $\beta = 0.65$)
- Select a reasonable number of samples for the simulation
- Use percentiles 10, 30, 50, 70, and 90
- Make sure you label your axes, annotate the plot, and feel free to use pretty (readable!) colors

Accumulator models of response time

Joachim Vandekerckhove Spring 2025