

公	主要参数L、d (D) mm															
差等级	≤10	> 10 ~ 16	> 16 ~ 25	> 25 ~ 40	> 40 ~ 63	> 63 ~ 100	> 100 ~ 160	> 160 ~ 250	> 250 ~ 400	> 400 ~ 630	> 630 ~ 1000	> 1000 ~ 1600	> 1600 ~ 2500	> 2500 ~ 4000	> 4000 ~ 6300	> 6300 ~ 10000
		公差值/µm														
1	0.4	0.5	0.6	0.8	1	1.2	1.5	2	2.5	3	4	5	6	8	10	12
2	0.8	1	1.2	1.5	2	2.5	3	4	5	6	8	10	12	15	20	25
3	1.5	2	2.5	3	4	5	6	8	10	12	15	20	25	30	40	50
4	3	4	5	6	8	10	12	15	20	25	30	40	50	60	80	100
5	5	6	8	10	12	15	20	25	30	40	50	60	80	100	120	150
6	8	10	12	15	20	25	30	40	50	60	80	100	120	150	200	250
7	12	15	20	25	30	40	50	60	80	100	120	150	200	250	300	400
8	20	25	30	40	50	60	80	100	120	150	200	250	300	400	500	600
9	30	40	50	60	80	100	120	150	200	250	300	400	500	600	800	1000
10	50	60	80	100	120	150	200	250	300	400	500	600	800	1000	1200	1500
11	80	100	120	150	200	250	300	400	500	600	800	1000	1200	1500	2000	2500
12	120	150	200	250	300	400	500	600	800	1000	1200	1500	2000	2500	3000	4000