

Injection Charge Pump / Charging Injection Horizontal Centrifugal Pump
Data Sheet

Parameter	Value	Parameter	Value
Company	Gulf of Suez Petroleum Company	Proposal Curve No.	10 x 14SD-4
Service	Injection Charge Pump / Charging Injection Pump	NPSH Req'd (Water), ft	18.0
Item No.	P-3A, B, C	No. of Stages	1
Motor Drive / Turbine	Elec. Motor Drive	RPM	1750
Size & Type	Horizontal Centrifugal, 10 x 14 SI	Des. Eff.	86.5
No. of Units	3	BHP	189
Total GPM	12,500	Max. BHP Rated Imp.	204
Liquid	Seawater filtered and deaerated	Max. Head Rated Imp., ft	190
P.T., F	Max. 100 °F	Min. Continuous (by MFR), GPM	300 (Est.)
Sp. Gr. at PT	1.03	Rotation Facing Coupling End	CCW
Vap. Press. at PT, psia	0.6	Water Cooling	None reqd
Vis. at PT, cSt	—	U.S. GPM at PT, Nor.	4170
Corr./Eros. Caused By	Salt & Chlorine	Disch. Press., psig	74
Suct. Press., psig Max.	100	Diff. Press., psi	67.5
Diff. Head, ft	151	NPSH Avail., ft	20