


← [course home \(/table-of-contents\)](/table-of-contents)



Queue


Data Structure (</data-structures-reference>)

Quick reference

A **queue** stores items in a first-in, first-out (FIFO) order.

Picture a queue like the line outside a busy restaurant. First come, first served.

enqueue(b)



Worst Case

space	$O(n)$
enqueue	$O(1)$
dequeue	$O(1)$
peek	$O(1)$

Strengths:

- **Fast operations.** All queue operations take $O(1)$ time.

Uses

- **Breadth-first search (/concept/bfs)** uses a queue to keep track of the nodes to visit next.
- **Printers** use queues to manage jobs—jobs get printed in the order they're submitted.

- **Web servers** use queues to manage requests—page requests get fulfilled in the order they're received.
- **Processes** wait in the CPU scheduler's queue for their turn to run.

Implementation

Queues are easy to implement with linked lists (</concept/linked-list/>):

- To enqueue, insert at the tail of the linked list.
- To dequeue, remove at the head of the linked list.

You *could* implement a queue with an array (</concept/array/>) or dynamic array (</concept/dynamic-array/>), but it would get kinda messy. Try drawing it out. You'll notice that you'd need to build out a "scoot over" or "re-center" operation that automatically fires when your queue items hit the bottom edge of the array.

← [course home \(/table-of-contents/\)](/table-of-contents/)

Next up: Stack → (</concept/stack?course=fc1§ion=queues-stacks>)

Want more coding interview help?

Check out **interviewcake.com** for more advice, guides, and practice questions.