Microsoft

Azure Key Vault Managed HSM

Azure Key Vault Premium Keys to Azure Managed HSM Migration – White Paper

Author: Robert McDaniel (Senior Consultant), Naresh Gupta (Senior Consultant)

This guide outlines a backup, restore, and disaster recovery strategy for **Azure Key Vault Managed HSM** in **GCC High, GCC and Commercial** environments, offering both conceptual guidance and a practical runbook to safeguard Microsoft 365 Customer Key assets and ensure compliance.

Introduction and Executive Summary

Migrating cryptographic keys from Azure Key Vault to Azure Managed Hardware Security Module (HSM) delivers dedicated, single-tenant HSM infrastructure with FIPS 140-3 Level 3 validated hardware, providing one of the highest levels of cryptographic module security available in the cloud. For organizations operating in regulated environments such as Azure Government (GCC High), this migration supports compliance with FedRAMP High and other government regulations while enabling customer-controlled encryption (key sovereignty) across Azure and Microsoft 365 platforms. This white paper provides a comprehensive, step-by-step roadmap for executing a PowerShell-based automation script, targeting technical decision-makers and implementers in government, healthcare, and enterprise IT organizations.

A central consideration in this migration is the cryptographic domain boundary: software-protected keys can be transferred via backup/restore with their original key material intact, but HSM-protected keys from Key Vault Premium **must be re-created** in the target Managed HSM, resulting in **different key material**. This means all applications consuming HSM-backed keys must update their key URIs after migration. The migration script automates this re-creation, but teams must plan for the downstream configuration changes it requires.

An additional architectural consideration, identified during real-world implementation projects, is that **Azure Key Vault Managed HSM supports only keys — not secrets or certificates**. Secrets and certificates must remain in Key Vault or be migrated to alternative secure storage. This limitation should be factored into migration planning from the outset.

Complete Pre-Migration Setup

Before migrating, ensure prerequisites are met: **enable purge protection** on the source Key Vault, activate the **target Managed HSM** (initialize its security domain), and assign all required **RBAC roles** for key access on **both** the Key Vault and HSM.

Validate with a Dry Run First

Use the migration script's **Dry Run** mode (`-DryRun`) to simulate the key transfer before any production changes. This mode identifies which keys would be migrated, which HSM keys would require re-creation, and which secrets/certificates cannot be moved — all **without making changes** to the environment.

Update All Key References Post-Migration

HSM-protected keys from Key Vault are **re-created** on the target HSM with the same properties but **different key material** due to crypto domain boundaries. After migration, **all applications must be reconfigured with the new Managed HSM key URIs**. Dependent services including disk encryption, SQL TDE, and AKS integrations must also be updated.

Phase 1 – Pre-Migration Preparation

Plan & Setup: Verify the source Key Vault is Premium SKU with purge protection enabled. Provision and activate the target Managed HSM (Standard_B1 or Enterprise_E1). Assign RBAC roles on both resources and install Azure CLI and PowerShell 7+.

Phase 2 – Migration Execution

Run Migration Script: Execute a dry-run to simulate the migration, review generated reports, then perform the production migration of keys with optional CMK validation testing.

Phase 3 – Post-Migration Verification

Validate & Reconfigure: Verify key counts and properties on the HSM match expectations. Update all application configurations and dependent Azure service key references to use new Managed HSM URIs. Handle secrets separately since they remain in Key Vault.

Phase 4 – Decommissioning

Monitor & Retire: Observe the source Key Vault for a grace period of 30–90 days to ensure no unexpected usage. Confirm all services are using HSM keys, then take a final backup and decommission the legacy vault.

Prerequisites

The following infrastructure and tooling must be in place before migration begins:

1. Azure Resources Required

- **Source Key Vault** — Standard or Premium SKU. Must have **purge protection enabled** and should contain the keys, secrets, and certificates targeted for migration. If migrating HSM-protected keys (key types ending in -HSM), the vault **must be Premium SKU**.
- **Target Managed HSM** — Azure Managed HSM with SKU **Standard_B1** or **Enterprise_E1**. The HSM must be **activated with its security domain** initialized, must have **purge protection enabled**, and a **private endpoint is recommended for production** deployments.

2. Azure CLI Installation

The Azure CLI must be installed and authenticated:

```
# Verify Azure CLI installation
az --version

# Log in to Azure
az login

# Set the active subscription (replace with your actual Subscription ID)
az account set --subscription "YOUR_SUBSCRIPTION_ID"
```

3. PowerShell Requirements

PowerShell 7+ (Core) is recommended; Windows PowerShell 5.1+ is the minimum supported version.

Required Permissions & Role Assignments

Proper permissions on both the source Key Vault and target Managed HSM are essential. The migrating identity (user account or service principal) requires read, backup, and key-creation rights.

Source Key Vault Permissions

Option A: RBAC-Based (Recommended)

Assign the following four roles on the source Key Vault:

Role	Purpose
Key Vault Crypto Officer	Read and backup keys
Key Vault Secrets Officer	Read and list secrets
Key Vault Certificates Officer	Read and list certificates
Key Vault Reader	General vault read access

```
$userId = az ad signed-in-user show --query id -o tsv
$kvId = az keyvault show --name "YOUR_SOURCE_KV" --query id -o tsv

az role assignment create --role "Key Vault Crypto Officer" --assignee $userId --scope $kvId
az role assignment create --role "Key Vault Secrets Officer" --assignee $userId --scope $kvId
az role assignment create --role "Key Vault Certificates Officer" --assignee $userId --scope
$kvId
az role assignment create --role "Key Vault Reader" --assignee $userId --scope $kvId

# Critical: Wait 60 seconds for RBAC propagation
Start-Sleep -Seconds 60
```

Option B: Access Policy-Based (Legacy)

For vaults using the legacy access policy model, grant key permissions (get, list, backup), secret permissions (get, list), and certificate permissions (get, list, backup) to the migrating user.

Target Managed HSM Permissions

Assign the **Managed HSM Crypto Officer** role (scope /keys) for key creation in the HSM, and the **Managed HSM Crypto Service Encryption User** role (scope /keys) if performing CMK validation with storage accounts:

```
$hsmName = "YOUR_TARGET_HSM"

az keyvault role assignment create --hsm-name $hsmName --role "Managed HSM Crypto Officer" `
  --assignee $userId --scope /keys

# For CMK validation with storage accounts
az keyvault role assignment create --hsm-name $hsmName `
  --role "Managed HSM Crypto Service Encryption User" `
  --assignee $userId --scope /keys

# Wait 60 seconds for RBAC propagation
Start-Sleep -Seconds 60
```

Storage Account Permissions (for CMK Validation)

If using the CMK validation scenario (Scenario 3), retrieve the storage account's managed identity principal ID and grant it key wrap/unwrap permissions on both the source Key Vault and target HSM. For the Key Vault, use az keyvault set-policy with --key-permissions get wrapKey unwrapKey; for HSM, assign the **Managed HSM Crypto Service Encryption User** role to the storage identity.

Pre-Migration Preparation

Step 1: Enable Purge Protection on the Source Key Vault

Purge protection is **required** for backup/restore operations and **cannot be disabled once enabled**:

```
az keyvault update --name "YOUR_SOURCE_KV" --resource-group "YOUR_RG" --enable-purge-
protection true
```

Verify the target Managed HSM also has purge protection enabled (it should be by default).

Step 2: Activate Managed HSM (if not already done)

Check HSM activation status and, if not activated, follow the security domain initialization process. This requires generating **3 or more separate RSA key pairs (2048-bit minimum)** and downloading the security domain with a quorum (m-of-n).

Reference:

Step 3: Upgrade Key Vault to Premium (if migrating HSM keys)

Only required if the source vault is Standard SKU and you intend to test HSM key types before migration:

```
az keyvault update --name "YOUR_SOURCE_KV" --resource-group "YOUR_RG" --sku premium
```

Step 4: Backup Source Key Vault (Recommended)

Document the current inventory of all keys, secrets, and certificates before migration for rollback and auditing purposes:

```
az keyvault key list --vault-name "YOUR_SOURCE_KV" -o table
az keyvault secret list --vault-name "YOUR_SOURCE_KV" -o table
az keyvault certificate list --vault-name "YOUR_SOURCE_KV" -o table
```

Migration Scenarios and Execution

Let's assume you have the migration script (named: Migrate-KeyVaultToManagedHSM-CLI.ps1) which supports four scenarios to accommodate testing and production requirements.

Scenario 1: Dry Run (Test Mode — Recommended First)

```
.\ImplementationGuides\Migrate-KeyVaultToManagedHSM-CLI.ps1 `
  -SourceKeyVaultName "kv-source" `
  -TargetManagedHSMName "hsm-target" `
  -ResourceGroupName "rg-keyvault" `
  -DryRun `
  -SkipCertificates
```

The script analyzes what would be migrated **without making any changes**. Output includes which keys would be migrated, which HSM keys will be recreated, and reports on secrets and certificates.

Scenario 2: Keys-Only Migration (Most Common)

```
.\ImplementationGuides\Migrate-KeyVaultToManagedHSM-CLI.ps1 `
  -SourceKeyVaultName "kv-existing-samesub-02" `
  -TargetManagedHSMName "mhsm-kv-il2-eus2" `
  -ResourceGroupName "existing-kv-rg" `
  -SkipCertificates
```

Scenario 3: Migration with CMK Validation (Production Ready)

```
.\ImplementationGuides\Migrate-KeyVaultToManagedHSM-CLI.ps1 `
  -SourceKeyVaultName "kv-source" `
  -TargetManagedHSMName "hsm-target" `
  -ResourceGroupName "rg-keyvault" `
  -ValidateWithCMK `
  -TestStorageAccountName "cmktest$(Get-Random -Max 9999)" `
  -TestKeyName "test-cmk-migration-key" `
  -TestDataSizeMB 10 `
  -CleanupTestResources `
  -SkipCertificates
```

This performs full **end-to-end validation** including creating a test key in the source Key Vault, provisioning a storage account with CMK encryption, uploading test data (10 MB), verifying data integrity via checksum, migrating keys to the HSM, updating the storage account to use the HSM key, and verifying both existing and new data accessibility. If -CleanupTestResources is specified, temporary resources are removed after validation. **Use case**: Full end-to-end validation including CMK encryption scenario testing.

Scenario 4: Migration with Custom Log Path

```
.\ImplementationGuides\Migrate-KeyVaultToManagedHSM-CLI.ps1 `
  -SourceKeyVaultName "kv-source" `
  -TargetManagedHSMName "hsm-target" `
  -ResourceGroupName "rg-keyvault" `
  -LogPath "C:\Logs\Migration-$(Get-Date -Format 'yyyyMMdd-HHmmss').log"
  -SkipCertificates
```

Identical to a standard keys-only migration but writes the console log to a custom file path for audit or archival purposes.

Understanding Migration Output

Generated Reports

The script produces four reports in the current working directory:

Report File	Contents
Migration-Log-CLI-\[timestamp].txt	Detailed execution log with timestamps, INFO/WARNING/ERROR/SUCCESS indicators, and step-by-step progress
Keys-Migration-Report-\[timestamp].json	Per-key JSON with name, key type, enabled status, migration status, migration action, and notes including the new HSM key URI
Secrets-Migration-Report-CLI-\[timestamp].json	Per-secret JSON documenting all secrets (not migrated), with content type and recommendation for alternative storage
Migration-Summary-Report-CLI-\[timestamp].json	Overall summary with inventory counts, migration statistics, recommendations, timestamp, and configuration

Example key migration report entry — a key migrated as "Recreated" includes a note with the new HSM key URI that applications must adopt:

```
{
  "Name": "test-key-01",
  "KeyType": "RSA",
  "Enabled": true,
  "MigrationStatus": "Recreated",
  "MigrationAction": "New key created in target HSM",
  "Notes": "Original key in source KV, new key created in target HSM with same properties.
Update app configs with new key URI: https://mhsm-target.managedhsm.azure.net/keys/test-key-
01"
}
```

Example secrets report entry — secrets receive a "Manual Review Required" action since they are not supported in Managed HSM:

```
{
  "Name": "db-connection-string",
  "ContentType": "text/plain",
  "Enabled": true,
  "MigrationAction": "Manual Review Required",
  "Notes": "Secrets are not supported in Managed HSM. Consider alternative storage or convert
to secure key if applicable."
}
```

Key Migration Outcomes

The following table summarizes how different key types are handled, and whether original key material is preserved:

Key Type	Source Key Vault	Target MHSM	Migration Method	Same Key Material?
RSA (software)	Standard / Premium	RSA-HSM	Backup → Restore	Yes
RSA-HSM (Premium)	Premium	RSA-HSM	Recreated	No (new key)
EC (software)	Standard / Premium	EC-HSM	Backup → Restore	Yes
EC-HSM (Premium)	Premium	EC-HSM	Recreated	No (new key)

⚠ **Critical**: HSM keys are **recreated** with the same properties (type, size, operations) but **different underlying key material** because key material cannot cross cryptographic domain boundaries. Applications consuming these keys **must** be updated to the new key URIs.

Migration Status Definitions

Status	Meaning	Action Required
Success	Key migrated via backup/restore	Update application config with new HSM URI
Recreated	Key recreated due to crypto domain boundary	⚠ **Critical**: Update app config **and** rotate all key references
Skipped	Key already exists in the target HSM	Verify existing key is correct
Failed	Migration error occurred	Review error logs, retry if needed
Planned	Dry run — would migrate in a real execution	Proceed to run actual migration

Post-Migration Steps

Step 1: Verify Migration

Confirm that **all expected keys are present in the target HSM** with correct types and sizes:

```
# List keys in target HSM
az keyvault key list --hsm-name "YOUR_HSM" -o table

# Compare count with source
az keyvault key list --vault-name "YOUR_SOURCE_KV" -o table

# Test a specific key operation
az keyvault key show --hsm-name "YOUR_HSM" --name "test-key-01"

# Compare key properties between source and target
az keyvault key show --vault-name "YOUR_SOURCE_KV" --name "test-key-01" `
  --query '{Type:key.kty, Size:key.n}' -o json
az keyvault key show --hsm-name "YOUR_HSM" --name "test-key-01" `
  --query '{Type:key.kty, Size:key.n}' -o json
```

Step 2: Update Application Configurations

Every key URI change format when moving from Key Vault to Managed HSM:

	URI Format
Old (Key Vault)	https://kv-source.vault.azure.net/keys/my-key/<guid>
New (Managed HSM)	https://hsm-target.managedhsm.azure.net/keys/my-key/<guid>

Update all application settings to reference the new HSM URIs. For **Azure App Service**:

```
az webapp config appsettings set `
  --name "YOUR_APP" --resource-group "YOUR_RG" `
  --settings KeyVaultUri="https://hsm-target.managedhsm.azure.net" KeyName="your-key-name"
```

For **Azure Functions**:

```
az functionapp config appsettings set `
  --name "YOUR_FUNCTION" --resource-group "YOUR_RG" `
  --settings KeyUri="https://hsm-target.managedhsm.azure.net/keys/my-key"
```

Step 3: Update Key References in Dependent Azure Services

Azure Disk Encryption — Update VM disk encryption to reference the Managed HSM key:

```
az vm encryption enable `
  --resource-group "YOUR_RG" --name "YOUR_VM" `
  --disk-encryption-keyvault "hsm-target" `
  --key-encryption-key "https://hsm-target.managedhsm.azure.net/keys/disk-key"
```

SQL Server Transparent Data Encryption (TDE) — Create a server key in the HSM and set it as the TDE protector:

```
az sql server key create `
  --resource-group "YOUR_RG" --server "YOUR_SQL_SERVER" `
  --kid "https://hsm-target.managedhsm.azure.net/keys/tde-key/version"

az sql server tde-key set `
  --resource-group "YOUR_RG" --server "YOUR_SQL_SERVER" `
  --server-key-type AzureKeyVault `
  --kid "https://hsm-target.managedhsm.azure.net/keys/tde-key/version"
```

AKS Secrets Store CSI Driver — Update the SecretProviderClass manifest to reference the HSM name:

```
apiVersion: secrets-store.csi.x-k8s.io/v1
kind: SecretProviderClass
metadata:
  name: azure-kvname-user-msi
spec:
  provider: azure
  parameters:
    usePodIdentity: "false"
    useVMManagedIdentity: "true"
    keyvaultName: "hsm-target"
    objects: |
      array:
        - |
          objectName: my-key
          objectType: key
          objectVersion: ""
    tenantId: "YOUR_TENANT_ID"
```

Troubleshooting Common Issues

The following table summarizes the six most common errors encountered during migration, their causes, and resolutions:

Issue / Error	Cause & Resolution
"Caller is not authorized to perform action…" (Forbidden)	Insufficient RBAC roles. **Solution**: Assign required roles (e.g., Key Vault Crypto Officer) and wait **60 seconds** for propagation before retrying.
"HSM not activated" (Security domain not initialized)	Managed HSM activation incomplete. **Solution**: Generate 3+ RSA key pairs (2048-bit minimum), create security domain exchange certificates, and download the security domain with quorum (m-of-n). Store the backup securely.
"MalformedBackupBlob — different crypto domain"	**Expected behavior** for HSM-protected keys. The script automatically handles this by recreating keys in the target HSM. **Verify** by checking the migration log for "Recreating HSM key" messages.
"Purge protection must be enabled"	Source Key Vault lacks purge protection. **Solution**: Enable it with az keyvault update --enable-purge-protection true. Note: this **cannot be disabled** once enabled.

Azure Policy blocks MHSM operations (Policy evaluation failed)	Compliance policy conflict. **Solution**: Add bypass tags to the HSM resource or create a policy exclusion for the HSM resource scope.
"Key is in deleted but recoverable state" (Conflict)	A soft-deleted key with the same name blocks re-creation. **Solution**: Either recover the deleted key (az keyvault key recover), purge it (az keyvault key purge), or wait for the retention period to expire (default 90 days).

Security Best Practices

The following ten best security practices should be implemented when operating Azure Managed HSM in production environments:

1. Use Private Endpoints for Production

Create a **private endpoint** for the Managed HSM and **disable public network access** to ensure only clients on permitted virtual networks can reach the HSM endpoint:

```
az network private-endpoint create `
  --name "pe-hsm-prod" --resource-group "YOUR_RG" `
  --vnet-name "vnet-prod" --subnet "subnet-hsm" `
  --private-connection-resource-id
"/subscriptions/YOUR_SUB/resourceGroups/YOUR_RG/providers/Microsoft.KeyVault/managedHSMs/YOUR_
HSM" `
  --group-id "managedhsm" --connection-name "hsm-connection"

az keyvault update --hsm-name "YOUR_HSM" --public-network-access Disabled
```

2. Enable Diagnostic Logging

Configure a **Log Analytics workspace** and enable diagnostic settings to capture **AuditEvent** logs and **AllMetrics**:

```
az monitor log-analytics workspace create --resource-group "YOUR_RG" --workspace-name "law-
hsm-logs"

$workspaceId = az monitor log-analytics workspace show `
  --resource-group "YOUR_RG" --workspace-name "law-hsm-logs" --query "id" -o tsv

az monitor diagnostic-settings create --name "hsm-diagnostics" `
  --resource
"/subscriptions/YOUR_SUB/resourceGroups/YOUR_RG/providers/Microsoft.KeyVault/managedHSMs/YOUR_
HSM" `
  --workspace $workspaceId `
  --logs '[{"category": "AuditEvent","enabled": true}]' `
  --metrics '[{"category": "AllMetrics","enabled": true}]'
```

3. Implement RBAC Best Practices

Apply **least-privilege access** by assigning specific roles rather than broad permissions:

- **Crypto Officer** — Create and manage keys (administrators only)
- **Crypto User** — Use keys for cryptographic operations (applications)
- **Crypto Service Encryption User** — Service-to-service encryption

Scope permissions to individual keys where possible (e.g., --scope /keys/app-specific-key).

4. Backup Security Domain

Store the security domain backup in **multiple secure locations**:

- **Hardware security modules** (YubiKey recommended)
- **Secure offline storage**
- **Geographically redundant** locations
- **Access-controlled vault**

This is critical: without the security domain backup, an HSM and all its keys cannot be recovered in a disaster scenario.

5. Regular Key Rotation

Create new key versions periodically and update application configurations to use the latest version:

```
az keyvault key create --hsm-name "YOUR_HSM" --name "prod-key" --kty RSA-HSM --size 4096
```

Applications can reference either the **latest version** (*https://hsm.managedhsm.azure.net/keys/prod-key*) or a **specific version** (*https://hsm.managedhsm.azure.net/keys/prod-key/version*).

6. Monitor and Alert

Set up Azure Monitor alerts for suspicious activity. Example configuration with a threshold of **ServiceApiHit > 1000** over a **5-minute window** evaluated every **1 minute**:

```
az monitor metrics alert create --name "hsm-high-operations" `
  --resource-group "YOUR_RG" `
  --scopes
"/subscriptions/YOUR_SUB/resourceGroups/YOUR_RG/providers/Microsoft.KeyVault/managedHSMs/YOUR_
HSM" `
  --condition "count ServiceApiHit > 1000" `
  --window-size 5m --evaluation-frequency 1m `
  --action "email=security@company.com"
```

7. Test Disaster Recovery

Conduct regular DR drills covering:

1. Security domain recovery process
2. Backup and restore procedures
3. Key restoration from backup
4. Failover procedures validation
5. Documentation and verification of recovery time objectives (RTO)

8. Use Managed Identities

Enable **managed identity** on applications and grant HSM-specific roles to the identity rather than using stored credentials:

```
az webapp identity assign --name "YOUR_APP" --resource-group "YOUR_RG"

$appIdentity = az webapp identity show --name "YOUR_APP" --resource-group "YOUR_RG"
  --query "principalId" -o tsv

az keyvault role assignment create --hsm-name "YOUR_HSM" `
  --role "Managed HSM Crypto User" --assignee-object-id $appIdentity --scope /keys
```

9. Implement Network Security

Configure **firewall rules** to deny all traffic by default and allow only trusted sources:

```
az keyvault update --hsm-name "YOUR_HSM" --bypass AzureServices --default-action Deny
az keyvault network-rule add --hsm-name "YOUR_HSM" --ip-address "YOUR_OFFICE_IP/32"
```

10. Regular Compliance Audits

Maintain a recurring audit schedule aligned with the following cadences:

Activity	Frequency
Review of RBAC assignments	Quarterly
Audit key access logs	Monthly
Verify security domain backups	Weekly
Test key rotation procedures	Monthly
Update disaster recovery documentation	Quarterly

Summary Checklist

Pre-Migration

- [ ] Azure CLI installed and logged in to correct subscription
- [ ] PowerShell 7+ installed
- [ ] Source Key Vault exists with purge protection enabled
- [ ] Target Managed HSM provisioned (Standard_B1 or Enterprise_E1) and activated
- [ ] RBAC roles assigned on both Key Vault and HSM (waited 60 seconds after assignment)
- [ ] Source Key Vault inventory backed up and documented
- [ ] Test environment validated (dry run completed)

- [ ] Maintenance window scheduled

Migration Execution

- [ ] Dry run completed successfully
- [ ] Migration reports reviewed (keys, secrets, summary)
- [ ] Production migration executed
- [ ] All keys migrated (source vs. target counts match)
- [ ] Migration logs reviewed for errors
- [ ] Recreated keys documented (new URIs recorded)

Post-Migration

- [ ] Key counts verified (source vs. target)
- [ ] Key properties compared (type, size)
- [ ] Application configurations updated with new HSM URIs
- [ ] Storage account CMK references updated
- [ ] SQL TDE keys updated
- [ ] Disk encryption keys updated
- [ ] AKS SecretProviderClass updated
- [ ] Secrets handled (kept in source vault or migrated separately)
- [ ] Test key operations performed in MHSM
- [ ] CMK validation tests passed (if applicable)
- [ ] Data integrity verified

Security & Operations

- [ ] Private endpoints configured
- [ ] Diagnostic logging enabled
- [ ] RBAC assignments verified (least privilege)
- [ ] Security domain backed up (multiple locations)
- [ ] Monitoring and alerts configured
- [ ] Managed identities implemented
- [ ] Network security rules configured
- [ ] Documentation updated
- [ ] DR procedures tested
- [ ] Team trained on new procedures

Decommissioning (After Validation Period)

- [ ] Source Key Vault access monitored (no unexpected usage)
- [ ] Applications confirmed using MHSM keys exclusively
- [ ] Grace period elapsed (30–90 days recommended)
- [ ] Source Key Vault disabled (optional)
- [ ] Final backup of source Key Vault completed
- [ ] Documentation archived

Support & Documentation

Microsoft Documentation

Resource	URL
Azure Managed HSM Overview	
Security Domain	
RBAC Built-in Roles	
CMK with Storage	
Best Practices	
Migration Planning	
Key Vault vs Managed HSM	
Pricing	

Common Integration Scenarios

Integration	Documentation URL
Azure SQL TDE	
Storage Account Encryption	
Disk Encryption	
AKS Integration	

Script Parameters Reference

Parameter	Required	Default	Description
-SourceKeyVaultName	Yes	—	Name of source Azure Key Vault
-TargetManagedHSMName	Yes	—	Name of target Managed HSM
-ResourceGroupName	No	Auto-detected	Resource group name
-DryRun	No	False	Test mode — no changes made
-SkipCertificates	No	False	Skip certificate migration
-ForceRecreateNonExportable	No	False	Force recreation of non-exportable keys

-LogPath	No	.\Migration-Log-CLI-[timestamp].txt	Custom log file path
-ValidateWithCMK	No	False	Enable CMK validation testing
-TestStorageAccountName	No	Auto-generated	Storage account name for CMK testing
-TestKeyName	No	test-cmk-migration-key	Key name for CMK testing
-TestDataSizeMB	No	10	Test data size in MB
-CleanupTestResources	No	False	Delete test resources after validation

This is a preliminary document and may be changed substantially prior to final commercial release of the software described herein.

The information contained in this document represents the current view of Microsoft Corporation on the issues discussed as of the date of publication. Because Microsoft must respond to changing market conditions, it should not be interpreted to be a commitment on the part of Microsoft, and Microsoft cannot guarantee the accuracy of any information presented after the date of publication.

This guide is for informational purposes only. Microsoft makes no warranties, express or implied, in this document.

Complying with all applicable copyright laws is the responsibility of the user. Without limiting the rights under copyright, no part of this document may be reproduced, stored in, or introduced into a retrieval system, or transmitted in any form or by any means (electronic, mechanical, photocopying, recording, or otherwise), or for any purpose, without the express written permission of Microsoft Corporation.

Microsoft may have patents, patent applications, trademarks, copyrights, or other intellectual property rights covering subject matter in this document. Except as expressly provided in any written license agreement from Microsoft, the furnishing of this document does not give you any license to these patents, trademarks, copyrights, or other intellectual property.

© 2020 Microsoft Corporation. All rights reserved.

The example companies, organizations, products, domain names, e-mail addresses, logos, people, places, and events depicted herein are fictitious. No association with any real company, organization, product, domain name, e-mail address, logo, person, place, or event is intended or should be inferred.

Microsoft, list Microsoft trademarks used in your white paper alphabetically are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries.

The names of actual companies and products mentioned herein may be the trademarks of their respective owners.