

Critical Reviews in Food Science and Nutrition



ISSN: 1040-8398 (Print) 1549-7852 (Online) Journal homepage: http://www.tandfonline.com/loi/bfsn20

Physical and Chemical Modification of Starches - A Review

Zia-ud- Din, Hanguo Xiong & Peng Fei

To cite this article: Zia-ud- Din, Hanguo Xiong & Peng Fei (2015): Physical and Chemical Modification of Starches - A Review, Critical Reviews in Food Science and Nutrition, DOI: 10.1080/10408398.2015.1087379

To link to this article: http://dx.doi.org/10.1080/10408398.2015.1087379



Full Terms & Conditions of access and use can be found at http://www.tandfonline.com/action/journalInformation?journalCode=bfsn20

Physical and chemical modification of starches - A review

Zia-ud-Din, Hanguo Xiong*, Peng Fei

College of Food Science and Technology, Huangzhong Agricultural University, Wuhan 430070

China

Corresponding author

Hanguo Xiong*,

Tel.: +86-27-87288377

Fax: +86-27-87286608

E-mail address: xionghanguo@163.com (Hanguo Xiong)

ABSTRACT

The development of green material in the last decade has been increased which tends to reduce the impact of human on the environment. Starch as an agro-sourced polymer has become much popular recently due to its characteristics such as wide availability, low cost and total compostability without toxic residues. Starch is the most abundant organic compound found in nature after cellulose. Starches are inherently unsuitable for most applications and, therefore, must be modified physically and/or chemically to enhance their positive attributes and/or to minimize their defects. Modification of starches is generally carried out by using physical methods that are simple and inexpensive due to the absence of chemical agents. On the other hand, chemical modification involves the exploitation of hydroxyl group present in the starches that brings about the desired results for the utilization of starches for specific applications. All these techniques have the tendency to produce starches with altered physicochemical properties

and modified structural attributes for various food and non-food applications. This paper reviews

the recent knowledge and developments using physical modification methods, some chemical modification methods and a combination of both to produce a novel molecule with substantial applications, in food industry along with future perspectives.

Key words: Physical, Chemical, Starch modification, Physicochemical properties, Structural attributes

Abbreviations

ANN, annealing;

DS, degree of substitution;

ECH, epichlorohydrin;

GCWS, granular cold water soluble;

HHP, high hydrostatic pressure;

HMT, heat moisture treatment;

PEF, pulse electric field;

PGS, pre-gelatinized starch;

POCl3, phosphoryl chloride;

SDS, slowly digestible starch;

STMP, sodium trimetaphosphate;

STPP, sodium tripolyphosphate

1. Introduction

Starch is one of the most abundant biopolymers and serves as energy reserve in many plants including cereals, tubers, roots, fruits and seeds. Starch molecules are the polymers of anhydrous glucose units which are typically accumulated in the unique and independent granules. Depending on the origin of starch, the granules can vary in shape, size, structure and chemical composition (Smith, 2001). Starch granules are generally found in roots, seeds and tubers, as well as in leaves, stems, fruits and even pollen. Grain seeds, for example, maize kernels, contain up to 75% of starch. The granule grows by apposition as the biosynthesis of the starch granules is initiated in the hilum part of the seed. The granules occur in all shapes and sizes (spheres, polygon, ellipsoids, platelets and irregular tubules). Depending on their botanical origin, they have the diameters ranging from 0.1 to 200 µm (Gallant, Bouchet, Buleon, & Perez, 1992; Hoover, 2001; Jane et al., 1994; Srichuwong et al., 2005; Tester & Karkalas, 2004).

From starch granules, two components of starch polysaccharides can be extracted: Amylose which is a pre-dominant α -(1-4) linked glucan and a more complex α -(1-4) linked branched glucan called amylopectin. Amylose has the tendency to retrograde and produce strong films and tough gels. On the other hand, amylopectin is more stable and produces weak films and soft gels when dispersed in water. The formation of entanglements is possible between amylose and amylopectin along with the presence of minor components such as proteins and lipids and all these can affect the physicochemical properties of starches to different extent depending upon the botanical source of the starch (Perez & Bertoft, 2010). The level of crystallinity in the native starches is being determined by the short branches of amylopectin within the granule. The starch

³ ACCEPTED MANUSCRIPT

polysaccharides are arranged into concentric rings inside the granule that radiate out from the central hilum to the surface of the granule (French, 1984).

The amorphous part of the starch granule is preferentially degraded by acid hydrolysis, α-amylase can solubilize both crystalline and amorphous regions (Colonna et al., 1988; Gerard et al., 2001). However, the process involved in the hydrolysis of crystalline region and especially the disruption of double helices from crystallite and their disentanglement are not well known (Andre, Buleon, Haser, & tran, 1999). Starch is believed to affect the viscosity, adhesion, texture, binding, gel formation, film formation and moisture retention. It is mainly used in bakery products, snacks, batters and coatings, meat products, sauces and gravies and dairy confectionery (Davies, 1995). Non-food applications of starch enlist textiles, alcohol-based fuels and adhesives and pharmaceuticals. Whereas the new applications include biodegradable packaging materials, low-calorie substitutes, thermoplastic materials with improved thermal and mechanical properties and thin films (Biliaderis, 1998).

Starch does not have physical and chemical properties suitable for certain type of processing in its native form due to their poor shear and thermal stability and high degree of retrogradation (Jayakody & Hoover, 2008). Furthermore, native starches can easily undergo syneresis besides the gelling tendency of the pastes (Bemiller, 1997). Therefore, the applications of starch in various industries like food, paper and textile can be increased by adopting various techniques of modification. In order to promote and enhance specific functional properties, starches are frequently modified by physical, chemical and enzymatic processes. The physical modification of starch is accomplished by moisture, heat, shear, or radiation and this modification has been gaining wider acceptance because of the absence of chemical reagents in the modified starch.

⁴ ACCEPTED MANUSCRIPT

Acquiring of desired functional properties is possible by using various methods of modification, which have specific applications in various industries. Chemical modification is extensively implemented, but there is also a mounting significance in the physical modification of starch, especially in food applications. The most important advantage of modification is that the starch is considered to be a natural material and a highly safe ingredient (Bemiller, 1997). Modification of starch is an ongoing process which can design a huge market for many new functional and value added properties resulting from these modifications (Kaur, Ariffin, Bhat & Karim, 2012).

Starches have been modified by adopting various methods of modification over the last few decades in order to acquire the desired industrial applications. Basically, there are four basic broad kinds of starch modifications; physical, chemical, enzymatic and genetic. A number of review articles (BeMiller, 1997; Jobling, 2004; Tharanathan, 2005) on the subject of starch modification are available. However, there has been an intense interest among the researchers in the last decade to develop novel methods for starch modification. This article is designed to be a critical overview for the science community on how to employ different modification methods to obtain a modified starch with well-designed composition and morphology.

2. Physical modification of starch

Physical modification of starch can be safely used in food products and can be achieved through alcoholic-alkaline, micronization and drum drying (Yan & Zhengbiao, 2010; Majzoobi et al., 2011; Ren et al., 2010). New methods are being evolved and one of the most common methods of physical modification of starch is pre-gelatinized starch (PGS) which has found wide applications in food industry. This type of physical modification is produced by drum drier, extruder and spray drier and generally regarded as instant starches (Karapantsios, 2006;

Majzoobi et al., 2011). Heating of starches in aqueous alcohol, high pressure and high temperature and alcoholic-alkaline treatment can be used to prepare granular cold water soluble (GCWS) starches. As compared to the traditional pre-gelatinized starches, GCWS starches exhibit smoother texture, greater viscosity and more processing tolerance (Yan & Zhengbiao, 2010). Vacuum ball grinding machine is generally used for preparation of micronized starches and during this process the granules are broken into small irregular granules by means of forces between the granules and the grinding balls (Ren et al., 2010).

Native starches are used for food processing but their commercial applications are limited because of their physical properties and colloidal sols (Laovachirasuwan et al., 2010). Due to instability under various kinds of pressure, shear and temperature, most of the native starches could not able to find their wider commercial type of applications. These starches lack the specific functional properties due to inertness, insolubility and highly resistant to enzymatic hydrolysis. To make the native starches suitable for industrial applications, these starches are modified in various ways to acquire the desired features such as heat tolerance, texture, adhesion and solubility (Anderson et al., 2002; Khunae, Tran, & Sirivongpaisal, 2007; Watcharatewinkul, Uttapap, & Rungsardthong, 2010; Viera & Sarmento, 2008; Jiranuntakul et al., 2001; Fechner, Waterwig, Kiesow, & Heilman et al., 2005). Many different methods are available now a days to modify the starch polymer (Piacquadio, Stefano, & Sciancalepore, 2000; Shin et al., 2005; Varavinit et al., 2007; Cham & Suwannaporn, 2010; Lin, Wang, & Chang, 2008). The molecular integrity plays a vital role in the classification of starches in a way whether the molecular integrity is preserved or destroyed after the process of modification. High moisture treatment (HMT) and annealing (ANN) are the processes in which the starch integrity is preserved and

these are regarded as hydrothermal processes. Whereas, the molecular integrity and the granular order is lost completely in the pre-gelatinization processes that comprises of drum drying, spray drying and extrusion (Ashogbon & Akintayo, 2014). Some of the new physical methods used for starch modification that have been developed over the past few years are listed in the Table 1.

2.1 Pre-gelatinized starch (PGS)

Pre-gelatinized starches also called as instant starches are pre-cooked and dried with the help of a drum that enable the products to form moderate stable type of suspension that disperse in cold water (Hodge & Osman, 1976). These types of products are extensively used in the textile industry, as a thickening agent in food industry and as an adhesive in foundry core binders (Colonna, Buleo, & Mercier, 1987). Drum drying is a widely accepted technique at industrial level. The process of drum drying enables the product to gain various textures and porous structures which ultimately affect its functional properties as displayed by the intensity of treatment used (Bonazzi et al., 1996). The control of drum drying equipment is laborious due to the affinity of dried sheet to moisture exchange as the online moisture measurement requires very short time to respond (Vlachos & Karapantsios, 2000). The rheological behavior of the pregelatinized starch treated with double drum dryer tends to form weak paste as reconstitution with water takes place. Therefore, the possible effects of the time (residence) of the material must be given great importance inside the gelatinization pool. The swollen starch granules played a vital role considering the rheology of the pastes (Anastasiades et al., 2002).

Spray drying is the most commonly used technique in food industry as a microencapsulation method for ingredient (Gharsallaoui et al., 2007). Since a long time ago, spray drying technique has been used by many scientists and researchers to prepare the pre-gelatinized starch without losing the granular integrity. It is a rapid technique which readily converts the liquid solution droplets into amorphous and semi-amorphous particles (Pitchon et al., 1981; Ruben, 1992). The dried spherical particles dried by spray drying through atomizing starch solution are commonly used to modify the starches physically. The drying kinetics involving single drop of inconsistent sizes played a vital role towards the understanding of spray drying operations related with food (Adhikari et al., 2003) especially in the context of morphology. The starch granules treated with spray drying often show hollow structure in the middle of granule and presenting a regular shape (Yan & Zhengbiao, 2010). This technique has the ability to produce spherical particles for improving the fluidity of solid. Fruit and vegetable powder have been produced using spray drying (Abu-Jdayil et al., 2004). Spray dried sweet potato powders have the characteristics to be added to various food system to provide a variety of functional benefits.

Conventional extrusion cooking process involves the use of high temperature which brings about physical modification in starchy and proteinacious kinds of food. The starchy and proteinacious food tends to swell at exposing to extrusion cooking owing to its pressure, high temperature and shear forces (Liu et al., 2011). During the process of extrusion cooking, the starch is compressed with the help of high pressure and forces that resulted into molecular changes and ultimately changing starch from granular and semi-crystalline material into a highly viscous, plastic material (Brummer et al., 2002). The retrogradation behavior after improved

extrusion cooking technology for the rice starches showed that extrusion cooking technology is an appropriate and potential method for the preparation of rice starch products with low percentage and rate of retrogradation in food industry. Another advantage associated with extrusion cooking is the absence of effluents and chemical reagents which may overcome the pollution and further analysis and hydrolysis of starch can bring about desired results such as microencapsulation (Zhang at al., 2014).

2.2 Hydrothermal modification

Annealing (ANN) and high moisture treatment (HMT) are the two most widely accepted hydrothermal treatments used to modify the starches without losing the integrity of the granules. The distinguished feature of these methods is that both processes occur below the gelatinization temperature of granules which ultimately help in preserving the granular structure. Moreover, the starch granules must remain in the mobile rubbery state during these hydrothermal modification processes. Detectable changes can be seen in the physico-chemical properties of starches during these processes within instantaneous time. Both processes bring about modification in the structure and properties of starches to different extents (Jayakody & Hoover, 2008). These modification methods require certain temperature and moisture levels to accomplish in the starch granules during certain period of time. HMT refers to the treatment of starch when low moisture levels are used whereas ANN is used for the treatment of starches having low or intermediate moisture levels.

2.2.1 Annealing (ANN)

The process of annealing is an effective method used for the reorganization of the molecular chains. This process has the advantage to increase the crystallinity of materials and weakens the

structural relaxation. Furthermore, the process of annealing provides theoretical evidence for the improvement of material by developing the thermal stability and mechanical properties of material (Shanshan et al., 2015). Based on the changes in structural and functional properties, it was proposed that annealing treatment helped in the enhancement of long range interaction of amylopectin molecules by re-arranging the molecules of amylose. Annealing process reduces the solubilization of α -glucan during swelling below 100°C which means that amylose must be more restricted from leaching out of the granule. This strengthens the view that there is molecular reorientation in the starch granule which makes the amorphous region more glassy with an elevted Tg (Morrison et al., 1993; Hoover & Vasanthan, 1994). This enhanced interaction of amylopectin ultimately resulted into homogeneity of crystal structure and stability of annealed starches thus, protecting the integrity of granules by increasing the gelatinization temperature and narrowing the temperature range of thermal transition. Furthermore, the increased interaction of amylopectin clusters lead to the decreased paste viscosity by inhibiting the swelling of normal starch granules (Shujun et al., 2014).

The main objective of the annealing process is to approach the glass transition temperature (Tq) in the presence of solvents such as water or glycerol which results into an increased molecular mobility and preventing the initiation of gelatinization process at the same time. In fact, the amorphous region of the starch granules is the most susceptible area to the initial water absorption and plasticization. Before the absorption of water, this region is more static and glassy and it is the hydration due to which the mobility of amorphous region increases (Weigh, Keto, Donald & Gidley et al., 2000). This situation results into vibrational movements of chains in both amorphous and crystalline regions (Tester & Debon, 2000). As the process of annealing

continues, the weaker and imperfect crystallites gradually reduce in number whereas the remaining crystallites become more perfect due to the process of re-crystallization and fusion (Jayakody & Hoover, 2008). The process of annealing has important industrial implications. The annealing process proved helpful in imparting different novel processing characteristics. Annealed starches result in higher gelatinization temperatures where many inexpensive chemical processes can be employed, thus justifying this process in terms of energy and time (Tester & Debon, 2000).

2.2.2 Heat Moisture Treatment (HMT)

Heat moisture treatment (HMT) refers to the hydrothermal technique involving the agitation of starch granules at low moisture levels but at high temperatures (80-140 °C) and low gelatinization temperatures (Jacobs & Delcour, 1998; Hoover, 2010). Changes that are induced by HMT in the starch product often resulted into properties such as starches with intact granular forms. HMT brings about changes for instances, decreases starch solubility, swelling power, amylose leaching and peak viscosity but increase in the pasting temperature is noted for starches treated with HMT (Chung, Liu, & Hoover, 2009; Gunaratne & Corke, 2007; Pinto, Vanier, Klein, Zavareze, Elias & Gutkoski et al., 2012; Sui et al., 2011). The degree to which these changes in the physicochemical characteristics of starches occur is mainly the function of modification in the semi-crystalline structure of starch granules (Ambigaipalan et al., 2014; Gunaratne & Hoover, 2002). Hoover and Manuel (1996) established that the process of HMT brought about changes in the both crystalline and amorphous regions to different extent. The prominent changes were proposed to occur in the amorphous region of the starch granules

through chain reactions in different botanical starches such as cereal, tuber and legumes (Hoover & Vasanthan, 1994; Jacobs & Delcour, 1998; Vermeylen et al., 2006).

Due to the diversity of the reaction conditions, it is very difficult to define the properties of HMT treated starches in a consistent way. These diverse reaction conditions include moisture content, temperature, botanical source, heat source, cooling process and length of treatment. Among these conditions, moisture and temperature are the most extensively studied HMT parameters (Vermeylen et al., 2006; Ambigaipalan et al., 2014). However, the moisture contents and heating length both affected the properties of maize starches to a greater extent (Zhongquan et al., 2015). HMT treated starches find applications on industrial level where these are used in the preparation of infant foods. Moreover, potato starches are also processed through HMT to improve its baking qualities and freeze-thaw stability in food industry (Collado & Corke, 1999).

2.3 Non-thermal physical modification of starches

Most of the food is preserved by exposing the product to high temperatures for a short period of time. These treatments resulted in the loss of essential nutrients, vitamins and flavors. In order to overcome these disadvantages, non-thermal technology is used to kill the pathogenic and spoilage causing organisms. Non-thermal treatments can be used to preserve color, texture, taste, nutrients and other components of food as compared to the traditional thermal processes (Li et al., 2008; Marselles-Fontanet & Martin-Bellose, 2007; Sampedro et al., 2007; Torregrosa et al., 2006). Different kinds of non-thermal treatments have different effects on the physicochemical properties of starches. Some of the non-thermal processes are using ultrasound effect, high hydrostatic pressure and microwave treatment of starches.

Ultrasonication can be used as a green technology to modify the structure, properties and composition of starches from different botanical sources. Depending on the conditions of experiment, ultrasonication either degrades or has a little effect on starch chains on the molecular level. The physicochemical properties of starch can be affected by the structural changes. Ultrasonication has been showed to increase the water solubility, decreases the gelatinization/ pasting viscosity/ swelling parameters/ retrogradation which shows that this process depends on factors like frequency, intensity, water and temperature of the starch-water system, duration of ultrasonication, type and structure of starch and composition of gas in the atmosphere. Ultrasonication induced cracks and pores in the granular structure of starch which further provide assistance in the modification of starch by augmenting the efficiency of the reactions. The process of ultrasonication has been employed by food and non-food industries and has achieved various benefits such as enhanced product yield and purity, shortened processing time, environment friendliness, production cost and reduced energy consumption (Zhu, 2015). This technique is very important in the following areas of food processing; deforming, extrusion, separation, viscosity alteration, crystallization, extraction, emulsification and homogenization (Iida et al., 2008).

In food industry, high hydrostatic pressure (HHP) involves treatment of food material using pressure from (100-1000 MPa) at room temperature to acquire the modification and sterilization of food material. This treatment destroys the non-covalent bonds which resulted into serious structural damages such as protein naturalization and starch gelatinization (Hu et al., 2011). Moreover, the important application of this technology is the achievement of starch gelatinization at room temperature. Starch gels treated with HHP has lower swelling index and

lower susceptibility to amylolytic enzymes as compared to the starch gels that are heat gelatinized (Blaszczak et al., 2005; Vallons & Arendt, 2009). The HHP gelatinized non-waxy and waxy rice starches has higher slow digestibility than the heat gelatinized ones during retrogradation while the slowly digestible starch (SDS) percentage was not positively co-related with enthalpy change of starch retrogradation. The higher SDS percentage was mainly attributed to the intact starch granules which were retained by using HHP treatment (Tian et al., 2014). Wheat starch suspensions were homogenized at increasing pressure up to 100 MPa to approximate the electrical and structural characteristics of wheat starch. Qiu et al. (2014) reported that the starch granules began to lose their native pattern at 60 and 80 MPa, moreover, many starch granules disintegrated into gel-like structures and their mean particle diameter increased significantly when homogenized at 100 MPa. A positive application of pressurized starch could be to use it as a fat substitute, these might stimulate fat droplets as these are considered micro-particles of well defined size distribution (Stute et al., 1996).

Pulse electric field (PEF) technology is a non-thermal food preservation method which involves preservation of food by killing and inactivating the pathogenic micro-organisms and enzymes resulted into minimum loss of original taste, color, nutrients, texture and heat liable functional components of food (Knorr & Angersbach, 1998). The technology of PEF treats the punpable liquid material with high intensity electric pulses (over 10 kV cm⁻¹) at short duration (less than 40 µs) in a processing chamber. PEF technology has been widely used for modifying larger molecules and enhancing chemical reactions apart from non-thermal pasteurization. The advantages of PEF treatment include continuous processing nature, uniform treatment intensity, low processing temperature and short treatment time. The PEF treatment can lead to an intra-

granular molecular re-arrangement of potato starch granules which resulted into changes related different physicochemical properties of treated starch inducing some new characteristics and functions (Han et al., 2009).

3. Chemical modification

Chemical modification is carried out by introducing a functional group into the polymer molecule of the starch granule in its native form that brings about distinctive changes in the physicochemical properties of starch molecule. This type of modification produces reflective modification in the gelatinization, proximate composition, pasting characteristics and retrogradation of native starch granules. Such modification helps in the stabilization of intra and inter-molecular bonds at different positions and locations. Factors such as starch source, reaction conditions, degree of substitution, type and distribution of substituting agent along the molecule of starch affect the functional and chemical properties of the modified starches. Chemical modification of starches is generally accomplished through derivatization such as acetylation, cationization, acid hydrolysis, oxidation and cross linking. However, these techniques are limited due to issues such as consumers' safety and environment. There has been an increasing trend to combine different kinds of chemical techniques to create new kinds of modification. Similarly, different chemical modification methods have been combined with physical modification methods such as radiation, extrusion and microwave to produce a starch with specific functional properties. Some of the recent chemical modification methods are summarized in Table 3.

3.1 Acetylated (Ac) starch

Acetylation of starch is a common chemical modification method during which part of the hydroxyl groups of glucose molecule is replaced by acetyl group resulted into modified molecular structure of the starch. These starches are produced by using acetic anhydride and an alkaline catalyst such as sodium hydroxide (Bello-Perez et al., 2010). Acetylated starches performed different functions depending upon the degree of substitution (DS). These starches having a low DS of about (0.01-0.2) may act as adhesion, thickening, texturizing, film forming, stabilizing and binding agent and also find numerous applications in food industry in baked goods, sauces, frozen foods, canned pie fillings, baby foods, snack foods and salad dressings. Acetylated starches with intermediate DS (0.2-1.5) and high DS (1.5-3.0) have been reported for high solubility in acetone and chloroform and thus, can be used as thermoplastic material (Luo & Shi, 2012). Acetylation of starches is performed to bring about desired changes in physical, functional and chemical properties of starches (Xu et al., 2004) and has been used by many researchers (Bello-Perez et al., 2010; Diop et al., 2011; Garg and Jana, 2011; Huang et al., 2007; Mbougueng, Tenin, Scher, & Tchiegang, 2012). Different factors play vital role in the inducement of changes caused by acetylation such as the source, ratio of amylose and amylopectin, the molecular structure of starch and the degree of substitution. The reaction efficiency and the number of acetyl groups induced in the starch molecule during the process of acetylation depend upon the reaction time, presence of catalyst, botanical origin, reagent concentration and structural characteristics of starch granules (Huang et al., 2007; Huber & BeMiller, 2000).

Acetylated starches with DS above 0.22 exhibited changes in the morphology of the starch granules. As compared to the native starch, acetylated starches are more resistant against

shearing and heating (Mello El Halal et al., 2015). The crystallinity of starch in context of breakdown, peak and final viscosities, swelling power, its pasting temperature and solubility is reduced by the process of acetylation. The decrease in the pasting temperature facilitates in getting the products having characteristics such as sensitivity to high temperatures and products having more stability during the process of cooking (Colussi et al., 2014). A significant amount of resistant to amyloglucosidase activity and small changes in the rheological properties are noted for the acetylation of retrograded starch as compared to the chemically unmodified starch. Additionally, the process of acetylation for the retrograded starch and its cross linking with adipic acid (compared to the chemically unmodified starch) resulted in an increased resistant against the amyloglucosidase action (30.56g/100g) (Zieba et al., 2014).

Acetylation of starches leads to structural reorganization owing to steric hindrance resulting in repulsion between starch molecules, thus facilitating an increase in water percolation within amorphous regions of granules and a consequent increase in swelling capacity (Lawal, 2004). Additionally, acetylation retards the development of an ordered structure following gelatinization which ultimately helps in retarding retrogradation, resulting in more fluid paste and better long term clarity (Lawal, 2004).

Introduction of acetyl groups in starch molecule resulted in structural changes as reflected by thermal properties of starches. Using the technique of differential scanning calorimetry (DSC), many researchers concluded that at lower temperatures, the acetylated starches go through phase transition as compared to their native counterparts, moreover, the heat of phase transition (enthalpy) is lower for acetylated starches although it is recorded on high pasting temperatures (Afolabi et al., 2012; Bello-Perez et al., 2010). Thermogravimetric studies (TGA) also reveal

high heat resistance for acetylated starches as compared to the native starches (Emeje et al., 2012; Garg & Jana, 2011; Luo & Zhou, 2012; Mina et al., 2011; Singh et al., 2011; Xia et al., 2011; Zhang et al., 2009; Zhang et al., 2012).

Currently, research has been carried out for exploring acetylated starches as loose substance (Fornal et al., 2012), surface active substance by enzymatic hydrolysis (Konowal et al., 2012), use of acetylated starch for production of films with barrier properties (Lopez, Zaritzky, Grossmann & Garcia, 2013; Zamudio-Flores et al., 2010), encapsulating properties (Murua-Pagola et al., 2009; Robert et al., 2012), biodegradable material (Mina et al., 2011), or reinforcing agents for bio-nanocomposites (Valodkar & Thakore, 2011).

3.2 Cationic starch

Cationic starches are vital industrial derivatives produced by introducing a positive ionic charge with the help of functional groups such as ammonium, imino, amino, sulfonium or phosphonium.

The hydroxyl group of the native starches is commonly replaced by an ionic charge by utilizing 2,3-epoxypropyltrimethylammonium chloride (ETA) as a cationic monomer under wet, dry or intermediate process. The wet method is the most commonly used process among the three. During the wet cationization of starches, the reaction is proceed in the forward direction by mixing starch with water to form a homogeneous suspension with a concentration of 40 % and adjusting the pH within 11-12 with the help of addition of chemical cationising agent. A starch will be cationized completely by maintaining all these reaction conditions and a temperature of 40-45 °C in 12-16 hours (Heinze, Haack, & Rensing, 2004). In dry cationization process (absence of liquid phase), the reagent is sprayed onto dry starch during the process of extrusion

whereas the same process is repeated and the mixtures are thermally treated during the semi dry processing. The main advantage of these processes is that these two methods are environment friendly but there is a likelihood of the by-product that may be produced along with the desired product and it may also be costly to separate both from each other (Radosta, Vorwery, Ebert, Begli et al., 2004). More dense starch would be resulted by following the dry cationization process compared to the wet cationization method. However, high amount of higher molar masses are obtained for wet cationic starch compared to the dry method (Santacruz, 2014).

Cationic starches find its application on large scale in the paper industry where these can play their role as an additive, surface size and coating binder agents. Cationic starches having ammonium groups on quaternary position are commonly used for commercial applications (Xie, Liu & Cui, 2005). Cationic starches are believed to have a potent activity against the microbes consequently used in the antimicrobial products formulations. Keeping in the view its antimicrobial activity, cationic starches have been able to draw the attention of the researchers for both academic and industrial point of view. The use of such polymeric materials with antimicrobial activity can act as matrix holding the antimicrobial agent or the polymer by itself can possess the antimicrobial activity (Munoz-Bonilla & Fernandez-Garcia, 2012). It has been shown in the previous studies that the starch derivatives with quaternary ammonium group can act as an antimicrobial agent but these are bacteriostatic rather than bactericides (Bendoraitiene et al., 2013).

Generally, the process of cationization brings about considerable changes in the granular structure and physicochemical properties of the starch especially in those having high degree of substitution. Higher peak viscosities, changes in setbacks and lower pasting temperatures were

also noted in the RVA of different types of starches exposed to cationization (Siau et al., 2004). Furthermore, lower transition temperature and smaller ΔH are noted for cationic starches in a comparative study with the native starches using the technique of DSC (Radosta, Vorwery, Ebert, Begli et al., 2004). Cationic starches has found numerous applications as flocculants for water treatment (Krentz, Lohmann, Schwarz, Bratskaya et al., 2006) as an additive in cosmetics products and textile (Heinze, Haack & Rensing, 2004) and these kind of starches (cationic starches) can be used for the dynamic coating for protein analysis in CE (Sakai-kato, Kato, Nakajima, Toyo'oka et al., 2006).

3.3 Cross-linked starch

Cross linking is a chemical modification method during which the native starches are chemically modified using different cross linking agents like sodium trimetaphosphate (STMP), sodium tripolyphosphate (STPP), epichlorohydrin (ECH) and phosphoryl chloride (POCl₃). This technique is believed to play an important role in improving the functional properties, the freeze thaw and the cold storage stabilities of the starch molecule (Chung et al., 2004; BeMiller, 2011). STMP, STPP, POCl₃ and a mixture of adipic acid and acetic anhydride can be used as crosslinking agents for food use. Among these reagents, the STMP, which is one of the most important food additives with low toxicity, is an efficient cross-linking agent (Gui-Jie, Peng, Xiang-Sheng, Xing, & Tong, 2006). One type of cross linked starch is distarch phosphate which is produced under alkaline conditions by reacting starch granules with STMP or POCl₃ (Wurzberg, 1986). The process of cross linking is believed to add intra- and inter-molecular bond at various location in the starch molecule that resulted in the stability of the granule (Acquarone & Rao, 2003; Singh et al., 2007) by utilizing the chemical reagents that form ether

or ester linkages between hydroxyl groups in the molecule of starch (Rutenberg & Solarek, 1984). It is reported that both amylopectin and amylose in starch granules can be cross linked. The amylose molecules, however, has less of the tendency to be cross-linked (Jane, Xu, Radosavljevic, & Seib, 1992). Likewise other chemical modification methods, cross linking of starches is also affected by many factors like source of the starch, the reagent composition and concentration, pH, extent of substitution, temperature and reaction time (Chung, et al., 2004). The molecular structure of starch granules is different by using different types of cross linking agents, therefore, the functional properties of treated starch are determined by the type of cross linking agent used (Sekar & Hanna, 2006).

The solubility of the cross linked starches was decreased with an enhancement in the degree of cross linking when measured as a function of temperature (Koo et al., 2010). Similar reports were presented by Kaur et al. (2006) for potato starches using different concentration of cross linking agents such as EPI and POCl₃. The decreased solubility can be explained by the fact that the degree of cross linking results in the compactness of granular structure in the starch molecules which ultimately cause less disintegration of starch granules during the process of gelatinization (Jyothi, Moorthy & Rajasekharan, 2006). Starches cross liked with STMP/STPP lead to a considerable decrease in paste clarity (Koo et al., 2010). This substantial decrease in paste clarity can be attributed to the change in the structure of starch granules caused by cross linking (Morikawa & Nishinari, 2000a). Moreover, no difference in crystallinity pattern has been found when modified corn starch is compared to the native starch. This can be reflected to the fact that the process of cross-linking mainly takes place in the amorphous region of starch granules showing no alteration in the crystalline patterns of the starches (Koo et al., 2010).

Cross linked starches show more thermal stability as evident by decrease in the weight loss compared to their native counterpart (Wongsagonsup et al., 2014). These attributes make cross linked starches more suitable for various industrial applications as exhibited by their stronger granular structure. The most interesting phenomenon is that the cross linked starches decompose promptly but the amount of residues are larger after the decomposition process as compared to the untreated starches. The thermal decomposition of cross linked starches is facilitated by the large number of phosphate group in the amorphous region as evident by the XRD spectra of cross linked sago starch showing more amorphous region with reduced diffraction intensity that might be resulted due to the replacement of some hydroxyl groups with phosphate groups during the process of cross linking (Singh & Nath, 2012).

Starch paste from cross-linked starch is highly viscous, heavy bodied, shorter textured and less likely to breakdown during severe agitation, cooking and exposure to low pH conditions. These starches are thus suitable for thickening and stabilizing the food system, e.g. soups, gravies, sauces, baby foods, fruit fillings, pudding and deep fried foods (Rutenberg & Solarek, 1984; Singh, Kaur, & McCarthy, 2007).

3.4 Other chemical modification methods

Modification of starches using mineral acids such as HCl or H₂SO₄ is a common type of modification method and these starches has a vast potential of applications. Depending on the desired viscosity or degree of conversion, the concentrated starch slurry is treated at temperature below the gelatinization temperature for a specific period of time (Thirathumthavorn & Charoenrein, 2005). Starches treated with acid manifest numerous properties such as increased solubility and alkali number, decreased tendency to retrograde, decreased swelling power,

increased ΔH and broadened temperature of gelatinization and loss in pasting viscosities (Beninca, Colman, Lacerda, Carvalho, Bannach et al., 2013; Osunsami et al., 1989; Sanguanpong et al., 2003; Atichokudomchai et al., 2001; Atichokudomchai et al., 2002). The mineral acid attacks both the amylose and amylopectin region of the starch but during the early stages of the process, the amorphous region is more vulnerable to its attack and later on the acid slowly shifts its activity towards the crystalline region of the starch granule (Wang & Wang, 2001). Keeping in the view these facts, the surface morphological attributes of acid thinned (6% HCl) starches are studied under scanning electron microscope (SEM). These starches have eroded their surfaces by acid suggesting that the process of erosion took place on the surface of starch granule (Atichokudomchai et al., 2000). It was observed that the surface is pre-dominantly occupied by amylopectin and phosphate containing domains with increasing the concentration of an acid (Wuttisela et al., 2009). Using the technique of atomic force microscopy (AFM), it was revealed that the roughness in the surface of starch granule can be minimized by treating the starches with acid hydrolysis (Beninca, Colman, Lacerda, Carvalho, Bannach et al., 2013).

Starch oxidation is an alternative method for improving starch properties that is widely used in industry. Oxidized starch is prepared commercially by reacting starch with a specific amount of oxidant under controlled pH and temperature. Oxidants such as potassium permanganate, sodium hypochlorite, hydrogen peroxide, peracetic acid, nitrogen dioxide and chromic acid have been employed to oxidize starches. Sodium hypochlorite is the most commonly commercial oxidant used for this technique (Sandhu et al., 2008; Wang & Wang, 2003). The oxidizing agent penetrates deeply into the amorphous regions and has minimal effect on the crystalline regions. These oxidizing agents formed carboxyl group on the starch molecule that resulted into low

retrogradation and syneresis of oxidized starch paste, whereas carbonyls play a negligible role in the prevention of retrogradation of starches (Kuakpetoon & Wang, 2006). These starches have attracted many researchers and these have numerous applications in food and non-food sectors. The reaction conditions and the type of oxidizing agent determine the functional properties of the final product (Lawal et al., 2005). The process of oxidation brings about changes that can be related with lower gelatinization temperature and ΔH of the starch consequently retarding the retrogradation of starch molecule as evident by the analysis of light transmittance (Sangseethong et al., 2009). During the process of oxidation of starches, the hydroxyl group of the starch molecule is first oxidized to carbonyl group and then to carboxyl group, so the level of oxidation in the treated starch is primarily determined by the number of carbonyl and carboxyl groups which believe to take place at C-2, C-3 and C-6 position on D-glucopyranosyl unit (Sanchev-Rivera et al., 2005; Guerra-Della Valle et al., 2009).

Starches are usually treated with propylene oxide in alkaline medium to prepare the hydroxypropylated starches (Schmitz et al., 2006). Improved freezing-thawing stability, water binding capacity, light transmittance, swelling power and improved solubility were noted for hydroxypropylated starches whereas phenomena like enzyme susceptibility, syneresis of paste and retrogradation can be hindered by exposing starches to propylene oxide (Schmitz et al., 2006; Jyothi, Moorthy, & Rajasekharan, 2007).

3.5 Dual modification

In order to further improve the functional properties and utilization of starches in various kinds of applications, chemical dual and other types of dual modification methods have been introduced in different kinds of starches. Dual modification of starches involves the combination

of either chemical and physical modification methods or chemical and enzymatic modification method. But the most commonly used is the dual chemical modification method that is widely used to modify the starches which involves a combination of two chemical modification methods such as acetylation/oxidation, cross linking/acetylation or cross linking/hydroxypropylation (Carmona-Garcia et al., 2009; Huang et al., 2007; Raina et al., 2006; Lui & Corke, 1999; Adebowale, Afolabi, & Olu-Owolabi, 2006; Zamudio-Flores et al., 2010). Chemically dual modified starches find large number of applications in food industry as binder, thickeners and emulsifiers whereas in non-food industry these can be utilized as heavy metal absorbents. It has been observed that the chemical and physical properties of the native plantain starch have been successfully improved by exposing the native starch to dual chemical modification process (oxidation/acetylation) (Zamudio-Flores et al., 2010). The swelling power is the most prominent factor in determining the outcome (Wattanachant et al., 2002) of the final product during the process of dual modification (hydroxypropylation and cross linking).

4. Conclusions and future outlook

The challenges involved in the modification of starches are the mitigation of the inherent short comings in the native starches such as loss of viscosity, easily to retrograde, insolubility and loss of ordered structure that ultimately provides the feasibility basis for wide applications of starches. The physical and dual modification has been the most promising methods of modification with large number of innovated techniques. Physical modification of starches can be divided into three categories (a) PGSs; (b) hydrothermally treated starches; and (c) non-thermally treated starches.

The most important application of PGSs starches is in puddings, pie fillings and baby foods as a thickening agent because of their ability to hydrate instantly and swell in water at ambient temperature. These can be obtained by heating the slurry above the gelatinization temperature and subsequently drying by drum, extrusion or spray drying. Hydrothermally treated starches involve the techniques of annealing and high moisture treatment that ultimately brings about changes in the physicochemical characteristics keeping the granular structure intact. Techniques such as HHP, UHP, microwave and PEF treatment can be included in the category of non-thermal treatment of starches and the functional and physicochemical characteristics of the treated starch depend upon the forces or pressure applied to the type of starch.

Progress in understanding the high value of chemically modified starches has encouraged the starch industry to produce modified starches using different modification reagents and starch sources. Some factors such as starch composition, concentration, type of reagent and reaction conditions may affect the reactivity of starch during chemical modifications like acetylation, hydroxypropylation and cross linking. The heterogeneity of granule population within a single starch source may also affect the extent of modification. The changes observed in the physicochemical, morphological, thermal and rheological properties of starches after modification may provide a crucial basis for understanding the efficiency of the starch modification process at industrial level. Products are also being looked for forming new items for consumption with conventional and non-conventional properties using the method of dual modification of starches.

For better understanding the process of modification of starches, research should be done and focused on the following given points:

- a) It has been appeared that the same test and analysis has been repeated for the problems and issues that had been resolved long ago. So, more through study and investigation should be done to avoid the repetition of the same procedures.
- b) New combination of techniques is required in order to obtain starches with more diversified and promising applications with variations in structure, composition and properties. Novel techniques such as ultrasound and microwave treatment can be adopted to obtain starches that would be environment friendly, the concept that recently coined as "green technology".
- c) Starch modification is being carried out since long ago in 1800. Though the efforts are large in chemical modification resulting in novel nutritional properties of resulting starches, but the health of the consumer and environment should also be taken into account.

References

Abu-Jdayil, B., Banat, F., Jumah, R., Al-Asheb, S., & Hammad, S. (2004). A comprehensive study of rheological characteristics of tomato paste and tomato powder solution. *International Journal of Food Properties*, 7, 483-497.

Acquarone, V.M., & Rao, M.A. (2003). Influence of sucrose on the rheology and granule size of cross-linked waxy maize starch dispersions heated at two temperatures. *Carbohydrate Polymers*, 51, 451-458.

Adebowale, K.O., Afolabi, T.A., & Olu-Owolabi, I. (2006). Functional, physicochemical and retrogradation properties of sword bean (*Canavalia gladiata*) acetylated and oxidized starches. *Carbohydrate Polymers*, 65, 92-101.

Adebowale, K.O., Henle, T., Schwarzenbolz, U., & Doert, T. (2009). Modification and properties of African yam bean (*Sphenostylis stenocarpa Hochst. Ex A. Rich.*) Harms starch I: Heat moisture treatments and annealing. *Food Hydrocolloids*, 23, 1947-1957.

Adhikari, B., Howes, T., Bhandari, B.R., & Truong, V. (2003). Experimental studies and kinetics of single drop drying and their relevant in drying of sugar-rich foods: A review. *International Journal of Food Properties*, *3*, 323-351.

Afolabi, T.A., Olu-Owolabi, B.I., Adebowale, K.O., Lawal, O.S., & Akintayo, C.O. (2012). Functional and tableting properties of acetylated and oxidized finger millet (*Eleusine coracana*) starch. *Starch/Stärke*, *64*, 326-337.

Akubor, P. I. (2007). Chemical and functional properties of modified and unmodified cassava and sweet potato starches. *Journal of Food Science and Technology-Mysore*, 44, 260–263.

Ambigaipalan, P., Hoover, R., Donner, E., & Liu, Q. (2014). Starch chain interactions within the amorphous and crystalline domains of pulse starches during heat–moisture treatment at different temperatures and their impact on physicochemical properties. *Food Chemistry*, *143*, 175–184.

Amorim, E. O. C., Doval, V. C., & Cristianini, M. (2011). Effect of ozonation on the sensory characteristics and pasting properties of cassava starch. *Procedia Food Science*, *1*, 914–919.

Anastasiades, A., Thanou, S., Loulis, D., Stapatoris, A., & Karapantsios, T. D. (2002). Rheological and physical characterization of pre-gelatinized maize starches. *Journal of Food Engineering*, 52, 57–66.

Anderson, A. K., Guraya, H. S., James, C., & Salvaggio, L. (2002). Digestibility and pasting properties of rice starch heat moisture treated at the melting temperature (Tm). *Starch-Stärke*, *54*, 401–409.

Andre, G., Buleon, A., Haser, R., & Tran, V. (1999). Amylose chain in an interacting context, II. Molecular modeling of a maltopentose fragment in the barley α -amylase catalytic site. *Biopolymers*, 50, 751-762.

Ashogbon, A.O., & Akintayo, E.T. (2014). Recent trend in the physical and chemical modification of starches from different botanical sources: A review. *Starch-Stärke*, 66, 41-57.

Atichokudomchai, N., Shobsngob, S., & Varavinit, S. (2000). Morphological properties of acid-modified tapioca starch. *Starch-Stärke*, 52, 283-289.

Atichokudomchai, N., Shobsngob, S., Chinachoti, P., & Varavinit, S. (2001). A study of some physicochemical properties of high-crystalline tapioca starch. *Starch-Stärke*, *53*, 577-581.

Atichokudomchai, N., Varavinit, S., & Chinachoti, P. (2002). A study of annealing and freeze-thaw stability of acid modified tapioca starches by Differential Scanning Calorimetry (DSC). *Starch-Stärke*, *54*, 343-349.

Bello-Perez, L.A., Agama-Acevedo, E., Zamudio-Flores, P.B., Mendez-Montealvo, G., & Rodriguez-Ambriz, S.L. (2010). Effect of low and high acetylation degree in the morphological, physicochemical and structural characteristics of barley starch. *LWT- Food Science and Technology*, 43, 1434-1440.

BeMiller, J. N. (1997). Starch modification: challenges and prospects. *Starch-Stärke*, 49, 127-131.

BeMiller, J.N. (2011). Pasting, paste, and gel properties of starch-hydrocolloid combinations (Review). *Carbohydrate Polymers*, 86, 386-423.

Bendoraitiene, J., Sarkinas, A., Danilovas, P.P., Rutkaite, R., Klimavicinte, R., & Zemaitaitis, A. (2013). Cationic starch iodophores. *Journal of Applied Polymer Sciences*, 128, 4346-4354.

Beninca, C., Colman, T.A.D., Lacerda, L.G., Carvalho, M.A.D., Demiate, I.M., Bannach, G., et al. (2013). Thermal, rheological and structural behaviors of natural and modified cassava starch granules, with sodium hypochlorite solution. *Journal of Thermal Analysis and Calorimetry*, 111, 2217-2222.

Biliaderis, C.G. (1998). Structures and phase transitions of starch polymers. In R.H. Walter (Ed.), *Polysaccharides association structures in food* (pp. 57-168). New York: Marcel-Dekker, Inc.

Blaszczak, W., Valverde, S., & Fornal, J. (2005). Effect of high pressure on the structure of potato starch. *Carbohydrate Polymers*, *59*, 377-383.

Bonazzi, C, Dumoulin, E., Raoult-Wack, A., Berk, Z., Bimbenet, J.J., Courtois, F., Trystram, G., & Vasseur, J. (1996). Food drying and dewatering. *Drying Technology*, *14*, 2135-2170.

Brummer, T., Meuser, F., Lengerich, B.V., & Niemann, C. (2002). Effect of extrusion cooking on molecular parameters of corn starch. *Starch-Stärke*, *54*, 1-8.

Cavallini, C. M., & Franco, C. M. L. (2010). Effect of acid-ethanol treatment followed by ball milling on structural and physicochemical characteristics of cassava starch. *Starch–Stärke*, 62, 236–245.

Cham, S., & Suwannaporn, P. (2010). Effect of hydrothermal treatment of rice flour on various rice noodles quality. *Journal of Cereal Science*, *51*, 284–291.

Che, L.-M., Li, D., Wang, L.-J., Chen, X. D., & Mao, Z.-H. (2007). Micronization and hydrophobic modification of cassava starch. *International Journal of Food Properties*, 10, 527–536.

Chiu, C.-W., Schiermeyer, E., Thomas, D. J., & Shah, M. B. (1998). Thermally inhibited starches and flours and process for their production. U.S. Patent 5,725,676.

Chung, H. –J., Woo, K.-S, & Lim, S.-T. (2004). Glass transition and enthalpy relaxation of cross linked corn starches. *Carbohydrate Polymers*, *55*, 9-15.

Chung, H.J., Liu, Q., & Hoover, R. (2009). Impact of annealing and heat–moisture treatment on rapidly digestible, slowly digestible and resistant starch levels in native and gelatinized corn, pea and lentil starches. *Carbohydrate Polymers*, 75, 436–447.

Collado, L.S., & Corke, H. (1999). Heat-moisture treatment effects on sweet potato starches differing in amylose content. *Food Chemistry*, 65, 339-346.

Colonna, P., Buleon, A., & Mercier, C. (1987). Physically modified starches. In T. Galliard (Ed.), Starch: Properties and Potential. Critical reports on applied chemistry (vol. 13, pp. 79-114). New York: Wiley.

Colussi, R., Pinto, V.Z., Mello El Halal, S.L., Vanier, N.L., Villanova, F.A., Marquez e Silva, R., Zavareze, E. D. R., & Dias, A.R.G. (2014). Structural, morphological and physicochemical properties of acetylated high-, medium-, and low- amylose rice starches. *Carbohydrate Polymers*, 103, 405-413.

Davies, L. (1995). Starch composition, modification, applications and nutritional value in foodstuffs. *Food Technology Europe*, *617*, 44-52.

Diop, C., Li, H.L., Xie, B.J., & Shi, J. (2011). Effect of acetic acid/acetic anhydride ratios on the properties of corn starch acetates. *Food Chemistry*, *126*, 1662-1669.

Emeje, M., Kalita, R., Isimi, C., Buragohain, A., Kunle, O., & Ofoefule, S. (2012). Synthesis, physicochemical characterization and functional properties of an esterified starch from an underutilized source in Nigeria. *African Journal of Food, Agriculture, Nutrition and Development*, 12, 7001-7018.

Fechner, P.M., Waterwig, S., Kiesow, A., Heilman, A. et al. (2005). Influence of water on molecular and morphological structure of various starches and starch derivatives. *Starch-Stärke*, 57, 605–615.

Ferrini, L. M. K., Rocha, T. S., Demiate, I. M., & Franco, C. M. L. (2008). Effect of acid-methanol treatment on the physicochemical and structural characteristics of cassava and maize starches. *Starch–Stärke*, 60, 417–425.

Fornal, J., Sadowski, J., Blaszczak, W., Jelinski, T., Stasiak, M., Molenda, M., et al., (2012). Influence of some chemical modification on the characteristics of potato starch powder. *Journal of Food Engineering*, 108, 515-522.

French, D. (1981). In. R. Whistler, E.F. Paschell & J.N. BeMiller, *Starch chemistry and technology* New York: Academic Press.

Gallant, D. J., Bouchet, B., Buleon, A., & Perez, S. (1992). Physical characteristics of starch granules and susceptibility to enzymatic degradation. *Eurpeon Journal Clinical Nutrition*, 46, 3-16.

Gerard, C., Colonna, P., Buleon, A., & Planchot, V. (2001). Amylolysis of maize mutant starches. Journal of the Science of Food and Agriculture, 81, 1281-1287.

Gharsallaoui, A., Roudant, G., Chambin, O., Voilley, A., & Saurel, R. (2007). Application of spray drying in microencapsulation of food ingrediants. An overview. *Food Research International*, 40, 1107-1121.

Grag, S., & Jana, A.K. (2011). Characterization and evaluation of acetylated starch with different aceyl groups and degrees of substitution. *Carbohydrate Polymers*, 83, 1623-1630.

Guerra-Della Valle, D., Sanchev-Rivera, M.M., Zamudio-Flores, P.B., Mendez-Montealvo, G., & Bello-Perez, L.A. (2009). Effect of chemical modification type on physicochemical and rheological characteristics of banana starch. *Revista Mexicana de Ingenieria Quimica*, 8, 197-203.

Gui-Jie, M., Peng, W., Xiang-Sheng, M., Xing, Z., & Tong, Z. (2006). Cross linking of corn starch with sodium trimetaphosphate in solid state by microwave irradiation. *Journal of Applied Polymer Science*, 102, 5854-5860.

Gunaratne, A., & Corke, H. (2007). Effect of hydroxypropylation and alkaline treatment in hydroxypropylation on some structural and physicochemical properties of heat–moisture treated wheat, potato and waxy maize starches. *Carbohydrate Polymers*, 68, 305–313.

Gunaratne, A., & Hoover, R. (2002). Effect of heat–moisture treatment on the structure and physicochemical properties of tuber and root starches. *Carbohydrate Polymers*, 49, 425–437.

Han, H. L., & Sosulski, F. W. (1998). Cationization of potato and tapioca starches using an aqueous alcoholic-alkaline process. *Starch–Stärke*, *50*, 487–492.

Han, Z., Zeng, X., Zhang, B., & Yu, S. (2009). Effect of pulsed electric fields (PEF) treatment on the properties of corn starch. *Journal of Food Engineering*, *93*, 318–323.

Han, Z., Zeng, X.A., Yu, S.J., & Chen, X.D. (2009). Effects of pulsed electric fields (PEF) treatment on physicochemical properties of potato starch. *Innovative Food Science and Emerging Technologies*, 10, 481-485.

Heinze, T., Haack, V., & Rensing, S. (2004). Starch derivatives of high degree of functionalization.7. preparation of cationic 2-hydroxypropyltrimethyl ammonium chloride starch. *Starch-Stärke*, 56, 288-296.

Hodge, S. & Osman, M. (1976). In O.R. Fennema (Ed.), Food Chemistry, Principles of food science part 1 (pp. 102-114) New York: Mercel Dekker.

Hoover, R. (2001). Composition, molecular structure, and physicochemical properties of tuber and root starches: A review. *Carbohydrates Polymers*, 45, 253–267.

Hoover, R. (2010). The impact of heat–moisture treatment on molecular structures and properties of starches isolated from different botanical sources. *Critical Reviews in Food Science and Nutrition*, 50, 835–847.

Hoover, R., & Manuel, H. (1996). The effect of heat–moisture treatment on the structure and physicochemical properties of normal maize, waxy maize, dull waxy maize and amylomaize V starches. *Journal of Cereal Science*, 23, 153–162.

Hoover, R., & Vasanthan, T. (1994). The effect of annealing on the physicochemical properties of wheat, oat, potato and lentil starches. *Journal of Food Biochemistry*, 17, 303-325.

Hoover, R., & Vasanthan, T. (1994). Effect of heat–moisture treatment on the structure and physicochemical properties of cereal, legume, and tuber starches. *Carbohydrate Research*, 252, 33–53.

Hu, X.T., Xu, X.M., Jin, Z.Y., Tian, Y.Q., Bai, Y.X., & Xie, Z.J. (2011). Retrogradation properties of rice starch gelatinized by heat and high hydrostatic pressure (HHP). *Journal of Food Engineering*, 106, 262-266.

Huang, J., Schols, H., Jin, Z., Sulmann, E., & Voragen, A.G.J. (2007). Pasting properties and (chemical) fine structure of acetylated yellow pea starch is affected by acetylation reagent type and granule size. *Carbohydrate Polymers*, 68, 397-406.

Huang, Z.-Q., Lu, J.-P., Li, X.-H., & Tong, Z. F. (2007). Effect of mechanical activation on physicochemical properties and structure of cassava starch. *Carbohydrate Polymers*, 68, 128–135.

Huber, K.C., & BeMiller, J.N. (2000). Channels of maize and sorghum starch granules. *Carbohydrate Polymers*, 41, 269-276.

Iida, Y., Tuziuti, T., Yasui, K., Towatu, A., & Kozuka, T. (2008). Control of viscosity in starch and polysaccharide solutions with ultrasound after gelatinization. *Innovative Food Science and Emerging Technologies*, *9*, 140-146.

Jacobs, H., & Delcour, J.A. (1998). Hydrothermal modifications of granular starch, with retention of the granular structure: A review. *Journal of Agricultural and Food Chemistry*, 46, 2895–2905.

Jane, J., Xu, A., Radosavljevic, M., & Seib, P.A. (1992). Location of amylose in normal starch granules. I. Susceptibility of amylose and amylopectin to cross-linking reagents. *Cereal chemistry*, 69, 405-409

.

Jane, J.-L., Kasemsuwan, T., Leas, S., Zobel, H., & Robyt, J. F. (1994). Anthology of starch granule morphology by scanning electron microscopy. *Starch-Stärke*, *46*, 121–129.

Jayakody, I., & Hoover, R. (2008). Effect of annealing on the molecular structure and physicochemical properties of starches from different botanical sources: A review. *Carbohydrate Polymers*, 74, 691–703.

Jiranuntakul, W., Puttanlek, C., Rungsardthong, V., Puncha- Arnon, S., & Uttapap, D. (2001). Microstructural and physicochemical properties of heat-moisture treated waxy and normal starches. *Journal Food Engineering*, 104, 246–258.

Jobling, S. (2004). Improving starch for food and industrial applications. *Current Opinion in Plant Biology*, 7, 210-218.

Jyothi, A. N., Moorthy, S. N., & Rajasekharan, K. N. (2007). Studies on the synthesis and properties of hydroxypropyl derivatives of cassava (*Manihot esculenta Crantz*) starch. *Journal of the Science of Food and Agriculture*, 87, 1964–1972.

Jyothi, A.N., Moorthy, S.N., & Rajasekharan, V. (2006). Effects of cross linking with epichlorohydrin on the properties of cassava (*Manihot esculenta Crantz*) starch. *Starch-Stärke*, 58, 292-299.

Karapantsios, T. D. (2006). Conductive drying kinetics of pregelatinized starch thin films. *Journal of Food Engineering*, 76, 477-489.

Kaur, B., Ariffin, F., Bhat, R., & Karim, A.A. (2012). Progress in starch modification in the last decade. *Food Hydrocolloids*, 26, 398–404.

Kaur, L., Singh, J., & Singh, N. (2006). Effect of cross linking on some properties of potato starches. *Journal of the Science of Food and Agriculture*, 86, 1945-1954.

Khunae, P., Tran, T., & Sirivongpaisal, P. (2007). Effect of heat moisture on structural and thermal properties of rice starch differing in amylose content. *Starch-Stärke*, *59*, 593–599.

Klein, B., Vanier, N. L., Moomand, K., Pinto, V. Z., Colussi, R., Zavareze, E. D. R., et al. (2014). Ozone oxidation of cassava starch in aqueous solution at different pH. *Food Chemistry*, 155, 167–173.

Knorr, D., & Angersbach, A. (1998). Impact of high intensity electric field pulses on plant membrance permeabilisation. *Trends in Food Science and Technology*, 9, 185-191.

Kohyama, K., & Sasaki, T. (2006). Differential scanning calorimetry and a model calculation of starches annealed at 20 and 50° C. *Carbohydrate Polymers*, *63*, 82–88.

Konowal, E., Lewandowicz, G., Le Thanh-Blicharz, J., & Prochaska, K. (2012). Physicochemical characteristics of enzymatically hydrolyzed derivatives of acetylated starch. *Carbohydrate Polymers*, 87, 1333-1341.

Koo, S.H., Lee, K.Y., & Lee, H.G. (2010). Effect of cross linking on physicochemical and physiological properties of corn starch. *Food Hydrocolloids*, 24, 619-625.

Krentz, D.O., Lohmann, C., Schwarz, S., & Bratskaya, S. et al. (2006). Properties and flocculation efficiency of highly cationized starch derivatives. *Starch-Starke*, *58*, 161-169. Kuakpetoon, D., & Wang, Y.-J. (2006). Structural characteristics and physicochemical properties of oxidized starches varying in amylose content. *Carbohydrate Research*, *341*, 1896-1915.

Laovachirasuwan, P., Peeerapattana, J., Srijesdaruk, V., Chitropas, P., & Otsuka, M. (2010). The physicochemical properties of a spray dried glutinous rice starch biopolymer. *Colloids and Surfaces B: Biointerfaces*, 78, 30–35.

41 ACCEPTED MANUSCRIPT

Lawal, O. (2004). Composition, physicochemical properties and retrogradation characteristics of native, oxidized, acetylated and acid thinned new cocoyam (Xanthosoma sagittifolium) starch. *Food Chemistry*, 87, 205-218.

Lawal, O.S., Adebowale, K.O., Ogunsanwo, B.M., Barba, L.L., & Ilo, N.S. (2005). Oxidized and acid thinned starches derivatives of hybrid maize: Functional characteristics wide-angle X-ray diffractometry and thermal properties. *International Journal of Biological Marcomoleclues*, 35, 71-79.

Lewandowicz, G., & Soral-Smietana, M. (2004). Starch modification by iterated syneresis. *Carbohydrate Polymers*, *56*, 403–413.

Li, Y. Q., Chen, Q., Liu, X. H., & Chen, Z. X. (2008). Inactivation of soybean lipoxygenase in soymilk by pulsed electric fields. *Food Chemistry*, *109*, 408–414.

Lim, S.-T., Han, J.-A., Lim, H. S., & BeMiller, J. N. (2002). Modification of starch by dry heating with ionic gums. *Cereal Chemistry*, 79, 601–606.

Lin, J. H., Wang, S. W., & Chang, Y. H. (2008). Effect of molecular size on gelatinization thermal properties before and after annealing of rice starch with different amylose contents. *Food Hydrocolloids*, 22, 156–163.

Liu, C.M., Zhang, Y.J., Liu, W., Wan, J., Wang, W.H., & Wu, L., et al. (2011). Preparation, physico-chemical and texture properties of texturized rice produced by improved extrusion cooking technology. *Journal of Cereal Sciences*, *54*, 473-480.

Lopez, O.V., Zaritzky, N.E., Grossmann, M.V.E. & Garcia, M.A. (2013). Acetylated and native corn starch blend films produced by blown extrusion. *Journal of Food Engineering*, *116*, 286-297.

Lui, H., & Corke, H. (1999). Physical properties of cross linked and acetylated normal and waxy rice starch. *Starch-Stärke*, *51*, 249-252.

Luo, Z., & Zhou, Z. (2012). Homogenous synthesis and characterization of starch acetates in ionic liquid without catalysts. *Starch/Stärke*, 64, 37-44.

Luo, Z.-G., & Shi, Y.-C. (2012). Preparation of acetyated waxy, normal and high-amylose maize starches with intermediate degrees of substitution in aqueous solution and their properties. *Journal of Agriculture and Food Chemistry*, 60, 9468-9475.

Maache-Rezzoug, Z., Maugard, T., Zarguili, I., Bezzine, E., et al. (2009). Effect of instantaneous controlled pressure drop (DIC) on Physicochemical properties of wheat, waxy and standard maize starches. *Journal of Cereal Science*, 49, 346–353.

Majzoobi, M., Radi, M., Farahnaky, A., Jamalian, J., Tongdang, T., & Mesbahi, G. (2011). Physicochemical properties of pre-gelatinized wheat starch produced by a twin drum drier. *Journal of Agricultural Science and Technology*, 13, 193-202.

Marselles-Fontanet, A. R. & Martin-Belloso, O. (2007). Optimization and validation of PEF processing conditions to inactivate oxidative enzymes of grape juice. *Journal of Food Engineering*, 83, 452–462.

Mbougueng, P.D., Tenin, D., Scher, J., & Tchiegang, C. (2012). Influence of acetylation on physicochemical, functional and thermal properties of potato and cassava starches. *Journal of Food Engineering*, 108, 320-326.

Mello El Halal, S.L., Colussi, R., Pinto, V.Z., Bartz, J., Radunz, M., Carreno, N.L.V., Dias, A.R.G., & Zavareze, E. D. R. (2015). Structure, morphology and functionality of acetylated and oxidized barley starches, *Food Chemistry*, *168*, 247-256.

Mina, J., Valadez-Gonzales, A., Herrera-Franco, P., Zuluaga, F., & Delvasto, S. (2011). Physicochemical characterization of neutral and acetylated thermoplastic cassava starch. *Dyna*, 166, 166-173.

Moorthy, S. N. (1985). Acetylation of cassava starch using perchloric acid catalysis. *Starch—Stärke*, *37*, 307–308.

Morikawa, K., & Nishinari, K. (2000a). Effects of concentration dependence of retrogradation behavior of dispersion for native and chemically modified potato starch. *Food Hydrocolloids*, *14*, 395-401.

Morikawa, K., & Nishinari, K. (2000b). Rheological and DSC studies of gelatinization of chemically modified starch heated at various temperatures. *Carbohydrate Polymers*, *43*, 241-247.

Morrison, W.R., Tester, R.F., Snape, C.E., Law, R., & Gidley, M.J. (1993). Swelling and gelatinization of cereal starches. IV. Some effects of lipid-complexed amylose and free amylose in waxy and normal barley starches. *Cereal Chemistry*, 70, 385-391.

Munoz-Bonilla, A., & Fernandez-Garcia, M. (2012). Polymeric materials with antimicrobial activity. *Progress in Polymer Science*, *37*, 281-339.

Murua-Pagola, B., Beristain-Guevara, C.L., & Martinez-Bustos, F. (2009). Preparation of starch derivatives using reactive extrusion and evaluation of modified starches as shell material for encapsulation of flavoring agents by spray drying. *Journal of Food engineering*, *91*, 380-386.

Nabeshima, E. H., & Grossmann, M. V. E. (2001). Functional properties of pregelatinized and cross-linked cassava starch obtained by extrusion with sodium trimetaphosphate. *Carbohydrate Polymers*, 45, 347–353.

45 ACCEPTED MANUSCRIPT

Nemtanu, M. R., & Minea, R. (2006). Functional properties of corn starch treated with corona electrical discharges. *Macromolecular Symposia*, 525–528.

Osundahunsi, O. F., & Mueller, R. (2011). Functional and dynamic rheological properties of acetylated starches from two cultivars of cassava. *Starch–Stärke*, 63, 3–10.

Osunsami, A. T., Akingbala, J. O., & Oguntimein, G. B. (1989). Effect of storage on starch content and modification of cassava starch. *Starch–Stärke*, *41*, 54–57.

Perez, S., & Bertoft, E. (2010). The molecular structure of starch components and their contribution to the architecture of starch granules: A comprehensive review. *Starch-Stärke*, 62, 389-420.

Piacquadio, P., Stefano, G. D., & Sciancalepore, V. (2000). The effect of heating at subgelatinization temperature on enzymatic digestibility of corn starch. *Starch-Stärke*, 52, 345–348.

Pinto, V.Z., Vanier, N.L., Klein, B., Zavareze, E.D.R., Elias, M.C., & Gutkoski, L.C., et al. (2012). Physicochemical, crystallinity, pasting and thermal properties of heat–moisture-treated pinhao starch. *Starch-Stärke*, *64*, 855–863.

Pitchon, E., O'Rourke, J.D., & Joseph, T.H. (1981). Process for cooking or gelatinizing materials. U.S. Patent, 4280851.

Pukkahuta, C., Shobsngob, S., & Varavinit, S. (2007). Effect of osmotic pressure on starch: new method of physical modification of starch. *Starch-Stärke*, 58, 78-90.

Qi, X., Tester, R. F., Snape, C. E., & Ansell, R. (2005). The effect of annealing on structure and gelatinization of maize starches with amylose dosage series. *Progress in Food Biopolymers and Research*, 1, 1–27.

Qiu, S., Li, Y., Chen, H., Liu, Y., & Yin, L. (2014). Effects of high pressure homogenization on thermal and electrical properties of wheat starch. *Journal of Food Engineering*, 128, 53-59.

Radosta, S., Vorwery, W., Ebert, A, Begli, A.H. et al. (2004). Properties of low-substituted cationic starch derivatives prepared by different derivatization processes. *Starch-Stärke*, *56*, 277-287.

Raina, C.S., Singh, S., Bawa, A.S., & Saxena, D.C. (2006). Some characteristics of acetylated, cross-linked and dual modified Indian rice starches. *European Food Research and Technology*, 223, 561-570.

Raja, K. C. M. (1992). Studies on alkali-modified cassava starch-changes of structural and enzyme (α-amylase) susceptibility properties. *Starch–Stärke*, 44, 133–136.

Ratnayake, W. S., & Jackson, D. S. (2008). Phase transition of cross-linked and hydroxy-propylated corn (Zea mays L.) starches. *LWT-Food Science Technology*, *41*, 346–358.

Reddy, I., & Seib, P.A. (2000). Modified waxy wheat starch compared to modified waxy corn starch. *Journal of Cereal Science*, *31*, 25-39.

Ren, G. Y., Li, D., Wang, L. J., Özkan, N., & Mao, Z. H. (2010). Morphological properties and thermo-analysis of micronized cassava starch. *Carbohydrate Polymers*, 79, 101-105.

Robert, P., Garcia, P., Reyes, N., Chavez, J., & Santos, J. (2012). Acetylated starch and inulin as encapsulating agents for gallic acid and their release behavior in a hydrophilic system. *Food Chemistry*, 134, 1-8.

Rolland-Sabate, A., Sanchez, T., Buléon, A., Colonna, P., Jaillais, B., Ceballos, H., et al. (2012). Structural characterization of novel cassava starches with low and high-amylose contents in comparison with other commercial sources. *Food Hydrocolloids*, 27, 161–174.

Rubens, R.W. (1992). Method and apparatus for cooking and spray drying starch. U.S. Patent, 5149799.

Rutenberg, M.W., & Solarek, D. (1984). Starch derivatives: Production and uses, R.L. Whistler, J.N. BeMiller, E.F. Paschall (eds.), Starch: Chemistry and Technology, Academic Press, London (1984), 312-388.

Sakai-kato, Kato, M., Nakajima, T., & Toyo'oka, T. et al. (2006). Cationic starch derivatives as dynamic additives for protein analysis in capillary electrophoresis. *Journal of Chromatography A*, *1111*, 127-132.

Sampedro, F., Rivas, A., Rodrigo, D., Martinz, A., & Rodrigo, M. (2007). Pulsed electric fields inactivation of Lactobacillus plantarum in an orange juice-milk based beverage: Effect of process parameters. *Journal Food Engineering*, 80, 931–938.

Sanchev-Rivera, M.M., Garicia-Suarez, F.T.L., & Bello-Perez, L.A. (2005). Partial characterization of banana starches oxidized by different levels of sodium hypochlorite. *Carbohydrate Polymers*, 62, 50-56.

Sandhu, K.S., Kaur, M., Singh, N., & lim, S.-T. (2008). A comparison of native and oxidized normal and waxy corn starches: Physicochemical, thermal, morphological and pasting properties. *LWT- Food Science and Technology*, 41, 1000-1010.

Sangseethong, K., Lertphanich, S., & Sriroth, K. (2009). Physicochemical properties of oxidized cassava starch prepared under various alkalinity levels. *Starch–Stärke*, *61*, 92–100.

Sangseethong, K., Termvejsayanon, N., & Sriroth, K. (2010). Characterization of physicochemical properties of hypochlorite- and peroxide-oxidized cassava starches. *Carbohydrate Polymers*, 82, 446–453.

Sanguanpong, V., Chotineeranat, S., Piyachomkwan, K., Oates, C. G., Chinachoti, P., & Sriroth, K. (2003). Hydration and physicochemical properties of small-particle cassava starch. *Journal of the Science of Food and Agriculture*, 83, 123–132.

Santacruz, S. (2014). Characterization of cationic potato starch by asymmetrical flow field-flow fractionation. Influence of ionic strength and degree of substitution. *Carbohydrate Polymers*, 106, 166-171.

Schmitz, C. S., De Simas, K. N., Santos, K., Joao, J. J., Amboni, R. D. D. M. C., & Amante, E. R. (2006). Cassava starch functional properties by etherification-hydroxypropylation. *International Journal of Food Science & Technology*, *41*, 681–687.

Seker, M., & Hanna, M.A. (2006). Sodium hydroxide and trimetaphosphate levels affect properties of starch extrudates. *Industrial Crop Products*, 23, 249-255.

Shanshan, L., Jiyou, G., Jun, C., Haiyan, T., & Yanhua, Z. (2015). Effect of annealing on the thermal properties of poly (lactic acid)/ starch blends. *International Journal of Biological Macromolecules*, 74, 297-303.

Shi, Y. C. (2008). Two- and multi-step annealing of cereal starches in relation to gelatinization. Agriculture Food Chemistry, 56, 1097–1104.

Shin, S. I., Kim, H. J., Ha, H. J., Lee, S. H., & Moon, T. W. (2005). Effect of hydrothermal treatment on formation and structural characteristics of slowly digestible non-pasted granular sweet potato starch. *Starch-Stärke*, *57*, 421–430.

Shujan, W., Jinrong, W., Jinglin, Y., & Shuo, W. (2014). A comparative study of annealing of waxy, normal and high amylose maize starches: the role of amylose molecule. *Food Chemistry*, 164, 332-338.

Siau, C.L., Karim, A.A., Norziah, M.H., & Wan Rosli, W.D. (2004). Effect of cationization of DSC thermal profiles pasting and emulsifying properties of sago starch. *Journal of the Science of Food and Agriculture*, 84, 1722-1730.

Singh, A.V., & Nath, L.K. (2012). Synthesis and evaluation of physicochemical properties of cross-linked sago starch. *International journal of Biological Macromolecules*, *50*, 14-18.

Singh, H., Chang, Y.H., Sodhi, N.S., & Singh, N. (2011). Influence of prior acid treatment on physicochemical and structural properties of acetylated sorghum starch. *Starch-Stärke*, *63*, 291-301.

Singh, J., & Singh, N. (2003). Studies on the morphological and rheological properties of granular cold water soluble corn and potato starches. *Food Hydrocolloids*, 17, 63-72.

Singh, J., Kaur, L., & McCarthy, O.J. (2007). Factors influencing the physicochemical, morphological, thermal and rheological properties of some chemical modified starches for food applications-A review. *Food Hydrocolloids*, 21, 1-22.

Smith, A. M. (2001). The biosynthesis of the starch granule. *Biomacromolecules*, 2, 335–341.

Srichuwong, S., Sunarti, T. C., Mishima, T., Isono, N., & Hisamatsu, M. (2005). Starches from different botanical sources I: Contribution of amylopectin fine structure to thermal properties and enzyme digestibility. *Carbohydrate Polymers*, 60, 529-538.

Steeneken, P. A. M., & Woortman, A. J. J. (2009). Superheated starch: A novel approach towards spreadable particle gels. *Food Hydrocolloids*, *23*, 394–405.

Stute, R., Klingler, R.W., Boguslawski, S., Eshtiaghi, M.N., & Knorr, D. (1996). Effect of high pressure treatment on starches. *Starch-Stärke*, 48, 399-408.

Sui, Z., Shah, A., & BeMiller, J.N. (2011). Cross-linked and stabilized in-kernel heat–moisture-treated and temperature-cycled normal maize starch and effects of reaction conditions on starch properties. *Carbohydrate Polymers*, 86, 1461–1467.

Szymonska, J., Krok, F., Komorowska-Czepirska, E., & Rebilas, K. (2003). Modification of granular potato starch by multiple deep-freezing and thawing. *Carbohydrate Polymers*, 52, 1–10.

Szymonska, J., Krok, F., & tomasik, P. (2000). Deep-freezing of potato starch. *International Journal of Biological Macromolecules*, 27, 307-314.

Takahashi, S., Maningat, C. C., & Seib, P. A. (1989). Acetylated and hydroxypropylated wheat starch: Paste and gel properties compared with modified maize and tapioca starches. *Cereal Chemistry*, 66, 499–506.

Tester, R. F., & Debon, S.J.J.(2000). Annealing of starch: A review. *International Journal of Biological Macromolecules*, 27, 1–12.

Tester, R. F., Karkalas, J., & Qi, X. (2004). Starch-composition, fine structure and architecture. *Journal Cereal Chemistry*, 39, 151–165.

Tharanathan, R. N. (2005). Starch-value addition by modification. *Critical Reviews in Food Science and Nutrition*, 45, 371-384.

Thiranthumthavorn, D., & Charoenrein, S. (2005). Thermal and pasting properties of acid treated rice starches. *Starch-Stärke*, *57*, 217-222.

Tian, Y., Li, D., Zhao, J., Xu, X., & Jin, Z. (2014). Effects of high hydrostatic pressure (HHP) on slowly digestible properties of rice starches. *Food Chemistry*, *152*, 225-229.

Torregrosa, F., Esteve, M. D., Frigola, A., & Cortes, C. (2006). Ascorbic acid stability during refrigerated storage of orange carrot juice treated by high pulsed electric field and comparison with pasteurized juice. *Journal of Food Engineering*, 73, 339–345.

Tran, T., Piyachomkwan, K., & Sriroth, K. (2007). Gelatinization and thermal properties of modified cassava starches. *Starch–Stärke*, *59*, 46–55.

Vallons, K.J.R., & Arendt, E.K. (2009). Effects of high pressure and temperature on buckwheat starch characteristics. *European Food Research and Technology*, 230, 343-351.

Valodkar, M., & Thakore, S. (2011). Organically modified nanosized starch derivatives as excellent reinforcing agents for bionanocomposites. *Carbohydrate Polymers*, 86, 1244-1251.

Varavinit, S., Paisanjit, W., Tukomane, T., & Pukkahuta, C. (2007). Effect of osmotic pressure on the cross-linking reaction of tapioca starch. *Starch-Stärke*, *59*, 290–296.

Veira, F. C., & Sarmento, S. B. S. (2008). Heat-moisture treatment and enzymatic digestibility of Peruvian carrot, sweet potato and ginger starches. *Starch-Stärke*, 60, 223–232.

Vermeylen, R., Goderis, B., & Delcour, J.A. (2006). An X-ray study of hydrothermally treated potato starch. *Carbohydrate Polymers*, *64*, 364–375.

Vlachos, N.A., & Karapantsios, T.D. (2000). Water content measurement of thin sheet starch products using a conductance technique. *Journal of Food Engineering*, 46, 91-98.

Wang, L., & Wang. Y.J. (2001). Structures and physicochemical properties of acid-thermal corn, potato and rice starches. *Starch-Stärke*, *53*, 570-576.

Wang, Y.-J., & Wang, L. (2003). Physicochemical properties of common and waxy corn starches oxidized by different levels of sodium hypochlorite. *Carbohydrate polymers*, *52*, 207-217.

Wangsagonup, R., Pujchakarn, T., Jitrakbumrung, S., Chaiwat, W., Fuongfuchat, A., Varavinit, S., Dangtip, S., & Suphantharika, M. (2014). Effect of cross linking on physicochemical properties of tapioca starch and its application in soup product. *Carbohydrate Polymers*, 101, 656-665.

Watcharatewinkul, Y., Uttapap, D., & Rungsardthong, V. (2010). Enzyme digestibility and acid/shear stability of heat-moisture treated canna starch. *Starch-Stärke*, 62, 205–216.

Wattanachant, S., Muhammad, S.K.S., Mat Hashim, D., & Rahman, R.A. (2002). Suitability of sago starch as a base for dual modification. *Songklanakarin Journal of Science and Technology*, 24, 431-438.

Weigh, T. A., Keto, K. L., Donald, A. M., & Gidley, M. J., et al. (2000). Side-chain liquid-crytalline model for starch. *Starch-Stärke*, *52*, 450–460.

Wurzburg, O. B. (1986). Nutritional aspects and safety of modified food starches. *Nutrition Reviews*, 44, 74-79.

Wuttisela, K., Triampo, W., & Triampo, D. (2009). Chemical force mapping of phosphate and carbon on acid-modified tapioca starch surface. *International Journal of Biological Marcomoleclues*, 44, 86-91.

Xia, L., Wenyuan, G, Qianqian, J., Luqi, H., & Changxiao, L. (2011). Study on morphology, crystalline structure and thermal properties of *Fritillaria ussuriensis* Maxim. Starch acetates with different degree of substitution. *Starch-Stärke*, 63, 24-31.

Xie, S.X., Liu, Q., & Cui, S.W. (2005). Starch modifications and application. S.W. Cui (Ed.), *Food Carbohydrates*, CRC Press, Boca Raton, FL (2005).

Xu, Y., Miladinov, V., & Hanna, M.A. (2004). Synthesis and characteristics of starch acetates with high substitution. *Cereal Chemistry*, 81, 735-740.

Yan, H., & Zhengbiao, G.U. (2010). Morphology of modified starches prepared by different methods. *Food Research International*, 43, 767-772.

Zamudio-Flores, P.B., Torres, A.V., Salgado-Delgado, R., & Bello-Perez, L.A. (2010). Influence of oxidation and acetylation of banana starch on the mechanical and water barrier properties of modified starch/chitosan blend films. *Journal of Applied Polymer Science*, 115, 991-998.

Zamudio-Flores, P.B., Vergas-Torres, A., Gutierrez, F., & Bello-Perez, L.A. (2010). Physicochemical characterization of dually-modified banana starch. *Agrociencia*, 44, 283-295.

Zarguili, I., Maache-Rezzoug, Z., Loisel, C., & Doublier, J.-L. (2006). Influence of DIL hydrothermal process conditions on the gelatinization properties of standard maize starch. *Journal of Food Engineering*, 77, 454–461.

Zhang, L., Xie, W., Zhao, X., Liu, Y., & Gao, W. (2009). Study on morphology, crystalline structure and thermal properties of yellow ginger starch acetates with different degrees of substitution. *Thermochimica Acta*, 495, 57-62.

Zhang, L., Zuo, B., Wu, P., Wang, Y., & Gao, W. (2012). Ultrasound effects on the acetylation of dioscorea starch isolated from *Dioscorea Zingiberensis* C.H. Wright. *Chemical Engineering and Processing, Process Intensification*, 54, 29-36.

Zhang, Y., Liu, W., Liu C., Luo, S., Li, T., Liu, Y., Wu, D., & Zuo, Y. (2014). Retrogradation behavior of high amylose rice starch prepared by improved extrusion cooking technology. *Food Chemistry*, 158, 255-261.

Zhongquan, S., Tianming, Y., Yue, Z., Xiaoting, Y., Xiangli, K., & Lianzhong, A. (2015). Effect of heat moisture treatment reaction conditions on the physicochemical and structural properties of maize starch: moisture and length of heating. *Food Chemistry*, 173, 1125-1132.

Zhu, F. (2015). Impact of ultrasound on structure, physicochemical properties, modification and applications of starch. *Trends in Food Science and Technology*, doi: 10.1016/j.tifs. 2014.12.008.

Zieba, T., Gryszkin, A., & Kapelko, M. (2014). Selected properties of acetylated starch. *Carbohydrate Polymers*, 99, 687-691.

Table 1 Recent methods of physical modification of starches

Physical modification	References
Deep freezing	Szymonska et al. (2000)
Multiple deep freezing and thawing	Szymonska et al. (2003)
Osmotic pressure treatment	Pukkahuta et al. (2007)
Superheated starch	Steeneken and Woortman (2009)
Instantaneous controlled pressure	Zarguili et al. (2006
Iterated syneresis	Lewandowicz and Soral-Smietana (2004)
Corona electrical discharges	Nemtanu and Minea (2006)
Thermally inhibited treatment (dry heating)	Chiu et al. (1998); Lim et al. (2002)
Pulse electric fields treatment	Han et al. (2009)
Micronization in vacuum ball mill	Che et al. (2007)
Mechanical activation- with stirring ball mill	Huang et al. (2007)
Drop (DIC) process	Maache-Rezzoug et al. (2009)

Table 2 Annealing and gelatinization parameters for tuber and cereal starches

Starch	ANN parameters			Gelatinization parameters					References	
Source	Tem	Steps	Tim	W:S ^{a)}	S:W ^b	$T_0^{c)}$	$T_p^{c)}$	$T_c^{c)}$	ΔH	
	p		e (h))	(°C	(°C	(°C	(J/g	
	(°C)))))	
Potato	-	-	-	-	-	59.	61.	66.	18.3	Vermeylen et al.
(native)						1	9	8		(2006)
Potato	50	Singl	72	10:01	-	61.	63.	70.	18	Kohyama &
(annealed		e				1	1	7		Sasaki (2006)
)										
Cassava	-	-	-	-	-	65.	71.	81.	8.8	Atichokundomch
(native)						4	5	5		ai et al. (2002)
Cassava	51	Singl	72	3.01	-	70.	74	81.	9.4	Atichokundomch
(annealed		e				7		3		ai et al. (2002)
)										
Normal	-	-	1	-	1:05	56.	67.	76.	17.6	Qi et al. (2005)
maize						9	7	5		
(native)										
Normal	55	Singl	168	Exces	1:05	72.	76.	82.	16.9	Qi et al. (2005)
maize		e		s		1	4	3		
(annealed										
)										

Waxy	55	Singl	168	Exces	1:05	73.	77.	83.	17.3	Qi et al. (2005)
maize		e		S		3	3	1		
(annealed										
)										
Waxy	-	-	-	-	1:03	76.	81.	87.	19.2	Shi (2008)
rice						2	2	1		
(native)										
Waxy	70	Singl	48	3:01	1:03	86.	90	93.	19.6	Shi (2008)
rice		e				9		7		
(annealed										
)										

^{-,} data not reported. a) Water: starch b) Starch: water

 ΔH Enthalpy of gelatinization

c) Onset (T_o) , mid-point (T_p) and conclusion (T_c) temperatures of gelatinization.

Table 3 Some common methods of chemical modification of starches

Chemical modification	References
Cationization	Han and Sosulski (1998)
Oxidation	Tran et al. (2007), Sangseethong et al. (2009,2010), Amorim et al.
	(2011), Klein et al. (2014), Beninca, Colman, Lacerda, Carvalho,
	Demiate et al. (2013)
Acid hydrolysis	Osunsami et al. (1989), Sanguanpong et al. (2003), Akubor (2007),
	Rolland-Sabate et al. (2012)
Alkaline	Raja (1992)
Cross-linking	Nabeshima and Grossmann (2001), Jyothi, Moorthy and
	Rajasekharan (2006), Tran et al. (2007), Varavinit et al. (2007).
Hydroxypropylation	Schmitz et al. (2006), Jyothi, Moorthy, and Rajasekharan (2007),
	Takahashi, Maningat, and Seib (1989)
Acetylation	Moorthy (1985), Tran et al. (2007), Osundahunsi and Mueller
	(2011), Mbougueng, Tenin, Scher and Tchiegang (2012)
Acid hyrolysis in	Ferrini et al. (2008), Cavallini and Franco (2010)
alcohol	




Fig.1 Drum drying technique for modification of starch







Fig. 2 SEM micrographs of maltodextrin granule from spray-drying

Reprinted from (Yan, H., & Zhengbiao, G.U. 2010) (with permission from Elsevier).





a: pregelatinized corn starch (\times 300) b: pregelatinized corn starch (\times 1200)



c pregelatinized potato starch $(\times 1200)$

Fig. 3 SEM micrographs of pregelatinized starch granule from extrusion

Reprinted from (Yan, H., & Zhengbiao, G.U. 2010) (with permission from Elsevier).




Fig. 4 SEM micrographs of low DS chemical modified starch granule (a: corn starch acetate; b:

phosphorylated starch; c: oxidized starch; d: cationic starch)

Reprinted from (Yan, H., & Zhengbiao, G.U. 2010) (with permission from Elsevier)