Name: Deras Pangestu Gusti (08)

Class: SIB 1G

NIM: 254107060114

JOBSHEET V
BRUTE FORCE AND DIVIDE CONQUER

5.1 Learning Outcome

After completing this practical session, students will be able to develop algorithms using Brute Force and Divide and Conquer approaches. They will also be able to implement these algorithms effectively in problem-solving scenarios.

5.2 Calculating Factorial Using Brute Force and Divide and Conquer Algorithms

There is a class diagram as follows:

Factorial
factorialBF(): int factorialDC(): int

Based on the class diagram above, a Java program will be created to calculate the factorial of a number using two different algorithms: Brute Force and Divide and Conquer. The calculation process differs between these two approaches, as illustrated below:

- Steps for computing factorial using the **Brute Force** algorithm:

$$20! = \underbrace{\underbrace{\underbrace{20 \; x \; 19}_{} \; x \; 18}_{} \; x \; 17 \; x \; \ldots \; x \; 5 \; x \; 4 \; x3 \; x \; 2 \; x \; 1}_{}$$

- Steps for computing factorial using the Divide and Conquer method:

$$20! = \underbrace{\underbrace{\underbrace{20 \; x \; 19}_{} \; x \; \underbrace{18 \; x \; 17}_{}}_{} \; x \; \underbrace{\ldots \; x \; 5}_{} \; x \; \underbrace{\underbrace{4 \; x3}_{} \; x \; \underbrace{2 \; x \; 1}_{}}_{}$$

5.2.1. Experiment Steps

1. Create a new project named **BruteForceDivideConquer** (or continue the previous project) and a package called **week5**.
2. Create a new class, `Factorial`

3. Complete the `Factorial` class with the attributes and methods as illustrated in the class diagram above.

a) Create `faktorialBF()` method:

```
int factorialBF(int n){
    int facto = 1;
    for(int i=1; i<=n; i++){
        facto = facto * i;
    }
    return facto;
}
```

b) Create `faktorialDC()` method:

```
int factorialDC(int n){
    if(n==1){
        return 1;
    }else{
        int facto = n * factorialDC(n-1);
        return facto;
    }
}
```

c) Run the `Faktorial` class by creating a new class named `MainFaktorial` and executing it.

d) Add `main()` function within `MainFactorial` class, and get the user input:

```
Scanner input = new Scanner(System.in);
System.out.print(s:"Input a number: ");
int num = input.nextInt();
```

e) Then, create an object of `Factorial` and call the `factorialDC()` method and `factorialBF()` method:

```
Factorial fk = new Factorial();
System.out.println("The factorial of "+num+" using BF: "+fk.factorialBF(num));
System.out.println("The factorial of "+num+" using DC: "+fk.factorialDC(num));
```

d) Make sure that no error appears!

5.2.2. Verification of Experiment Results

Compare the output of your compiled program with the following image.

```
Input a number: 5
The factorial of 5 using BF: 120
The factorial of 5 using DC: 120
```

```java
package com.jobsheet4;

import java.util.Scanner;

public class BruteForceDivideConquer
{
    Run | Debug | Run main | Debug main
    public static void main(String[] args)
    {
        Scanner input = new Scanner(System.in);

        System.out.print(s: "Input a number: ");
        int num = input.nextInt();

        Factorial fk = new Factorial();
        System.out.println("The factorial of " + num + " using BF: " + fk.factorialBF(num));
        System.out.println("The factorial of " + num + " using DC: " + fk.factorialDC(num));

        input.close();
    }
}

class Factorial
{
    int factorialBF (int n)
    {
        int facto = 1;
        for (int i = 1; i <= n ; i++)
        {
            facto = facto * i;
        }
        return facto;
    }

    int factorialDC(int n)
    {
        if (n == 1)
        {
            return 1;
        }
        else
        {
            int facto = n * factorialDC(n - 1);
            return facto;
        }
    }
}
```

```
Input a number: 5
The factorial of 5 using BF: 120
The factorial of 5 using DC: 120
```

5.2.3. Questions

1. In the base case of the Divide and Conquer algorithm for calculating factorial, explain the differences in the code structure between the `if` and `else` conditions!

   If condition (base case) is used to stop the recursion & else condition (Recursive Case) is used to continue the recursion

2. Is it possible to modify the loop in the `factorialBF()` method to use an alternative to the `for` loop? Please explain and give example if needed!

   Yes, it can use while loop or do-while loop. The exemple of using while loop:

```
class Factorial
{

    int factorialBF(int n)
    {
        int facto = 1;
        int i = 1;
        while (i <= n)
        {
            facto = facto * i;
            i++;
        }
        return facto;
    }
```

3. Please explain the differences between `facto = facto*i;` and `int facto = n * factorialDC(n-1);` !

   *facto = facto * i (iterative) use to keeps updating one variable in a loop. int facto = n * factorialDC(n - 1) (recursive) use to creates a chain of function calls, each holding its own variable until the base case resolves.*

4. Make a conclusion about the differences in how each method works. `factorialBF()` and `factorialDC()`!

   Brute Force (factorialBF()) builds the result step by step in one continuous flow, while Divide and Conquer (factorialDC()) builds it indirectly through multiple recursive calls that resolve back to the base case.

5.3 Calculating Exponentiation Using Brute Force and Divide and Conquer Algorithms

In this practical session, we will create a Java program to calculate the exponentiation of a number using two different algorithms: Brute Force and Divide and Conquer. This session will utilize an Array of Objects to manage multiple objects, unlike the previous session, which focused only on a single factorial object.

5.3.1. Experiment Steps

1. In the **week5** package, create a new class named **Power**. Inside this class, define attributes for the base number and its exponent.

```
int baseNumber, exponent;
```

2. Add parameterized constructor

```
Power(int n, int e){
    baseNumber = n;
    exponent = e;
}
```

3. Add `powerBF()` method

```
int powerBF(int n, int e){
    int result = 1;
    for(int i=0; i<e; i++){
        result = result*n;
    }
    return result;
}
```

4. Add `powerDC()` method

```
int powerDC(int n, int e){
    if(e==1){
        return n;
    }else{
        if(e%2==1){
            return (powerDC(n, e/2)*powerDC(n, e/2)*n);
        }else{
            return (powerDC(n, e/2)*powerDC(n, e/2));
        }
    }
}
```

5. Next, create a new class that contains the `main` method. This class can be named `PowerMain`. Add code in the main class to input the number of elements for which the exponentiation will be calculated.

```
Scanner input = new Scanner(System.in);
System.out.print(s:"Input element number: ");
int elemen = input.nextInt();
```

6. The value obtained in step 5 will be used to instantiate an array of objects. In the following code, add a process to fill the array with multiple base numbers along with their respective exponents.

```
Power[] png = new Power[elemen];
for(int i=0;i<elemen;i++){
    System.out.print("Input base number for "+(i+1)+"th element: ");
    int basis = input.nextInt();
    System.out.print("Input exponent for "+(i+1)+"th element: ");
    int exp = input.nextInt();
    png[i] = new Power(basis, exp);
}
```

7. Call `powerBF()` and `powerDC()` method to perform power calculation using both brute force and DC approach!

```
System.out.println(x:"POWER RESULT USING BRUTEFORCE:");
for (Power p : png) {
    System.out.println(p.baseNumber+"^"+p.exponent+": "+p.powerBF(p.baseNumber, p.exponent));
}
System.out.println(x:"POWER RESULT USING DIVIDE AND CONQUER:");
for (Power p : png) {
    System.out.println(p.baseNumber+"^"+p.exponent+": "+p.powerDC(p.baseNumber, p.exponent));
}
```

5.3.2. Verification of Experiment Results

The result must be like this:

```
Masukkan jumlah elemen: 3
Masukan nilai basis elemen ke-1: 2
Masukan nilai pangkat elemen ke-1: 3
Masukan nilai basis elemen ke-2: 4
Masukan nilai pangkat elemen ke-2: 5
Masukan nilai basis elemen ke-3: 6
Masukan nilai pangkat elemen ke-3: 7
HASIL PANGKAT BRUTEFORCE:
2^3: 8
4^5: 1024
6^7: 279936
HASIL PANGKAT DIVIDE AND CONQUER:
2^3: 8
4^5: 1024
6^7: 279936
```

```java
package com.jobsheet4;

import java.util.Scanner;

public class BruteForceDivideConquer2
{
    Run | Debug | Run main | Debug main
    public static void main(String[] args)
    {
        Scanner input = new Scanner(System.in);

        System.out.print(s: "Input element number: ");
        int element = input.nextInt();

        Power[] png = new Power[element];
        for (int i = 0; i < element; i++)
        {
            System.out.print("Input base number for " + (i + 1) + "th element: ");
            int basis = input.nextInt();
            System.out.print("Input exponent for " + (i + 1) + "th element: ");
            int exp = input.nextInt();
            png[i] = new Power(basis, exp);
        }

        System.out.println(x: "POWER RESULT USING BRUTEFORCE:");
        for (Power p : png)
        {
            System.out.println(p.baseNumber + "^" + p.exponent + ": " + p.powerBF(p.baseNumber, p.exponent));
        }
        System.out.println(x: "POWER RESULT USING DEVIDE AND CONQUER:");
        for (Power p : png)
        {
            System.out.println(p.baseNumber + "^" + p.exponent + ": " + p.powerDC(p.baseNumber, p.exponent));
        }

        input.close();
    }
}
```

```
class Power
{
    int baseNumber, exponent;

    Power(int n, int e)
    {
        baseNumber = n;
        exponent = e;
    }

    int powerBF(int n, int e)
    {
        int result = 1;
        for (int i = 0; i < e; i++)
        {
            result = result * n;
        }
        return result;
    }

    int powerDC(int n, int e)
    {
        if (e == 1)
        {
            return n;
        }
        else
        {
            if (e % 2 == 1)
            {
                return (powerDC(n, e/2) * powerDC(n, e/2) * n);
            }
            else
            {
                return (powerDC(n, e/2) * powerDC(n, e/2));
            }
        }
    }
}
```

```
Input element number: 3
Input base number for 1th element: 2
Input exponent for 1th element: 3
Input base number for 2th element: 4
Input exponent for 2th element: 5
Input base number for 3th element: 6
Input exponent for 3th element: 7
POWER RESULT USING BRUTEFORCE:
2^3: 8
4^5: 1024
6^7: 279936
POWER RESULT USING DEVIDE AND CONQUER:
2^3: 8
4^5: 1024
6^7: 279936
```

5.3.3. Questions

1. Explain the differences between the two methods created `powerBF()` dan `powerDC()`!

   poweBF() is straightforward but inefficient for large exponents & powerDC() is more efficient thanks to divide-and-conquer, but requires recursion and more memory.

2. Does the **combine** stage exist in the provided code? Show the relevant part!

   Yes, this is the relevant code:

```
if (e % 2 == 1)
{
    return (powerDC(n, e/2) * powerDC(n, e/2) * n);
}
else
{
    return (powerDC(n, e/2) * powerDC(n, e/2));
}
```

3. In the `powerBF()` method, parameters are used to pass the base number and its exponent, even though the `Power` class already contains attributes for these values (`baseNumber` and `exponent` atribute). Do you think it is still relevant for the method to have parameters? Could the method be implemented without parameters instead? If so, how would the `powerBF()` method be structured without parameters?

   The method is still relevant to have parameters, it can be implemented without parameter too. This is the powerBF() method without using parameters:

```
int powerBF()
{
    int result = 1;
    for (int i = 0; i < exponent; i++)
    {
        result = result * baseNumber;
    }
    return result;
}
```

4. Summarize how the `powerBF()` and `powerDC()` methods work!
   powerBF() uses a loop to multiply the base number by itself repeatedly & powerDC() uses recursion to break the problem into smaller subproblems.

5.4 Calculating Array Sum Using Brute Force and Divide and Conquer Algorithms

In this experiment, we will practice how the divide, conquer, and combine processes are applied in a case study of calculating a company's profit over several months.

5.4.1. Experiment Steps

1. In the **week5** package, create a new class named **`Sum`**. Add the parametrized constructor as well.

```
double profits[];

Sum(int el){
    profits = new double[el];
}
```

2. Add `totalBF()` method which will calculate the total value of the array using an iterative approach.

```
double totalBF(){
    double total=0;
    for(int i=0;i<profits.length;i++){
        total = total+profits[i];
    }
    return total;
}
```

3. Add `totalDC()` method that will calculate the total value of the array using Divide and Conquer

```
double totalDC(double arr[], int l, int r){
    if(l==r){
        return arr[l];
    }

    int mid = (l+r)/2;
    double lsum = totalDC(arr, l, mid);
    double rsum = totalDC(arr, mid+1, r);
    return lsum+rsum;
}
```

4. Create a new class named `SumMain`. This class should contain the `main` method, where users can specify the number of months for which the profit will be calculated. Additionally, instantiate an object within this class to access attributes and methods from the `Sum` class.

```
Scanner input = new Scanner(System.in);
System.out.print(s:"Input element number: ");
int element = input.nextInt();
```

5. Create `Sum` object and assign the profit value in each array element

```
Sum sm = new Sum(element);
for(int i=0;i<element;i++){
    System.out.print("Masukkan keuntungan ke-"+(i+1)+": ");
    sm.profits[i] = input.nextDouble();
}
```

6. Call both oof `totalBF()` and `totalDC()` methods!

```
System.out.println("Profit total using BF: "+sm.totalBF());
System.out.println("Profit total using DC: "+sm.totalDC(sm.profits,l:0,element-1));
```

5.4.2. Verification of Experiment Results

Verify the results and it must be matched with the following!

```
Input element number: 5
Input profit #1: 10
Input profit #2: 20
Input profit #3: 30
Input profit #4: 40
Input profit #5: 50
Profit total using BF: 150.0
Profit total using DC: 150.0
```

```java
package com.jobsheet4;

import java.util.Scanner;

public class BruteForceDivideConquer3
{
    Run | Debug | Run main | Debug main
    public static void main(String[] args)
    {
        Scanner input = new Scanner(System.in);

        System.out.print(s: "Input element number: ");
        int element = input.nextInt();

        Sum sm = new Sum(element);
        for (int i = 0; i < element; i++)
        {
            System.out.print("Input profit " + (i + 1) + ": ");
            sm.profits[i] = input.nextDouble();
        }

        System.out.println("Profit total using BF: " + sm.totalBF());
        System.out.println("Profit total using DC: " + sm.totalDC(sm.profits, l: 0, element - 1));

        input.close();
    }
}

class Sum
{
    double profits[];

    Sum(int el)
    {
        profits = new double[el];
    }

    double totalBF()
    {
        double total = 0;
        for (int i = 0; i < profits.length; i++)
        {
            total += profits[i];
        }
        return total;
    }

    double totalDC(double arr[], int l, int r)
    {
        if (l == r)
        {
            return arr[l];
        }

        int mid = (l + r) / 2;
        double lsum = totalDC(arr, l, mid);
        double rsum = totalDC(arr, mid + 1, r);
        return lsum + rsum;
    }

}
```

```
Input element number: 5
Input profit 1: 10
Input profit 2: 20
Input profit 3: 30
Input profit 4: 40
Input profit 5: 50
Profit total using BF: 150.0
Profit total using DC: 150.0
```

5.4.3. Questions

1. Why is `mid` variable needed in `totalDC()` method?

   The mid variable allows the algorithm to recursively compute sums of smaller segments and then combine them, making the method efficient and structured.

2. Explain the following statements in `totalDC()` method?

```
double lsum = totalDC(arr, l, mid);
double rsum = totalDC(arr, mid+1, r);
```

lsum is recursively calculates the sum of the left half of the array, from index l up to mid & rsum is recursively calculates the sum of the right half of the array, from index mid+1 up to r.

3. Why is it necessary to sum the results of `lsum` and `rsum` as shown below??

```
return lsum+rsum;
```

The summation of lsum and rsum is crucial because it reconstructs the full solution from the smaller subproblems.

4. What is the base case of `totalDC()` method?

```
if (l == r)
{
    return arr[l];
}
```

5. Draw a conclusion about how `totalDC()` works!

totalDC() splits the array into smaller parts, solves each part recursively, and then combines the results to produce the total sum.

5.5. Assignments

A university has a list of student grades with data as shown in the table below.

Name	Student ID (NIM)	Year of Admission	Midterm Score (UTS)	Final Score (UAS)
Ahmad	220101001	2022	78	82
Budi	220101002	2022	85	88
Cindy	220101003	2021	90	87
Dian	220101004	2021	76	79
Eko	220101005	2023	92	95
Fajar	220101006	2020	88	85
Gina	220101007	2023	80	83
Hadi	220101008	2020	82	84

a) Find the highest Midterm Score (UTS) using the Divide and Conquer approach.

b) Find the lowest Midterm Score (UTS) using the Divide and Conquer approach.

c) Calculate the average Final Score (UAS) of all students using the Brute Force approach.

```java
package com.jobsheet4;

public class Assigment
{
    Run | Debug | Run main | Debug main
    public static void main(String[] args)
    {
        System.out.println(x: "=== STUDENT SCORE ANALYSIS ===\n");

        StudentScores student = new StudentScores();

        int Highest = student.Highest (student.uts, left: 0, student.uts.length - 1);
        System.out.println(x: "a) Highest Midterm Score (UTS) - Divide & Conquer");
        System.out.println("   Student : " + student.names[Highest]);
        System.out.println("   NIM     : " + student.nim[Highest]);
        System.out.println("   Score   : " + student.uts[Highest]);
        System.out.println();

        int Lowest = student.Lowest (student.uts, left: 0, student.uts.length - 1);
        System.out.println(x: "b) Lowest Midterm Score (UTS) - Divide & Conquer");
        System.out.println("   Student : " + student.names[Lowest]);
        System.out.println("   NIM     : " + student.nim[Lowest]);
        System.out.println("   Score   : " + student.uts[Lowest]);
        System.out.println();

        float avg = student.Average(student.uas);
        int sum = 0;
        for (int s : student.uas) sum += s;
        System.out.println(x: "c) Average Final Score (UAS) - Brute Force");
        System.out.printf (format: "   Sum     : %d%n", sum);
        System.out.printf (format: "   Count   : %d students%n", student.uas.length);
        System.out.printf (format: "   Average : %.3f%n", avg);
    }
}
```

```java
class StudentScores
{
    String[] names = {"Ahmad", "Budi", "Cindy", "Dian", "Eko", "Fajar", "Gina", "Hadi"};
    String[] nim    = {"220101001","220101002","220101003","220101004", "220101005","220101006","220101007","22010100
    int[] uts = {78, 85, 90, 76, 92, 88, 80, 82};
    int[] uas = {82, 88, 87, 79, 95, 85, 83, 84};

    int Highest (int[] arr, int left, int right)
    {
        if (left == right) return left;

        int mid = (left + right) / 2;
        int leftMax  = Highest (arr, left, mid);
        int rightMax = Highest (arr, mid + 1, right);

        return arr[leftMax] >= arr[rightMax] ? leftMax : rightMax;
    }

    int Lowest (int[] arr, int left, int right)
    {
        if (left == right) return left;

        int mid = (left + right) / 2;
        int leftMin  = Lowest (arr, left, mid);
        int rightMin = Lowest (arr, mid + 1, right);

        return arr[leftMin] <= arr[rightMin] ? leftMin : rightMin;
    }

    float Average(int[] arr)
    {
        int total = 0;
        for (int i = 0; i < arr.length; i++)
        {
            total += arr[i];
        }
        return (float) total / arr.length;
    }
}
```

```
=== STUDENT SCORE ANALYSIS ===

a) Highest Midterm Score (UTS) - Divide & Conquer
   Student : Eko
   NIM     : 220101005
   Score   : 92

b) Lowest Midterm Score (UTS) - Divide & Conquer
   Student : Dian
   NIM     : 220101004
   Score   : 76

c) Average Final Score (UAS) - Brute Force
   Sum     : 683
   Count   : 8 students
   Average : 85,375
```