arXiv:2606.03695v1 [cs.CL] 2 Jun 2026

Don't Forget Your Embeddings: Robust Knowledge Erasure via Precise Editing of Embeddings

Clara Haya Suslik **Or Shafran** **Mor Geva**
Blavatnik School of Computer Science and AI, Tel Aviv University
{clarasuslik@mail, ordavids1@mail, morgeva@tauex}.tau.ac.il

Abstract

As language models are increasingly deployed in real-world applications, the ability to erase specific knowledge from them becomes critical for safety and compliance. Prominent methods seek persistent removal by updating the model's parameters, yet the target knowledge often can be recovered through adversarial prompting or relearning. In this work, we hypothesize this limitation stems in part from existing methods overlooking the embedding layer. To address this, we introduce EMBedding ERasure (EMBER), a plug-n-play erasure module that leverages Sparse Matrix Factorization for precise erasure of concept-related features from token embeddings. Through comprehensive evaluations across diverse concepts on Gemma-2-2B-it and Llama-3.1-8B-Instruct, we find that augmenting existing methods with EMBER consistently improves erasure efficacy and specificity across task formats, with minimal coherence loss. Moreover, it dramatically improves robustness to relearning, reducing regained accuracy by up to 50%, limiting it to 35% on Llama compared to 70%–76% for prior methods. Further analysis shows that the coherence cost is localized, affecting only a small set of concept-exclusive tokens. Our work establishes that precise embedding-level intervention is necessary for robust concept erasure, and demonstrates that existing methods can benefit from such augmentation.[1]

1 Introduction

The widespread adoption of language models (LMs) has driven growing interest in methods for erasing certain knowledge from them, in order to control their outputs and improve safety (Yao and Xu, 2024; Liu et al., 2024, 2025). A promising approach to achieving this is *persistent knowledge erasure*, which aims to eliminate the target knowledge by modifying the model's weights (Li et al., 2024; Gur-Arieh et al., 2025b; Ashuach et al., 2026).




Figure 1: Existing concept erasure methods primarily target MLP layers, overlooking knowledge encoded in token embeddings. We propose EMBER as a precise editing module for token embeddings. Combining EMBER with existing methods improves erasure quality while boosting robustness against relearning.

However, increasing evidence suggests these methods do not fully remove the target knowledge. Methods leave traces of the target knowledge which then can be recovered via prompting or adversarial training (Deeb and Roger, 2024; Zhang et al., 2024b; Hong et al., 2025; Fan et al., 2025), and often remain form-dependent (Ye et al., 2025), with unlearning in one format failing to generalize to others (e.g., failing to generate the answer while correctly selecting it from multiple choices).

In this work, we hypothesize that these failures stem in part from existing techniques overlooking parameters beyond the MLP layers. Specifically, while MLP layers have been shown to play a key role in knowledge recall (Geva et al., 2021; Dai et al., 2022), LMs also contain a nontrivial portion of their knowledge in their token embeddings (Geva et al., 2023; Wen-Yi and Mimno, 2023; Zhong and Andreas, 2024; Grindrod and Grindrod, 2025). This overlooked source of knowledge could make it easier for the model to "relearn" the erased concept, and push erasure methods failing to ac-

[1] Our code is available at https://github.com/ClarSu/EMBER-Embedding-Erasure

count for it towards aggressive updates that reduce the model's utility.

To tackle this gap, we introduce **EMBedding ERasure (EMBER**; Figure 1), a precise erasure method that operates on the embedding matrix, designed to augment MLP-focused methods to achieve robust erasure. We follow the framework by Gur-Arieh et al. (2025b), which edits LM weights by disentangling them into sparse interpretable features. Unlike recent methods that disentangle and remove features from MLPs using sparse autoencoders (SAEs) (Gur-Arieh et al., 2025b; Ashuach et al., 2026), here we leverage a disentangler based on matrix factorization (MF) and apply it to the embedding matrix. Specifically, EMBER localizes embedding features that are shared by small sets of tokens. Features related to the target concept are then subtracted from the embeddings of those tokens, removing the concept-related component while leaving the rest of each embedding intact.

We assess the effectiveness of EMBER through comprehensive experiments on Gemma-2-2B-it (Team et al., 2024) and Llama-3.1-8B-Instruct (Grattafiori et al., 2024) with diverse concepts, testing leading erasure methods, alongside an MF-based MLP erasure variant, with and without EMBER. Erasure performance is evaluated along multiple axes of efficacy, specificity, generation coherence (Taori et al., 2023), and robustness to relearning (Deeb and Roger, 2024). Efficacy and specificity are evaluated using multiple-choice questions, with additional evaluation of generalization to open-ended question answering.

Our results show that augmenting existing erasure methods with EMBER consistently improves their performance across evaluations, with only a marginal decrease in model coherence. More importantly, ensembling yields significant gains in erasure robustness, decreasing the relearning accuracies of RMU (Li et al., 2024) and CRISP (Ashuach et al., 2026) by 31%–33% on Llama and 16%–24% on Gemma. Our full MF-based method further reduces relearning accuracy on Llama to 35%, roughly half of 70%–76% for prior methods.

In addition, EMBER substantially outperforms baselines that edit the same token embeddings via noise injection and mean patching, confirming that the improvements come from EMBER's Sparse MF-guided edits, rather than arbitrary perturbations. Moreover, although hyperparameters were tuned on multiple-choice evaluations, the erasure gains are preserved in open-ended question answering, suggesting that EMBER edits generalize across input formats.

Finally, we analyze the effect of EMBER on generation quality for prompts containing the edited tokens in non-concept contexts. We find that disruption is highly localized: EMBER modifies at most 0.14% of the vocabulary per concept, and coherence degradation concentrates mainly on concept-exclusive tokens, demonstrating that EMBER's edits are precise and concept-driven.

To conclude, our work provides the first empirical study of the role of the embedding layer in concept erasure, identifying it as a critical bottleneck. We tackle this gap with EMBER, a localize-then-edit method that uses sparse matrix factorization for precise erasure in embedding space. Through comprehensive experiments, we show that ensembling EMBER with existing methods moderately improves erasure efficacy and specificity, while dramatically boosting robustness to relearning, reducing regained accuracy by up to 33%. These gains are preserved, though less pronounced, in open-ended evaluation, suggesting that EMBER targets conceptual knowledge rather than format-specific shortcuts. Overall, our findings show that precise updates to the embedding matrix are fundamental to achieving robust concept erasure, shifting the focus beyond existing MLP-focused interventions.

2 Preliminaries and Notation

We focus on autoregressive transformer-based LMs (Vaswani et al., 2017), assuming a model with hidden dimension d, MLP inner-dimension d_a, vocabulary $\mathcal{V}$, and embedding matrix $E \in \mathbb{R}^{|\mathcal{V}| \times d}$. We denote by $\mathbf{e}_t \in \mathbb{R}^d$ the row of E corresponding to the embedding of a token $t \in \mathcal{V}$.

Concept Erasure in Language Models We follow the common problem setup of concept erasure (e.g., Eldan and Russinovich, 2023; Li et al., 2024; Gandikota et al., 2026; Gur-Arieh et al., 2025b; Ashuach et al., 2026): Given a model $\mathcal{M}$ and a target concept C (e.g., Harry Potter), we aim to perform a *persistent* and *robust* update to the model parameters such that $\mathcal{M}$ no longer reliably generates knowledge about C, without degrading other knowledge or capabilities. Here, persistent refers to a weight modification (as opposed to inference-time interventions), and robust refers to resistance to adversarial recovery, such as relearning or jailbreak attacks. Given a set of questions about C, our

goal is to update the parameters of $\mathcal{M}$ to produce an erased model $\mathcal{M}'$ that achieves chance-level accuracy on this set while maintaining $\mathcal{M}$'s performance on other concepts and tasks. To this end, we assume access to $\mathcal{S}_C$, a *target set* of sentences containing information on C, and $\mathcal{S}_N$, a *neutral set* of sentences representing a general distribution unrelated to C. These sets serve as the primary data for the erasure procedure.

Matrix Factorization (MF) Matrix factorization (MF) represents high-dimensional data through a set of shared latent factors and example-specific coefficients. Given a data matrix $A \in \mathbb{R}^{d \times n}$ with n activation or embedding vectors as columns, and a chosen number of factors k , MF factorizes A as

$$A \approx ZY, \tag{1}$$

where $Z \in \mathbb{R}^{d \times k}$ is a *factor dictionary* and $Y \in \mathbb{R}^{k \times n}$ is a *coefficient matrix*. Each column $\mathbf{z}_i \in \mathbb{R}^d$ of Z defines a reusable direction in the original representation space, while $Y_{i,j}$ specifies the contribution of factor $\mathbf{z}_i$ to the j-th example. Thus, each activation or embedding vector is represented as a combination of shared directions. We next describe how we use MF to find features[2] in embedding space for concept erasure.

3 EMBER

To move beyond MLP-only erasure, we propose EMBER, a method for precise editing of model embeddings. EMBER follows a localize-then-edit approach and involves three stages of (1) decomposing token embeddings into fine-grained features (§3.1), (2) identifying features that correspond to the target concept (§3.2), and (3) erasing these features from the embeddings of a small set of concept-related tokens (§3.3).

3.1 Finding Embedding Features with Sparse Matrix Factorization

Representation-learning methods often encourage interpretable factors through sparsity, which pressures latent factors to correspond to more localized and disentangled features (Hoyer, 2004; Makhzani and Frey, 2014; Bricken et al., 2023; Huben et al., 2024; Gao et al., 2025; Shafran et al., 2026). Following this line of work, we impose sparsity directly on the factor coefficients (i.e., Y in Eq. 1) using a hard winner-takes-all (WTA) constraint, keeping only the 1% token coefficients with the largest magnitudes per factor and setting the rest to zero. This turns the factorization into a sparse low-rank approximation problem.

Unlike unconstrained low-rank factorization, which admits a closed-form solution via truncated SVD, the sparsity constraint makes the joint optimization non-convex. We therefore optimize the factors using alternating least squares, iteratively solving for one factor while holding the other fixed and intermittently applying the WTA constraint to the coefficient matrix Y. In this paper, we refer to this method as **Sparse Matrix Factorization (Sparse MF)**. For the exact algorithm, see §A.1.

For a concept C, we start by defining the set of unique tokens $\mathcal{V}^* \subset \mathcal{V}$ that appear in $\mathcal{S}_C \cup \mathcal{S}_N$, and denoting the part of E corresponding to the embeddings of $\mathcal{V}^*$ as $E_{\mathcal{V}^*} \in \mathbb{R}^{|\mathcal{V}^*| \times d}$. We apply Sparse MF only to $E_{\mathcal{V}^*}$ rather than the full E, both for computational efficiency and to focus the factorization on embeddings related to C. Intuitively, the embeddings of semantically related tokens (e.g., `Harry`, `Hogwarts`, `wand`) are expected to have shared features (Mikolov et al., 2013). Including tokens from $\mathcal{S}_N$ allows us to later separate such concept-specific features from general features. Thus, factorizing $E_{\mathcal{V}^*}^\top$ yields[3]

$$E_{\mathcal{V}^*}^\top \approx ZY, \tag{2}$$

with $Z \in \mathbb{R}^{d \times k}$ and $Y \in \mathbb{R}^{k \times |\mathcal{V}^*|}$. The columns of Z are directions in the embedding space, which we refer to as **embedding features**. The entry $Y_{i,j}$ represents the contribution of feature $\mathbf{z}_i$ to the reconstruction of the embedding of token j. Applying the sparsity operator to the rows of Y yields embedding features $\mathbf{z}_i$ that correspond to a small subset of the tokens (the non-zero entries of $Y_{i,:}$) that share the direction $\mathbf{z}_i$ in embedding space.

3.2 Identifying Concept-Related Features

The procedure above recovers k embedding features, each corresponding to a shared direction across embeddings of $\mathcal{V}^*$. These features include both concept-specific features (arising from informative tokens in $\mathcal{S}_C$) and general features that are not specific to C. To select the concept-specific subset, we score features by the attribution of their non-zero token entries in Y and then verify the resulting candidates with an LLM-as-judge.

[2] By *features* we refer to factors associated with a concept.

[3] We reuse the notation Z and Y from Eq.1, as the factors play the same conceptual role.

For each token $t \in \mathcal{V}^*$ we assign a label $\ell_t \in \{\texttt{concept}, \texttt{neutral}, \texttt{both}\}$ based on whether it appears in $\mathcal{S}_C$, $\mathcal{S}_N$, or both. Let $\mathcal{T}_C := \{t \in \mathcal{V}^* : \ell_t = \texttt{concept}\}$ and $\mathcal{T}_N := \{t \in \mathcal{V}^* : \ell_t = \texttt{neutral}\}$ be the sets of concept- and neutral-labeled tokens. For each feature $\mathbf{z}_i$, we compute a mass-ratio statistic over the coefficient matrix Y:

$$\rho_i = \frac{\frac{1}{|\mathcal{T}_C|}\sum_{t\in\mathcal{T}_C}|Y_{i,t}|}{\frac{1}{|\mathcal{T}_N|}\sum_{t\in\mathcal{T}_N}|Y_{i,t}|}. \tag{3}$$

A high ρ_i indicates that $\mathbf{z}_i$ is predominantly associated with concept-specific tokens. We keep only features with mass-ratio greater than a threshold τ. We further filter the remaining features using an LLM that checks whether the tokens with non-zero entries in $Y_{i,:}$ match C (for more details see §A.3). This process yields the final set of concept-related features $\mathcal{F}_C$ for erasure.

3.3 Erasing Concept-Related Features

We now turn to removing the contribution of concept-related features $\mathcal{F}_C$ from $E_{\mathcal{V}^*}$. Notably, the factorization of $E_{\mathcal{V}^*}$ (Eq. 2) explicitly decomposes each token embedding into a sum of feature contributions, thus allowing us to subtract only the concept-related part. For every token $t \in \mathcal{V}^*$, the factorization gives:

$$\mathbf{e}_t = ZY_{:,t} + \boldsymbol{\varepsilon}_t = \sum_{i=1}^{k} Y_{i,t}\,\mathbf{z}_i + \boldsymbol{\varepsilon}_t, \tag{4}$$

where $\boldsymbol{\varepsilon}_t = \mathbf{e}_t - ZY_{:,t}$ is the reconstruction error and $Y_{i,t}\mathbf{z}_i$ is the contribution of feature $\mathbf{z}_i$ to $\mathbf{e}_t$. This sum can be split into a concept-related part and the rest:

$$\mathbf{e}_t = \sum_{i\in\mathcal{F}_C} Y_{i,t}\,\mathbf{z}_i \;+\; \sum_{i\notin\mathcal{F}_C} Y_{i,t}\,\mathbf{z}_i \;+\; \boldsymbol{\varepsilon}_t. \tag{5}$$

To erase the target concept from $\mathbf{e}_t$, we reconstruct it without the contributions of concept-related features:

$$\mathbf{e}_t \leftarrow \mathbf{e}_t - \delta \sum_{i\in\mathcal{F}_C} Y_{i,t}\,\mathbf{z}_i, \tag{6}$$

where $\delta \geq 0$ is a hyperparameter controlling erasure strength; $\delta = 1$ subtracts the exact concept contribution recovered by the factorization, while $\delta > 1$ over-subtracts which we find to often improve erasure in practice (see §C.3). We apply this edit only to tokens $t \in \mathcal{T}_C$ which are reconstructed with at least one concept-specific feature, i.e., where $Y_{i,t} \neq 0$ for at least one $\mathbf{z}_i \in \mathcal{F}_C$; all other embeddings remain unchanged.

4 Experiments

In this section, we evaluate the role of token embeddings in concept erasure and assess the effectiveness of EMBER. First, we test whether embedding-level edits add value beyond MLP-based erasure methods by augmenting leading erasure methods with EMBER and comparing the ensembled configurations to their original counterparts. Second, we examine whether the gains of EMBER stem from its Sparse MF-guided edits rather than from arbitrary embedding perturbations. We do so by comparing EMBER against simple embedding-editing baselines that perturb the same token embeddings.

4.1 Experimental Setup

Our experiments assess concept erasure across multiple metrics and target concepts on two models: Gemma-2-2B-it (Team et al., 2024) and Llama-3.1-8B-Instruct (Grattafiori et al., 2024).

Evaluation Metrics We evaluate models post-erasure across four axes:

- **Efficacy**: We measure the model's accuracy in answering questions about C, termed **concept accuracy** (↓). A successful method drives this score toward 0.25 chance.
- **Specificity**: We use two evaluations to assess whether erasure damages knowledge beyond the target concept: **similar-domain accuracy** (↑), measured on adjacent, non-target topics, and accuracy on the **MMLU** (↑) benchmark (Hendrycks et al., 2021).
- **Coherency**: We use **AlpacaEval** (↑) (Taori et al., 2023) to evaluate if the model remains coherent after erasure, reporting both instruction-following and fluency scores.
- **Robustness**: To test whether erasure persists under adversarial pressure, we fine-tune $\mathcal{M}'$ on a small set of concept-related paragraphs and measure the resulting concept accuracy, termed **relearning accuracy** (↓) (Deeb and Roger, 2024). Implementation details are in §B and §C.4.

We summarize the efficacy-utility tradeoff with a harmonic-mean score that aggregates inverted concept accuracy, similar-domain accuracy, MMLU accuracy, and both AlpacaEval scores, each normalized by the corresponding pre-erasure score of $\mathcal{M}$ to make them comparable across concepts and settings. Exact normalization formulas are in §C.1.

Open-Ended (OE) vs. Multiple-Choice (MC) We evaluate erasure under two question-answering formats. In MC question answering, the model selects an answer from a fixed set of 4 options; this measures whether the model can still *recognize* concept-related content among distractors. In OE question answering, the model needs to generate a free-form answer that is judged for correctness; this measures whether the model can still *produce* concept-related content. Evaluating under both formats lets us separate suppression of generation from removal of underlying knowledge.

In practice, we find that MC is the more challenging setting; erasure methods achieve substantially lower concept accuracy in OE, even when tuned for MC. Therefore, for the main results we tune hyperparameters for MC. Since unlearning is often form-dependent (Ye et al., 2025), we also evaluate EMBER (tuned for MC) in the OE setup to test whether its gains transfer across formats. We also conduct the reverse experiment, tuning hyperparameters for OE and evaluating transfer to MC. Results for this experiment are provided in §E.

Concepts and Data We evaluate erasure on 18 concepts spanning diverse domains, including fictional works (e.g., Harry Potter), events (e.g., World War II), and safety- or age-sensitive topics (e.g., Cannabis, Pornography). This set includes 11 concepts used in prior works (Eldan and Russinovich, 2023; Gur-Arieh et al., 2025b; Hong et al., 2025), which we extend with an additional 7 concepts to cover a wider range of knowledge types.

For each concept C, we sample $n = 300$ sentences from concept-related Wikipedia pages to serve as $\mathcal{S}_C$, and another n sentences from English Wikipedia to create $\mathcal{S}_N$. For evaluation, we craft a set of 100 questions per concept and split them 50-50 for validation and test. For specificity evaluation, we also create questions on concepts from similar domains (e.g., asking about other famous fantasy novels when erasing Harry Potter). Each question is written in two formats: an open-ended version and a multiple-choice version. The full list of concepts and details on question construction are provided in §B.

4.2 Erasure Methods and Baselines

Erasure methods We evaluate persistent-erasure methods, all operate on MLP layers: RMU (Li et al., 2024), CRISP (Ashuach et al., 2026), and PISCES (Gur-Arieh et al., 2025b). **RMU** steers the model's internal representations of $\mathcal{S}_C$ toward random vectors while preserving the representations of $\mathcal{S}_N$. **CRISP** instead identifies SAE features that are strongly activated on $\mathcal{S}_C$ but not on $\mathcal{S}_N$, and fine-tunes the model to suppress these features on $\mathcal{S}_C$ while preserving them on $\mathcal{S}_N$. **PISCES** leverages SAE features for precise, targeted MLP edits without fine-tuning. In addition, we evaluate an MF-based erasure variant, denoted **SNMF**, which finds semi-nonnegative MF features (Shafran et al., 2026) from MLP activations and applies directional ablation (Arditi et al., 2024) to MLP weights across layers (see full description in §A.2). For all methods, hyperparameters are selected on the validation set using the harmonic-mean score, with **relearning accuracy** computed only on the final selected configuration. Full protocol details are in §C.

Ensembles For each erasure method, we test the method when applied in isolation and when ensembled with EMBER (denoted +EMBER). We also evaluated the optimizer modification proposed by Fan et al. (2025), which uses sharpness-aware minimization (**SAM**) during unlearning fine-tuning to encourage flatter, more relearning-resistant minima. However, consistent with the authors' findings, SAM is designed for fine-tuning-based methods that update all model parameters, and it did not produce improvements in our setting (see §D.1).

Embedding editing baselines To verify that EMBER performs meaningful edits beyond simple perturbations, we compare EMBER alone against two baselines that edit the same set of token embeddings: **Mean**, which replaces each edited token embedding with the mean embedding vector across the vocabulary; and **Noise**, which adds Gaussian noise to each embedding, with the per-token magnitude set by EMBER's edit on that token and a strength parameter σ tuned analogously to δ in EMBER (see §C), thereby isolating the contribution of the edit direction from its magnitude.

4.3 Results

Results are presented in Table 1 and Figure 2. We exclude PISCES from the main results as it targets output suppression in open-ended generation, leading to low MC performance; results are reported in §D.2.

Ensembling with EMBER improves the efficacy-utility tradeoff Augmenting existing MLP-based methods with EMBER improves erasure

	Gemma-2-2B-it						Llama-3.1-8B-Instruct					
	MC		OE				MC		OE			
Method	Con↓	Sim↑	Con↓	Sim↑	MM↑	Alp↑	Con↓	Sim↑	Con↓	Sim↑	MM↑	Alp↑
EMBER	**49.4**	86.4	**25.3**	77.1	53.7	1.96	**45.8**	85.4	**35.8**	71.9	63.6	1.91
Mean	62.8	**87.6**	29.6	**78.6**	54.2	1.96	69.6	88.4	40.9	74.0	63.9	1.92
Noise	62.2	**87.6**	30.7	78.4	**54.8**	**1.97**	76.9	**90.6**	47.4	**75.9**	**64.6**	**1.95**
SNMF	43.7	69.9	12.9	48.2	48.4	**1.96**	43.8	75.1	10.7	53.2	58.7	**1.95**
+ EMBER	37.7	77.8	9.7	59.6	51.0	1.95	29.1	76.4	6.7	56.1	60.4	1.92
CRISP	32.9	70.9	**2.1**	41.9	52.6	**1.96**	36.9	76.6	4.8	43.4	59.3	1.92
+ EMBER	**29.2**	**82.0**	10.1	**69.1**	**53.2**	1.94	26.9	79.2	10.8	56.0	60.4	1.91
RMU	43.4	72.4	7.3	46.0	50.3	1.95	22.8	78.0	**4.2**	44.9	**62.2**	**1.95**
+ EMBER	29.9	80.8	12.0	63.8	51.8	1.95	**22.2**	**81.6**	8.1	**56.4**	62.0	1.90
Baseline	73.3	89.2	52.3	81.9	54.2	1.95	84.4	92.4	67.1	79.3	65.0	1.96

Table 1: Evaluation results on Gemma-2-2B-it and Llama-3.1-8B-Instruct, showing concept accuracy (Con), similar-domain accuracy (Sim), MMLU performance (MM), and AlpacaEval average score (Alp). Concept and similar-domain accuracies are reported for multiple-choice (MC) and open-ended (OE) question answering. The top group contains embedding-only methods; the bottom group contains MLP-based methods, optionally combined with EMBER. **Bold+underline** = best within group. ↓↑ indicate whether lower/higher is better.




Figure 2: Robustness evaluation results, showing for each method its post-erasure concept QA accuracy (Unlearn) and accuracy after relearning (Relearn), averaged over 18 concepts. Lower values indicate more effective erasure; a smaller gap between Relearn and Unlearn bars reflects greater robustness to relearning.

in the MC setting, reducing concept accuracy by an average of 8.1 points across methods and models, with reductions reaching 14.7 points for SNMF on Llama. Similar-domain accuracy also improves consistently, with 7.9–11.1 points increase in Gemma and 1.3–3.6 in Llama. MMLU remains stable across configurations. These gains come at minimal coherence cost: AlpacaEval decreases by at most 0.05 point. In the OE setting, adding EMBER can slightly increase concept accuracy, yet the scores remain far below the unedited baseline in all cases. Similar-domain accuracy improves substantially in OE, with gains ranging from 11.4–27.2 points on Gemma and 2.9–12.6 points on Llama. Notably, SNMF+EMBER, our full MF-based pipeline, is competitive with CRISP and RMU individually, yet EMBER yields its largest gains when combined with them.

EMBER substantially enhances robustness to relearning Figure 2 presents the relearning evaluation results, showing the gap between post-erasure accuracy and post-relearning accuracy. Across all settings, augmenting with EMBER consistently reduces the accuracy recovered through relearning. On Gemma, adding EMBER reduces RMU's relearning accuracy from 56%→47%, and CRISP's from 55%→42%, a 16%-24% relative reduction. On Llama, relearning accuracy drops from 70%→47% for RMU, and from 76%→52% for CRISP. SNMF+EMBER recovers only 6 accuracy points via relearning on both models, the smallest gap among methods. This halves the best prior method's relearning accuracy on Llama (35% vs. 70%). Overall, these results suggest that localize-then-edit methods are inherently more resistant to relearning than fine-tuning-based approaches.

EMBER's gains stem from precise edits rather than arbitrary perturbations Considering the results in Table 1, EMBER achieves substantially lower concept accuracy than the embedding-editing baselines (e.g., 45.8% vs. 69.6–76.9% on Llama) while maintaining high specificity and coherence. This shows that effective erasure requires more than identifying the correct tokens: the edit must also

target the right direction. Baseline perturbations spread their norm across untargeted directions, preserving coherence but leaving much of the concept intact. EMBER instead removes the concept-specific component directly, yielding a targeted edit that achieves substantially stronger erasure.

5 Token-Level Coherence Analysis

A natural concern with EMBER is whether editing the embeddings of concept-related tokens affects generation when these tokens appear in contexts *unrelated* to the target concept. Namely, editing the token `Harry` when erasing Harry Potter should not hinder the model's ability to discuss Prince Harry. We expect that such degradation would correlate with the concept-exclusivity of the tokens edited: tokens like `Hogwarts` carry almost no meaning outside Harry Potter, so removing their concept-specific component strips most of their semantic content. Conversely, tokens like `Harry` retain broad meaning across many contexts, therefore their edits should be far less disruptive.

To test this, for each edited token we use an LLM to construct a prompt with the token in a context neutral to the target concept. Then, we query the pre- and post-erasure models with that prompt and compare their responses. We categorize response changes with an LLM judge into three labels: *consistent* (coherent and factually consistent), *semantic shift* (coherent but factually divergent or off-topic) and *incoherent* (see prompt in §F.3).

Figure 3 shows the distributions of token TF-IDF scores for each label across all concepts and erasure methods. The results confirm our hypothesis: incoherent responses cluster at substantially higher TF-IDF scores than consistent ones, showing that coherence degradation is more likely for concept-specific tokens.

Table 2 shows example responses. After erasing Valentine's Day with SNMF+EMBER from Llama, its answer to a prompt with `rose`, a low-score token, is consistent. When asked about `romance`, a higher-score token, it generates a coherent response discussing "romance" as a genre, demonstrating semantic shift from the base response describing romance as an emotion. Prompting with the even higher-scored token `romantic` results in an incoherent response. The example of Prince Harry further illustrates EMBER's disentanglement: the erased Gemma model answers correctly when asked about Prince Harry, yet fails to recognize Harry Potter,




Figure 3: Distribution of TF-IDF scores (log scale) by response label. Incoherent responses (red) are concentrated at higher TF-IDF scores (more concept-specific) than consistent responses (green).

demonstrating that the edit targets the Harry Potter concept rather than the token `Harry` itself.

Critically, the same pattern (higher incoherence at higher TF-IDF scores) appears for standalone methods that do not edit embeddings at all, suggesting that coherence degradation is not solely a side-effect of EMBER's edits. Furthermore, EMBER modifies at most 31–86 tokens on Gemma and 22–174 on Llama; corresponding to at most 0.034% and 0.136% of the respective vocabularies. Even within that set, the affected tokens tend to be concept-exclusive. Therefore, coherence degradation is mostly localized and concept-specific.

6 Related Work

Machine Unlearning and Concept Erasure Most methods for unlearning in LMs optimize a forget-set objective while retaining performance on a retain set (Jang et al., 2023; Eldan and Russinovich, 2023; Yao and Xu, 2024; Zhang et al., 2024a; Li et al., 2024; Ashuach et al., 2026). A common limitation of these gradient-based methods is low specificity: broad parameter updates often harm model utility on unrelated tasks (Lynch et al., 2024; Sharkey et al., 2025), driving a persistent erasure–utility tradeoff (Blanco-Justicia et al., 2025). A parallel line of work takes a localize-then-edit approach, using causal analysis to identify knowledge-storing parameters and applying targeted closed-form weight updates (Meng et al., 2022, 2023; Gur-Arieh et al., 2025b). A deeper

Concept	Prompt	Response	Category
Valentine's Day	`Please describe the scent of a` **`rose`**`.`	*The scent of a* ***rose*** *is a complex and multi-faceted fragrance that can vary...*	*consistent*
	`How would you define` **`romance`**`?`	*In music,* ***romance*** *can refer to a style...*	*semantic shift*
	`Can you suggest a` **`romantic`** `movie for tonight?`	*Here are some classic and modern* ***romantic*** *movie... assistant...* (repetitive loop)	*incoherent*
Harry Potter	`Tell me about Prince` **`Harry`**	*Prince* ***Harry****, the Duke of Sussex, is...*	*consistent*
	`Who is the main character in` **`Harry`** `Potter?`	*Please provide me with the context! ...*	*semantic shift*

Table 2: Example responses after applying SNMF+EMBER to erase Valentine's Day in Llama and Harry Potter in Gemma. Edited tokens are marked in **bold**. Additional responses for other methods and concepts are in §F.4.

problem shared across both paradigms is *shallow unlearning*: the erased knowledge can be recovered through adversarial fine-tuning or different prompting (Deeb and Roger, 2024; Zhang et al., 2024b; Gong et al., 2025; Ye et al., 2025; Hong et al., 2025; Fan et al., 2025; Barez et al., 2025). EMBER addresses these limitations by extending erasure to the embedding layer, achieving substantially better relearning robustness and narrowing the tradeoff.

Matrix Factorization for Disentanglement Early MF work showed that decomposing representations into shared latent factors can recover parts-based structure in image data (Lee and Seung, 1999; Hoyer, 2004) with more recent work extending this to neural representations in vision-model activations (Collins et al., 2018; Zhang et al., 2021; Fel et al., 2023b,a). In LMs, factorization-based methods have similarly been used to analyze MLP and residual stream activations to localize features (Yun et al., 2021; Shafran et al., 2026). While previous works focused on disentanglement of hidden-state activations, we apply sparse MF to localize concept structure directly in the embedding matrix.

Knowledge Localization in LM Parameters Prior knowledge localization work has primarily focused on MLP layers (Geva et al., 2021; Dai et al., 2022; Meng et al., 2022). Yet, embeddings also encode substantial factual and semantic information (Geva et al., 2023; Zhong and Andreas, 2024), making the embedding matrix a natural but underexplored localization target. Beyond location, methods differ in granularity: while early work localized knowledge to individual neurons (Dai et al., 2022), more recent work shifts toward feature-level localization, using learned directions from SAEs (Bricken et al., 2023; Huben et al., 2024; Gur-Arieh et al., 2025b; Ashuach et al., 2026) or matrix factorization (Lee and Seung, 1999; DING et al., 2010; Shafran et al., 2026). We extend this feature-level view to the embedding matrix, applying MF directly to LM embeddings.

Embedding Edits Early work on word embeddings established that they encode rich semantic structure as linear directions (Mikolov et al., 2013; Pennington et al., 2014), motivating research on embedding debiasing (Bolukbasi et al., 2016; Ravfogel et al., 2020). In the context of embedding editing, He et al. (2025) showed that editing only the token embeddings of a text-to-image model can remove implicit biases with minimal collateral damage. Recently, Hou et al. (2026) applied embedding edits for class-level unlearning, but their method targets encoder-only classification models with no text generation capability. To our knowledge, EMBER is the first method to apply embedding edits for concept erasure in generative LLMs.

7 Conclusion

Despite progress in concept erasure, existing methods leave target knowledge recoverable through relearning. We show that this weakness stems in part from their MLP-centric focus, which overlooks concept knowledge encoded in token embeddings. We address this gap with EMBER, a concept-erasure method that uses Sparse Matrix Factorization to remove concept-related features through precise edits to the embeddings. Across 18 diverse concepts, augmenting existing erasure methods with EMBER improves efficacy and specificity with minimal coherence cost, while significantly improving robustness to relearning, reducing regained accuracy by up to 33% for existing methods, and up to 50% for our SNMF variant. We further show that the resulting token-level coherence cost is localized, concentrated in a small set of mostly concept-exclusive tokens. These findings establish targeted embedding-level editing as a key component of robust concept erasure, motivating a shift beyond the MLP-centric view of prior work.

Limitations

Language coverage Our token selection and editing pipeline relies on English Wikipedia data, so the edited tokens are English-specific. While language-specificity is a common limitation in concept erasure, it is particularly relevant for EMBER, which operates directly on token embeddings; erasure applied to English tokens would not suppress the same concept when accessed through tokens in other languages. Extending EMBER to multilingual settings, for example by drawing $\mathcal{S}_C$ from Wikipedia pages in multiple languages, is a natural direction for future work.

Editing the input embedding only We use EMBER to edit only the input embedding matrix, and not the unembedding matrix, as early experiments showed that even small modifications to U degrade generation quality severely, likely due to its direct role in next-token prediction. While editing E alone proves sufficient (and notably, our results on Gemma, which uses tied embeddings, show no evidence of concept recovery through standard relearning), a knowledgeable adversary could in principle bypass the edited E by copying the intact U back into the embedding layer, circumventing the erasure. Most modern LLMs use untied embeddings, where this concern does not apply.

Recovery of embedding features for certain concepts Our work assumes that knowledge is often encoded in token embeddings. While our results support this view, it could be that for some concepts (e.g., very narrow or rare concepts), the embeddings would not be an effective target for erasure. Analyzing this is an interesting direction for future work.

Noise in the feature selection process The set of tokens labeled as concept-specific is derived from corpus co-occurrence and may include semantically unrelated tokens, introducing noise into the editing process. Corpus-level measures such as TF-IDF scoring or auxiliary model-based filtering could improve token selection precision.

Ethical Considerations

EMBER is designed to enhance model safety by augmenting existing erasure methods, providing the fine-grained control needed to robustly remove dangerous, private, or copyrighted knowledge. Like all model editing techniques, our approach carries a dual-use risk: a highly effective, hard-to-reverse erasure method could maliciously be used to suppress legitimate information. Nevertheless, we argue that the necessity for robust safety mechanisms outweighs these risks. Notably, this work not only provides a practical alignment tool but also deepens our understanding of how language models store conceptual knowledge by highlighting the vital role of the embedding layer.

Acknowledgments

We thank Yoav Gur Arieh, Noam Steinmetz, Amit Elhelo, Asaf Avrahamy, and Daniela Gottesman for their valuable feedback, which helped shape and refine the direction of this research. We also thank Omri Wolf for suggesting the name EMBER. This research was supported in part by the Academic Research Program at Google, Len Blavatnik and the Blavatnik Family Foundation, the Israel Science Foundation grant 1083/24, and a grant from Coefficient Giving. Icons used in our figures were sourced from Flaticon and Magnific.

References

Andy Arditi, Oscar Obeso, Aaquib Syed, Daniel Paleka, Nina Panickssery, Wes Gurnee, and Neel Nanda. 2024. Refusal in language models is mediated by a single direction. *Advances in Neural Information Processing Systems*, 37:136037–136083.

Tomer Ashuach, Dana Arad, Aaron Mueller, Martin Tutek, and Yonatan Belinkov. 2026. CRISP: Persistent concept unlearning via sparse autoencoders. In *Proceedings of the 2026 Annual Meeting of the Association for Computational Linguistics (ACL)*. Association for Computational Linguistics. To appear.

Fazl Barez, Tingchen Fu, Ameya Prabhu, Stephen Casper, Amartya Sanyal, Adel Bibi, Aidan O'Gara, Robert Kirk, Ben Bucknall, Tim Fist, Luke Ong, Philip H. S. Torr, Kwok-Yan Lam, Robert Trager, David Krueger, Sören Mindermann, José Hernández-Orallo, Mor Geva, and Yarin Gal. 2025. Open problems in machine unlearning for ai safety. *ArXiv*, abs/2501.04952.

Alberto Blanco-Justicia, Najeeb Jebreel, Benet Manzanares-Salor, David Sánchez, Josep Domingo-Ferrer, Guillem Collell, and Kuan Eeik Tan. 2025. Digital forgetting in large language models: A survey of unlearning methods. *Artificial Intelligence Review*, 58(3):90.

Tolga Bolukbasi, Kai-Wei Chang, James Y Zou, Venkatesh Saligrama, and Adam T Kalai. 2016. Man is to computer programmer as woman is to homemaker? debiasing word embeddings. *Advances in neural information processing systems*, 29.

Trenton Bricken, Adly Templeton, Joshua Batson, Brian Chen, Adam Jermyn, Tom Conerly, Nick Turner, Cem Anil, Carson Denison, Amanda Askell, Robert Lasenby, Yifan Wu, Shauna Kravec, Nicholas Schiefer, Tim Maxwell, Nicholas Joseph, Zac Hatfield-Dodds, Alex Tamkin, Karina Nguyen, and 6 others. 2023. Towards monosemanticity: Decomposing language models with dictionary learning. *Transformer Circuits Thread*. Https://transformer-circuits.pub/2023/monosemantic-features/index.html.

Edo Collins, Radhakrishna Achanta, and Sabine Süsstrunk. 2018. Deep feature factorization for concept discovery. In *Computer Vision - ECCV 2018 - 15th European Conference, Munich, Germany, September 8-14, 2018, Proceedings, Part XIV*, Lecture Notes in Computer Science, pages 352–368. Springer.

Gheorghe Comanici, Eric Bieber, Mike Schaekermann, Ice Pasupat, Noveen Sachdeva, Inderjit Dhillon, Marcel Blistein, Ori Ram, Dan Zhang, Evan Rosen, Luke Marris, Sam Petulla, Colin Gaffney, Asaf Aharoni, Nathan Lintz, Tiago Cardal Pais, Henrik Jacobsson, Idan Szpektor, Nan-Jiang Jiang, and 3416 others. 2025. Gemini 2.5: Pushing the frontier with advanced reasoning, multimodality, long context, and next generation agentic capabilities. *Preprint*, arXiv:2507.06261.

Damai Dai, Li Dong, Yaru Hao, Zhifang Sui, Baobao Chang, and Furu Wei. 2022. Knowledge neurons in pretrained transformers. In *Proceedings of the 60th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 8493–8502, Dublin, Ireland. Association for Computational Linguistics.

Aghyad Deeb and Fabien Roger. 2024. Do unlearning methods remove information from language model weights? *arXiv preprint arXiv:2410.08827*.

Chris DING, TAO LI, and Michael I JORDAN. 2010. Convex and semi-nonnegative matrix factorizations. *IEEE transactions on pattern analysis and machine intelligence*, 32(1):45–55.

Ronen Eldan and Mark Russinovich. 2023. Who's harry potter? approximate unlearning in llms. *ArXiv*, abs/2310.02238.

Chongyu Fan, Jinghan Jia, Yihua Zhang, Anil Ramakrishna, Mingyi Hong, and Sijia Liu. 2025. Towards LLM unlearning resilient to relearning attacks: A sharpness-aware minimization perspective and beyond. In *Forty-second International Conference on Machine Learning*.

Thomas Fel, Victor Boutin, Louis Béthune, Rémi Cadène, Mazda Moayeri, Léo Andéol, Mathieu Chalvidal, and Thomas Serre. 2023a. A holistic approach to unifying automatic concept extraction and concept importance estimation. In *Advances in Neural Information Processing Systems 36: Annual Conference on Neural Information Processing Systems 2023, NeurIPS 2023, New Orleans, LA, USA, December 10 - 16, 2023*.

Thomas Fel, Agustin Martin Picard, Louis Béthune, Thibaut Boissin, David Vigouroux, Julien Colin, Rémi Cadène, and Thomas Serre. 2023b. CRAFT: concept recursive activation factorization for explainability. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition, CVPR 2023, Vancouver, BC, Canada, June 17-24, 2023*, pages 2711–2721. IEEE.

Rohit Gandikota, Sheridan Feucht, Samuel Marks, and David Bau. 2026. Erasing conceptual knowledge from language models. *Advances in Neural Information Processing Systems*, 38:60681–60713.

Leo Gao, Tom Dupré la Tour, Henk Tillman, Gabriel Goh, Rajan Troll, Alec Radford, Ilya Sutskever, Jan Leike, and Jeffrey Wu. 2025. Scaling and evaluating sparse autoencoders. In *The Thirteenth International Conference on Learning Representations, ICLR 2025, Singapore, April 24-28, 2025*. OpenReview.net.

Gemini Team, Rohan Anil, Sebastian Borgeaud, Jean-Baptiste Alayrac, Jiahui Yu, Radu Soricut, Johan Schalkwyk, Andrew M. Dai, and 1 others. 2023. Gemini: A family of highly capable multimodal models. *arXiv preprint arXiv:2312.11805*.

Mor Geva, Jasmijn Bastings, Katja Filippova, and Amir Globerson. 2023. Dissecting recall of factual associations in auto-regressive language models. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing*, pages 12216–12235.

Mor Geva, Roei Schuster, Jonathan Berant, and Omer Levy. 2021. Transformer feed-forward layers are key-value memories. In *Proceedings of the 2021 Conference on Empirical Methods in Natural Language Processing*, pages 5484–5495.

Yichen Gong, Delong Ran, Xinlei He, Tianshuo Cong, Anyu Wang, and Xiaoyun Wang. 2025. Safety misalignment against large language models. *Proceedings 2025 Network and Distributed System Security Symposium*.

Google DeepMind. 2026. Gemini (version 3.1 flash lite). `https://deepmind.google/technologies/gemini/`. Large language model.

Aaron Grattafiori, Abhimanyu Dubey, Abhinav Jauhri, Abhinav Pandey, Abhishek Kadian, Ahmad Al-Dahle, Aiesha Letman, Akhil Mathur, Alan Schelten, Alex Vaughan, Amy Yang, Angela Fan, Anirudh Goyal, Anthony Hartshorn, Aobo Yang, Archi Mitra, Archie Sravankumar, Artem Korenev, Arthur Hinsvark, and 542 others. 2024. The llama 3 herd of models. *Preprint*, arXiv:2407.21783.

Jumbly Grindrod and Peter Grindrod. 2025. Word meanings in transformer language models. *ArXiv*, abs/2508.12863.

Yoav Gur-Arieh, Roy Mayan, Chen Agassy, Atticus Geiger, and Mor Geva. 2025a. Enhancing automated interpretability with output-centric feature descriptions. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 5757–5778.

Yoav Gur-Arieh, Clara Haya Suslik, Yihuai Hong, Fazl Barez, and Mor Geva. 2025b. Precise in-parameter concept erasure in large language models. In *Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing*, pages 18986–19006, Suzhou, China. Association for Computational Linguistics.

Feng He, Chao Zhang, and Zhixue Zhao. 2025. Minimal, local, and robust: Embedding-only edits for implicit bias in t2i models. In *Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing*, pages 15385–15403.

Dan Hendrycks, Collin Burns, Steven Basart, Andy Zou, Mantas Mazeika, Dawn Song, and Jacob Steinhardt. 2021. Measuring massive multitask language understanding. In *9th International Conference on Learning Representations, ICLR 2021, Virtual Event, Austria, May 3-7, 2021*. OpenReview.net.

Yihuai Hong, Lei Yu, Haiqin Yang, Shauli Ravfogel, and Mor Geva. 2025. Intrinsic test of unlearning using parametric knowledge traces. In *Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing*, pages 19513–19535, Suzhou, China. Association for Computational Linguistics.

Iyad Ait Hou, Shrenik Borad, Harsh Sharma, Pooja Srinivasan, Rebecca Hwa, and Aya Zirikly. 2026. Parameter-efficient token embedding editing for clinical class-level unlearning. *arXiv preprint arXiv:2603.19302*.

Patrik O. Hoyer. 2004. Non-negative matrix factorization with sparseness constraints. *J. Mach. Learn. Res.*, 5:1457–1469.

Robert Huben, Hoagy Cunningham, Logan Riggs Smith, Aidan Ewart, and Lee Sharkey. 2024. Sparse autoencoders find highly interpretable features in language models. In *The Twelfth International Conference on Learning Representations*.

Joel Jang, Dongkeun Yoon, Sohee Yang, Sungmin Cha, Moontae Lee, Lajanugen Logeswaran, and Minjoon Seo. 2023. Knowledge unlearning for mitigating privacy risks in language models. In *Proceedings of the 61st Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 14389–14408.

Daniel D Lee and H Sebastian Seung. 1999. Learning the parts of objects by non-negative matrix factorization. *nature*, 401(6755):788–791.

Quentin Lhoest, Albert Villanova del Moral, Yacine Jernite, Abhishek Thakur, Patrick von Platen, Suraj Patil, Julien Chaumond, Mariama Drame, Julien Plu, Lewis Tunstall, Joe Davison, Mario Šaško, Gunjan Chhablani, Bhavitvya Malik, Simon Brandeis, Teven Le Scao, Victor Sanh, Canwen Xu, Nicolas Patry, and 13 others. 2021. Datasets: A community library for natural language processing. In *Proceedings of the 2021 Conference on Empirical Methods in Natural Language Processing: System Demonstrations*, pages 175–184, Online and Punta Cana, Dominican Republic. Association for Computational Linguistics.

Nathaniel Li, Alexander Pan, Anjali Gopal, Summer Yue, Daniel Berrios, Alice Gatti, Justin D Li, Ann-Kathrin Dombrowski, Shashwat Goel, Gabriel Mukobi, and 1 others. 2024. The wmdp benchmark: measuring and reducing malicious use with unlearning. In *Proceedings of the 41st International Conference on Machine Learning*, pages 28525–28550.

Sijia Liu, Yuanshun Yao, Jinghan Jia, Stephen Casper, Nathalie Baracaldo, Peter Hase, Yuguang Yao, Chris Yuhao Liu, Xiaojun Xu, Hang Li, and 1 others. 2025. Rethinking machine unlearning for large language models. *Nature Machine Intelligence*, 7(2):181–194.

Zheyuan Liu, Guangyao Dou, Zhaoxuan Tan, Yijun Tian, and Meng Jiang. 2024. Towards safer large language models through machine unlearning. In *Findings of the Association for Computational Linguistics: ACL 2024*, pages 1817–1829.

Aengus Lynch, Phillip Guo, Aidan Ewart, Stephen Casper, and Dylan Hadfield-Menell. 2024. Eight methods to evaluate robust unlearning in llms. *CoRR*, abs/2402.16835.

Alireza Makhzani and Brendan J. Frey. 2014. k-sparse autoencoders. In *2nd International Conference on Learning Representations, ICLR 2014, Banff, AB, Canada, April 14-16, 2014, Conference Track Proceedings*.

Kevin Meng, David Bau, Alex Andonian, and Yonatan Belinkov. 2022. Locating and editing factual associations in gpt. *Advances in neural information processing systems*, 35:17359–17372.

Kevin Meng, Arnab Sen Sharma, Alex J Andonian, Yonatan Belinkov, and David Bau. 2023. Mass-editing memory in a transformer. In *The Eleventh International Conference on Learning Representations*.

Tomas Mikolov, Wen-tau Yih, and Geoffrey Zweig. 2013. Linguistic regularities in continuous space word representations. In *Proceedings of the 2013 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies*, pages 746–751, Atlanta, Georgia. Association for Computational Linguistics.

Neel Nanda and Joseph Bloom. 2022. Transformerlens. `https://github.com/TransformerLensOrg/TransformerLens`.

OpenAI. 2026. ChatGPT (Version 5.2). https://chatgpt.com. Model runtime version: 5.2. Accessed: May 25, 2026.

Adam Paszke, Sam Gross, Francisco Massa, Adam Lerer, James Bradbury, Gregory Chanan, Trevor Killeen, Zeming Lin, Natalia Gimelshein, Luca Antiga, Alban Desmaison, Andreas Kopf, Edward Yang, Zachary DeVito, Martin Raison, Alykhan Tejani, Sasank Chilamkurthy, Benoit Steiner, Lu Fang, and 2 others. 2019. Pytorch: An imperative style, high-performance deep learning library. In *Advances in Neural Information Processing Systems 32*, pages 8024–8035. Curran Associates, Inc.

Jeffrey Pennington, Richard Socher, and Christopher Manning. 2014. GloVe: Global vectors for word representation. In *Proceedings of the 2014 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pages 1532–1543, Doha, Qatar. Association for Computational Linguistics.

Shauli Ravfogel, Yanai Elazar, Hila Gonen, Michael Twiton, and Yoav Goldberg. 2020. Null it out: Guarding protected attributes by iterative nullspace projection. In *Proceedings of the 58th annual meeting of the association for computational linguistics*, pages 7237–7256.

Or Shafran, Atticus Geiger, and Mor Geva. 2026. Constructing interpretable features from compositional neuron groups. In *Proceedings of the 64th Annual Meeting of the Association for Computational Linguistics (ACL 2026)*, Toronto, Canada. Association for Computational Linguistics.

Lee Sharkey, Bilal Chughtai, Joshua Batson, Jack Lindsey, Jeffrey Wu, Lucius Bushnaq, Nicholas Goldowsky-Dill, Stefan Heimersheim, Alejandro Ortega, Joseph Isaac Bloom, Stella Biderman, Adrià Garriga-Alonso, Arthur Conmy, Neel Nanda, Jessica Mary Rumbelow, Martin Wattenberg, Nandi Schoots, Joseph Miller, William Saunders, and 10 others. 2025. Open problems in mechanistic interpretability. *Transactions on Machine Learning Research*. Survey Certification.

Aaditya Singh, Adam Fry, Adam Perelman, Adam Tart, Adi Ganesh, Ahmed El-Kishky, Aidan McLaughlin, Aiden Low, AJ Ostrow, Akhila Ananthram, Akshay Nathan, Alan Luo, Alec Helyar, Aleksander Madry, Aleksandr Efremov, Aleksandra Spyra, Alex Baker-Whitcomb, Alex Beutel, Alex Karpenko, and 467 others. 2026. Openai gpt-5 system card. *Preprint*, arXiv:2601.03267.

Rohan Taori, Ishaan Gulrajani, Tianyi Zhang, Yann Dubois, Xuechen Li, Carlos Guestrin, Percy Liang, and Tatsunori B. Hashimoto. 2023. Stanford alpaca: An instruction-following llama model. https://github.com/tatsu-lab/stanford_alpaca.

Gemma Team, Morgane Riviere, Shreya Pathak, Pier Giuseppe Sessa, Cassidy Hardin, Surya Bhupatiraju, Léonard Hussenot, Thomas Mesnard, Bobak Shahriari, Alexandre Ramé, Johan Ferret, Peter Liu, Pouya Tafti, Abe Friesen, Michelle Casbon, Sabela Ramos, Ravin Kumar, Charline Le Lan, Sammy Jerome, and 179 others. 2024. Gemma 2: Improving open language models at a practical size. *Preprint*, arXiv:2408.00118.

Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Łukasz Kaiser, and Illia Polosukhin. 2017. Attention is all you need. *Advances in neural information processing systems*, 30.

Andrea W Wen-Yi and David Mimno. 2023. Hyperpolyglot LLMs: Cross-lingual interpretability in token embeddings. In *The 2023 Conference on Empirical Methods in Natural Language Processing*.

Wikimedia Foundation. 2024. Wikimedia downloads. https://dumps.wikimedia.org. English Wikipedia dump.

Thomas Wolf, Lysandre Debut, Victor Sanh, Julien Chaumond, Clement Delangue, Anthony Moi, Pierric Cistac, Tim Rault, Remi Louf, Morgan Funtowicz, Joe Davison, Sam Shleifer, Patrick von Platen, Clara Ma, Yacine Jernite, Julien Plu, Canwen Xu, Teven Le Scao, Sylvain Gugger, and 3 others. 2020. Transformers: State-of-the-art natural language processing. In *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing: System Demonstrations*, pages 38–45, Online. Association for Computational Linguistics.

Yuanshun Yao and Xiaojun Xu. 2024. Large language model unlearning. *Advances in Neural Information Processing Systems*, 37:105425–105475.

Xiaotian Ye, Mengqi Zhang, and Shu Wu. 2025. Llm unlearning should be form-independent. *ArXiv*, abs/2506.07795.

Zeyu Yun, Yubei Chen, Bruno A. Olshausen, and Yann LeCun. 2021. Transformer visualization via dictionary learning: contextualized embedding as a linear superposition of transformer factors. In *Proceedings of Deep Learning Inside Out: The 2nd Workshop on Knowledge Extraction and Integration for Deep Learning Architectures, DeeLIO@NAACL-HLT 2021, Online, June 10 2021*, pages 1–10. Association for Computational Linguistics.

Ruihan Zhang, Prashan Madumal, Tim Miller, Krista A. Ehinger, and Benjamin I. P. Rubinstein. 2021. Invertible concept-based explanations for cnn models with non-negative concept activation vectors. *Proceedings of the AAAI Conference on Artificial Intelligence*, 35(13):11682–11690.

Ruiqi Zhang, Licong Lin, Yu Bai, and Song Mei. 2024a. Negative preference optimization: From catastrophic collapse to effective unlearning. In *First Conference on Language Modeling*.

Zhiwei Zhang, Fali Wang, Xiaomin Li, Zongyu Wu, Xianfeng Tang, Hui Liu, Qi He, Wenpeng Yin, and

Suhang Wang. 2024b. Catastrophic failure of llm unlearning via quantization. *arXiv e-prints*, pages arXiv–2410.

Ziqian Zhong and Jacob Andreas. 2024. Algorithmic capabilities of random transformers. *Advances in Neural Information Processing Systems*, 37:104357–104382.

A Sparse Matrix Factorization

A.1 Algorithm and Hyperparameters

Given $A = E_{\mathcal{V}^*}^\top \in \mathbb{R}^{d\times|\mathcal{V}^*|}$, we seek $Z \in \mathbb{R}^{d\times k}$ and $Y \in \mathbb{R}^{k\times|\mathcal{V}^*|}$ minimizing the reconstruction loss

$$\|A - ZY\|_F^2, \tag{7}$$

where $\|\cdot\|_F$ denotes the Frobenius norm, subject to a WTA sparsity constraint on Y. Because the constraint makes the joint problem non-convex, we alternate between two closed-form least-squares updates, each with a small ridge term λI added inside the matrix inverse for numerical stability.

Factor update With Y fixed, the optimal Z is

$$Z \leftarrow AY^\top\big(YY^\top + \lambda I\big)^{-1}. \tag{8}$$

Coefficient update With Z fixed, the optimal Y is

$$Y \leftarrow \big(Z^\top Z + \lambda I\big)^{-1}Z^\top A. \tag{9}$$

After each coefficient update, the WTA operator is applied in place: for each row i of Y, all but the $\lceil s\cdot|\mathcal{V}^*|\rceil$ entries with the largest absolute values are set to zero, where $s \in (0, 1]$ is the sparsity fraction. Between the two updates, we rescale each row of Y to unit ℓ_2 norm and absorb the scale into the corresponding column of Z; this preserves the product ZY while keeping the two factors at comparable scales. Both Z and Y are initialized with i.i.d. $\mathcal{N}(0, 1)$ draws. Training stops early when the reconstruction error fails to decrease by more than 10^{-4} for 500 consecutive iterations, up to a maximum of $T = 20{,}000$ iterations.

Hyperparameters We fix sparsity $s = 0.01$ and ridge $\lambda = 10^{-4}$. We selected the number of factors k and the number of sentences $|\mathcal{S}_C| = |\mathcal{S}_N|$ used to construct $\mathcal{V}^*$ by inspecting the qualitative nature of the recovered features on the first 11 concepts using Gemma-2-2B-it, varying $k \in \{100, 200, 300\}$ and $|\mathcal{S}| \in \{100, 200, 300\}$. We found $k = 100$ and $|\mathcal{S}| = 300$ to yield semantically coherent, concept-specific features without over-fragmenting the vocabulary, and fixed these values for all concepts and subsequent experiments on Gemma-2-2B-it. For Llama-3.1-8B-Instruct, whose hidden dimension is approximately $1.8\times$ larger ($d = 4096$ vs. $d = 2304$), we scaled k proportionally to $k = 200$ and kept all other hyperparameters fixed.

A.2 SNMF for MLP Activations

The **SNMF** method complements the embedding edits of EMBER by applying Semi-NMF to the MLP layers. For each concept, we factorize the MLP activations on $\mathcal{S}_C \cup \mathcal{S}_N$, identify the concept-specific features, and erase them by editing the MLP weight matrices. This section describes the factorization algorithm; feature selection and weight editing are detailed in §A.3 and §A.4.

For each transformer layer l, we collect the post-nonlinearity MLP activations of all tokens in $\mathcal{S}_C \cup \mathcal{S}_N$ and arrange them column-wise into a matrix $A_l \in \mathbb{R}^{d_{\text{mlp}}\times n_{\text{tok}}}$, where d_{mlp} is the MLP inner dimension and n_{tok} is the total number of tokens. Following Shafran et al. (2026), we factorize each A_l as

$$A_l \approx ZY, \tag{10}$$

with $Z \in \mathbb{R}^{d_{\text{mlp}}\times k}$ unconstrained and $Y \in \mathbb{R}^{k\times n_{\text{tok}}}$ constrained to be non-negative entry-wise. The non-negativity of Y reflects the structure of MLP activations: each entry $Y_{i,j} \geq 0$ specifies how much feature i contributes to reconstructing the activation of token j, yielding a purely additive decomposition. As argued by Shafran et al. (2026), non-negativity constraints encourage parts-based representations that tend to be more interpretable.

Sparsity Unlike the embedding variant (§A.1), where sparsity is imposed on the coefficient matrix Y, here we impose WTA sparsity on the factor dictionary Z: after each Z update, for each column $\mathbf{z}_i$, all but the $\lceil s\cdot d_{\text{mlp}}\rceil$ entries with the largest absolute values are zeroed. This directly identifies the small subset of MLP neurons that define each feature.

Updates With Y fixed, Z is updated in closed form identically to §A.1, followed by WTA sparsification of each column:

$$Z \leftarrow AY^\top\big(YY^\top + \lambda I\big)^{-1}. \tag{11}$$

With Z fixed, $Y^\top$ is updated via the multiplicative rule of DING et al. (2010), which guarantees non-negativity is preserved at every iteration:

$$Y^\top \leftarrow Y^\top \odot \sqrt{\frac{\big[A^\top Z\big]_+ + Y^\top\big[Z^\top Z\big]_-}{\big[A^\top Z\big]_- + Y^\top\big[Z^\top Z\big]_+}}, \tag{12}$$

where $[M]_+ = \max(M, 0)$ and $[M]_- = \max(-M, 0)$ are the element-wise positive and negative parts, and $\odot$ is element-wise multiplication.

Between the two updates we apply the same row-wise rescaling of Y as in §A.1. Z is initialized with i.i.d. $\mathcal{N}(0, 1)$ draws; $Y^\top$ is initialized with i.i.d. $\mathcal{U}(0, 1)$ draws (strictly positive, since a zero entry would otherwise remain zero under the multiplicative update). Training uses the same early-stopping criterion as §A.1: improvement $< 10^{-4}$ for 500 consecutive iterations, up to $T = 20{,}000$ iterations.

Hyperparameters We use the same sparsity $s = 0.01$, ridge $\lambda = 10^{-4}$, number of sentences, and number of factors k as in §A.1. The factorization is run independently for each layer, yielding k feature directions per layer.

From MLP features to weight-space directions Each column $\mathbf{z}_i \in \mathbb{R}^{d_{\text{mlp}}}$ of Z is a sparse direction in the MLP's hidden space: its $\lceil s \cdot d_{\text{mlp}} \rceil$ non-zero entries identify the neurons that jointly define feature i (Shafran et al., 2026). We project $\mathbf{z}_i$ into the residual-stream dimension d via either MLP's input or output weights:

$$\mathbf{f}_i^{\text{in}} = W_{\text{in}}\, \mathbf{z}_i \ \in \mathbb{R}^d, \tag{13}$$

$$\mathbf{f}_i^{\text{out}} = W_{\text{out}}^\top \mathbf{z}_i \ \in \mathbb{R}^d, \tag{14}$$

where $W_{\text{in}} \in \mathbb{R}^{d \times d_{\text{mlp}}}$ and $W_{\text{out}} \in \mathbb{R}^{d_{\text{mlp}} \times d}$. $\mathbf{f}_i^{\text{in}}$ is the residual-stream direction that most activates the neurons of feature i, i.e., what the MLP "reads" to produce this feature. $\mathbf{f}_i^{\text{out}}$ is the residual-stream direction to which the neurons of feature i write when they fire, i.e., what the MLP "writes" for this feature.

A.3 Feature Selection

Ratio-based pre-filtering We score each feature i using the same mass-ratio statistic ρ_i defined in Eq. 3. For MLP features (§A.2), Y is the non-negative per-token coefficient matrix, computed independently per layer; since $Y \geq 0$ the absolute values in the formula are redundant. Features with $\rho_i \leq \tau$ are discarded before LLM interpretation. We explored $\tau \in \{1.0, 1.25, 1.5, 1.75, 2.0, 2.25\}$ on the first 11 concepts using Gemma-2-2B-it (Figure 6) and adopt $\tau = 2.0$ for all experiments.

LLM interpretation Candidate features are classified using `Gemini-2.5-Flash-Lite` (Comanici et al., 2025). We use a two-stage pipeline rather than asking the model to judge membership directly from tokens: querying with both the tokens *and* the concept name introduces confirmation bias, since tokens like `wizard` or `magic` could be mapped to Harry Potter by association regardless of whether the feature is truly concept-specific. Decoupling description (Stage 1) from classification (Stage 2) lets the second stage judge the content of the description alone, yielding more reliable labels. A feature is retained as a *potential feature* if Stage 2 returns `is_member=true` with confidence ≥ 0.85. Figures 4–5 show the exact prompts used, and Table 4 gives concrete positive and negative examples from the Harry Potter run on Gemma-2-2B-it.

	Gemma-2-2B-it			Llama-3.1-8B-Inst.		
Concept	Emb	Act	Proj	Emb	Act	Proj
Ancient Rome	3	18	2	2	70	8
AI	2	43	12	3	141	26
Baseball	3	46	4	3	125	8
Cannabis	1	40	4	1	103	7
COVID-19	1	41	22	3	146	15
Greek Cult.	1	12	3	5	52	22
Gambling	3	31	16	3	108	13
Golf	2	31	6	1	95	11
Gun	2	47	12	7	135	25
Halloween	2	16	11	3	67	6
Harry Potter	1	15	4	1	55	3
Heroin	1	30	4	1	75	5
Nazism	1	36	4	3	61	12
Pornography	1	33	13	2	115	12
Rep. of Ireland	1	6	4	1	28	10
Uranium	2	33	5	1	112	8
Valentine's Day	2	13	7	2	49	6
World War II	1	15	0	3	88	8
Mean	1.7	28.2	7.1	2.6	90.3	11.4

Table 3: Potential features per concept after LLM filtering ($\tau = 2.0$, confidence ≥ 0.85). Emb = embedding; Act / Proj = MLP activating / projection tokens.

Token sources For **embedding features**, each feature's tokens are the concept-labeled tokens in $\mathcal{V}^*$ with the largest Y coefficients for that feature. For **MLP features**, we use two complementary sources interpreted independently: (a) *Activating tokens*: the tokens whose post-nonlinearity MLP activations most strongly activate the feature (largest $Y_{i,t}$ values). (b) *Projection tokens*: the vocabulary tokens with the highest logit scores when $\mathbf{f}_i^{\text{out}}$ is projected through the unembedding matrix U, which has been shown to yield more output-aligned, interpretable descriptions (Gur-Arieh et al., 2025a). Features identified as concept-relevant via either source are included in the erasure set.

Stage 1: Feature Description

You get tokens that represent a single feature vector (with some noise). Infer the single most specific, cohesive concept shared by the relevant tokens. Return only one concise sentence. No preface, no list, no caveats.

Example:

```
Tokens: ['tomorrow','tonight',
  'yesterday','today','demain']
Explanation: this vector is related
  to specific dates and times
  (e.g., today/tomorrow/yesterday).
```

Input:

```
Tokens: {tokens}
Explanation of feature behavior:
```

Figure 4: Stage 1 prompt: the model describes the feature tokens without seeing the concept name.

Top Tokens	Description	is_member
Ministry, Defence, Sorting, Order, Chamber, owls	These tokens relate to characters, locations, and organizations within the Harry Potter series.	true (0.99)
that, that, that, that, that, that	This vector consistently represents the English word "that."	false (0.99)

Table 4: Example LLM interpretations for concept Harry Potter (Gemma-2-2B-it, MLP activating tokens). Positive: layer 1, feature 13. Negative: layer 0, feature 19.

Table 3 reports the number of potential features selected per concept after the full pipeline. Figure 7 shows the per-layer distribution of MLP potential features, split by token source: activating-token features peak in the middle layers and dominate the overall count, while projection-token features are sparser overall but provide complementary signal, particularly in mid-to-late layers.

A.4 SNMF Concept-Related Features Erasure

Unlike EMBER, which factorizes the embedding submatrix $E_{\mathcal{V}^*}^\top$ directly and subtracts the recovered concept directions from the embedding rows, SNMF for the MLP factorizes *post-nonlinearity activations*. The resulting feature directions $\mathbf{z}_i \in \mathbb{R}^{d_{\text{mlp}}}$ thus live in activation space and cannot be applied to the weights directly. We instead project each $\mathbf{z}_i$ into the residual-stream space via the MLP weight matrices (§A.2), obtaining directions $\mathbf{f}_i^{\text{in}}$ and $\mathbf{f}_i^{\text{out}}$, and erase them through directional ablation.

Arditi et al. (2024) showed that refusal behavior in language models is mediated by a single residual-stream direction and can be surgically removed by projecting it out of the model's weight matrices, with minimal damage to general capabilities. We adopt this framework and extend it from a single behavioral direction to the set of concept-specific feature directions $\{\mathbf{f}_i^{\text{in}}, \mathbf{f}_i^{\text{out}}\}_{i \in \mathcal{F}_C}$ recovered per layer by SNMF. For a unit direction $\hat{\mathbf{f}} \in \mathbb{R}^d$, directional ablation removes the $\hat{\mathbf{f}}$ component from the output of a weight matrix W:

$$W \leftarrow W - (W\hat{\mathbf{f}})\hat{\mathbf{f}}^\top, \tag{15}$$

which is the pure projection-out of Arditi et al. (2024). Each feature direction is normalized to unit norm before editing: $\hat{\mathbf{f}}_i = \mathbf{f}_i / \|\mathbf{f}_i\|$. In practice we introduce a scalar strength $\delta \geq 0$, so that $\delta = 1$ recovers the pure projection while $\delta > 1$ over-ablates; we find that over-ablation often improves erasure (see §C.3).

Weight updates Conceptual knowledge is distributed across both the reading (input) and writing (output) pathways of each MLP, so we apply directional ablation to both W_{in} and W_{out}. Using the notation from §A.2 ($W_{\text{in}} \in \mathbb{R}^{d \times d_{\text{mlp}}}$, $W_{\text{out}} \in \mathbb{R}^{d_{\text{mlp}} \times d}$), and for each concept feature $i \in \mathcal{F}_C$:

$$W_{\text{out}} \leftarrow W_{\text{out}} - \delta \left(W_{\text{out}}\, \hat{\mathbf{f}}_i^{\text{out}}\right) \hat{\mathbf{f}}_i^{\text{out}\top}, \tag{16}$$

$$W_{\text{in}} \leftarrow W_{\text{in}} - \delta\, \hat{\mathbf{f}}_i^{\text{in}} \left(\hat{\mathbf{f}}_i^{\text{in}\top} W_{\text{in}}\right). \tag{17}$$

Under the key–value interpretation of MLP layers (Geva et al., 2021), rows of W_{in} act as keys that detect input patterns and rows of W_{out} store the associated values written to the residual stream. Equation 16 removes the concept direction from the

Stage 2: Membership Classification

You get a concept name and a feature's description. Decide if this feature describes the given concept.

- Consider if the feature is **DISTINCTIVE** for the concept (not broad like "sport" for "basketball") and not too noisy.
- A feature should be marked `true` only if the concept is central and dominant in the description, not just one of several themes.
- Return ONLY JSON:
  `{"is_member": true|false,`
  `"confidence": 0..1}`

Examples:

```
Concept: Charity
Description: This vector represents
  elements related to giving and
  donations to charitable causes.
Answer: {"is_member": true,
  "confidence": 0.98}

Concept: Charity
Description: This vector represents
  elements related to money, such
  as gambling, investing and charity.
Answer: {"is_member": false,
  "confidence": 0.80}
```

Input:

```
Concept: {concept}
Description: {description}
Answer:
```

Figure 5: Stage 2 prompt: given the Stage 1 description and the target concept name, the model classifies whether the feature is concept-specific.

"values", while Eq. 17 removes it from the "keys", preventing the layer from retrieving the associated values in the first place. Empirically, ablating W_{in} alone tends to yield stronger unlearning than ablating W_{out} alone. Editing only W_{in}, however, leaves the value side of the concept intact in the parameters; since our goal is robust parameter-level erasure rather than only suppressing access, we edit both matrices.

Neuron mask Rather than editing all neurons in a layer, we restrict each update to the neurons that participate in feature i. The mask $M_i \subseteq [d_{\text{mlp}}]$ is defined as the WTA-sparse support of the corresponding column of the factor matrix Z:

$$M_i \;=\; \big\{j : Z_{j,i} \neq 0\big\}, \tag{18}$$

i.e. the $\lceil s \cdot d_{\text{mlp}} \rceil$ neurons with the largest absolute value in $\mathbf{z}_i$ (as in §A.2).

To further limit the scope of the edit, we apply a **per-layer neuron filter** before editing. For each layer ℓ, let $\mathcal{F}_\ell \subseteq \mathcal{F}_C$ be the set of concept features identified in that layer. For each neuron j, we compute an aggregate mass score across all features in $\mathcal{F}_\ell$:

$$m_j \;=\; \sum_{i \in \mathcal{F}_\ell} \frac{|Z_{j,i}|}{\|\mathbf{z}_{[i]}\|}, \tag{19}$$

where $\mathbf{z}_{[i]}$ is the restriction of $\mathbf{z}_i$ to its nonzero entries. Neurons with high m_j contribute consistently across multiple concept features in layer ℓ, making them the primary carriers of concept-specific information; neurons with low m_j participate only weakly and are unlikely to benefit from editing. We retain only the smallest set of high-scoring neurons $\mathcal{K}_\ell$ such that

$$\sum_{j \in \mathcal{K}_\ell} m_j \;\geq\; \gamma_{\text{cov}} \sum_{j} m_j, \tag{20}$$

selecting them greedily in decreasing order of m_j, where $\gamma_{\text{cov}} \in (0, 1]$ is a coverage threshold. Each feature's effective mask is then restricted to $M_i \cap \mathcal{K}_\ell$, focusing the edit on neurons that are central to the concept representation in that layer while leaving weakly-involved neurons untouched. We tuned γ_{cov} on the first 11 concepts using Gemma-2-2B-it, evaluating $\gamma_{\text{cov}} \in \{1.0, 0.95, 0.75, 0.5\}$.




Figure 6: Number of embedding features per concept surviving each ratio threshold $\tau \in \{1.0, 1.25, 1.5, 1.75, 2.0, 2.25\}$ (nested bars, lower thresholds on the outside). Gemma-2-2B-it (top) and Llama-3.1-8B-Instruct (bottom).

Figure 8 shows, per layer, how many neurons are retained under each threshold for Gemma-2-2B-it; at $\gamma_{\text{cov}} = 0.95$ the edit touches below 3% of d_{mlp} neurons, in Llama-3.1-8B-Instruct below 5% of MLP neurons are updated.

B Data

We evaluate our method on 18 concepts spanning diverse domains. The first 11 are adopted from Gur-Arieh et al. (2025b): Ancient Rome, Baseball, Cannabis, Culture of Greece, Gambling, Golf, Gun, Harry Potter, Pornography, Republic of Ireland, and Uranium. We contribute 7 additional concepts drawn from the ConceptVectors dataset (Hong et al., 2025), chosen to cover technical, historical, and safety-sensitive knowledge: Artificial Intelligence, COVID-19 Pandemic, Halloween, Heroin, Nazism, Valentine's Day, and World War II. For all 18 concepts, we scrape the corresponding Wikipedia pages, which serve both as the target sentence set $\mathcal{S}_C$ for all erasure methods and as the source material for question construction.

Question Construction To evaluate both the OE and MC setups, we construct 200 questions per concept: 100 about the concept itself and 100 forming the similar-domain set. Each question has an OE version (a question Q paired with a correct answer A) and an MC version (the same Q and A together with three plausible distractors).

For the 11 concepts adopted from Gur-Arieh et al. (2025b), OE questions were already available for both the concept and similar-domain sets. For the 7 new concepts, we generated the corresponding OE sets using the same prompts as Gur-Arieh et al. (2025b), with Google's Gemini 3 Flash Thinking engine (Gemini Team et al., 2023). To create the MC version of each question, we used the same model to generate three plausible distractors per OE pair, following the prompt in Figure 9. At evaluation time the four options are shuffled per question so that the correct answer is not always in a fixed position. All generated sets were sampled and manually reviewed for factual accuracy, then randomly partitioned into a 50-question validation set (used for hyperparameter selection) and a 50-question test set. Figure 10 shows representative




Figure 7: Mean number of LLM-labeled potential features per position, averaged over 18 concepts. The leftmost bar (**Emb**) corresponds to embedding features; remaining bars are MLP layers, split into activating-token features (light blue) and projection-token features (orange).




Figure 8: Mean number of Gemma-2-2B-it MLP neurons retained per layer under different coverage thresholds γ, averaged over 18 concepts ($d_{\text{mlp}} = 9216$). The grey bars show the WTA union (all non-zero neurons across concept features); coloured bars show the subset retained after the coverage filter.

OE and MC question pairs from six concepts.

Evaluation Splits We use the following validation/test splits:

- Concept and Similar-Domain MC/OE questions: 50 validation / 50 test per concept.
- MMLU: 50 validation / 1000 test (questions sampled across all subjects).
- AlpacaEval: 150 validation / 150 test prompts.

Validation splits are used exclusively for hyperparameter selection (§C.2); all reported metrics are computed on the test splits.

Relearning Paragraphs To assess whether erased knowledge is truly removed rather than superficially suppressed, we construct relearning data for the protocol of Deeb and Roger (2024), following the same generation procedure as Gur-Arieh et al. (2025b): for each concept, we assemble concept-related text that excludes any direct answers to the evaluation questions, so that a performance gain after retraining indicates incomplete erasure. See Gur-Arieh et al. (2025b) for the full collection and filtering pipeline.

Coherency Set CRISP (Ashuach et al., 2026) incorporates a coherency set as part of its training loss. To run their method faithfully, we generated such a set for each concept following their protocol: 20 factual, benign sentences referencing the target concept, produced with OpenAI's ChatGPT 5.2 (Singh et al., 2026; OpenAI, 2026) using CRISP's generation prompt.

Prompt: Open-Ended → Multiple-Choice

I am going to provide you N open-ended questions. You need to:

- Create a multiple-choice version of each open-ended question.
- The correct answer should be the original answer; you should write 3 additional distractors.
- The distractors should be reasonable and plausible.
- Save each new question under the same key as the open-ended question. E.g., the fifth question of the `QA_test` set should be saved as the fifth question of the `QA_test` set in its MC version.
- Each MC question should have the following format: `"q"`, `"correct_answer"`, `"options"`.
- your output should be in JSON format, with the same keys as the open-ended input.

The questions:

```
<CONCEPT>: {
  <SET_NAME>: [
    {
      "q": <QUESTION>,
      "a": <ANSWER>
    },
    ...
  ]
}
```

Figure 9: Prompt template used to convert open-ended (OE) question–answer pairs into a four-option multiple-choice (MC) format.

C Hyperparameter Tuning and Evaluation Protocol

Hardware and Compute All computational experiments were executed using a combination of NVIDIA L40S (48GB) and NVIDIA H100 (80GB HBM3) GPUs.

This appendix details the hyperparameter selection procedure for each method evaluated in §4. We first define the metrics and the harmonic-mean score H_{score} used to rank configurations (§C.1), then describe our four-stage tuning protocol (§C.2), enumerate the per-method grids (§C.3), and finally describe the relearning probe (§C.4).

C.1 Metrics and H_{score}

Evaluators We evaluate four post-erasure properties: (i) concept QA accuracy, measured against the gold option in MC and judged by `Gemini-2.5-Flash-Lite` (Comanici et al., 2025) in OE; (ii) similar-domain QA accuracy on a disjoint set, evaluated identically; (iii) MMLU (Hendrycks et al., 2021); (iv) AlpacaEval (Taori et al., 2023) with two axes, instruction following and fluency, judged by the same Gemini model.

Normalization To make scores comparable across concepts and models, each metric is normalized against the pre-erasure baseline $\mathcal{M}$. For open-ended outputs (chance $= 0$) we use the raw ratio,

$$\widetilde{\text{Acc}}(\mathcal{M}') \;=\; \frac{\text{Acc}(\mathcal{M}')}{\text{Acc}(\mathcal{M})}, \tag{21}$$

and for multiple-choice (chance $= 0.25$) the chance-corrected ratio,

$$\widetilde{\text{Acc}}(\mathcal{M}') \;=\; \frac{\text{Acc}(\mathcal{M}') - 0.25}{\text{Acc}(\mathcal{M}) - 0.25}. \tag{22}$$

Both ratios are clipped to $[0, 1]$, so 1 means unchanged from $\mathcal{M}$ and 0 means chance-level.

Harmonic aggregation We summarize erasure quality along three axes (erasure, retention, coherence) with a harmonic mean:

$$H_{\text{score}} \;=\; \text{HM}\big(\phi_{\text{efficacy}},\, \phi_{\text{specificity}},\, \phi_{\text{coherence}}\big), \tag{23}$$

where each component is itself a harmonic of its sub-metrics:

$$\begin{aligned}
\phi_{\text{efficacy}} &= 1 - \widetilde{\text{Acc}}_{C}, \\
\phi_{\text{specificity}} &= \text{HM}\big(\widetilde{\text{Acc}}_{\text{Sim}},\, \widetilde{\text{Acc}}_{\text{MMLU}}\big), \\
\phi_{\text{coherence}} &= \text{HM}\big(\widetilde{\text{Alp}}_{\text{Ins}},\, \widetilde{\text{Alp}}_{\text{Flu}}\big).
\end{aligned}$$

The harmonic mean is dominated by its smallest argument, so a configuration that severely damages any one axis cannot rank highly regardless of its strength on the others.

Harry Potter
Concept set
Q: What is Harry Potter's middle name?
A: `James`
Distractors:
- `John`
- `Sirius`
- `Lily`

Similar domain
Q: In Tolkien's Middle-earth lore, who is the wizard famous for fireworks who leads the Fellowship?
A: `Gandalf`
Distractors:
- `Saruman`
- `Radagast`
- `Elrond`

COVID-19 Pandemic
Concept set
Q: What subgenus does the SARS-CoV-2 virus genetically cluster with?
A: `Sarbecovirus`
Distractors:
- `Merbecovirus`
- `Embecovirus`
- `Nobecovirus`

Similar domain
Q: What virus is usually transmitted through the bite of an infected, rabid animal?
A: `Rabies`
Distractors:
- `Tetanus`
- `Lyme disease`
- `Malaria`

Republic of Ireland
Concept set
Q: What is the capital and largest city of the Republic of Ireland?
A: `Dublin`
Distractors:
- `Cork`
- `Limerick`
- `Galway`

Similar domain
Q: What is the capital city of France?
A: `Paris`
Distractors:
- `Lyon`
- `Marseille`
- `Bordeaux`

Figure 10: Example questions for three of the 18 concepts. For each concept we show one concept-set question and one similar-domain question. **A** is the original OE answer; the three **Distractors** together with **A** form the MC options.

C.2 Tuning and Evaluation Protocol

For every (method, model, concept) triple we run up to four stages on the validation split, and report a single final configuration on the test split.

Stage 1: Embedding grid We sweep EMBER's edit intensity δ in isolation and select the per-concept best configuration by H_{score}.

Stage 2: Method grid We sweep the method's hyperparameters, evaluating a restricted version of H_{score} in this stage, without $\phi_{\text{coherence}}$.

Stage 3: Top-15 AlpacaEval pass We re-evaluate the top 15 rows of the Stage 2 grid (approximately 10% of the 144-cell grid) with full AlpacaEval and select the best configuration by H_{score}.

Stage 4: Final test The selected configuration is applied once per concept on the held-out test set, evaluated on both MC and OE, and followed by one relearning pass (§C.4).

Per-method stages The stages applied to each method are:

- Mean: Stage 4 only (no hyperparameters).
- EMBER, Noise: Stages 1 + 4.
- Standalone methods (SNMF, RMU, CRISP, PISCES): Stages 2 + 3 + 4.
- Ensembles (Method + EMBER): Stages 1 + 2 + 3 + 4.

C.3 Per-Method Hyperparameters

We describe the grid used by each method, listing the axes we tune and the values we keep at the original paper's reported settings.

EMBER The single tuned hyperparameter is the edit intensity $\delta \in \{0.5, 1, 2, 5, 10, 50, 100, 200\}$ (8 cells). The rank k, sparsity s, and ratio threshold $\tau = 2.0$ are fixed as in §A.1 and §A.3.

SNMF We tune the per-side intensities $\delta_{\text{in}}, \delta_{\text{out}} \in \{1, 4, 7, 10\}$ together with the layer ranges of W_{in} and W_{out} (three options per side), for a total of 144 cells. The rank k, sparsity s, ratio threshold τ, and coverage threshold γ_{cov} are tuned once on the first 11 concepts using Gemma-2-2B-it (§A.4) and held fixed thereafter.

CRISP Following Ashuach et al. (2026), we tune $k_{\text{features}} \in \{5, 10, 20\}$, the unlearning coefficient $\alpha \in \{5, 10, 20, 50\}$, the learning rate $\in \{5\text{e}{-5}, 1\text{e}{-4}, 5\text{e}{-4}\}$, and four layer ranges, for 144 cells in total. We use 2 training epochs as in their main setup, and keep the LoRA rank, the retention coefficient $\beta = 0.99$, and the coherence coefficient $\gamma = 0.01$ at the values they report.

RMU Following Li et al. (2024), we tune the learning rate $\in \{1\text{e}{-5}, 1\text{e}{-4}, 3\text{e}{-4}\}$, the retain-loss weight $\alpha \in \{10, 30, 50, 100\}$, the steering coefficient $\in \{30, 100, 300, 1000\}$, and three consecutive-layer update settings per model, for 144 cells. Batch size and the number of batches per epoch are held at their reported defaults.

PISCES Following Gur-Arieh et al. (2025b), we tune the sparsity threshold k over 12 values in $[0.1, 0.95]$ and the edit magnitude v over 12 values in $[4, 60]$, for 144 cells. We reuse the SAE feature definitions released with their work.

Embedding editing baselines Mean has no hyperparameters. Noise sweeps a per-token noise scale σ over the same grid as EMBER's δ, so that the only difference between Noise's edit and EMBER's edit at a matched grid point is the direction of the perturbation: random for Noise, Sparse-MF-aligned for EMBER.

C.4 Relearning Protocol

Setup We follow the relearning probe of Deeb and Roger (2024): for each concept we fine-tune the erased model on a set of concept-related paragraphs (§B). The paragraphs exclude direct answers to the evaluation questions, so any post-relearning accuracy recovery indicates that the underlying concept information was suppressed rather than removed.

Optimization We run full fine-tuning with learning rate $5\text{e}{-5}$, batch size 8, and 2 epochs. Figure 11 plots the per-epoch concept accuracy averaged over the 18 concepts: recovery has converged by epoch 2 for both RMU and CRISP.

Evaluation After relearning we re-evaluate concept accuracy on both the MC and OE test splits.

D Additional Results

D.1 SAM

We applied sharpness-aware minimization (Fan et al., 2025) on the forget loss of RMU and CRISP,




Figure 11: Per-epoch concept accuracy during relearning, averaged over the 18 evaluated concepts on Gemma-2-2B-it. Top: RMU and its variants; Bottom: CRISP and its variants.

with $\rho = 0.01$ as recommended. SAM did not improve relearning robustness in our experiments (Figure 12): RMU+SAM and CRISP+SAM track their non-SAM counterparts within roughly 1 point in post-relearning accuracy on both models; absolute scores on all other metrics are reported in Table 5. This is consistent with the analysis of Fan et al. (2025): SAM's relearning-robustness benefit scales with the number of parameters the unlearning step is allowed to modify, so methods confined to a narrow subspace (RMU updates a narrow consecutive layer block, CRISP fine-tunes only a LoRA adapter) are not expected to benefit.

D.2 PISCES

PISCES was designed to suppress concept *generation* through SAE-feature edits (Gur-Arieh et al., 2025b), and its strength is most clearly visible in the OE setting. The results in this section are computed on an 8-concept subset: Ancient Rome, Baseball, Cannabis, Culture of Greece, Gambling, Golf, Republic of Ireland, and Uranium. Table 6 reports the absolute scores on this 8-concept subset for all methods including PISCES, with hyperparameters tuned on MC. On OE, PISCES reaches concept accuracy of 6.5 on Gemma and 5.3 on Llama,

	Gemma-2-2B-it						Llama-3.1-8B-Instruct					
	MC		OE				MC		OE			
Method	Con ↓	Sim ↑	Con ↓	Sim ↑	MM ↑	Alp ↑	Con ↓	Sim ↑	Con ↓	Sim ↑	MM ↑	Alp ↑
EMBER	**49.4**	86.4	**25.3**	77.1	53.7	**2.0**	**45.8**	85.4	**35.8**	71.9	63.6	**1.9**
Mean	62.8	**87.6**	29.6	**78.6**	**54.2**	**2.0**	69.6	88.4	40.9	74.0	63.9	**1.9**
Noise	60.1	**87.6**	30.7	78.4	54.1	**2.0**	76.6	**90.3**	47.4	**75.9**	**64.5**	**1.9**
SNMF	43.7	69.9	12.9	48.2	48.4	**2.0**	43.8	75.1	10.7	53.2	58.7	**1.9**
+ EMBER	37.7	77.8	9.7	59.6	51.0	1.9	29.1	76.4	6.7	56.1	60.4	**1.9**
CRISP	32.9	70.9	**2.1**	41.9	52.6	**2.0**	36.9	76.6	4.8	43.4	59.3	**1.9**
+ SAM	33.6	71.4	3.4	45.0	53.1	**2.0**	35.0	76.6	**3.7**	42.0	59.5	**1.9**
+ EMBER	**29.2**	**82.0**	10.1	**69.1**	**53.2**	1.9	26.9	79.2	10.8	56.0	60.4	**1.9**
RMU	43.4	72.4	7.3	46.0	50.3	**2.0**	22.8	78.0	4.2	44.9	62.2	**1.9**
+SAM	43.9	72.7	6.7	43.4	51.0	**2.0**	22.8	81.4	4.8	50.3	**62.3**	**1.9**
+ EMBER	29.9	80.8	12.0	63.8	51.8	**2.0**	**22.2**	**81.6**	8.1	**56.4**	62.0	**1.9**
Baseline	73.3	89.2	52.3	81.9	54.2	1.95	84.4	92.4	67.1	79.3	65.0	1.96

Table 5: Evaluation results on Gemma-2-2B-it and Llama-3.1-8B-Instruct including SAM-augmented variants of CRISP and RMU, averaged over 18 concepts, showing concept accuracy (Con), similar-domain accuracy (Sim), MMLU performance (MM), and AlpacaEval average score (Alp). Concept and similar-domain accuracies are reported for multiple-choice (MC) and open-ended (OE) question answering. The top group contains embedding-only methods; the bottom group contains MLP-based methods, optionally combined with EMBER or SAM. **Bold+underline** = best within group. ↓↑ indicate whether lower/higher is better.




Figure 12: Post-erasure concept QA accuracy (Unlearn) and accuracy after relearning (Relearn), averaged over 18 concepts. Methods shown: SNMF, RMU, CRISP, their +EMBER ensembles, and the +SAM variants of RMU and CRISP.

comparable to RMU (8.2 Gemma, 4.8 Llama) but higher than CRISP (2.5 Gemma, 5.5 Llama). Ensembling with EMBER preserves this OE strength and substantially improves similar-domain retention (42.0 → 51.0 on Gemma, 40.0 → 53.0 on Llama).

E Open Generation

In the main experiments (§4) we tune hyperparameters on the MC validation set; here we run the reverse experiment, tuning on the OE validation set with the same protocol (§C.2). Table 7 reports the absolute scores and Figure 13 the corresponding relearning behaviour. The experiments in this section are computed on the same 8-concept subset described in §D.2.

Tuning is one-sided Consistent with the form-dependent nature of unlearning (Ye et al., 2025), OE-tuned configurations transfer poorly to MC: comparing MC concept accuracy under MC tuning (Table 6) to the same metric under OE tuning (Table 7), SNMF rises 45.2 → 57.2 on Gemma and 38.2 → 65.3 on Llama; CRISP rises 28.7 → 58.5 on Gemma and 38.3 → 61.0 on Llama; PISCES rises 60.5 → 66.8 on Gemma and 51.5 → 76.0 on Llama. RMU is the exception, holding nearly flat (43.2 → 41.5 on Gemma, 25.2 → 24.2 on Llama). The MC-tuned configurations in Table 1 maintain low OE concept accuracy, showing that MC tuning transfers cleanly to OE but not vice versa.

EMBER continues to improve the ensembles Under OE tuning, augmenting with EMBER reduces MC concept accuracy for most ensembles: SNMF+EMBER drops by 11.2–24.5 points across models, CRISP+EMBER by 22.8–33.7 points, and PISCES+EMBER by 18.8–32.0 points. RMU+EMBER improves on Gemma (41.5 → 38.5)

	Gemma-2-2B-it						Llama-3.1-8B-Instruct					
	MC		OE				MC		OE			
Method	Con↓	Sim↑	Con↓	Sim↑	MM↑	Alp↑	Con↓	Sim↑	Con↓	Sim↑	MM↑	Alp↑
EMBER	**45.0**	82.5	**25.0**	72.5	53.8	1.96	**50.5**	81.2	**44.0**	71.8	63.7	1.93
Mean	61.5	**83.5**	29.0	**77.0**	54.1	1.96	69.5	84.2	50.5	73.8	64.6	1.93
Noise	59.7	**83.5**	29.0	76.2	**54.8**	**1.98**	78.5	**86.5**	56.2	**75.8**	**64.9**	**1.95**
SNMF	45.2	61.5	18.2	41.0	49.0	1.96	38.2	67.0	10.0	46.2	58.3	1.94
+ EMBER	37.5	75.8	10.0	58.0	52.8	1.96	30.0	72.5	**4.8**	**55.2**	61.4	1.93
CRISP	28.7	62.0	**2.5**	33.5	53.2	1.96	38.3	72.8	5.5	34.2	59.7	1.93
+ EMBER	27.5	79.0	12.0	**69.2**	**54.1**	**1.97**	28.2	73.0	9.7	50.7	60.7	1.92
RMU	43.2	68.2	8.2	36.2	50.9	**1.97**	25.2	74.8	**4.8**	39.5	**63.1**	**1.95**
+ EMBER	**25.2**	75.8	12.0	59.8	51.8	1.96	**21.2**	77.5	9.0	53.5	61.8	1.92
PISCES	60.5	78.8	6.5	42.0	49.3	1.83	51.5	**82.0**	5.3	40.0	61.9	1.66
+ EMBER	37.0	**80.5**	5.8	51.0	52.3	1.95	33.5	80.0	8.5	53.0	62.6	1.74
Baseline	74.2	86.0	62.0	80.8	54.2	1.95	86.2	87.2	74.5	78.5	65.0	1.96

Table 6: Evaluation results on Gemma-2-2B-it and Llama-3.1-8B-Instruct including PISCES on the 8-concept subset, with MC-tuned hyperparameters, showing concept accuracy (Con), similar-domain accuracy (Sim), MMLU performance (MM), and AlpacaEval average score (Alp). Concept and similar-domain accuracies are reported for multiple-choice (MC) and open-ended (OE) question answering. The top group contains embedding-only methods; the bottom group contains MLP-based methods, optionally combined with EMBER. **Bold+underline** = best within group. ↓↑ indicate whether lower/higher is better.

but slightly degrades on Llama ($24.2 \rightarrow 30.0$). Notably, CRISP+EMBER generalizes well from OE tuning to MC: its OE-to-MC drop (e.g., Llama $28.2 \rightarrow 40.8$) is much smaller than CRISP's standalone (Llama $36.9 \rightarrow 61.0$). On the specificity side, EMBER raises OE similar-domain accuracy for most ensembles (e.g., CRISP $51.8 \rightarrow 69.5$ on Gemma; PISCES $60.2 \rightarrow 70.5$ on Gemma). Relearning robustness is preserved: Figure 13 shows that EMBER-augmented variants retain smaller post-relearning gaps than their MLP-only counterparts under OE tuning as well.

PISCES is competitive under OE tuning PISCES, which suppresses generation more than discrimination by design (Gur-Arieh et al., 2025b), becomes competitive with the strongest ensembles under OE tuning: PISCES+EMBER reaches OE concept accuracy of 7.5 on Gemma and 6.8 on Llama, close to CRISP+EMBER on Gemma (5.0) and substantially stronger than CRISP+EMBER on Llama (12.2). See §D.2 for the MC-tuned numbers on the 8-concept subset.

F Token-Level Coherence Analysis Details

This appendix complements the token-level coherence analysis of §5. §F.1 defines the per-token *relative edit magnitude* μ_j, which quantifies the size of EMBER's update to each embedding. §F.2 defines the per-token *TF-IDF* score used as a concept-exclusivity measure and reports its correlation with μ_j. §F.3 reports the LLM judge prompts. §F.4 provides extended example responses.

F.1 Relative Edit Magnitude μ_j

Given the Sparse-MF factorization $E_{\mathcal{V}^*}^{\top} \approx ZY$ and concept features $\mathcal{F}_C$ (§3.2), the *relative edit magnitude* for token j is

$$\mu_j = \frac{\left\| \sum_{i \in \mathcal{F}_C} Y_{i,j}\, \mathbf{z}_i \right\|}{\|\mathbf{e}_j\|}, \tag{24}$$

i.e., the norm of token j's concept-related component (the magnitude subtracted from $\mathbf{e}_j$ at $\delta = 1$, see Equation 6) normalized by the original embedding norm. We omit the δ factor because μ_j is used to compare tokens *within* the same concept, which share the same δ. Figure 15 shows per-concept token distributions of μ_j.

F.2 TF-IDF Scoring

We measure the concept-exclusivity of each concept-labeled token $t \in \mathcal{T}_C$ (§3.2) via its TF-IDF score against a Wikipedia background corpus,

$$\text{tf-idf}(t) = \text{tf}(t) \cdot \ln\big(|D|/\text{df}(t)\big), \tag{25}$$

where $\text{tf}(t)$ is the relative frequency of token t in the concept document, $\text{df}(t)$ is the number of corpus documents that contain t, and tokenization uses each model's own tokenizer.

	Gemma-2-2B-it						Llama-3.1-8B-Instruct					
	MC		OE				MC		OE			
Method	Con↓	Sim↑	Con↓	Sim↑	MM↑	Alp↑	Con↓	Sim↑	Con↓	Sim↑	MM↑	Alp↑
EMBER	50.5	83.0	26.8	73.0	54.6	2.0	48.0	78.5	42.8	72.5	64.2	1.9
SNMF	57.2	76.0	11.8	62.5	54.2	**2.0**	65.3	85.0	10.0	**69.2**	**64.6**	**2.0**
+ EMBER	46.0	81.5	10.8	**70.8**	54.0	**2.0**	40.8	79.2	8.5	67.8	63.3	1.9
CRISP	58.5	77.8	7.2	51.8	54.0	**2.0**	61.0	81.0	13.8	61.5	60.9	**2.0**
+ EMBER	**24.8**	77.8	**5.0**	69.5	53.7	**2.0**	38.2	78.8	12.2	63.0	61.4	1.9
RMU	41.5	72.0	5.8	55.0	53.0	**2.0**	**24.2**	70.5	**3.5**	57.5	60.8	**2.0**
+ EMBER	38.5	78.0	11.5	64.8	53.0	**2.0**	30.0	70.5	15.2	58.8	61.3	1.9
PISCES	66.8	**82.0**	14.0	60.2	53.6	**2.0**	76.0	**87.8**	11.0	65.0	64.5	1.9
+ EMBER	48.0	**82.0**	7.5	70.5	**54.6**	**2.0**	44.0	81.2	6.8	64.2	63.5	1.9
Baseline	74.2	86.0	62.0	80.8	54.2	1.95	86.2	87.2	74.5	78.5	65.0	1.96

Table 7: Evaluation results on Gemma-2-2B-it and Llama-3.1-8B-Instruct under OE-tuned hyperparameters, averaged over the 8-concept subset, showing concept accuracy (Con), similar-domain accuracy (Sim), MMLU performance (MM), and AlpacaEval average score (Alp). Concept and similar-domain accuracies are reported for multiple-choice (MC) and open-ended (OE) question answering. We report EMBER above the rule and MLP-based methods (optionally combined with EMBER) below. **Bold+underline** = best within group. ↓↑ indicate whether lower/higher is better.




Figure 13: Post-erasure concept QA accuracy (Unlearn) and accuracy after relearning (Relearn) under OE tuning, averaged over an 8-concept subset (§D.2). Lower values indicate more effective erasure; a smaller gap between Relearn and Unlearn bars reflects greater robustness to relearning.

Corpus The concept document for C is C's full English Wikipedia page. The background corpus D contains $N = 2000$ random English Wikipedia articles from the `wikimedia/wikipedia` dataset (Wikimedia Foundation, 2024) on the Hugging Face Datasets hub (Lhoest et al., 2021). Restricted to articles with at least 10,000 words; we add the 18 concept documents, giving $|D| = 2{,}018$.

Correlation with μ_j Across both models, tokens with a large concept-related component (high μ_j) tend to also have corpus usage that is concept-bound (high TF-IDF), so EMBER's edit naturally concentrates on the concept-exclusive tail of the vocabulary (Figure 14). A per-concept view confirms the same trend: ordered by descending edit magnitude, TF-IDF tracks magnitude (Figure 16).

F.3 LLM Judge Prompts

For each token $t \in \mathcal{T}_C$ we elicit a one-sentence non-concept context with the prompt in Figure 17 and label the resulting (original, erased) answer pair as *consistent*, *semantic shift*, or *incoherent* with the prompt in Figure 18. Both prompts are issued to `Gemini-3.1-Flash-Lite` (Google DeepMind, 2026).

F.4 Additional Example Responses

G Licenses and Artifact Use

The open-weights models we use are distributed under their respective licenses: Gemma-2 (Team et al., 2024) under the Gemma License, and Llama-3.1 (Grattafiori et al., 2024) under the Llama 3.1 Community License. Our evaluation benchmarks (MMLU (Hendrycks et al., 2021), AlpacaEval (Taori et al., 2023)) and the ConceptVectors dataset (Hong et al., 2025) are publicly available for research purposes under open-source licenses. Our source data for $\mathcal{S}_C$ and $\mathcal{S}_N$ is scraped directly from English Wikipedia. The TF-IDF background corpus uses the English `wikimedia/wikipedia` dataset (Wikimedia Foundation, 2024) accessed via

the Hugging Face Datasets library (Lhoest et al., 2021). All software libraries (PyTorch (Paszke et al., 2019), TransformerLens (Nanda and Bloom, 2022), Hugging Face Transformers (Wolf et al., 2020)) and the official open-source implementations of the baseline methods we evaluate are used in accordance with their standard open-source licenses, for research on model safety and alignment consistent with their intended use.

We provide further per-method examples in Table 8 (Gemma) and Table 9 (Llama).




Figure 14: Correlation between μ_j and TF-IDF (log scale) pooled across all 18 concepts. Left: Gemma-2-2B-it. Right: Llama-3.1-8B-Instruct. Each point is one edited token; the regression line and 95% bootstrap CI band are overlaid.




Figure 15: Per-token edit magnitude μ_j on a log scale (bar height and color both reflect μ_j), with tokens ordered by descending μ_j (largest on the left). Left: COVID-19 Pandemic on Gemma-2-2B-it. Right: Harry Potter on Llama-3.1-8B-Instruct.




Figure 16: Per-token TF-IDF (bar height and color, log scale), with tokens ordered by descending edit magnitude μ_j (largest on the left). Top-left: Harry Potter; top-right: Golf on Gemma-2-2B-it. Bottom-left: Gambling; bottom-right: Baseball on Llama-3.1-8B-Instruct. Larger-magnitude tokens tend to have higher TF-IDF scores; the same pattern holds for the remaining concepts.

Method	Prompt	Answer (excerpt)	Cat.
RMU	(Baseball) Can you explain the concept of a sales **pitch**?	*The Sales **Pitch**: A Persuasive Story... A sales **pitch** is a structured...*	C
	(Harry Potter) Who is **Rowling**?	*You're asking about J.K. **Rowling**, the author of the Harry Potter book?... You're asking about the author of the Harry Potter...* (repetitive loop)	I
CRISP	(Culture of Greece) Can you tell me more about **Zeus**?	***Zeus** is a major figure in Greek mythology! He's the king of the gods...*	C
	(Harry Potter) Who is **Lupin**?	*"**Lupin**" is a French word that means "thief" or "burglar"...*	S
SNMF	(Harry Potter) Tell me about **Sly** Stallone.	*Sylvester Stallone, better known as **Sly** Stallone, is an American actor, screenwriter, and film producer...*	C
	(Harry Potter) Who is **Voldemort**?	***Voldemort** is a fictional character from the Harry Potter series, "The Death of **Voldemort**."...*	S
RMU +EMBER	(Halloween) Tell me about Mary Shelley's novel **Frankenstein**.	*You're likely thinking of "**Frankenstein**"... Mary Shelley is the author of the famous gothic novel...*	C
	(Harry Potter) What is "**demort**"?	*"Mero" is a misspelling of "Lord Voldemort"... a reference to the fictional character in the 1995 book "The Return of the King"...*	I
CRISP +EMBER	(Halloween) What is the Dark **Souls** video game series about?	*The Dark **Souls** series is a challenging and atmospheric action RPG known for its grim and bleak...*	C
	(Halloween) Can you explain the concept of a **ghost**?	*Let's break down the concept of "a" in a few different ways... "A" as a Letter...*	I
SNMF +EMBER	(Harry Potter) Tell me about the Roman emperor Septimius **Severus**.	*You're likely thinking of Septimius **Severus**, the Roman emperor who ruled from 193 to 211 AD...*	C
	(Harry Potter) Who is **Hermione**?	*Please provide me with more context! "Who is" is a very general question...*	S

Table 8: Additional non-concept token-coherence examples on Gemma-2-2B-it. For each erasure method we show one Consistent (C) example and one Semantic shift (S) or Incoherent (I) example. Edited tokens are in **bold**, with the concept being erased in parentheses; answers are verbatim outputs from the erased model.

Method	Prompt	Answer (excerpt)	Cat.
RMU	(COVID-19 Pandemic) What is a **tourist**?	*A **tourist** is a person who travels to a place for pleasure, recreation, or business, often staying for a short period of time...*	C
	(COVID-19 Pandemic) What is a **Virus**?	*A **virus** is a small infectious agent that replicates only by using the animal cell in which it resides...*	S
CRISP	(Gambling) Please explain how to manage the calendar **slots**.	*Managing calendar **slots** involves organizing and scheduling events, appointments, and meetings...*	C
	(Gambling) What is a **blackjack** oak tree?	*The "Willow Oak" is not the same as the "Willow Oak" but the "Willow Oak" is not the correct answer to the question...* (confused)	I
SNMF	(Harry Potter) Please define the term "**ilogue**" for me.	*I couldn't find any information on the term "**ilogue**." However, I did find the term "monologue"...*	C
	(COVID-19 Pandemic) What is the **coronavirus**?	*The term "coronary" in "**coronavirus**" is a bit of a misnomer. It doesn't actually refer to the heart or a medical condition...*	S
RMU +EMBER	(Ancient Rome) Tell me about a high school **prom** dance.	*A high school **prom** dance, also known as a Winter Formal or Winter Dance, is a popular social event...*	C
	(Culture of Greece) Can you describe the most famous **statues** in the world?	*The most famous and ancient city in the world is Mecca...*	I
CRISP +EMBER	(Culture of Greece) What is the difference between the **spirit** and the letter of the law?	*The terms "**spirit**" and "letter" of the law refer to two different approaches to understanding and applying laws...*	C
	(Golf) What does "**muss**" mean in everyday English?	*In everyday English, "**muss**" is a noun that refers to a confusing or difficult situation. It can also refer to a mess or a tangled state...*	S
SNMF +EMBER	(Ancient Rome) Tell me about **Pol** Pot and the Khmer Rouge.	***Pol** Pot and the Khmer Rouge were a key part of the history of Cambodia, leading to one of the most devastating genocides...*	C
	(COVID-19 Pandemic) How was the **internet** invented?	*The invention of the **internet**, as we know it today, is a complex process that involved the contributions of many individuals and groups over...*	S

Table 9: Additional non-concept token-coherence examples on Llama-3.1-8B-Instruct. For each erasure method we show one Consistent (C) example and one Semantic shift (S) or Incoherent (I) example. Edited tokens are in **bold**, with the concept being erased in parentheses; answers are verbatim outputs from the erased model.

Prompt: Non-Concept Context Generation

Write exactly ONE short sentence that is a natural user message containing the exact token `{token}` (preserve its capitalisation and characters exactly; do not complete a sub-word fragment). The sentence must NOT mention or reference `{concept}` in any way. The token must appear surrounded by spaces. The phrasing should invite the model to use or repeat the token in its reply. If no natural sentence fits, fall back to: `What is "{token}"?`

Examples for token `Harry` *in concept* `Harry Potter`*:*

- "Tell me about Prince Harry."
- "Who is Harry Houdini?"

Reply with ONLY the single sentence itself. No explanation, no quotes around it.

Figure 17: Prompt template used to elicit a concept-neutral context for each edited token. Placeholders `{token}` and `{concept}` are substituted at call time.

Prompt: Coherence Judging

You score an erased language model's answer against a reference answer.

The model was asked:
`{prompt}`

REFERENCE answer (from the original, unedited model):
`{original}`

CANDIDATE answer (from an erased model):
`{answer}`

Assign the CANDIDATE one of three labels, comparing it to the REFERENCE:

- *Consistent* – conveys essentially the same information / meaning as the reference; the underlying knowledge is intact. Minor surface artifacts such as a single word repeated once or twice, or slightly different phrasing, do NOT lower the label if the overall content and meaning are intact.
- *Semantic shift* – the specific information is changed, lost, made generic, or replaced by a refusal / clarification request.
- *Incoherent* – degenerate, broken, empty, or output so repetitive it conveys no meaningful content.

Worked examples (Prompt: "`What is the name of the first Harry Potter book?`"; Reference: "`. . . Harry Potter and the Philosopher's Stone, published in 1997. . .`"):

- "`I'm not familiar with that series. Could you clarify what you mean?`" → *Semantic shift* (loses the specific information).
- "`Potter Potter the the the stone stone stone`" → *Incoherent* (broken, repetitive).
- "`The first Harry Harry Potter book is called 'Harry Potter and the Philosopher's Stone', published in 1997.`" → *Consistent* (content preserved; doubled `Harry` is a minor surface artifact).

Reply with a one-line JSON of the form `{"justification": "<1-2 sentences>", "label": "<consistent|semantic shift|incoherent>"}`.

Figure 18: Prompt template used by the LLM judge to assign one of the three labels of §5 to each (original, erased) answer pair.