CENG 495 - Cloud Computing
Spring 2024
Homework 2

Adıgüzel, Gürhan İlhan
e244802@metu.edu.tr

May 12, 2024

---

1 Introduction

This report documents the deployment process of the Expense Splitter Website developed with Docker containers and Docker Compose. In this report, decisions during deployment, a detailed overview of the deployment workflow, challenges encountered and solutions, deployment steps, system architecture and screenshots of the deployed application are provided.

2 Decisions Made During Deployment

- **Front-end Technology**: I chose Flutter for front-end development due to have easy UI design to want to use clean-architecture principles and also my past experience and familiarity with the language.
- **Back-end Framework**: I selected Flask a lightweight web framework written in Python, for back-end development due to its simplicity.
- **Database Solution**: I chose MongoDB as the database solution for its support for handling unstructured data, providing efficient data management for the application and also because I am experienced in using it.

3 Challenges Encountered

- **Creating Local MongoDB Container:** Initially, I had difficulty in setting up a local MongoDB container. To handle this, I installed the local MongoDB Docker image and configured the port to 27017.
- **Building Dockerfiles for Flask Microservices:** I had the wrong address request issue when creating Dockerfiles for Flask microservices and trying to communicate with the MongoDB container. To overcome this, I configured the Flask application to connect to the MongoDB container using "host.docker.internal" instead of "localhost" to ensure communication between services.
- **Dockerizing the Flutter Web App:** While dockerizing the Flutter web app and I faced a compatibility issues. To resolve this, I authored a Dockerfile within the Flutter project, enabling the building and running of the 'flutter build web' within a container.
- **CORS Errors Between Frontend and Backend:** There were Cross-Origin Resource Sharing (CORS) errors between the frontend and backend components. To handle this issue, I modified the backend files to allow CORS from all origins, ensuring unrestricted communication between frontend and backend.
- **Composing Different Containers:** To simplify the orchestration process, I carefully defined dependencies between containers in the 'docker-compose.yml' file. This ensured smooth communication and cooperation among services.

4 Deployment Workflow Using Docker and Docker Compose

4.1 Containerization with Docker

1. **Backend Microservices**: Flask microservices were containerized using Docker and Dockerfiles were created for each microservice, and Docker images were built and run as Docker containers.
2. **Database Setup**: MongoDB was deployed locally as a Docker image using the following commands:

```
docker pull mongodb/mongodb-community-server:latest
docker run --name mongodb -p 27017:27017 -d mongodb/mongodb-community-server:latest
```

   These commands pulled the latest MongoDB Docker image and created a container named "mongodb" with port 27017 exposed for access.
3. **Frontend Development**: The Flutter web app was containerized using Docker, with a Dockerfile defining the build environment and dependencies. A Docker container was instantiated to host the Flutter web app.

4.2 Orchestration with Docker Compose

1. **Compose File Creation**: A Docker Compose file (`docker-compose.yml`) was created to define services, networks, and volumes for the application. Configuration for MongoDB, Flask microservices, and the Flutter web app was specified in the Compose file.
2. **Service Orchestration**: Docker Compose was used to orchestrate the deployment process. The `docker-compose up` command initiated the deployment, creating containers, networks, and volumes as per the specified configuration.

5 System Architecture Overview

The system architecture consists of frontend, backend, and database components encapsulated within Docker containers. Interaction between components is facilitated through Docker networks.



Figure 1: System Design Diagram

6 Screenshots



Figure 2: Register Page



Figure 3: Dashboard Page



Figure 4: Add Event Page



Figure 5: Event Details Page



Figure 6: Add Expense Page



Figure 7: Expenses Page



Figure 8: Docker Images



Figure 9: Docker Containers

7 Conclusion

In conclusion, the deployment of the Expense Splitter web application using Docker and Docker Compose has been successfully accomplished. By executing the command ‘docker-compose up‘, all services can be initiated, enabling the application to be accessible and fully operational within a containerized environment.