

Languages that are and are not Regular

CENG 280

Course outline

- Preliminaries: Alphabets and languages
- Regular languages
 - Regular expressions
 - Finite automata: DFA and NFA
 - Finite automata - regular languages
 - Languages that are and that are not regular, Pumping lemma
 - State minimization for DFA
- Context-free languages
- Turing-machines

Languages that are and are not Regular

- Methods to show that a language is regular
- Methods to show that a language is not regular

Regular Languages

To show that a language L is regular, one of the following methods can be used:

Regular Languages

To show that a language L is regular, one of the following methods can be used:

- write a regular expression α such that $L = \mathcal{L}(\alpha)$

Regular Languages

To show that a language L is regular, one of the following methods can be used:

- write a regular expression α such that $L = \mathcal{L}(\alpha)$
- construct an NFA M such that $L = L(M)$

Regular Languages

To show that a language L is regular, one of the following methods can be used:

- write a regular expression α such that $L = \mathcal{L}(\alpha)$
- construct an NFA M such that $L = L(M)$
- use closure properties, e.g., for regular languages L_1 and L_2 , show $L = L_1 \cap L_2$, $L = L_1 \cup L_2$, $L = L_1 L_2$, or $L = \Sigma^* \setminus L_1$ (more examples can be added)

Regular Languages

To show that a language L is regular, one of the following methods can be used:

- write a regular expression α such that $L = \mathcal{L}(\alpha)$
- construct an NFA M such that $L = L(M)$
- use closure properties, e.g., for regular languages L_1 and L_2 , show $L = L_1 \cap L_2$, $L = L_1 \cup L_2$, $L = L_1 L_2$, or $L = \Sigma^* \setminus L_1$ (more examples can be added)

Example

$\Sigma = \{0, 1, \dots, 9\}$. $L = \{n \mid n \text{ divisible by 2 and 3}\}$ (decimal representations without leading 0's). Show that L is regular.

Regular Languages

To show that a language L is regular, one of the following methods can be used:

- write a regular expression α such that $L = \mathcal{L}(\alpha)$
- construct an NFA M such that $L = L(M)$
- use closure properties

Regular Languages

To show that a language L is regular, one of the following methods can be used:

- write a regular expression α such that $L = \mathcal{L}(\alpha)$
- construct an NFA M such that $L = L(M)$
- use closure properties

Example

Is L regular or not? L' is regular.

$$L = \{xy \in \Sigma^* \mid x \in L' \text{ and } y \notin L'\}$$

Regular Languages

To show that a language L is regular, one of the following methods can be used:

- write a regular expression α such that $L = \mathcal{L}(\alpha)$
- construct an NFA M such that $L = L(M)$
- use closure properties

Example

Is L^R regular or not? L is regular.

$$L^R = \{w^R \in \Sigma^* \mid w \in L\}$$

Regular Languages

To show that a language L is regular, one of the following methods can be used:

- write a regular expression α such that $L = \mathcal{L}(\alpha)$
- construct an NFA M such that $L = L(M)$
- use closure properties

Example

Is L regular or not?

$$L = \{w \in \Sigma^* \mid w \text{ has property } P\}, |L| \text{ is finite}$$

Languages that are not regular

- To show that a language L is not regular, we use the following property of regular languages: as a string is scanned from left to right, the amount of memory required to determine if $w \in L$ or $w \notin L$ must be bounded.

Languages that are not regular

- To show that a language L is not regular, we use the following property of regular languages: as a string is scanned from left to right, the amount of memory required to determine if $w \in L$ or $w \notin L$ must be bounded.
- In RL, infinite languages can be represented with Kleene star (cycle in automata), which induce a periodicity/pattern.

Languages that are not regular

- To show that a language L is not regular, we use the following property of regular languages: as a string is scanned from left to right, the amount of memory required to determine if $w \in L$ or $w \notin L$ must be bounded.
- In RL, infinite languages can be represented with Kleene star (cycle in automata), which induce a periodicity/pattern.

Theorem

Let L be a regular language. There is an integer $n \geq 1$ such that any string $w \in L$ with $|w| \geq n$ can be rewritten as $w = xyz$ such that $y \neq \epsilon$, $|xy| \leq n$ and $xy^iz \in L$ for each $i \geq 0$.

Pumping lemma application

Theorem

Let L be a regular language. There is an integer $n \geq 1$ such that any string $w \in L$ with $|w| \geq n$ can be rewritten as $w = xyz$ such that $y \neq \epsilon$, $|xy| \leq n$ and $xy^iz \in L$ for each $i \geq 0$.

- For each regular language L , \rightarrow assume that L is regular

Pumping lemma application

Theorem

Let L be a regular language. There is an integer $n \geq 1$ such that any string $w \in L$ with $|w| \geq n$ can be rewritten as $w = xyz$ such that $y \neq \epsilon$, $|xy| \leq n$ and $xy^iz \in L$ for each $i \geq 0$.

- For each regular language L , \rightarrow assume that L is regular
- there exists $n \geq 1$ such that \rightarrow this is a general term do not pick a number!!!

Pumping lemma application

Theorem

Let L be a regular language. There is an integer $n \geq 1$ such that any string $w \in L$ with $|w| \geq n$ can be rewritten as $w = xyz$ such that $y \neq \epsilon$, $|xy| \leq n$ and $xy^iz \in L$ for each $i \geq 0$.

- For each regular language L , \rightarrow assume that L is regular
- there exists $n \geq 1$ such that \rightarrow this is a general term do not pick a number!!!
- for each $w \in L$ with $|w| \geq n$ \rightarrow write a string with respect to n , use it to reach a contradiction

Pumping lemma application

Theorem

Let L be a regular language. There is an integer $n \geq 1$ such that any string $w \in L$ with $|w| \geq n$ can be rewritten as $w = xyz$ such that $y \neq \epsilon$, $|xy| \leq n$ and $xy^iz \in L$ for each $i \geq 0$.

- For each regular language L , \rightarrow assume that L is regular
- there exists $n \geq 1$ such that \rightarrow this is a general term do not pick a number!!!
- for each $w \in L$ with $|w| \geq n$ \rightarrow write a string with respect to n , use it to reach a contradiction
- there exists a split $w = xyz$ with $y \neq \epsilon$, $|xy| \leq n$ \rightarrow consider each possible split satisfying these constraints

Pumping lemma application

Theorem

Let L be a regular language. There is an integer $n \geq 1$ such that any string $w \in L$ with $|w| \geq n$ can be rewritten as $w = xyz$ such that $y \neq \epsilon$, $|xy| \leq n$ and $xy^iz \in L$ for each $i \geq 0$.

- For each regular language L , \rightarrow assume that L is regular
- there exists $n \geq 1$ such that \rightarrow this is a general term do not pick a number!!!
- for each $w \in L$ with $|w| \geq n$ \rightarrow write a string with respect to n , use it to reach a contradiction
- there exists a split $w = xyz$ with $y \neq \epsilon$, $|xy| \leq n$ \rightarrow consider each possible split satisfying these constraints
- for each $i \geq 0$ $xy^iz \in L$ \rightarrow show that there exists an i such that $xy^iz \notin L$, contradiction

Pumping lemma application

For each regular language L ,

- there exists $n \geq 1$ such that
- for each $w \in L$ with $|w| \geq n$
- there exists a split $w = xyz$ with $y \neq \epsilon$, $|xy| \leq n$
- for each $i \geq 0$ $xy^iz \in L$

→ *this is a general term do not pick a number!!!*

→ *write a string with respect to n , use it to reach a contradiction*

→ *consider each possible split satisfying these constraints*

→ *show that there exists an i such that $xy^iz \notin L$, contradiction*

Example

Show that $L = \{a^k b^k \mid k \geq 0\}$ is not regular.

Pumping lemma application

For each regular language L ,

- there exists $n \geq 1$ such that
- for each $w \in L$ with $|w| \geq n$
- there exists a split $w = xyz$ with $y \neq \epsilon$, $|xy| \leq n$
- for each $i \geq 0$ $xy^iz \in L$

→ *this is a general term do not pick a number!!!*

→ *write a string with respect to n , use it to reach a contradiction*

→ *consider each possible split satisfying these constraints*

→ *show that there exists an i such that $xy^iz \notin L$, contradiction*

Example

Show that $L = \{a^i \mid i \text{ is prime}\}$ is not regular.

Pumping lemma application

For each regular language L ,

- there exists $n \geq 1$ such that
- for each $w \in L$ with $|w| \geq n$
- there exists a split $w = xyz$ with $y \neq \epsilon$, $|xy| \leq n$
- for each $i \geq 0$ $xy^iz \in L$

→ *this is a general term do not pick a number!!!*

→ *write a string with respect to n , use it to reach a contradiction*

→ *consider each possible split satisfying these constraints*

→ *show that there exists an i such that $xy^iz \notin L$, contradiction*

Example

Show that $L = \{w \in \{a, b\}^* \mid w \text{ has equal number of } a \text{ and } b\}$ is not regular.

Pumping lemma application

For each regular language L ,

- there exists $n \geq 1$ such that
- for each $w \in L$ with $|w| \geq n$
- there exists a split $w = xyz$ with $y \neq \epsilon$, $|xy| \leq n$
- for each $i \geq 0$ $xy^iz \in L$

→ *this is a general term do not pick a number!!!*

→ *write a string with respect to n , use it to reach a contradiction*

→ *consider each possible split satisfying these constraints*

→ *show that there exists an i such that $xy^iz \notin L$, contradiction*

Example

Show that $L = \{ww^R \in \{a, b\}^*\}$ is not regular.

Pumping lemma application

For each regular language L ,

- there exists $n \geq 1$ such that
- for each $w \in L$ with $|w| \geq n$
- there exists a split $w = xyz$ with $y \neq \epsilon$, $|xy| \leq n$
- for each $i \geq 0$ $xy^iz \in L$

→ *this is a general term do not pick a number!!!*

→ *write a string with respect to n , use it to reach a contradiction*

→ *consider each possible split satisfying these constraints*

→ *show that there exists an i such that $xy^iz \notin L$, contradiction*

Example

Show that $L = \{wcw \mid w \in \{a, b\}^*\}$ is not regular.