

# Finite Representations of Languages

CENG 280

# Finite Representations of Languages

Regular expressions

Regular languages

# Finite Representations of Languages

The goal is to represent the languages with finite specifications. Consider an alphabet  $\Sigma$ , the number of finite representations of languages (it should be a string), and the number of languages over  $\Sigma$ .

# Finite Representations of Languages

The goal is to represent the languages with finite specifications. Consider an alphabet  $\Sigma$ , the number of finite representations of languages (it should be a string), and the number of languages over  $\Sigma$ .

*No matter how powerful our methods for representing the languages, only countably many languages can be represented.*

# Finite Representations of Languages

The goal is to represent the languages with finite specifications. Consider an alphabet  $\Sigma$ , the number of finite representations of languages (it should be a string), and the number of languages over  $\Sigma$ .

*No matter how powerful our methods for representing the languages, only countably many languages can be represented.*

## Example

$L = \{w \in \{0,1\}^* \mid$   
 $w \text{ has exactly three occurrences of } 0 \text{ and they are not consecutive} \}$

## Definition (Regular expressions)

The regular expressions over an alphabet  $\Sigma$  are all strings over the alphabet  $\Sigma \cup \{ (, ), \emptyset, U, \star \}$  that can be obtained as follows:

## Definition (Regular expressions)

The regular expressions over an alphabet  $\Sigma$  are all strings over the alphabet  $\Sigma \cup \{ (, ), \emptyset, U, \star \}$  that can be obtained as follows:

- 1-  $\emptyset$  and each member of  $\Sigma$  is a regular expression

## Definition (Regular expressions)

The regular expressions over an alphabet  $\Sigma$  are all strings over the alphabet  $\Sigma \cup \{ (, ), \emptyset, U, \star \}$  that can be obtained as follows:

- 1-  $\emptyset$  and each member of  $\Sigma$  is a regular expression
- 2- If  $\alpha$  and  $\beta$  are regular expressions then so is  $(\alpha\beta)$



## Definition (Regular expressions)

The regular expressions over an alphabet  $\Sigma$  are all strings over the alphabet  $\Sigma \cup \{ (, ), \emptyset, U, \star \}$  that can be obtained as follows:

- 1-  $\emptyset$  and each member of  $\Sigma$  is a regular expression
- 2- If  $\alpha$  and  $\beta$  are regular expressions then so is  $(\alpha\beta)$
- 3- If  $\alpha$  and  $\beta$  are regular expressions then so is  $(\alpha U \beta)$

## Definition (Regular expressions)

The regular expressions over an alphabet  $\Sigma$  are all strings over the alphabet  $\Sigma \cup \{ (, ), \emptyset, U, \star \}$  that can be obtained as follows:

- 1-  $\emptyset$  and each member of  $\Sigma$  is a regular expression
- 2- If  $\alpha$  and  $\beta$  are regular expressions then so is  $(\alpha\beta)$
- 3- If  $\alpha$  and  $\beta$  are regular expressions then so is  $(\alpha U \beta)$
- 4- If  $\alpha$  is a regular expression then so is  $\alpha^\star$

## Definition (Regular expressions)

The regular expressions over an alphabet  $\Sigma$  are all strings over the alphabet  $\Sigma \cup \{ (, ), \emptyset, U, \star \}$  that can be obtained as follows:

- 1-  $\emptyset$  and each member of  $\Sigma$  is a regular expression
- 2- If  $\alpha$  and  $\beta$  are regular expressions then so is  $(\alpha\beta)$
- 3- If  $\alpha$  and  $\beta$  are regular expressions then so is  $(\alpha U \beta)$
- 4- If  $\alpha$  is a regular expression then so is  $\alpha^\star$
- 5- Nothing is a regular expression unless it follows from 1-4

# Regular Expressions

## Definition (Regular expressions)

The regular expressions over an alphabet  $\Sigma$  are all strings over the alphabet  $\Sigma \cup \{ (, ), \emptyset, U, \star \}$  that can be obtained as follows:

- 1-  $\emptyset$  and each member of  $\Sigma$  is a regular expression
- 2- If  $\alpha$  and  $\beta$  are regular expressions then so is  $(\alpha\beta)$
- 3- If  $\alpha$  and  $\beta$  are regular expressions then so is  $(\alpha U \beta)$
- 4- If  $\alpha$  is a regular expression then so is  $\alpha^\star$
- 5- Nothing is a regular expression unless it follows from 1-4

Note that, even though  $\alpha U \beta U \gamma$  and  $\alpha\beta\gamma$  are not officially a regular expression (why?), we use it due to the associativity of concatenation and union operations.

# Regular Languages

Every regular expression defines a language. Symbols  $\cup$  and  $\star$  are interpreted as union and Kleene star, respectively, and juxtaposition is string concatenation.

# Regular Languages

Every regular expression defines a language. Symbols  $\cup$  and  $\star$  are interpreted as union and Kleene star, respectively, and juxtaposition is string concatenation.

## Definition (Languages defined by regular expressions)

For a regular expression  $\alpha$ ,  $\mathcal{L}(\alpha)$  is the language represented by  $\alpha$  and it is defined as

# Regular Languages

Every regular expression defines a language. Symbols  $\cup$  and  $\star$  are interpreted as union and Kleene star, respectively, and juxtaposition is string concatenation.

## Definition (Languages defined by regular expressions)

For a regular expression  $\alpha$ ,  $\mathcal{L}(\alpha)$  is the language represented by  $\alpha$  and it is defined as

$$1- \mathcal{L}(\emptyset) = \emptyset \text{ and } \mathcal{L}(a) = \{a\} \text{ for each } a \in \Sigma$$

# Regular Languages

Every regular expression defines a language. Symbols  $\cup$  and  $\star$  are interpreted as union and Kleene star, respectively, and juxtaposition is string concatenation.

## Definition (Languages defined by regular expressions)

For a regular expression  $\alpha$ ,  $\mathcal{L}(\alpha)$  is the language represented by  $\alpha$  and it is defined as

- 1-  $\mathcal{L}(\emptyset) = \emptyset$  and  $\mathcal{L}(a) = \{a\}$  for each  $a \in \Sigma$
- 2- If  $\alpha$  and  $\beta$  are regular expressions then  $\mathcal{L}(\alpha\beta) = \mathcal{L}(\alpha)\mathcal{L}(\beta)$



# Regular Languages

Every regular expression defines a language. Symbols  $U$  and  $\star$  are interpreted as union and Kleene star, respectively, and juxtaposition is string concatenation.

## Definition (Languages defined by regular expressions)

For a regular expression  $\alpha$ ,  $\mathcal{L}(\alpha)$  is the language represented by  $\alpha$  and it is defined as

- 1-  $\mathcal{L}(\emptyset) = \emptyset$  and  $\mathcal{L}(a) = \{a\}$  for each  $a \in \Sigma$
- 2- If  $\alpha$  and  $\beta$  are regular expressions then  $\mathcal{L}(\alpha\beta) = \mathcal{L}(\alpha)\mathcal{L}(\beta)$
- 3- If  $\alpha$  and  $\beta$  are regular expressions then  $\mathcal{L}(\alpha U \beta) = \mathcal{L}(\alpha) \cup \mathcal{L}(\beta)$

# Regular Languages

Every regular expression defines a language. Symbols  $U$  and  $\star$  are interpreted as union and Kleene star, respectively, and juxtaposition is string concatenation.

## Definition (Languages defined by regular expressions)

For a regular expression  $\alpha$ ,  $\mathcal{L}(\alpha)$  is the language represented by  $\alpha$  and it is defined as

- 1-  $\mathcal{L}(\emptyset) = \emptyset$  and  $\mathcal{L}(a) = \{a\}$  for each  $a \in \Sigma$
- 2- If  $\alpha$  and  $\beta$  are regular expressions then  $\mathcal{L}(\alpha\beta) = \mathcal{L}(\alpha)\mathcal{L}(\beta)$
- 3- If  $\alpha$  and  $\beta$  are regular expressions then  $\mathcal{L}(\alpha U \beta) = \mathcal{L}(\alpha) \cup \mathcal{L}(\beta)$
- 4- If  $\alpha$  is a regular expression then so is  $\mathcal{L}(\alpha^\star) = \mathcal{L}(\alpha)^\star$

# Regular Languages

## Definition (Languages defined by regular expressions)

For a regular expression  $\alpha$ ,  $\mathcal{L}(\alpha)$  is the language represented by  $\alpha$  and it is defined as

- 1-  $\mathcal{L}(\emptyset) = \emptyset$  and  $\mathcal{L}(a) = \{a\}$  for each  $a \in \Sigma$
- 2- If  $\alpha$  and  $\beta$  are regular expressions than  $\mathcal{L}(\alpha\beta) = \mathcal{L}(\alpha)\mathcal{L}(\beta)$
- 3- If  $\alpha$  and  $\beta$  are regular expressions than  $\mathcal{L}(\alpha U \beta) = \mathcal{L}(\alpha) \cup \mathcal{L}(\beta)$
- 4- If  $\alpha$  is a regular expression than so is  $\mathcal{L}(\alpha^*) = \mathcal{L}(\alpha)^*$

## Example

- 1- What is  $\mathcal{L}(b(aUb)^*)$

# Regular Languages

## Definition (Languages defined by regular expressions)

For a regular expression  $\alpha$ ,  $\mathcal{L}(\alpha)$  is the language represented by  $\alpha$  and it is defined as

- 1-  $\mathcal{L}(\emptyset) = \emptyset$  and  $\mathcal{L}(a) = \{a\}$  for each  $a \in \Sigma$
- 2- If  $\alpha$  and  $\beta$  are regular expressions then  $\mathcal{L}(\alpha\beta) = \mathcal{L}(\alpha)\mathcal{L}(\beta)$
- 3- If  $\alpha$  and  $\beta$  are regular expressions then  $\mathcal{L}(\alpha \cup \beta) = \mathcal{L}(\alpha) \cup \mathcal{L}(\beta)$
- 4- If  $\alpha$  is a regular expression then so is  $\mathcal{L}(\alpha^*) = \mathcal{L}(\alpha)^*$

## Example

- 1- What is  $\mathcal{L}(b(a \cup b)^*)$
- 2- Write a regular expression representing the set of words over  $\{0, 1\}$  that has exactly three occurrences of 0 and they are not consecutive.

# Regular Languages

The class of **regular languages** consists of all languages  $L$  such that  $L = \mathcal{L}(\alpha)$  for some regular expression  $\alpha$ . The class of regular languages over  $\Sigma$  is precisely the closure of the set of languages  $\{\{\sigma\} \mid \sigma \in \Sigma\} \cup \{\emptyset\}$  with respect to union, concatenation, and Kleene star.

# Regular Languages

The class of **regular languages** consists of all languages  $L$  such that  $L = \mathcal{L}(\alpha)$  for some regular expression  $\alpha$ . The class of regular languages over  $\Sigma$  is precisely the closure of the set of languages  $\{\{\sigma\} \mid \sigma \in \Sigma\} \cup \{\emptyset\}$  with respect to union, concatenation, and Kleene star.

## Definition

Let  $D$  be a set, let  $n \geq 0$ , and let  $R \subseteq D^{n+1}$  be a  $(n+1)$ -ary relation on  $D$ . Then a subset  $B$  of  $D$  is said to be **closed under**  $R$  if  $b_{n+1} \in B$  whenever

$$b_1, \dots, b_n \in B \text{ and } (b_1, \dots, b_n, b_{n+1}) \in R$$

Any property of the form "the set  $B$  is closed under relations  $R_1, \dots, R_m$ " is called a closure property of  $B$ .

# Regular Languages

The class of **regular languages** consists of all languages  $L$  such that  $L = \mathcal{L}(\alpha)$  for some regular expression  $\alpha$ . The class of regular languages over  $\Sigma$  is precisely the closure of the set of languages  $\{\{\sigma\} \mid \sigma \in \Sigma\} \cup \{\emptyset\}$  with respect to union, concatenation, and Kleene star.

## Definition

Let  $D$  be a set, let  $n \geq 0$ , and let  $R \subseteq D^{n+1}$  be a  $(n+1)$ -ary relation on  $D$ . Then a subset  $B$  of  $D$  is said to be **closed under**  $R$  if  $b_{n+1} \in B$  whenever

$$b_1, \dots, b_n \in B \text{ and } (b_1, \dots, b_n, b_{n+1}) \in R$$

Any property of the form "the set  $B$  is closed under relations  $R_1, \dots, R_m$ " is called a closure property of  $B$ .

## Definition

The closure of a relation  $R$  with respect to property  $P$  is the relation obtained by adding the minimum number of ordered pairs to  $R$  to obtain property  $P$ .

# Regular Languages

The class of **regular languages** consists of all languages  $L$  such that  $L = \mathcal{L}(\alpha)$  for some regular expression  $\alpha$ . The class of regular languages over  $\Sigma$  is precisely the closure of the set of languages  $\{\{\sigma\} \mid \sigma \in \Sigma\} \cup \{\emptyset\}$  with respect to union, concatenation, and Kleene star.



# Regular Languages

The class of **regular languages** consists of all languages  $L$  such that  $L = \mathcal{L}(\alpha)$  for some regular expression  $\alpha$ . The class of regular languages over  $\Sigma$  is precisely the closure of the set of languages  $\{\{\sigma\} \mid \sigma \in \Sigma\} \cup \{\emptyset\}$  with respect to union, concatenation, and Kleene star.

How to prove that  $L$  is regular ?

# Regular Languages

The class of **regular languages** consists of all languages  $L$  such that  $L = \mathcal{L}(\alpha)$  for some regular expression  $\alpha$ . The class of regular languages over  $\Sigma$  is precisely the closure of the set of languages  $\{\{\sigma\} \mid \sigma \in \Sigma\} \cup \{\emptyset\}$  with respect to union, concatenation, and Kleene star.

How to prove that  $L$  is regular ?

How to prove that  $L$  is not regular ?

# Regular Languages

The class of **regular languages** consists of all languages  $L$  such that  $L = \mathcal{L}(\alpha)$  for some regular expression  $\alpha$ . The class of regular languages over  $\Sigma$  is precisely the closure of the set of languages  $\{\{\sigma\} \mid \sigma \in \Sigma\} \cup \{\emptyset\}$  with respect to union, concatenation, and Kleene star.

How to prove that  $L$  is regular ?

How to prove that  $L$  is not regular ?

For some language  $L$ , an algorithm that answers the question is  $w \in L$  is called a **language recognition device**. On the other hand, descriptions of how a string from a language can be produced are called **language generators**.

# Regular Languages

The class of **regular languages** consists of all languages  $L$  such that  $L = \mathcal{L}(\alpha)$  for some regular expression  $\alpha$ . The class of regular languages over  $\Sigma$  is precisely the closure of the set of languages  $\{\{\sigma\} \mid \sigma \in \Sigma\} \cup \{\emptyset\}$  with respect to union, concatenation, and Kleene star.

How to prove that  $L$  is regular ?

How to prove that  $L$  is not regular ?

For some language  $L$ , an algorithm that answers the question is  $w \in L$  is called a **language recognition device**. On the other hand, descriptions of how a string from a language can be produced are called **language generators**.

Consider a device (an algorithm) to recognize strings that include 11 as a substring